

# Power Supply

- I757225001
- I757225002
- I757230002
- I757240002
- I757930000
- I757940000
- I757230005
- I757240005

## Redundant Power Supply Specifications Mini Redundant AC-DC 250W AT Type Power Supply

| Part Number | Descriptions            |                                |     |    |      |      |      |    |
|-------------|-------------------------|--------------------------------|-----|----|------|------|------|----|
| I757225001  | Input Range             | AC 98~132V/190~260V @ 47~63 Hz |     |    |      |      |      |    |
|             | Normal Output Range     | Max.                           | 25A | -- | 10A  | 0.5A | 0.5A | -- |
|             |                         | Min.                           | 4A  | -- | 1.5A | 0    | 0    | -- |
|             | MTBF(hours)             | 100,000 hours                  |     |    |      |      |      |    |
|             | Safety                  | UL / CUL / TUV                 |     |    |      |      |      |    |
|             | EMI                     | FCC / CE / ISJ-B               |     |    |      |      |      |    |
|             | Compatible with Chassis | ARC-6205 , ARC-6414 , ARC-6608 |     |    |      |      |      |    |



PS/2

## PS/2 Power Supply Specifications AC-DC 250W AT Type Power Supply

| Part Number | Descriptions            |                                |     |    |    |      |      |    |
|-------------|-------------------------|--------------------------------|-----|----|----|------|------|----|
| I757225002  | Input Range             | AC 90~135V/180~264V @ 47~63 Hz |     |    |    |      |      |    |
|             | Normal Output Range     | Max.                           | 26A | -- | 9A | 0.5A | 0.5A | -- |
|             |                         | Min.                           | 3A  | -- | 1A | 0    | 0    | -- |
|             | MTBF(hours)             | 100,000 hours                  |     |    |    |      |      |    |
|             | Safety                  | UL / CUL / TUV / CSA           |     |    |    |      |      |    |
|             | EMI                     | FCC / CE / ISJ-B               |     |    |    |      |      |    |
|             | Compatible with Chassis | ARC-6205 , ARC-6414 , ARC-6608 |     |    |    |      |      |    |



## PS/2 Power Supply Specifications AC-DC 300W AT Type Power Supply

| Part Number | Descriptions            |                                |     |    |      |      |      |    |
|-------------|-------------------------|--------------------------------|-----|----|------|------|------|----|
| I757230002  | Input Range             | AC 90~132V/180~260V @ 47~63 Hz |     |    |      |      |      |    |
|             | Normal Output Range     | Max.                           | 25A | -- | 14A  | 0.5A | 0.5A | -- |
|             |                         | Min.                           | 7A  | -- | 2.5A | 0    | 0    | -- |
|             | MTBF(hours)             | 100,000 hours                  |     |    |      |      |      |    |
|             | Safety                  | UL / CUL / TUV / CSA           |     |    |      |      |      |    |
|             | EMI                     | FCC / CE / ISJ-B               |     |    |      |      |      |    |
|             | Compatible with Chassis | ARC-6205 , ARC-6414 , ARC-6608 |     |    |      |      |      |    |



## PS/2 Power Supply Specifications AC-DC 400W AT Type Power Supply

| Part Number | Descriptions            |                                |     |    |      |    |    |    |
|-------------|-------------------------|--------------------------------|-----|----|------|----|----|----|
| I757240002  | Input Range             | AC 95~132V/190~263V @ 47~63 Hz |     |    |      |    |    |    |
|             | Normal Output Range     | Max.                           | 50A | -- | 20A  | 1A | 1A | -- |
|             |                         | Min.                           | 7A  | -- | 2.5A | 0A | 0A | -- |
|             | MTBF(hours)             | 100,000 hours                  |     |    |      |    |    |    |
|             | Safety                  | UL / CUL / TUV / CSA           |     |    |      |    |    |    |
|             | EMI                     | FCC / CE / ISJ-B               |     |    |      |    |    |    |
|             | Compatible with Chassis | ARC-6205 , ARC-6414 , ARC-6608 |     |    |      |    |    |    |



PS/2



## PS/2 Power Supply Specifications DC-DC 300W AT Type Power Supply

| Part Number | Descriptions            |                                |     |    |      |    |    |    |
|-------------|-------------------------|--------------------------------|-----|----|------|----|----|----|
| I757930000  | Input Range             | DC -40~-57V                    |     |    |      |    |    |    |
|             | Normal Output Range     | Max.                           | 33A | -- | 14A  | 1A | 1A | -- |
|             |                         | Min.                           | 7A  | -- | 2.5A | 0  | 0  | -- |
|             | MTBF(hours)             | 100,000 hours                  |     |    |      |    |    |    |
|             | Safety                  | UL / TUV / CSA                 |     |    |      |    |    |    |
|             | EMI                     | FCC / CE / ISJ-B               |     |    |      |    |    |    |
|             | Compatible with Chassis | ARC-6205 , ARC-6414 , ARC-6608 |     |    |      |    |    |    |

## PS/2 Power Supply Specifications DC-DC 400W ATX Type Power Supply

| Part Number | Descriptions            |                                |     |     |      |    |    |       |
|-------------|-------------------------|--------------------------------|-----|-----|------|----|----|-------|
| I757940000  | Input Range             | DC -42~-57V                    |     |     |      |    |    |       |
|             | Normal Output Range     | Max.                           | 30A | 28A | 14A  | 1A | 1A | 850mA |
|             |                         | Min.                           | 3A  | 1A  | 0.5A | 0A | 0A | 0A    |
|             | MTBF(hours)             | 100,000 hours                  |     |     |      |    |    |       |
|             | Safety                  | UL / TUV / CSA                 |     |     |      |    |    |       |
|             | EMI                     | FCC / CE / ISJ-B               |     |     |      |    |    |       |
|             | Compatible with Chassis | ARC-6205 , ARC-6414 , ARC-6608 |     |     |      |    |    |       |



## PS/2 Power Supply Specifications AC-DC 300W ATX Type Power Supply

| Part Number | Descriptions            |                                |     |     |      |    |    |      |
|-------------|-------------------------|--------------------------------|-----|-----|------|----|----|------|
| I757230005  | Input Range             | AC 90~132V/180~260V @ 47~63 Hz |     |     |      |    |    |      |
|             | Normal Output Range     | Max.                           | 30A | 28A | 10A  | 1A | 1A | 1.5A |
|             |                         | Min.                           | 3A  | 1A  | 1.5A | 0  | 0  | 0A   |
|             | MTBF(hours)             | 100,000 hours                  |     |     |      |    |    |      |
|             | Safety                  | UL / CUL / TUV / CSA           |     |     |      |    |    |      |
|             | EMI                     | FCC / CE / ISJ-B               |     |     |      |    |    |      |
|             | Compatible with Chassis | ARC-6205 , ARC-6414 , ARC-6608 |     |     |      |    |    |      |



## PS/2 Power Supply Specifications AC-DC 400W ATX Type Power Supply

| Part Number | Descriptions            |                                |     |     |      |    |    |      |
|-------------|-------------------------|--------------------------------|-----|-----|------|----|----|------|
| I757240005  | Input Range             | AC 90~132V/180~260V @ 47~63 Hz |     |     |      |    |    |      |
|             | Normal Output Range     | Max.                           | 30A | 28A | 14A  | 1A | 1A | 1.5A |
|             |                         | Min.                           | 3A  | 1A  | 1.5A | 0A | 0A | 0A   |
|             | MTBF(hours)             | 100,000 hours                  |     |     |      |    |    |      |
|             | Safety                  | UL / CUL / TUV / CSA           |     |     |      |    |    |      |
|             | EMI                     | FCC / CE / ISJ-B               |     |     |      |    |    |      |
|             | Compatible with Chassis | ARC-6205 , ARC-6414 , ARC-6608 |     |     |      |    |    |      |

