

# Power Supply

- I757230008
- I757240006
- I757230004
- I757220000
- I757215002
- I757215001
- I757215003
- I757230009

**PS/2 Power Supply Specifications**  
**AC-DC 300W ATX Type Power Supply**

Part Number	Descriptions							
I757230008	Input Range	AC 90~132V/180~260V @ 47~63 Hz						
	Normal Output Range		+5V	+3.3V	+12V	-5V	-12V	+5Vsb
		Max.	30A	14A	12A	0.5A	0.5A	1.5A
	Min.	2.5A	1A	1.5A	0A	0A	0.3A	
	MTBF(hours)	100,000 hours						
	Safety	UL / CUL / TUV / CSA						
EMI	FCC / CE / I5J-B							
Compatible with Chassis	ARC-6205 , ARC-6414 , ARC-6608							



**PS/2 Power Supply Specifications**  
**AC-DC 400W ATX-12V Type Power Supply**

Part Number	Descriptions							
I757240006	Input Range	AC 90~264V Full Range @ 47~63 Hz						
	Normal Output Range		+5V	+3.3V	+12V	-5V	-12V	+5Vsb
		Max.	35A	28A	20A	0.8A	1A	2A
	Min.	2.5A	1A	1A	0A	0A	0.1A	
	MTBF(hours)	100,000 hours						
	Safety	UL / CUL / TUV						
EMI	FCC / CE / I5J-B							
Compatible with Chassis	ARC-6205 , ARC-6414 , ARC-6608							



## IU

**IU Power Supply Specifications**  
**AC-DC 300W ATX Type Power Supply**

Part Number	Descriptions							
I757230004	Input Range	AC 115~230V Full Range @ 50~60 Hz						
	Normal Output Range		+5V	+3.3V	+12V	-5V	-12V	+5Vsb
		Max.	25A	14A	12A	0.5A	1A	1.5A
	Min.	3A	1A	2A	0.05A	0.05A	0.5A	
	MTBF(hours)	100,000 hours						
	Safety	UL / CUL / TUV						
EMI	FCC / CE							
Compatible with Chassis	AEC-204 , AEC-206							



**IU Power Supply Specifications**  
**AC-DC 200W ATX Type Power Supply**

Part Number	Descriptions							
I757220000	Input Range	AC 90~132V/180~260V @ 47~63 Hz						
	Normal Output Range		+5V	+3.3V	+12V	-5V	-12V	+5Vsb
		Max.	25A	14A	8A	0.5A	0.5A	1.5A
	Min.	3A	1A	2A	0.05A	0.05A	0.1A	
	MTBF(hours)	100,000 hours						
	Safety	UL / CUL / TUV						
EMI	FCC / CE							
Compatible with Chassis	AEC-204 , AEC-206							



## IU



**IU Power Supply Specifications**  
**AC-DC 150W ATX Type Power Supply**

Part Number	Descriptions							
I757215002	Input Range	AC 90~132V/180~265V @ 35~70 Hz						
	Normal Output Range		+5V	+3.3V	+12V	-5V	-12V	+5Vsb
		Max.	14A	7A	8A	0.2A	0.3A	2A
	Min.	1A	0.54A	0.5A	0A	0A	0A	
	MTBF(hours)	50,000 hours						
	Safety	UL / CUL / TUV / CSA						
EMI	FCC / CE							
Compatible with Chassis	AEC-204 , AEC-206							

**IU Power Supply Specifications**  
**AC-DC 150W ATX Type Power Supply**

Part Number	Descriptions							
I757215001	Input Range	AC 90~132V/180~265V @ 35~70 Hz						
	Normal Output Range		+5V	+3.3V	+12V	-5V	-12V	+5Vsb
		Max.	14A	--	8A	0.2A	1A	--
	Min.	1A	--	0.5A	0A	0A	--	
	MTBF(hours)	100,000 hours						
	Safety	UL / CUL / TUV / CSA						
EMI	FCC / CE							
Compatible with Chassis	AEC-204 , AEC-206							



**IU Power Supply Specifications**  
**DC-DC 150W ATX Type Power Supply**

Part Number	Descriptions							
I757215003	Input Range	DC -21V~DC -28V @ 35~70 Hz						
	Normal Output Range		+5V	+3.3V	+12V	-5V	-12V	+5Vsb
		Max.	10A	10A	6A	0.5A	1A	1.5A
	Min.	1A	1A	0A	0A	0A	0A	
	MTBF(hours)	50,000 hours						
	Safety	UL / CUL / TUV / CSA						
EMI	FCC / CE							
Compatible with Chassis	AEC-204 , AEC-206							



**IU Power Supply Specifications**  
**AC-DC 300W ATX12V Type Power Supply**

Part Number	Descriptions							
I757230009	Input Range	AC 115~240V Full Range @ 47~63 Hz						
	Normal Output Range		+5V	+3.3V	+12V	-5V	-12V	+5Vsb
		Max.	12A	16A	16A	2A	1A	2A
	Min.	1A	1.5A	1.5A	0A	0A	0A	
	MTBF(hours)	100,000 hours						
	Safety	UL / CUL / TUV / CSA						
EMI	FCC / CE							
Compatible with Chassis	AEC-204 , AEC-206							

