


COM-QM87

COM Express CPU Type 6 Module with Intel® Core™ i5 Processor, BGA1364



Features

- Onboard 4th Generation Intel® Core™ i5 Processor
- Intel® QM87 PCH
- Dual-Channel DDR3L 1333/1600MHz SODIMM, Up to 16 GB
- Gigabit Ethernet (iAMT 9.0 Support)
- CRT, 18/24-bit Dual-Channel LVDS LCD, eDP
- USB3.0 x 4, USB2.0 x 8, SATA x 4
- PCI-Express [x16] x 1, PCI-Express [x1] x 7
- COM Express Basic Module, Pin-out Type 6, COM.0 Rev. 2.1
- IEEE 1588 Compatible

Specifications


System	
Form Factor	COM Express Basic module, Pin-out Type 6, COM. 0 Rev. 2.1
Processor	Onboard 4th Generation Intel® Core™ i5 Processor
System Memory	Dual-Channel DDR3L 1333/1600MHz SODIMM, up to 16 GB
Chipset	Intel® QM87
I/O Chipset	Intel® QM87
Ethernet	Intel® I217LM for 10/1000/1000Base-TX
TPM	v1.2 (optional)
BIOS	AMI BIOS
Wake On LAN	Yes
Watchdog Timer	iTE8518E-L, 255 levels
H/W Status Monitoring	Supports CPU Temperature Monitoring.
Expansion Interface	PCI Express [x1] x 7, LPC Bus x 1, SMBus x1
Power Requirement	Normal: +12V
Power Consumption (Typical)	Intel® i5-4400E 2.7GHz, DDR3L 16GB 3.31A@+12V (w/ ECB-920A)
Board Size	4.92" x 3.75" (125mm x 95mm)
Gross Weight	0.66 lb (0.3 Kg)
Operation Temperature	32 °F ~ 140 °F (0 °C ~ 60 °C)
Storage Temperature	-40 °F ~ 176 °F (-40 °C ~ 80 °C)
Operation Humidity	0% ~ 90% relative humidity, non-condensing
MTBF (Hours)	—
Display	
Chipset	Intel® QM87 PCH
Memory	Shared system memory up to 512MB
Resolution	Up to 2560 x 2048 for CRT (two display), 2048 x 1536 for three displays Up to 1920 x 1200 (UXGA) for LCD/HDMI Up to 2560 x 1600 for DP Up to 2548 x 1536 for DVI
LCD Interface	18/24-bit dual channel LVDS
I/O	
Storage	SATA x 4
Serial Port	TX/RX x 2
Parallel Port	—
USB	USB 2.0 x 8
PS/2 Port	—
IrDA	—
Audio	High definition audio
GPIO	Up to 4 in and 4 out



Packing List

- M2.5 Screw x 5
- Product CD
- COM-QM87


Block Diagram



COM-QM87

Dimension

Unit: mm



Ordering Information

Part Number	COM Express Type	CPU	Memory	Display	LVDS	Storage	LAN	USB	URAT	Expansion Slot	Power	Temp
COM-QM87-A10	6 (COM.0 Rev.2.1)	4th Generation Intel® Core™ i5-4400E/2.7GHz (BGA1364)	DDR3L SODIMM x 2 up to 16GB	CRT, LVDS, DDI, eDP/LVDS	18/24b 2CH (LVDS share between eDP)	SATA x 4	GbE x 1	USB3.0 x 4 USB2.0 x 8	2 (TX/RX)	PCI-E [16] x 1, PCI-E [1] x 7	12V	0°C ~ 60°C

Optional Accessories

- ECB-920A-A10**
 COM Express Type 1/6/10 Carrier Board, Gigabit Ethernet, USB, 2 COM, 4 SATA, PCIe, AT/ATX, Legacy Free, Rev. A1.0
- PER-A125**
 Heat Spreader, For COM-QM87, Onboard CPU
- PER-A115**
 CPU Cooler, 45W, for COM Express Basic Size, to be used with Heat Spreader