

ECB-916M B1.0

COM Express Carrier Board

Launched in Q2

Features

- Supports COM Express Module Rev. 2.0 Pin-out Type 1/2
- RJ-45 x 2, Supports Gigabit Ethernet
- VGA/ DVI-D Connector
- 7.1 Channel Audio
- PATA Connector x 1, SATA Port x 3 (4), CompactFlash™ Type 2 Slot x 1
- USB Port x 5, COM Port x 2
- PCI-Express [x16] Slot x 1, PCI-Express [x1] Slot x 1, PCI Slot x 1
- ExpressCard Slot x 1, Mini PCI Slot x 1, Mini Card Slot x 1
- AT/ ATX Power Input
- LPC Connector x 1, microATX Form Factor



Specifications

System	
Form Factor	Micro-ATX
COM Express Connector	x2
I/O Chipset	Winbond W83627DHG
Front Panel Control	10-pin (5x2) header
Ethernet	Intel® 82573L, 10/100/1000 Base-TX, RJ-45 x 1 10/100 Base-TX or 10/100/1000 Base-TX, RJ-45 x 1 (From CPU module)
Expansion Interface	PCI-Express [x1] slot x1 (additional 2 for test only) PCI-Express [x16] slot x 1 ==> Add a 3-pin header for SDVO enabled or disabled PCI slot x 1 Mini Card slot x 1 ExpressCard slot x 1
Power Supply Type	Mini-PCI slot x1
CMOS Battery	RTC battery socket x 1
BIOS	SPI x1 Firmware Hub x 1 (with DIP Switch for BIOS Selection)
Board Size	9.6" x 9.6"(243.84mm x 243.84mm)
Gross Weight	1.32 lb (0.6 Kg)
Operating Temperature	32°F ~ 140°F (0°C ~ 60°C)
Storage Temperature	-40°F ~ 176°F (-40°C ~ 80°C)
Operating Humidity	0% ~ 90% relative humidity, non-condensing
MTBF (Hours)	—
Display	
DVI/CRT	DVI 29-pin + DB 15-pin stack-type connector
LVDS	30-pin (15 x 2) dual-channel LVDS connector x 1
SDVO	40pin (20 x 2) SDVO connector x 1
Touch Screen	Yes
I/O	
Storage	40-pin PATA connector x1 SATA 3.0Gb/s x 3 CompactFlash™ Type 2 slot x 1
Serial Port	RS-232 Port x 1 RS-232/422/485 Port x 1
Parallel Port	—
USB	Type-A connector x 4
PS/2 Port	—
Digital I/O	Supports 8-bit (Programmable)
Audio	Audio jack x 3, Line-in, Line-out, Mic-in Audio Codec: Realtek ALC888 Buzzer x 1
IrDA	—
Switch/Button	Power button x 1 Reset button x 1

Packing List

- TBD

Ordering Information

• TF-ECB-916M-B10

COM Express Carrier Board, Micro-ATX, Dual Gigabit Ethernet, 2COM (WINBOND), USB, PCI-Express, AT/ATX, Rev.B1.0