

PCM-3115C

PCMCIA Modules

PC/104 2-slot PCMCIA Module



Specifications

Standard	Complies with PCMCIA v.2.1 and JEIDA v4.2
Memory	Programmable 8KB boot FLASH ROM
Interface	16-bit data bus
Indicator	Busy status LED
Power Requirement	+5V

Features

- PCMCIA Socket Supports Two Type 1/2 Cards or One Type 3 Card
- Bootable Function From Linear Flash Card, ATA Card and SRAM Card
- ISA Interface

Ordering Information

- **TF-PCM-3115C**
PC/104 Board 2-slot PCMCIA Module

PCM-3116

Mass Storage Modules

PC/104 PCMCIA/ CompactFlash™ to IDE Module



Specifications

Connector	40-pin IDE and 4-pin power connectors
Power Requirement	+5V
Operating Temperature	32°F ~ 158°F (0°C ~ 70°C)

Features

- Allows System to Access the PCMCIA or CompactFlash™ ATA Card Directly as a 0°C ~ 60°C IDE Drive
- Type 1/2/3 PCMCIA and Type 1/2 CompactFlash™ Cards
- No Driver Required

Ordering Information

- **TF-PCM-3116**
PC/104 IDE to PCMCIA/ CompactFlash™ Module
- **TF-PCM-3116PC**
PC/104 IDE to PCMCIA Module
- **TF-PCM-3116PC/F**
IDE to PCMCIA Drive with 3.5" Floppy Disk Drive Form Factor