


# PER-C10L

Mini-PCI Module With One Ethernet Port



## Specifications

Form Factor	Mini-PCI Type 3 A 2" x 2.35" (50.8 mm x 59.6 mm)
Controller	Realtek 8100C for 10/100Base-TX Ethernet Intel® 82541GI / Realtek 8110SC for 10/100/1000Base-TX Ethernet
Speed	Supports 10/100/1000Base-TX, auto-negotiation
Function	IEEE 802.3x compliant flow control IEEE 802.1Q Virtual LAN Wake-on-LAN
Power Requirement	+ 3.3V
Operating Temperature	32°F ~ 140°F (0°C ~ 60°C)

## Features

- Mini-PCI Type 3 Interface
- 10/100Base-TX or 10/100/1000Base-TX Ethernet x 1
- Wake-on-LAN Function
- Pin-header For LAN Status LED

## Packing List


- LAN Cable
- Quick Installation Guide
- Product CD
- PER-C10L

## Ordering Information

- **TF-PER-C10L-A10**  
Mini-PCI, 10/100Base-TX LAN Module, w/  
Realtek, 8100C, Rev. A1.0
- **TF-PER-C10L-A10-01**  
Mini-PCI, 10/100/1000Base-TX LAN Module, w/  
Realtek, 8110SC, Rev. A1.0
- **TF-PER-C10L-A10-02**  
Mini-PCI, 10/100Base-TX LAN Module, with  
Intel®, 82551QM, Rev. A1.0
- **TF-PER-C10L-A10-03**  
Mini-PCI, 10/100/1000Base-TX LAN Module, with  
Intel®, 82541GI, Rev. A1.0

# PER-C40C

Mini-PCI Module With 4 RS-232 COM Ports



## Specifications

Form Factor	Mini-PCI Type 3 A 2" x 2.35" (50.8 mm x 59.6 mm)
UART Chipset	OXFORD OXmPCI954
Power Requirement	+3.3V
Operating Temperature	32°F ~ 140°F (0°C ~ 60°C)

## Features

- Mini-PCI Type 3 Interface
- Four RS-232 Ports Onboard
- Full Duplex Serial Communication

## Packing List

- RS-232 Cable
- Product CD
- PER-C40C

## Ordering Information

- **TF-PER-C40C-B10-01**  
Mini-PCI 4-port RS-232 Module, Rev. B1.0