


# PER-C20L

## ■ Mini-PCI Module With Dual Ethernet Ports



### Specifications

Form Factor	Mini-PCI Type III A 2" x 2.35" (50.8 mm x 59.6 mm)
Controller	Intel® 82551ER (does not support Wake-on-LAN Function)/ optional Intel® 82551QM
Speed	Supports 10/100Base-TX, auto-negotiation
Function	IEEE 802.3x compliant flow control IEEE 802.1Q Virtual LAN Wake-on-LAN
Power Requirement	+3.3V
Operating Temperature	32°F ~ 140°F (0°C ~ 60°C)

### Features

- Mini-PCI Type III Interface
- 10/100Base-TX Ethernet x 2
- Pin-header for LAN Status LED

### Packing List


- LAN Cable
- Quick Installation Guide
- Utility CD
- PER-C20L

### Ordering Information

- **TF-PER-C20L-A10**  
Mini-PCI, 10/100Base-TX LAN Module, w/Intel® 82551ER, Rev A1.0

# PER-C10L

## ■ Mini-PCI Module With One Ethernet Port



### Specifications

Form Factor	Mini-PCI Type III A 2" x 2.35" (50.8 mm x 59.6 mm)
Controller	Intel® 82551QM / Realtek 8100C for 10/100Base-TX Ethernet Intel® 82541GI / Realtek 8110SC for 10/100/1000Base-TX Ethernet
Speed	Supports 10/100/1000Base-TX, auto-negotiation
Function	IEEE 802.3x compliant flow control IEEE 802.1Q Virtual LAN Wake-on-LAN
Power Requirement	+ 3.3V
Operating Temperature	32°F ~ 140°F (0°C ~ 60°C)

### Features

- Mini-PCI Type III Interface
- 10/100Base-TX or 10/100/1000Base-TX Ethernet x 1
- Wake-on-LAN Function
- Pin-header For LAN Status LED

### Packing List

- LAN Cable
- Quick Installation Guide
- Utility CD
- PER-C10L

### Ordering Information

- **TF-PER-C10L-A10**  
Mini-PCI, 10/100Base-TX LAN Module, w/Realtek, 8100C, Rev. A1.0
- **TF-PER-C10L-A10-01**  
Mini-PCI, 10/100/1000Base-TX LAN Module, w/Realtek, 8110SC, Rev. A1.0
- **TF-PER-C10L-A10-02**  
Mini-PCI, 10/100Base-TX LAN Module, w/Intel®, 82551QM, Rev. A1.0
- **TF-PER-C10L-A10-03**  
Mini-PCI, 10/100/1000Base-TX LAN Module, w/Intel®, 82541GI, Rev. A1.0