


PER-U00A

AC97 Audio Daughter Board + USB x 4

Audio Daughter Board/ USB Card

14

Accessories



Specifications

System	
Chipset	ALC655 AC97 CODEC
Line-out	50mW/20Ω Amplifier built in
Line-in	Shares with surround output, 50mW/ 20Ω Amplifier built in
MIC-in	Shares with Center and Left output, Auto detection
Universal Serial Bus	Four USB 2.0 ports, TYPE-A connectors for PER-U00A version
Surround	Surround output for PER-U00A-A11 version
Center	Center output for PER-U00A-A11 version
Power Requirement	ATX12V, 5V Required
Operating Temperature	32°F ~ 140°F (0°C ~ 60°C)

Features

- Meets Performance Requirements for Audio on PC99/2001 System
- Meets Microsoft® WHQL/WLP 2.0 Audio Requirements
- 16-Bit Stereo Full-duplex CODEC With 48KHz Sampling Rate
- Direct Sound 3D Compatible
- Compliant with AC97 2.3 Specifications
- 3 Phone Jacks and CD-in
- Line-in Shared with Surround Output, MIC-in Shared with Center and Left Output
- 4 USB Type-A Connectors Support (For PER-U00A Version)


Ordering Information

- **TF-PER-U00A**
AC 97 Audio Daughter Board
- **TF-PER-U00A-A12**
AC 97 Audio Daughter Board with 4 USB, Rev. A1.2

PER-T061

ECX Extension Board

ECX Proprietary Modules



Specifications

System	
Form Factor	ECX Extension Board (AAEON Proprietary)
Controller	Chrontel CH7308 (LVDS)/ CH7307 (DVI), Silicon Image Sil3132CNU (SATA)
LCD Interface	24-bit Dual-channel LVDS TFT LCD (LVDS version)
DVI	Yes, DVI-D x 1 (DVI version)
SATA	SATA II with RAID 0 & RAID 1
Serial Port	RS-232 x 4
USB	USB2.0 x 1
Board Size	3.2" (L) x 2.57" (W) (81.4mm x 65.3mm)

Packing List

- **9681T06100**
Cable Kit
 - 1709070500 SATA Cable
 - 1701100206 COM Port Cable
 - 1709100207 USB Cable
 - 1700200200 DVI Cable
- Quick Installation guide
- Utility CD
- PER-T061

Ordering Information

- **TF-PER-T061-A10**
ECX Extension Board LVDS Version
- **TF-PER-T061-A10-01**
ECX Extension Board DVI Version