


PER-V05V

Mini-PCI Video Module



Specifications

Form Factor	Mini-PCI Type 3 A 2" x 2.35" (50.8mm x 59.6mm)
Graphic Chipset	Volari™ Z9s (100 MHz)
Display	CRT output
Resolution	Up to 1600 x 1200 @ 85 MHz
Power Requirement	+3.3V
Operating Temperature	32°F ~ 140°F (0°C ~ 60°C)

Features

- Mini-PCI Type 3 Interface
- One VGA Output, Resolution Up To 1600 x 1200 @ 85 Hz
- Memory Size 32M DDR2

Packing List


- 1703150070
D-Sub Cable
- Quick Installation Guide
- Product CD
- PER-V05V

Ordering Information

- TF-PER-V05V-A11
Mini-PCI VGA Module, Rev. A1.1

PER-V30C

Mini-PCI Video Capture Module



Specifications

Form Factor	Mini-PCI Type 3 B 1.8" x 2.35" (50.9mm x 59.7mm)
Video Decoder	Philips SAA7131E
Video Input	CVBS & S-Video
Video Format Support	NTSC & PAL
Sample Rate	720 pixels/line
Software Support	Window® 2000/XP WDM Driver or DirectShow based application
Operating Temperature	32°F ~ 140°F (0°C ~ 60°C)

Features

- Mini-PCI Type 3 Interface
- Single Channel Video Capture with Philips SAA7131E
- NTSC/PAL Video Format Support

Packing List

- 1700090306
SVHS Cable
- Audio-in Cable
- RF-In Antenna Cable
- Product CD
- PER-V30C

Ordering Information

- TF-PER-V30C-A12
Mini-PCI, Single Channel Video Capture Module with Philips SAA 7131E Rev. A1.2