


EMB-QM67

Embedded Motherboard with Socket G2 (rPGA988B) 2nd Generation for Intel® Core™ i7/i5/Celeron® QC/ DC Processor



Features

- Socket G2 (rPGA988B) 2nd Generation for Intel® Core™ i7/i5/ Celeron® QC/ DC Processor
- Intel® QM67
- 204-pin Dual-Channel DDR3 1066/1333/1600MHz SODIMM x 2, Up to 8 GB
- Gigabit Ethernet x 2
- Intel® Integrated Graphics Engine Supports Dual View by VGA, DVI, HDMI, 24b, 2CH LVDS
- HD Audio
- SATA 3.0Gb/s x 2, Support RAID 0,1,5,10
- USB2.0 x 8, COM x 6
- PCI-Express [x4] x 1, Mini PCI-Ex 1, CFast™ x 1, TPM x 1 (Optional)



Specifications

System	
Form Factor	Mini-ITX motherboard
Processor	Socket G2 (rPGA988B) 2nd Generation for Intel® Core™ i7/i5/Celeron® QC/ DC processor
System Memory	204-pin Dual-Channel DDR3 1066/1333/1600 MHz SODIMM x 2, up to 8GB
Chipset	Intel® QM67
Ethernet	10/100/1000Base-TX, RJ-45 x 2
Audio	HD Audio Realtek ALC 892 Codec with phone Jack
BIOS	AMI BIOS 64Mbit SPI ROM
Watchdog Timer	Reset: 1 sec. ~ 255 min. and 1 sec. or 1 min./step
H/W Status Monitoring	Monitoring system temperature, voltage, and cooling fan status
Expansion Interface	PCI-E [x4] x 1, Mini PCI-Esocket x 1, CFast™ x 1, TPM Module x 1 (Optional)
Power Requirement	DC 12V/ ATX
Power Consumption	66W @ Intel® Core™ i7-2710QE, DDR3 1333/4GB, DC
Board Size	6.7" x 6.7" (170mm x 170mm)
Gross Weight	1.32 lb (0.6Kg)
Operating Temperature	32°F ~ 140°F (0°C ~ 60°C)
Storage Temperature	-4°F ~ 158°F (-20°C~70°C)
Operating Humidity	5% ~ 95% relative humidity, non-condensing
MTBF (Hours)	70,000
Display	
Chipset	Intel® Core™ i7/i5 + QM67
Memory	Shared system memory up to 256MB
Graphic Engine	2nd Generation Intel® Core™ i7/i5/Celeron® integrated Gen 5.75 graphics
Resolution	Up to 2048 x 1536 @ 60 Hz for CRT Up to 1366 x 768 @ 60 Hz for LCD
Output Interface	DB-15 x 1, DVI-D x 1, HDMI x 1, LVDS x 1
I/O	
Storage	SATA 6.0Gb/s x 2, SATA 3.0Gb/s x 2, CFast™ x 1
Serial Port	RS-232 x 5 (box headers) RS-232/422/485 x 1, supports 5/12V on the 9th (on I/O)
KB & Mouse	Keyboard x 1, Mouse x 1
USB	USB2.0 x 8
Digital I/O	8-bit Programmable
Audio	Audio Jack x 3 (Mic-in, Line-in, Line-out)

Packing List

- 1709070800
SATA Cable
- 1702151201
SATA Power Cable
- M20QM6700
Metal I/O Bracket
- 9657666600
Jumper Cap
- 1701100206
COM Cable
- Product DVD
- EMB-QM67

