


IMBA-Q77

Industrial Motherboard with Intel® 3rd Generation Core™ i7/i5/i3 Processor



Features

- Intel® 3rd Generation Core™ i7/i5/i3 LGA 1155 Processor
- Intel® Q77
- Dual-Channel DDR3 1600 (Only for 3rd Generation CPU)/1333/1066MHz DIMM x 4, Up to 32 GB
- 10/100/1000Base-TX x 2 (LAN1 Supports Intel® iAMT 8.0)
- Three Independent Displays With VGA (On-board Only), DisplayPort™, DVI-D
- SATA 3.0Gb/s x 4, SATA 6.0Gb/s x 2, Support RAID 0,1,5,10
- USB2.0 x 8, USB3.0 x 4, COM x 6, LPT x 1, IrDA Tx/Rx Header x 1
- PCI-Express [x16] x 1, PCI-Express [x4] x 1, PCI-Express [x1] x 2, PCI x 3
- TPM 1.2 (Optional)



Specifications

System	
Form Factor	ATX
Processor	Intel® 3rd generation Core™ i7/i5/i3 LGA 1155 Processor
System Memory	Dual-channel DDR3 1600(only for 3rd gen CPU)/1333/1066MHz DIMM x 4, up to 32GB, Unbuffered Memory
Chipset	Intel® Q77
Ethernet	LAN1: Intel® 82579 (Supports Intel® iAMT 8.0) , LAN2: Intel® 82583V, 10/100/1000Base-TX, RJ-45 x 2
BIOS	AMI SPI Flash BIOS-128Mb ROM
Expansion Interface	PCI-Express[x16] x 1, PCI-Express[x4] x 1, PCI-Express[x1] x 2, PCI x 3, TPM 1.2 onboard (Optional)
Watchdog Timer	System reset : 1~255 steps by software programming
H/W Status Monitoring	System temperature, Voltage, and Cooling fan status
Battery	Lithium battery
Power Requirement	ATX Standard 24-pin connector x 1, 4-pin +12V connector x 1, CPU fan x 1, System fan x 1 with 4-pin wafer Supports SMART FAN control
Power Consumption	40W with Intel® Core™ i7-3770@3.4GHz
Operation Temperature	32 °F ~ 140 °F (0 °C ~ 60 °C)
Storage Temperature	-4 °F ~ 158 °F (-20 °C ~ 70 °C)
Operation Humidity	5% ~ 90% relative humidity, non-condensing
Board Size	12"(L) x 9.6"(W)(305mm x 244mm)
Gross Weight	1.76 lb (0.8 Kg)
MTBF (Hours)	56,000
Display	
Chipset	Intel® 3rd generation Core™ i7/i5/i3 Processor + Intel® Q77
Graphic Engine	Intel® HD Graphic Support, Three independent display
Resolution	Up to 2048 x 1536 @ 75Hz for CRT, Up to 2560 x 1600 @ 85Hz for DisplayPort™, 1080P for HDMI (optional)
Output Interface	Onboard VGA, DVI-D x 1, DisplayPort™ x 2 (HDMI optional)
I/O	
Storage	SATA 6.0Gb/s x 2, SATA 3.0Gb/s x 4, Support RAID 0/1/5/10
Serial Port	COM x 6 (Box header x 5, external DB-9 x 1), COM 1: RS-232/422/485 (external DB-9), COM 2~6 : RS-232 (Box header)
KB & Mouse	Keyboard x 1 & Mouse x 1
USB	USB2.0 x 8, USB3.0 x 4
Audio	Audio Jack x 3 (Mic-in / Line-in / Line-out)
Digital I/O	8-bit programmable (4-in / 4-out)

Packing List

- 1700100353
USB2.0 Cable
- 1701100305
COM Port Cable
- 1709070800
SATA Cable
- Product DVD
- IMBA-Q77

