


# PER-V02B

## Mini PCI TTL to DVI LCD Signal Conversion Module



### Specifications

Form Factor	Mini PCI Type III A 2" x 2.35" (50.8 mm x 59.6 mm)
Signal Conversion Chipset	Silicon Image™ Sil1160CTU
Power Requirement	+3.3V
Operating Temperature	32°F ~ 140°F (0°C ~ 60°C)

### Features

- **TTL to DVI LCD Signal Conversion**
- **Resolution up to 1600 x 1200**

### Packing List

- TTL LCD Cable
- Quick Installation Guide
- PER-V02B

### Ordering Information


- **TF-PER-V02B-A10**  
Mini PCI, TTL to DVI LCD, Signal Conversion Module, Rev. A1.0

### Optional Accessories

- **1700200200**  
DVI Cable
- **1703400207**  
TTL Cable for PFM-530I, PFM-535I, PFM-620S, GENE-6310B, GENE-6320, GENE-6350, PCM-6892A/B, PCM-6893, ETX-625

# PER-V05V

## Mini PCI Video Module



### Specifications

Form Factor	Mini PCI Type III A 2" x 2.35" (50.8mm x 59.6mm)
Graphic Chipset	Volari Z9s (100Mhz)
Display	CRT output
Resolution	Up to 1600 x 1200 @85MHz
Power Requirement	+3.3V
Operating Temperature	32°F ~ 140°F (0°C ~ 60°C)

### Features

- **Mini PCI Type III Interface**
- **One VGA output, Resolution Up to 1600 x 1200@85Hz**
- **Memory Size 32M DDRII**

### Packing List

- D-Sub Cable
- Quick Installation Guide
- Utility CD
- PER-V05V

### Ordering Information

- **TF-PER-V05V-A10**  
Mini PCI Video Module, Rev. A1.0