



Advanced Embedded Fanless Controller With PCI And PC/104+ Expansion



Features

- Fanless Design
- Wide Power Input Range
- PCI Slot x 1, PC/104+ Socket x 2 (Stack)
- High Performance; Up To Celeron® M CPU
- Compact Size
- Ideal For Vehicle Application
- ATX Power Function




Specifications

System	
Processor	Intel® Celeron® M Processor, up to 1.5 GHz
System Memory	DDR SODIMM x 1, Max. 1 GB
Expansion	PCI x 1, PC/104+ x 2 (Stack)
VGA/ Keyboard/ Mouse	VGA x 1, PS/2 Keyboard & Mouse x 1
Ethernet	10/100Base-TX, RJ-45 x 1
SSD	CompactFlash™ x 1
Hard Disk Storage	2.5" SATA/IDE Hard Disk Drive bracket x 1 in system
Serial	RS-232 x 3, RS-232/422/485 x 1
Audio	Mic-in/ Line-in/ Line-out, requires an extension cable
USB	USB2.0 x 4
System Control	Power on/ off switch x 1, Reset button x 1
LED Indicator	Power LED x 1, Hard Disk Drive active LED x 1
Watchdog Timer	Generates a time-out system reset, setting via software
Power Supply	1. DC Input: Internal DC-DC Converter (Default) Input voltage: 9V DC ~ 30V DC
	2. AC Input: External Power Adapter (Optional) Input voltage: 100V AC ~ 240V AC @ 50 ~ 60Hz
Power Consumption	Intel® Celeron® M 600 MHz 1.6A@12V
MTBF (Hours)	40,000
OS Support	Windows® XP, Windows® XP Embedded, WinCE, Linux
Mechanical	
Construction	Rugged Aluminum Alloy chassis
Color	Mustard
Mounting	Wallmount
Dimension	8.43" (W) x 3.73" (H) x 9.36" (D) (214mm x 94.8mm x 237.8mm)
Carton Dimension	13.23" (W) x 11.57" (H) x 10.24" (D) (336mm x 294mm x 260mm)
Net Weight	12.4 lb (5.63 Kg)
Environmental	
Operating Temperature	-4°F ~ 140°F (-20°C ~ 60°C) (Celeron® M 1.5 GHz/ CompactFlash™) -4°F ~ 131°F (-20°C ~ 55°C) (Celeron® M 1.5 GHz/ HDD)
Storage Humidity	5~95%@40°C, non-condensing
Vibration	5 grms/ 5 ~ 500Hz/ random operation (CompactFlash™)
	1 grms/ 5 ~ 500Hz/ random operation (With Hard Disk Drive)
Shock	50 g peak acceleration (11 msec. duration) (CompactFlash™)
	20 g peak acceleration (11 msec. duration) (Hard Disk Drive)
EMC	CE/FCC class A

AEC-6905

Dimension

Unit: mm



Ordering Information

- **TF-AEC-6905-A1-1010**
Embedded Controller, Celeron® M 1.5 GHz, Fanless, 1 PCI, 1 PC/104+, DC 9-30V, 512 MB RAM
- **TF-AEC-6905-A2-1010**
Embedded Controller, Celeron® M 600 MHz, Fanless, 1 PCI, 1 PC/104+, DC 9-30V, 512 MB RAM

Optional Accessories

- **1757912001**
AC Adapter (120W), Input AC 100~240V; Output: DC 19V
- **1702031830**
Power Cord (US type)
- **1702031831**
Power Cord (European type)
- **1702031810**
Power Cord (Japanese Type)