# TF-PER-M05

### **TalkCam**



# **Specifications**

Main Specifications	
Interface	USB2.0
Sensor	1/4" CMOS Sensor
Effective pixels	1.3 Mega Pixels
Max Resolution	1280 x1024 (SXGA)
Max Frame Rate	30fps (640x480:30fps, 1280x1024: 15fps)
Lens view angle	54°
Focus range	4cm to infinity
White Balance	Auto
Auto Exposure (AE)	Auto
USB cable length	150cm
Weight	60g(USB cable included)

Dimension	1.57" (H) x 2.56" (W) x 4.65" (D) (40mm x 65mm x 118mm) (USB cable excluded)
Working temperature	41°F ~ 104°F (5°C ~ 40°C)
Working humidity	20%~80%
Rating voltage	5V
Rating power consumption	1500mW
Rating input current	300mA

#### **Ordering Information**

• TF-PER-M05 TalkCam

# **TF-PER-M08**

### **Handheld Scanner**



## **Specifications**

Main Specifications	
Light Source	650 nm visible laser diode
Depth of Field	35 – 200 mm for UPC/EAN 100%
Scan Angle	52°
Scan Rate	500 scans per second
Pitch/Roll/Skew Angle	65° / 30° / 65°
Minimum Bar Width	5 mil @ PCS 90% (Code 39)
Print Contrast	30% @ UPC/EAN 100%
Indicators (LED)	Three-color LED (green, red & blue)
Beeper Operation	Programmable tone & beep time
System Interfaces	Keyboard, RS-232C, USB1.1, wand

#### **Features**

- Powerful Scanning Performance
- Z-SCAN Technology
- Streamlined, Rugged Design
- LED Scan Indicator and Programmable Beeper
- Flexible Communications

### **Ordering Information**

• TF-PER-M08

Handheld Scanner