


IMBM-B75A

Micro-ATX Industrial Motherboard with Intel® 2nd/3rd Generation Core™ i7/ i5/ i3/ Pentium® Processor

10

Embedded & Industrial Motherboards



Features

- Intel® 2nd/3rd Generation Core™ i7/ i5/ i3/ Processors
- Intel® B75
- DDR3 1600/1333/1066 MHz DIMM x 4, Max. 32GB
- Dual/Three Independent Display: VGA, HDMI x 3
- Gigabit Ethernet x 2
- Onboard TPM
- SATA 6.0Gb/s x 1, SATA 3.0Gb/s x 4
- USB3.0 x 4, USB2.0 x 6



Specifications

System	
Form Factor	Micro ATX
Processor	Intel® 2nd/3rd Generation Core™ i7/ i5/ i3/ Processors
System Memory	Dual-Channel DDR3 1066/1333 DIMM x 4(Up to 32GB) Un-buffered Memory
Chipset	Intel® B75
I/O Chipset	ITE IT8783F
Ethernet	Realtek 8111F, Gigabit Ethernet, RJ-45 x 2
BIOS	AMI BIOS SPI flash ROM - 64Mb
Wake On LAN	Yes
Watchdog Timer	1~255 steps, can be set with software on Super I/O
TPM	Yes
H/W Status Monitoring	Temperature Monitor on CPU/Chassis Voltage Monitor on Vcore /5V/3.3V/12V Fan Monitor on CPU/Chassis
Expansion Interface	PCIe [x16] x 1, PCIe [x4] x 1, PCI x 2
Battery	Lithium battery
Power Requirement	24-pin ATX connector x 1, 8-pin ATX 12V connector x 1, CPU fan x 1, System fan x 2 with 4-pin wafer for Smart FAN support
Power Consumption	—
Board Size	9.6" x 9.6" (244 mm x 244 mm)
Gross Weight	1.76 lb (0.8 Kg)
Operation Temperature	32°F ~ 140°F (0°C ~ 60°C)
Storage Temperature	-40°F ~ 185°F (-40°C ~ 85°C)
Operation Humidity	0% ~ 90%RH, non-condensing
MTBF (Hours)	83,000
Display	
Graphic Engine	Intel® Graphics Media Accelerator
Resolution	VGA: 1920 x 1200 @60Hz HDMI: 1920 x 1080 @60Hz
Output Interface	VGA x 1, HDMI x 3
I/O	
Storage	SATA 6.0 Gb/s x 1, SATA 3.0 Gb/s x 4
Serial Port	COM 1: RS-232/422/485 x 1(external DB-9) COM 2~5: RS-232 x 4(Box header)
Parallel Port	SPP/EPP/ECP Mode
USB	USB3.0 x 4, USB2.0 x 6
Digital I/O	8-bit programmable (4-in / 4-out)
PS/2 Port	PS/2 Port x 2 (Keyboard & Mouse)
Audio	Line-in, Mic-in, Line-out


Packing List

- SATA Cable
- COM Port Cable
- I/O Shield
- Product CD
- IMBM-B75A

IMBM-B75A

Dimension

Unit: mm



Ordering Information

Part number	CPU	RAM	Fan/Fanless	Display	Storage	LVDS	LAN	USB	RS-232	RS-232/422/485	Expansion Slot	Power	Temp.
IMBM-B75A-A20-G2	Socket	DIMM	Fan	VGA, HDMI x 3	SATA 2 x 4, SATA 3 x 1	—	GbE x 2	USB2.0 x 6, USB3.0 x 4	4	1	PCI-E [x16] x 1, PCI-E [x4] x 1, PCI x 2	ATX	0°C ~ 60°C

Optional Accessories

- **175921156B**
CPU Cooler
- **1709070800**
SATA Cable
- **1701100260**
COM Port Cable
- **1701260305**
LPT Cable
- **1709100330**
USB2.0 Cable
- **1700190450**
USB3.0 Cable