


HDMI IN Carrier Board

HDMI IN Carrier Board


UPCR-HDMI-A10-0001

2-pin power wafer



HDMI

FPC 61-pin



Features

- FPC 61-pin MIPI CSI
- HDMI 2.0
- Windows®10



Specifications

System	
	FPC 61-pin MIPI CSI x 1 (Lontium.LT6911UXC) 2-pin Power Wafer x 2 HDMI 2.0 x 1 Color Format: CSC disabled: RGB565/666/888, YUV422 8/10-bit, Legacy YUV420 8-bit CSC enabled: RGB565/666/888, YUV422 8-bit Video Resolutions 3840×2160p@30fps 1920×1200@30fps 1920×1080@30fps 1680×1050@30fps 1440×900@30fps 1366×768p@30fps 1280×1024p@30fps 1280×960p@30fps 1280×800p@30fps 1280×768p@30fps 1280×720p@30fps 1280×600p@30fps 1152×864p@30fps 1024×768p@30fps 800×600p@30fps/720×576i@60fps *Once change resolution or frequency please reboot or unplug and plug in HDMI IN carrier board
I/O	
Dimension	1.9" x 0.9" (49mm x 23mm)
Net Weight	0.44 lb. (0.2Kg)
Gross Weight	0.88 lb. (0.4Kg)
Operating Temperature	32°F ~ 140°F (0°C ~ 60°C), 0.5m/s airflow
Operation Humidity	10% ~ 80% relative humidity, non-condensing
Certification	—

Packing List

- HDMI IN Carrier Board
- FPC cable
- Power cable

Ordering Information

Part Number	Description
UPCR-HDMI-A10-0001	HDMI IN carrier board for UP Squared i12, UP Squared Pro 7000, UP Xtreme i12
9651HDBK01	HDMI IN bracket kit