

ACD-110D

10.1" Multi-Touch Display Monitor

Preliminary



Features

- 10.1" LED B/L LCD
- P-CAP Multi-touch screen
- Multiple mounting: VESA 75

Max Resolution	1280 x 800
Max. Colors	262K colors
Luminance	350 cd/m ²
Viewing Angle	160°(H)/ 160°(V)
Back Light	LED
Back Light MTBF (hours)	50,000
Touch Screen	
Type	5-wire, Analog Resistive
Light Transmission	>80%
Light Time	35 Million activations

Specifications

System	
Input Signal	VGA, DVI-D
On Screen Display Control	Auto, Menu, Up, Down, LCD On/Off
I/O Connector	DB15: VGA x1 DVI-D x1 USB Mini A x1 Power input x1
OS support	Windows® XP 32 bit Windows® 7 32/64 bit Windows® 8 32/64 bit Linux Ubuntu 12.04
Mechanical	
Construction	IP65 aluminum front bezel & SGCC chassis
Mounting	VESA75
Dimension	9.97" x 6.72" x 1.57" (253.21mm x 170.81mm x 40mm)
Gross Weight	4.4 lb (2 kg)
Net Weight	2.64 lb (1.2 kg)
Environmental	
Operating Temperature	32°F ~ 113°F (0°C ~ 45°C) w/o airflow 32°F ~ 122°F (0°C ~ 50°C) w/ airflow
Storage Temperature	14°F ~ 140°F (-10°C ~ 60°C)
Storage Humidity	5%~90% @40°C, non-condensing
Vibration	1 g rms/ 5~ 500Hz/ operation – With HDD
Shock	15 G peak acceleration (11 msec. duration)
EMC	CE/FCC class A
Power Supply	
DC input	DC 12V with Lockable Power adapter
LCD	
Display type	10.1" TFT LCD

Ordering Information

ACD-110DHTT-A1-1010

10. 1" WXGA . Ultra-Slim Touch. Monitor w/ P-CAP T/S

Packing List

ACD-110D

Power Adapter
USB Cable for Touch Screen
VGA Cable

Optional Accessories

- 1702031802
Power Cord (US Type)
- 1702031803
Power Cord (European Type)
- 170203180E
Power Cord (Japan Type)