

# ACS-2U01

High Performance Mini-ITX Embedded Chassis



## Features

- Supports Mini-ITX Motherboard Standard I/O Shielding
- Supports 1 x 3.5"/ 2 x 2.5" Internal HDD Bays
- 1 LP or FH Add-On Card Supported For Expandability
- High-performance Thermal Solution with Low Noise Fan
- Embedded with Flex ATX Power / (Optional DC Power Adapter)
- Supports Wallmount Bracket (Optional)



## Specifications

System	
M/B Form Factor	Mini-ITX
Dimension (W x D x H)	10.04" x 9.06" x 3.46" (255mm x 230mm x 88mm)
Color	Black/Silver
Processor Support	TDP: 84W
Drive Bay	3.5" x 1/ 2.5" internal HDD bay x 2; 2.5" internal HDD bracket (optional) x 1
Expansion Slot	Low-profile add-on card x 1 /Full-height add-on card via riser card (optional)
System Cooling	80mm PWM fan x 1
Front I/O	USB 2.0 x 2 or USB 3.0 x 2 Audio x 2
Button	Power button x 1 Reset button x 1
LED	Power LED x 1
Power Supply	Flex-ATX power supply
Others	Antenna hole x 2(reserved)
Environment	Operating Temperature : 0°C ~ 40°C (-32°F ~ 104°F) Storage Temperature : -40°C ~ 70°C (-40°F ~158°F) Operating Humidity : 5% ~ 90% (non-condensing) Storage Humidity : 5% ~ 95% (non-condensing)

## Packing List

- Screw Bag
- ACS-2U01