

NIM-S26A

Intel® XL710 PCI-Express 10G SFP+ 4 Ports Module



Features

- PCI-Express Host Interfaces
- 10G SFP+ Fiber Port x 4



Network Appliance Options

- **FWS-8500**
Network Appliance, Intel® Coletto Creek 8925, 8 NIM Slots, 2U, 650W Redundant

Specifications

Main Specification	
Form Factor	10G Fiber Module
Main Chipset	Intel® XL710 Ethernet Controller x 1
Bypass	—
Host Interface	PCI-Express [x8]
LAN Port	SFP+ 10 GbE Connector x 4
Indicator	LED x 4 for Active/Link
Qualification	CE/FCC Class A
Operation Temp.	32°F ~ 104°F (0°C ~ 40°C)
Dimension	5.71" x 3.03" (145mm x 77mm)

Ordering Information

- **NIM-S26A-A10-01**
Intel® XL710 PCI-Express 10G SFP+ 4 Ports Module for FWS-8500

NIM-S26B

Intel® XL710 PCI-Express 40G QSFP 2 Ports Module



Features

- PCI-Express Host Interface
- 40 GbE QSFP Fiber Port x 2



Network Appliance Options

- **FWS-8500**
Network Appliance, Intel® Coletto Creek 8925, 8 NIM Slots, 2U, 650W Redundant
- **FWS-7400**
1U Rackmount Network Appliance, Intel® H81 with 1 Network Interface Modules
- **FWS-7820**
1U Rackmount Network Appliance, Intel® C236 with 4 Network Interface Modules
- **FWS-7810/7811**
1U Rackmount Network Appliance, Intel® C226 with 1 Network Interface Modules
- **FWS-7520**
1U Rackmount Network Appliance, Intel® Broadwell DE with 3 of NIM appliance

Specifications

Main Specification	
Form Factor	40G Fiber Module
Main Chipset	Intel® Fortville XL710 Ethernet Controller x 1
Bypass	—
Host Interface	PCI-Express [x8]
LAN Port	QSFP 40GbE Connector x 2
Indicator	LED x 2 for Active/Link
Qualification	CE/FCC Class A
Operation Temp.	32°F ~ 104°F (0°C ~ 40°C)
Dimension	5.71" x 3.03" (145mm x 77mm)

Ordering Information

- **NIM-S26B-A10-01**
Intel® XL710 PCI Express 40GbE QSFP 2 Ports Module for FWS-8500
- **NIM-S26B-A10-F20-0002**
Intel® XL710 PCI Express 40GbE QSFP 2 Ports Module for FWS-7820
- **NIM-S26B-A10-F20-0001**
Intel® XL710 PCI Express 40GbE QSFP 2 Ports Module for FWS-7520
- **NIM-S26B-A10-F20-0003**
Intel® XL710 PCI Express 40GbE QSFP 2 Ports Module for FWS-7400/7810/7811