

Rugged Docking Station (For RTC-600A)



Features

- Flexible for User to Tilt A Suitable Viewing Angle
- USB x 4, and Ethernet Ports Extension, COM Port and DC-IN
- LED Indicate Charging Status
- 75mm VESA Hole Pattern Supports Mounting
- Easy to Install, For Quick Repair & Ease in Maintenance



Specifications

System	
I/O	USB 2.0 x 2, RJ-45 jack for 10/100Base-TX Ethernet x 1, RS-232 x 1
DC Input	DC in 12V
LED Indicator	Blue: Tablet in, Orange: Tablet out
Mechanical	
Color	Black
Construction	PC
Dimensions (W x H x D)	8.7" x 4.37" x 1.73" (221mm x 111mm x 44mm)
Gross Weight	—
Environmental	
Operating Temperature	32°F ~ 104°F (0°C~40°C)
Storage Temperature	14°F ~ 122°F (-10°C~50°C)
ESD	Air +/- 8KV, Contact +/- 4KV
EMC/ Safety	CE/FCC Class B/UL
Power Supply	
AC/DC Adapter	AC Power input: 100V-240V, 50Hz-60Hz, 36W DC Power output: 12V
DC/DC Adapter	—

Ordering Information

Part Number	Applied Models	Stand	Expansion I/O
RDS-1210-0000	For RTC-600 Series	Yes	COM x 1, USB x 2, LAN x 1

Dimension

Unit: mm

