

# UP Nexus WCL Edge PRELIMINARY

UP Nexus WCL System with Intel® Core™ processors (Series 3)



Front View



Rear View



## Features

- Intel® Core™ processors (Series 3)
- Onboard LPDDR5 Memory up to 48GB
- Onboard UFS Storage up to 256GB
- 2.5GbE x 2 (Intel® Ethernet Controller I226-IT)
- USB 3.2 x 2 (Type A x 2)
- USB 3.2 Gen 2x2 (Type-C) x 1
- 40-pin GPIO x 1
- HDMI 2.1 (TMDS) x 2 / DP 1.4a via USB Type-C
- RS-232/422/485 x 2
- M.2 2230 E-Key, M.2 2280 M-Key, M.2 2242 M-Key
- TPM 2.0
- 12V-24V DC-in




## Specifications

System	
CPU	Intel® Core™ 7 processor 350 Intel® Core™ 5 processor 320
Memory	Up to 16GB onboard LPDDR5
Graphics	Intel® Graphics
Storage	Up to 256GB onboard UFS
Ethernet	2.5GbE x 2 (Intel® Ethernet Controller I226-IT)
WiFi/BT	Optional with M.2 2230 E-Key x 1
Expansion Slot	M.2 2230 E-Key x 1 (CNVI, PCIe Gen 4 [x1], USB 2.0, UART) M.2 2280 M-Key x 1 (PCIe Gen 4 [x2]) M.2 2242 M-Key x 1 (PCIe Gen 4 [x1])
Security	TPM 2.0
OS Support	Windows 11 Ubuntu 24.04
I/O Placements	
USB	USB 3.2 Gen 2 (Type-A) x 2 USB 3.2 Gen 2x2 (Type-C) x 1
Display Port	HDMI 2.1 (TMDS) x 1 DP 1.4a via USB Type C
Ethernet	2.5GbE x 2 (Intel® Ethernet Controller I226-IT)
COM	RS-232/422/485 x 2
Audio	Audio Jack x 1 (Mic-in+Line-out)
GPIO	40-pin GPIO x 1
Power Supply	
Power requirement	12V-24V DC-in (Lockable plug)
Power supply type	AT/ATX
Power Consumption (Typical)	TBD
Mechanical	
Mounting	—
Dimensions (WxHxD)	TBD
Net Weight	TBD
Gross Weight	TBD
Environment	
Operating Temperature	-4°F ~ 140°F (-20°C ~ 60°C) / 0.7 airflow
Operating Humidity	0% ~ 90% relative humidity, non-condensing
Storage Temperature	-4°F ~ 158°F (-20°C ~ 70°C)
MTBF	TBD
Certification	CE/FCC Class A, RoHS Compliant, REACH



## Dimension

Unit: mm



## Ordering Information

Part Number	CPU	Memory	Storage	Operating Temp.	Cooling
UPN-WCL01-SYS-A10-350-32128	Intel® Core™ 7 processor 350	32GB	128GB	-20°C ~ 60°C	Passive heatsink
UPN-WCL01-SYS-A10-350-16128	Intel® Core™ 7 processor 350	16GB	128GB	-20°C ~ 60°C	Passive heatsink
UPN-WCL01-SYS-A10-320-16128	Intel® Core™ 5 processor 320	16GB	128GB	-20°C ~ 60°C	Passive heatsink

## Optional Accessories

Part Number	Description
1255X00032	(TF)AC/DC Adapter.Input AC.100~240V.Output DC.12V.MAX 72W.6.0A.180D.W/ LOCK.EDAC.EA10681U(120)
170X000799	(TF)Power Cord. 3P. 125V. 10A. 180D. USA. 1. 8M. I-SHENG. SP305B/IS-14N SVT 18/3 60C CT-12 Black
170X001024	(TF)EU Power Cord.3P.250V.10A.VDE.1.8M.I-SHENG.SP23/IS-14N H05VV-F 3G 0.75 CT-12.Black
170X001231	(TF)China Power Cord.3P.250V.10A.180D.1800mm.I SHENG ELECTRIC.SP-506A+IS-14N
170X000806	(TF)Power Cord. 3P. 125V. 7A. 1. 8M. I-SHENG. U4NCB3T6B1218002. SP305B/IS-14N VCTF. Black. BSMI
170X000803	(TF)Power Cord.3P.125V/7A.PSE Certificate.1.8M.I-SHENG.U4NCB3P6C1218002. SP305B/IS-14N VCTF 0.75/3 Black 1.8M
170X000810	(TF)Power Cord.3P.250V.16A.Korea.1.8M.I-SHENG.SP23/IS-14N H05VV-F 3G 0.75 CT-12 Black
170X000805	(TF)Power Cord.3P.250V.10A.SWISS.1.8M.I-SHENG.SP-027C/IS-14N H05VV-F 3G 0.75mm CT-12 Black

## Packing List

- UP Nexus WCL Edge