



### Features

- ATX Form Factor
- For Evaluation Purpose
- Debug port Display
- Supports DiskOnChip2000
- Supports One Type II Compact Flash Memory
- Onboard Power ON and Reset Bottom
- 16-bit DIO, Wake-On-LAN

### Specifications

#### System

- **SSD** Type II CompactFlash x 1  
Supports DiskOnChip2000
- **Expansion Interface** 32-bit PCI Slot X 4  
16-bit ISA slot X 3 (One space share with PCI)
- **Ethernet** 10/100Base-T RJ-45 connector x 1
- **Battery** Lithium battery
- **Size** 12" (L) X 7.5" (W) (304.8mm x 190.5mm)
- **Operating temperature** 32°F to 140°F (0°C to 60°C)

#### I/O

- **MIO** EIDE (UDMA100) x 2, FDD x 1, KB x 1, Mouse x 1, Serial Port x 4, Parallel x 1
- **Audio** Line in x 1, Line out x 1, Mic x 1
- **USB** Onboard 2 USB 1.1 ports
- **Power connector** Standard ATX and AT Power Connector

#### Display

- **CRT Interface** D-SUB 15 female
- **LCD Interface** One 30 pin DF13 Connector for LVDS Panel
- **TV-out** 6 pin JST2.0 Connector

#### Ordering information

##### Standard

- **ECB-2600** ATX Carrier Board for ETX CPU Modules with 6 Expansion Slots

##### Optional

- **Cable Kit for ECB-2600**