

Display Monitor Spec Template for 2004 Master Catalogue

AP-LDLD1041-01

10.4" Display Monitor, 1500 nits, AC, Housing

[Product photo with point-outs; hand-made is working]



Features (no more than 5~7 items)

- Very High Brightness
- High Contrast Ratio
- Short Response Time
- Wide Viewing Angle
- Sunlight Readable

System Specifications

- **Construction**
Stainless steel chassis & aluminum alloy front panel
- **Input Signal**
RGB, Composite video, S-Video
- **OSD Control**
Brightness, Contrast, H/V-position, Color, Phase, Clock, Management

- **Mounting**
Panel Mount
- **Power Supply**
External 50W power adapter
- **OS support**
MS DOS, Windows 98/SE, Windows NT4.0, Windows 2000, Windows XP
- **Dimension (W x H x D)**
340 x 228 x 54.2mm
- **Net Weight**
3.15Kg

Power Supply

- **External Power Adaptor:**
 - Input: 100 to 240 ±10% Vac, Full Range
 - Output: +12Vdc@5A

LCD Specifications

- **Model**
AP-LDLD1041-01
- **Display type**
10.4" color TFT LCD
- **Max. resolution**
800 x 600
- **Max. colors**
262K
- **Dot size (mm)**
0.264 x 0.264

- **Luminance (cd/m²)**
1500 (TYP)
- **Viewing angle**
120 ° (Horizontal)
100 ° (Vertical)
- **Brightness control**
Yes

Environment Specifications

- **Operating temperature**
0 ° ~ 50 (32~122 °C)
- **Storage temperature**
-20 ° ~ 60 (-4~140 °C)
- **Operating humidity**
10 to 90% @40 °C, non-condensing, without touchscreen
- **Vibration**
1.5G / 10Hz ~ 200Hz~10Hz (30 min for each Axis) / non-operation
- **Shock**
50G/20ms, half-sin, one time

Ordering Information

AP-LDLD1041-01

10.4" Display Monitor, 1500 nits, AC, Housing