


# PER-1110

Riser card for PCM-4896/4896L/5896/6890B/6892/6893/  
6894/6896



## Features

- Supports two PCI master slots
- Supports AD select

1

Compact Board

2

Sub Compact Board

3

Full-Size CPU Card

4

Half-Size CPU Card

5

Media PC

6

Embedded ATX Board

7

PC/104 Module

8

Mini PCI Module

9

Accessory

# PCM-3538T

DVO LVDS Transmitter/Receiver Module



## Features

- Using transmitter device module *THC63LVDM83A* chipset, transmitter converts 28 bit of CMOS/TTL data into LVDS data stream
- Scalable Bandwidth: VGA (640 x 480) to SXGA (1280 x 1024)
- Supports LVDS channel (3 data pairs & 1 clock pair) for 18/24 bit LVDS panel or up to two channel for 18/24/36/48 bit LVDS panel
- Cable Distance support: 5M or above (depend on cable quality)
- Wide frequency range:
  - One channel (20 ~ 85 M Hz)
  - Two channel (20 ~ 170 M Hz)
- 28:4 Data channel compression at up to 298 MB per second throughput.
- Input port using TTL signal with DF13 connector (2x20, 2x10, 2x5).
- Output LVDS differential signal for LVDS panel