



## Features

- Onboard AMD 486DX5-133 CPU (SQFP)
- SM712 LCD controller with 2MB memory
- One 10/100Base-T Fast Ethernet
- Supports DiskOnChip® up to 1GB and Type II CompactFlash Memory
- Four COM Ports
- PC/104 expansion connector

## Specifications

### System

- **CPU** AMD DX5-133 (SQFP)
- **System Memory** FPM/EDO onboard 16MB, SIMM x 1, Max. 64MB
- **2<sup>nd</sup> Cache Memory** Onboard 128KB L2 Cache
- **Chipset** ALi 1487/1489
- **I/O Chipset** ITE IT8661F, Fully 16-bit I/O decoded
- **BIOS** AMI 128KB Flash BIOS
- **Ethernet** Realtek RTL8139C, 10/100Base-T RJ-45 connector x 1
- **SSD** Supports DiskOnChip® up to 1GB, Type II CompactFlash Socket
- **Watchdog Timer** Can generate a system reset, IRQ15 or NMI
- **Expansion Interface** ISA interface, PC/104 connector x 1
- **Battery** Lithium battery
- **DMA** 7 DMA channels (8237 equivalent)
- **Interrupt** 15 interrupt levels (8259 equivalent)
- **Power supply voltage** +5V (4.75V to 5.25V), -12V, +3.3V, AT.
- **Size/ Weight** 7.3" (L) x 4.8" (W) (185 mm x 122 mm), 0.66lb. (0.3Kg)
- **Operating temperature** 32°F to 140°F (0°C to 60°C)

### I/O

- **MIO** IDE x 1, FDD x 1, KB+Mouse x 1, RS-232 x 3, RS-232/422/485 x 1, Parallel x1

### Display

- **Chip** SM-712
- **Memory Size** Built in 2MB SGRAM
- **Resolution** 1024 x 768@ 16bpp colors
- **LCD Interface** 36 bit TFT/DSTN/MONO LCD panel

## Packing List

- IDE cable
- FDD cable
- Parallel Port cable
- Serial Port cable (x 2) 9657456000
- Serial Port cable (x 2) 1701100305
- KB/Mouse cable 1700060192
- Quick Installation Guide
- Utility CD