

The Industrial Platform that fit your needs



Dimension: 8.35" (W) x 2.53" (H) x 4.21" (D)


BOXER
AEC-6820
Fanless Embedded
Control PC

- Transmeta Engine
- WinCE.net / CFD / Optional HDD kit
- 2 PCMCIA slots for expansion
- Ethernet / 2 COM / 4 USB / Audio
- Operating Temperature: -15~70 degree C
- Anti-vibration up to 6 g rms / Anti-shock up to 100g

Accessory

↳ HDD Kit

(P/N:9741681001)



- Standard 2.5" Hard Disk
- Anti-vibration up to 1G / Anti-shock up to 15G

↳ DIN Rail Mounting Kit

(P/N:9741681003)



- Universal Patented Spring Lock Design
- DIN Rail : NS 35/7.5 , NS 35/15

↳ AC Input Adapter Kit


(P/N:9741681002)



- Input: AC 90~264V, 47~63Hz
- Output : 12~17V, 3A, 36W Max
- Safety: UL, CUL, TUV, CE, PSE, CB, FCC, BSMI, EK, 3C

↳ Ultra Cooling Kit

(P/N:9741681004)



- Cooling down 10~20° C for whole system in AEC-68X0 series
- USB interface
- 14.25CFM / 5 x 5 x 1 cm / 5000 rpm FAN

↳ Easy I/O Module



- Text Mode LCD Module with 5 hot keys (coming soon)

↳ USB to Parallel Port Adapter Kit

(P/N:9681681000)



- USB1.1 / IEEE1284 compliant
- Support Win 98/2K/XP

↳ UPS module

- Rechargeable battery module (coming soon)