CE EMC
TEST REPORT

for

Fanless Embox

MODEL: ETKD-JPHOKI01-xxxxxxxxxx (Where x is 0-9, A-Z, a-z, - or blank)

Test Report Number:
T130924D14-E

Issued to:

AAEON Technology Inc.

5F, No.135, Lane 235, Pao Chiao Rd, Hsin-Tien Dist.,
New Taipei City, Taiwan, R.O.C.

Issued by:

Compliance Certification Services Inc.

Xindian Lab.

No.163-1, Jhongsheng Rd., Xindian Dist.,
New Taipei City, 23151 Taiwan.
TEL: 886-2-22170894

FAX: 886-2-22171029

Issued Date: September 30, 2013

Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NVLAP, NIST or any government agencies. The test results in the report only apply to the tested sample.

Revision History

Rev.		Issue Date		Revisions	Effect Page	Revised By
00		September 30, 2013		Initial Issue	ALL	Eva Fan

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

TABLE OF CONTENTS

1 TEST CERTIFICATION 4
2 TEST RESULT SUMMARY 5
3 EUT DESCRIPTION 6
4 TEST METHODOLOGY 7
4.1. DECISION OF FINAL TEST MODE 7
4.2. EUT SYSTEM OPERATION 7
5 SETUP OF EQUIPMENT UNDER TEST 8
5.1. DESCRIPTION OF SUPPORT UNITS 8
5.2. CONFIGURATION OF SYSTEM UNDER TEST 9
6 FACILITIES AND ACCREDITATIONS 10
6.1. FACILITIES 10
6.2. ACCREDITATIONS 10
6.3. MEASUREMENT UNCERTAINTY 10
7 EMISSION TEST 11
7.1. CONDUCTED EMISSION MEASUREMENT 11
7.2. CONDUCTED EMISSION MEASUREMENT AT TELECOMMUNICATION PORTS 16
7.3. RADIATED EMISSION MEASUREMENT 20
7.4. HARMONICS CURRENT MEASUREMENT 28
7.5. VOLTAGE FLUCTUATION AND FLICKER MEASUREMENT 33
8 IMMUNITY TEST 36
8.1. GENERAL DESCRIPTION 36
8.2. GENERAL PERFORMANCE CRITERIA DESCRIPTION 37
8.3. ELECTROSTATIC DISCHARGE (ESD) 38
8.4. RADIATED, RADIO-FREQUENCY, ELECTROMAGNETIC FIELD (RS) 45
8.5. ELECTRICAL FAST TRANSIENT (EFT) 48
8.6. SURGE IMMUNITY TEST 51
8.7. CONDUCTED RADIO FREQUENCY DISTURBANCES (CS) 53
8.8. POWER FREQUENCY MAGNETIC FIELD 56
8.9. VOLTAGE DIPS & VOLTAGE INTERRUPTIONS 58
9 PHOTOGRAPHS OF THE TEST CONFIGURATION 60
APPENDIX 1 - PHOTOGRAPHS OF EUT A1-1

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

1 TEST CERTIFICATION

Product:	Fanless Embox
Model:	ETKD-JPHOKI01-xxxxxxxxxx (Where x is 0-9, A-Z, a-z, - or blank)
Brand:	AAEON
Applicant:	**AAEON Technology Inc.** 5F, No.135, Lane 235, Pao Chiao Rd, Hsin-Tien Dist., New Taipei City, Taiwan, R.O.C.
Manufacturer:	**AAEON Technology Inc.** 5F, No.135, Lane 235, Pao Chiao Rd, Hsin-Tien Dist., New Taipei City, Taiwan, R.O.C.
Tested:	September 24, 2013 ~ September 29, 2013
Applicable Standards:	**EN 55022: 2010, Class A** **CISPR 22: 2008 (Ed 6.0)** **EN 61000-3-2: 2006 + A1: 2009 + A2: 2009** **EN 61000-3-3: 2008** **EN 55024: 2010** IEC 61000-4-2: 2008 IEC 61000-4-3: 2006 + A1: 2007 + A2: 2010 IEC 61000-4-4: 2012 IEC 61000-4-5: 2005 IEC 61000-4-6: 2008 IEC 61000-4-8: 2009 IEC 61000-4-11: 2004

Deviation from Applicable Standard
None

The above equipment was tested by Compliance Certification Services Inc. for compliance with the requirements of technical standards specified above under the EMC Directive 2004/108/EC. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved by:	Reviewed by:
Sam Hu	Vesta Hsu
Sam Hu Assistant Manager	Vesta Hsu Supervisor of report document dept.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

2 TEST RESULT SUMMARY

EMISSION			
Standard	**Item**	**Result**	**Remarks**
EN 55022: 2010 CISPR 22: 2008 (Ed 6.0)	Conducted (Power Port)	PASS	Meet Class A limit
	Conducted (Telecom port)	PASS	Meet Class A limit
	Radiated	PASS	Meet Class A limit
EN 61000-3-2: 2006 + A1: 2009 + A2: 2009	Harmonic current emissions	PASS	Meet Class A limit
EN 61000-3-3: 2008	Voltage fluctuations & flicker	PASS	Meets the requirements

IMMUNITY【 EN 55024 (2010) 】			
Standard	**Item**	**Result**	**Remarks**
IEC 61000-4-2: 2008	ESD	PASS	Meets the requirements of Performance Criterion A
IEC 61000-4-3: 2006 + A1: 2007 + A2: 2010	RS	PASS	Meets the requirements of Performance Criterion A
IEC 61000-4-4: 2012	EFT	PASS	Meets the requirements of Performance Criterion A
IEC 61000-4-5: 2005	Surge	PASS	Meets the requirements of Performance Criterion A
IEC 61000-4-6: 2008	CS	PASS	Meets the requirements of Performance Criterion A
IEC 61000-4-8: 2009	PFMF	N/A	Please see the page 57
IEC 61000-4-11: 2004	Voltage dips & voltage variations	PASS	Meets the requirements of **Voltage Dips:** 1) >95% reduction Performance Criterion A 2) 30% reduction Performance Criterion A **Voltage Interruptions:** 1) >95% reduction Performance Criterion C

Note: 1. The statements of test result on the above are decided by the request of test standard only; the measurement uncertainties are not factored into this compliance determination.

2. The information of measurement uncertainty is available upon the customer's request.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

3 EUT DESCRIPTION

Product	Fanless Embox
Brand Name	AAEON
Model	ETKD-JPHOKI01-xxxxxxxxxx (Where x is 0-9, A-Z, a-z, - or blank)
Applicant	AAEON Technology Inc.
Housing material	Metal Case
Identify Number	T130924D14
Received Date	September 24, 2013
EUT Power Rating	12VDC from AC Adaptor
AC Power During Test	230VAC / 50Hz to AC Adaptor
AC Adaptor Manufacturer	FSP GROUP INC.
AC Adaptor Model Number	FSP084-DMAA1
AC Adaptor Power Rating	Input: 100-240VAC~1.3A, 50-60Hz; Output: 12VDC 7A
AC Power Cord Type	Unshielded, 1.8m (Detachable) to AC Adapter
DC Power Cord Type	Unshielded, 1.0m (Non-Detachable, with two cores) to AC Adapter
OSC/Clock Frequencies	25MHz; 32.768KHz; 27MHz; 14.318MHz

Model Differences

Model Name	Differences	Tested (Check)
ETKD-JPHOKI01-B01-01	Original	☒
ETKD-JPHOKI01-xxxxxxxxxx	1. For marketing purpose only. 2. Where x is 0-9, A-Z, a-z, - or blank	☐

I/O PORT

I/O PORT TYPES	Q'TY	TESTED WITH
1. COM Port	3	3
2. VGA Port	1	1
3. Earphone Port	1	1
4. Microphone Port	1	1
5. USB Port	4	4
6. LAN Port	1	1
7. CN1 Port	1	1
8. CN2 Port	1	1
9. ENCODER/COUNTER Port	1	1

Note: Client consigns only one model sample to test (Model Number: ETKD-JPHOKI01-B01-01).

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

4 TEST METHODOLOGY

4.1. DECISION OF FINAL TEST MODE

The EUT was tested together with the above additional components, and a configuration, which produced the worst emission levels, was selected and recorded in this report.

The test configuration/ modes are as the following:

Conduction Mode (Power port):

1	**1920X1080, VF=60Hz**

Conduction Modes (Telecom port):

1	**10Mbps**
2	**100Mbps**
3	**1Gbps**

Radiation Mode:

1	**1920X1080, VF=60Hz**
	1920X1080, VF=60Hz / 1-6GHz

Conduction (Power port): Mode 1
Conduction (Telecom port): Mode 2
Radiation: Mode 1

4.2. EUT SYSTEM OPERATION

1. Windows 7 boots system.
2. Run Emctest.exe to activate all peripherals and display “H” pattern on monitor screen.
3. Run Winemc.exe and choose “com 3” to test EUT.
4. Run Winemc.exe and choose media player to play music.
5. Run Winemc.exe then choose “E:/ & F:/” to test EUT.
6. Press the start menu, select executive and type ping 192.168.0.2 –t (EUT), ping 192.168.0.1 –t (Server PC).

Note: Test program is self-repeating throughout the test.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

5 SETUP OF EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

EUT Devices:

No.	Equipment	Model No.	Brand Name
1	CPU (1.6GHz)	Intel Atom N2600	Intel
2	Memory (2GB)	V73CAG02808R-J11	ProMOS
3	Power Adaptor	FSP084-DMAA1	FSP GROUP INC.
4	SSD (32GB)	D2ST2-32GJ20AW1ES	Innodisk


Peripherals Devices:

No.	Equipment	Model No.	Serial No.	FCC ID / BSMI ID	Brand Name	Data Cable	Power Cord
1	Earphone & Microphone	MSB301	N/A	N/A	e-Sense	Unshielded, 1.8m	N/A
2	USB Mouse	M-UAE96	F93A90A5BU90L20	DOC BSMI: T41126	hp	Shielded, 1.8m	N/A
3	USB Keyboard	KU-0316	BC3870FVBWH079	DOC BSMI: R33001	hp	Shielded, 1.8m	N/A
4~5	Modem	AL-56ERM	N/A	DOC	GALILEO	Shielded, 1.0m	Unshielded, 1.8m
6	Modem	AL-56ERM	N/A	DOC	GALILEO	Shielded, 1.0m	Unshielded, 1.8m with a core
7	USB HDD	HD-EG5	XCV0S5K280108C8	DOC BSMI: R33021	SONY	Shielded, 0.8m	N/A
8	USB HDD	HD-EG5	XCV0S5K28010888	DOC BSMI: R33021	SONY	Shielded, 0.8m	N/A
9	Monitor	LA2405WG	CN420403XZ	DOC BSMI: R33001	hp	Shielded, 1.8m with two cores	Unshielded, 1.8m
10	Server PC	DCSM	DGN4Z1S	DOC BSMI: R33002	DELL	Unshielded, 20m	Unshielded, 1.8m
11	CN 1 Cable	N/A	N/A	N/A	N/A	Unshielded, 1.8m	N/A
12	CN 2 Cable	N/A	N/A	N/A	N/A	Unshielded, 1.8m	N/A
13	ENCODER/COUNTER Cable	N/A	N/A	N/A	N/A	Unshielded, 1.8m	N/A

Note:
1) All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2) Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

5.2. CONFIGURATION OF SYSTEM UNDER TEST



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

6 FACILITIES AND ACCREDITATIONS

6.1. FACILITIES

All measurement facilities used to collect the measurement data are located at CCSrf Taiwan Xindian Lab. at No.163-1, Jhongsheng Rd., Xindian Dist., New Taipei City, 23151 Taiwan.

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. All receiving equipment conforms to CISPR 16-1-1, CISPR 16-1-2, CISPR 16-1-3, CISPR 16-1-4 and CISPR 16-1-5.

6.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

Taiwan	TAF
USA	A2LA

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

Canada	Industry Canada
Norway	Nemko
Japan	VCCI
Taiwan	BSMI
USA	FCC

Copies of granted accreditation certificates are available for downloading from our web site, http:///www.ccsrf.com

6.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Uncertainty
Conducted emissions (Power port)	0.15MHz ~ 30MHz	± 1.56
Conducted emissions (Telecom port)	0.15MHz ~ 30MHz	± 2.19
Radiated emissions	30MHz ~ 1000MHz	± 3.88
	1000MHz ~ 6000MHz	± 3.23

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Consistent with industry standard (e.g. CISPR 22: 2005, clause 11, Measurement Uncertainty) determining compliance with the limits shall be base on the results of the compliance measurement. Consequently the measure emissions being less than the maximum allowed emission result in this be a compliant test or passing test.

The acceptable measurement uncertainty value without requiring revision of the compliance statement is base on conducted and radiated emissions being less than U_{CISPR} which is 3.6dB and 5.2dB respectively. CCS values (called U_{Lab} in CISPR 16-4-2) is less than U_{CISPR} as shown in the table above. Therefore, MU need not be considered for compliance.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7 EMISSION TEST

7.1. CONDUCTED EMISSION MEASUREMENT

7.1.1. LIMITS

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

NOTE:
(1) The lower limit shall apply at the transition frequencies.
(2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
(3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

7.1.2. TEST INSTRUMENTS

Conducted Emission room # B				
Name of Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Due**
TEST RECEIVER	R&S	ESCI	100234	06/10/2014
LISN (EUT)	FCC	FCC-LISN-50-32-2	08009	03/25/2014
LISN	SCHWARZBECK	NSLK 8127	8127382	01/07/2014
BNC CABLE	EMCI	CFD300-NL	BNC B4	03/14/2014
Pulse Limiter	R&S	ESH3-Z2	100374	01/09/2014
THERMO-HYGRO METER	WISEWIND	201A	No. 05	06/10/2014
Test S/W	EZ-EMC			

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. N.C.R = No Calibration Request.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.1.3. TEST PROCEDURES (please refer to measurement standard or CCS SOP PA-031)

Procedure of Preliminary Test


- The EUT and Support equipment, if needed, was set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per EN 55022 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor standing equipment, it is placed on the ground plane, which has a 15 cm non-conductive covering to insulate the EUT from the ground plane.
- All I/O cables were positioned to simulate typical actual usage as per EN 55022.
- The test equipment EUT installed received AC main power, through a Line Impedance Stabilization Network (LISN), which supplied power source and was grounded to the ground plane.
- All support equipment power received from a second LISN.
- The EUT test program was started. Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.
- The Receiver scanned from 150kHz to 30MHz for emissions in each of the test modes.
- During the above scans, the emissions were maximized by cable manipulation.
- The test mode(s) described in Item 4.1 were scanned during the preliminary test.
- After the preliminary scan, we found the test mode described in Item 4.1 producing the highest emission level.
- The EUT configuration and cable configuration of the above highest emission levels were recorded for reference of the final test.

Procedure of Final Test

- EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.
- The test data of the worst-case condition(s) was recorded.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.1.4. TEST SETUP



- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

7.1.5. DATA SAMPLE

Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
x.xx	42.95	0.55	43.50	73	-29.50	Q	L1

Freq. = Emission frequency in MHz
Reading = Uncorrected Analyzer/Receiver reading
Factor = Insertion loss of LISN + Cable Loss + Pulse Limit
Result = Reading + Factor
Limit = Limit stated in standard
Margin = Reading in reference to limit
P = Peak Reading
Q = Quasi-peak Reading
A = Average Reading
L1 = Hot side
L2 = Neutral side


Calculation Formula

Margin (dB) = Result (dBuV) – Limit (dBuV)

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.1.6. TEST RESULTS

Model No.	ETKD-JPHOKI01-B01-01	6dB Bandwidth	9 kHz
Environmental Conditions	24°C, 60% RH	Test Mode	Mode 1
Tested by	Julon Liu	Phase	L1
Standard	EN 55022 CLASS A		




Conducted Emission Readings							
Frequency Range Investigated				150 kHz to 30 MHz			
Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
0.1539	39.38	10.16	49.54	79.00	-29.46	P	L1
0.1924	38.34	10.08	48.42	79.00	-30.58	P	L1
0.3379	30.24	9.99	40.23	79.00	-38.77	P	L1
1.9460	25.10	10.06	35.16	73.00	-37.84	P	L1
16.2900	32.39	10.30	42.69	73.00	-30.31	P	L1
29.9300	32.55	10.48	43.03	73.00	-29.97	P	L1

Note: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).
2. The emission level was or more than 2dB below the Average limit, so no re-check anymore.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Model No.	ETKD-JPHOKI01-B01-01	6dB Bandwidth	9 kHz
Environmental Conditions	24°C, 60% RH	Test Mode	Mode 1
Tested by	Julon Liu	Phase	L2
Standard	EN 55022 CLASS A		



Conducted Emission Readings							
Frequency Range Investigated				150 kHz to 30 MHz			
Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
0.1580	39.76	10.08	49.84	79.00	-29.16	P	L2
0.1980	40.45	10.00	50.45	79.00	-28.55	P	L2
0.4780	27.20	9.95	37.15	79.00	-41.85	P	L2
2.3340	25.09	10.07	35.16	73.00	-37.84	P	L2
12.4460	30.57	10.25	40.82	73.00	-32.18	P	L2
16.2939	32.48	10.33	42.81	73.00	-30.19	P	L2

Note: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).
2. The emission level was or more than 2dB below the Average limit, so no re-check anymore.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.2. CONDUCTED EMISSION MEASUREMENT AT TELECOMMUNICATION PORTS

7.2.1. LIMITS

For Class A Equipment

FREQUENCY (MHz)	Voltage Limit (dBuV)		Current Limit (dBuA)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 ~ 0.5	97 ~ 87	84 ~ 74	53 ~ 43	40 ~ 30
0.5 ~ 30.0	87	74	43	30

NOTE: The limits decrease linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

For Class B Equipment

FREQUENCY (MHz)	Voltage Limit (dBuV)		Current Limit (dBuA)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	84 ~ 74	74 ~ 64	40 ~ 30	30 ~ 20
0.5 - 30.0	74	64	30	20

NOTE: The limits decrease linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

7.2.2. TEST INSTRUMENTS

Conducted Emission room # B				
Name of Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Due**
TEST RECEIVER	R&S	ESCI	100234	06/10/2014
LISN (EUT)	FCC	FCC-LISN-50-32-2	08009	03/25/2014
LISN	SCHWARZBECK	NSLK 8127	8127382	01/07/2014
BNC CABLE	EMCI	CFD300-NL	BNC B4	03/14/2014
Pulse Limiter	R&S	ESH3-Z2	100374	01/09/2014
THERMO-HYGRO METER	WISEWIND	201A	No. 05	06/10/2014
ISN	TESEQ	ISN T800	29449	12/10/2013
Test S/W	EZ-EMC			

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. N.C.R = No Calibration Request.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.2.3. TEST PROCEDURE (please refer to measurement standard or CCS SOP PA-031)

- Selecting ISN for unscreened cable or a current probe for screened cable to take measurement.
- The port of the EUT was connected to the remote side support equipment through the ISN/Current Probe and communication in normal condition.
- Making a overall range scan by using the test receiver controlled by controller and record at least six highest emissions for showing in the test report.
- Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.
- In case of measuring on the screened cable, the current limit shall be applied; otherwise the voltage limit should be applied.
- The following test modes was scanned during the preliminary test:

Modes:


1	**10Mbps**
2	**100Mbps**
3	**1Gbps**

- After the preliminary scan, we found the following test mode(s) producing the highest emission level and test data of the worst case was recorded.

Mode: 2

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.2.4. TEST SETUP



- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

7.2.5. DATA SAMPLE

Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)
x.xx	62.95	0.55	63.50	87	-23.50	Q

Freq. = Emission frequency in MHz
Reading = Uncorrected Analyzer/Receiver reading
Factor = Insertion loss of LISN + Cable Loss + Pulse Limit
Result = Reading + Factor
Limit = Limit stated in standard
Margin = Reading in reference to limit
P = Peak Reading
Q = Quasi-peak Reading
A = Average Reading


Calculation Formula

Margin (dB) = Result (dBuV) – Limit (dBuV)

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.2.6. TEST RESULTS

Model No.	ETKD-JPHOKI01-B01-01	6dB Bandwidth	9 kHz
Environmental Conditions	24°C, 60% RH	Test Mode	Mode 2
Tested by	Julon Liu	Standard	EN 55022 CLASS A



Conducted Emission Readings						
Frequency Range Investigated				150 kHz to 30 MHz		
Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)
0.4780	27.46	19.80	47.26	87.37	-40.11	P
2.3300	24.49	19.73	44.22	87.00	-42.78	P
4.6660	24.96	19.73	44.69	87.00	-42.31	P
8.5500	30.77	19.76	50.53	87.00	-36.47	P
14.7700	45.20	19.87	65.07	87.00	-21.93	P
29.9340	45.39	20.41	65.80	87.00	-21.20	P

Note: The emission level was or more than 2dB below the Average limit, so no re-check anymore.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.3. RADIATED EMISSION MEASUREMENT

7.3.1. LIMITS

Below 1GHz

FREQUENCY (MHz)	dBuV/m (At 10m)	
	Class A	Class B
30 ~ 230	40	30
230 ~ 1000	47	37

Above 1GHz

Frequency (MHz)	Class A (dBuV/m) (At 3m)		Class B (dBuV/m) (At 3m)	
	Average	Peak	Average	Peak
1000 ~ 3000	56	76	50	70
3000 ~ 6000	60	80	54	74

NOTE: The lower limit shall apply at the transition frequencies.

According to EN55022: 2010 clause 6.2, the measurement frequency range shown in the following table:

Highest frequency generated or used within the EUT or on which the EUT operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Less than 108	1000
108-500	2000
500-1000	5000
Above 1000	5 times of the highest frequency or 6GHz, whichever is less

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.3.2. TEST INSTRUMENTS

Open Area Test Site # I				
Name of Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Due**
MEASURE RECEIVER	R&S	ESCI	101339	01/21/2014
SPECTRUM ANALYZER	ADVANTEST	R3132	120900008	No Calibration Required
ANTENNA	SUNOL	JB1	A100209-3	09/09/2014
AMPLIFIER	SCHAFFNER	CPA9231A	3626	10/07/2013
CABLE	EMCI	8Dr	N-TYPE #I5、I6	01/31/2014
THERMO-HYGRO METER	WISEWIND	201A	No. 03	06/10/2014
Test S/W	EZ-EMC			
Above 1GHz Used				
SPECTRUM ANALYZER (9kHz-30GHz)	R&S	FSP 30	100112	10/21/2013
ANTENNA (1-18GHz)	ETS	3117	00139062	11/04/2013
AMPLIFIER (1-26.5GHz)	HP	8449B	3008A01266	12/16/2013
CABLE (1-40GHz)	HUBER +SUHNER	SUCOFLEX 102	33106/2	12/16/2013
CABLE (1-40GHz)	HUBER +SUHNER	SUCOFLEX 102	33633/2	12/16/2013
CABLE (1-26.5GHz)	HUBER +SUHNER	SUCOFLEX 104PEA	33960/4PEA	12/16/2013
THERMO-HYGRO METER	WISEWIND	201A	No. 02	05/14/2014
Test S/W	EZ-EMC			

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. N.C.R = No Calibration Request.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.3.3. TEST PROCEDURE (please refer to measurement standard or CCS SOP PA-031)

Procedure of Preliminary Test

- The equipment was set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane. When the EUT is a floor standing equipment, it is placed on the ground plane which has a 15 cm non-conductive covering to insulate the EUT from the ground plane.
- Support equipment, if needed, was placed as per EN 55022.
- All I/O cables were positioned to simulate typical usage as per EN 55022.
- The EUT received AC power source from the outlet socket under the turntable. All support equipment power received from another socket under the turntable.
- The antenna was placed at 3 or 10 meter away from the EUT as stated in EN 55022. The antenna connected to the Spectrum Analyzer via a cable and at times a pre-amplifier would be used.
- The Analyzer / Receiver quickly scanned from 30MHz to 6000MHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- The test mode(s) described in Item 4.1 were scanned during the preliminary test:
- After the preliminary scan, we found the test mode described in Item 4.1 producing the highest emission level.
- The EUT and cable configuration, antenna position, polarization and turntable position of the above highest emission level were recorded for the final test.


Procedure of Final Test

- EUT and support equipment were set up on the turntable as per the configuration with highest emission level in the preliminary test.
- The Analyzer / Receiver scanned from 30MHz to 6000MHz. Emissions were scanned and measured rotating the EUT to 360 degrees, varying cable placement and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- Recorded at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. Below 1GHz the Q.P. reading and above 1GHz the Peak and Average reading are presented.
- The test data of the worst-case condition(s) was recorded.


This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.3.4. TEST SETUP

Below 1GHz



Above 1GHz



- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.3.5. DATA SAMPLE

Below 1GHz

Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/Q)	Pol. (H/V)
x.xx	14.0	12.2	26.2	40	-13.8	Q	H

Above 1GHz

Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/A)	Pol. (H/V)
x.xx	42.95	0.55	43.50	60	-16.50	A	H

Freq. = Emission frequency in MHz
Reading = Uncorrected Analyzer/Receiver reading
Factor = Antenna Factor + Cable Loss - Amplifier Gain
Result = Reading + Factor
Limit = Limit stated in standard
Margin = Reading in reference to limit
P = Peak Reading
Q = Quasi-peak Reading
A = Average Reading
H = Antenna Polarization: Horizontal
V = Antenna Polarization: Vertical

Calculation Formula


Margin (dB) = Result (dBuV/m) – Limit (dBuV/m)

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.3.6. TEST RESULTS

Below 1GHz

Model No.	ETKD-JPHOKI01-B01-01	Test Mode	Mode 1
Environmental Conditions	26°C, 60% RH	6dB Bandwidth	120 kHz
Antenna Pole	Vertical	Antenna Distance	10m
Detector Function	Quasi-peak.	Tested by	Kirin Ho
Standard	EN 55022 CLASS A		




Radiated Emission Readings									
Frequency Range Investigated				30 MHz to 1000 MHz at 10m					
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)	Detector (P/Q)	Pol. (H/V)
80.1200	59.31	-20.80	38.51	40.00	-1.49	100	223	Q	V
120.3600	50.22	-14.07	36.15	40.00	-3.85	100	320	Q	V
200.0399	51.23	-14.88	36.35	40.00	-3.65	100	144	Q	V
230.3600	50.36	-16.28	34.08	47.00	-12.92	100	152	Q	V
240.1000	53.47	-15.89	37.58	47.00	-9.42	100	360	Q	V
250.1200	53.62	-15.41	38.21	47.00	-8.79	100	257	Q	V
720.3600	42.51	-4.40	38.11	47.00	-8.89	400	149	Q	V

Note: 1. The other emission levels were very low against the limit.
2. P= Peak Reading; Q= Quasi-peak Reading.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Model No.	ETKD-JPHOKI01-B01-01	Test Mode	Mode 1
Environmental Conditions	26°C, 60% RH	6dB Bandwidth	120 kHz
Antenna Pole	Horizontal	Antenna Distance	10m
Detector Function	Quasi-peak.	Tested by	Kirin Ho
Standard	EN 55022 CLASS A		



Radiated Emission Readings									
Frequency Range Investigated				30 MHz to 1000 MHz at 10m					
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)	Detector (P/Q)	Pol. (H/V)
84.1200	**50.03**	**-20.70**	**29.33**	**40.00**	**-10.67**	**400**	**226**	**Q**	**H**
118.3200	**49.31**	**-14.36**	**34.95**	**40.00**	**-5.05**	**400**	**320**	**Q**	**H**
240.1200	**55.11**	**-15.88**	**39.23**	**47.00**	**-7.77**	**400**	**158**	**Q**	**H**
250.0300	**50.36**	**-15.42**	**34.94**	**47.00**	**-12.06**	**400**	**111**	**Q**	**H**
451.2700	**46.31**	**-9.53**	**36.78**	**47.00**	**-10.22**	**100**	**144**	**Q**	**H**
720.3100	**45.28**	**-4.40**	**40.88**	**47.00**	**-6.12**	**100**	**258**	**Q**	**H**

Note: 1. The other emission levels were very low against the limit.
2. P= Peak Reading; Q= Quasi-peak Reading.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Above 1GHz

Model No.	ETKD-JPHOKI01-B01-01	**Test Mode**	Mode 1
Environmental Conditions	25°C, 52% RH	**6dB Bandwidth**	1 MHz
Antenna Pole	Vertical / Horizontal	**Antenna Distance**	3m
Highest frequency generated or used	1600MHz	**Upper frequency**	6000MHz
Detector Function	Peak and average.	**Tested by**	Andy Lin
Standard	EN 55022 CLASS A		

Radiated Emission Readings							
Frequency Range Investigated				**Above 1GHz at 3m**			
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/A)	Pol. (H/V)
1110.000	**55.57**	**-7.64**	**47.93**	**76.00**	**-28.07**	**P**	**V**
1320.000	**55.86**	**-6.91**	**48.95**	**76.00**	**-27.05**	**P**	**V**
1710.000	**52.90**	**-4.34**	**48.56**	**76.00**	**-27.44**	**P**	**V**
1755.000	**53.54**	**-3.93**	**49.61**	**76.00**	**-26.39**	**P**	**V**
1880.000	**51.65**	**-2.78**	**48.87**	**76.00**	**-27.13**	**P**	**V**
2095.000	**47.94**	**-1.53**	**46.41**	**76.00**	**-29.59**	**P**	**V**

Radiated Emission Readings							
Frequency Range Investigated				**Above 1GHz at 3m**			
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/A)	Pol. (H/V)
1050.000	**57.44**	**-7.86**	**49.58**	**76.00**	**-26.42**	**P**	**H**
1275.000	**56.32**	**-7.07**	**49.25**	**76.00**	**-26.75**	**P**	**H**
1430.000	**55.12**	**-6.52**	**48.60**	**76.00**	**-27.40**	**P**	**H**
1605.000	**53.33**	**-5.31**	**48.02**	**76.00**	**-27.98**	**P**	**H**
1920.000	**53.05**	**-2.40**	**50.65**	**76.00**	**-25.35**	**P**	**H**
2405.000	**51.30**	**-1.06**	**50.24**	**76.00**	**-25.76**	**P**	**H**

Note: 1. The other emission levels were very low against the limit.
2. P= Peak Reading; A= Average Reading.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.4. HARMONICS CURRENT MEASUREMENT

7.4.1. LIMITS OF HARMONICS CURRENT MEASUREMENT

Limits for Class A equipment	
Harmonics Order n	Max. permissible harmonics current A
Odd harmonics	
3	2.30
5	1.14
7	0.77
9	0.40
11	0.33
13	0.21
15<=n<=39	0.15x15/n
Even harmonics	
2	1.08
4	0.43
6	0.30
8<=n<=40	0.23x8/n

Limits for Class D equipment		
Harmonics Order n	Max. permissible harmonics current per watt mA/W	Max. permissible harmonics current A
Odd Harmonics only		
3	3.4	2.30
5	1.9	1.14
7	1.0	0.77
9	0.5	0.40
11	0.35	0.33
13	0.30	0.21
15<=n<=39	3.85/n	0.15x15/n

NOTE: 1. Class A and Class D are classified according to item 7.4.3.

2. According to section 7 of EN 61000-3-2, the above limits for all equipment except for lighting equipment having an active input power > 75 W and no limits apply for equipment with an active input power up to and including 75 W.

7.4.2. TEST INSTRUMENTS

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
H/F Measurement System	EMC Partner	HAR1000-1P	189	08/13/2014
Digital Power Meter	Protronix	1201	201091	No Calibration Required
Software	HARCS V4.19			

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.4.3. TEST PROCEDURE (please refer to measurement standard or CCS SOP PA-029)

- The EUT was placed on the top of a wooden table 0.8 meters above the ground and operated to produce the maximum harmonic components under normal operating conditions for each successive harmonic component in turn.
- The classification of EUT is according to section 5 of EN 61000-3-2.
- The EUT is classified as follows:

  Class A: Balanced three-phase equipment, Household appliances excluding equipment as Class D, Tools excluding portable tools, Dimmers for incandescent lamps, audio equipment, equipment not specified in one of the three other classes.


  Class B: Portable tools; Arc welding equipment which is not professional equipment.

  Class C: Lighting equipment.

  Class D: Equipment having a specified power less than or equal to 600 W of the following types: Personal computers and personal computer monitors and television receivers.

- The correspondent test program of test instrument to measure the current harmonics emanated from EUT is chosen. The measure time shall be not less than the time necessary for the EUT to be exercised.

7.4.4. TEST SETUP



- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.


This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.4.5. TEST RESULTS

Power Consumption	21.40W	Test Results	PASS
Environmental Conditions	25°C, 51% RH, 1001mbar	Limits	Class ☒ A ☐ B ☐ C ☐ D
Test Mode	Operating	Tested by	Julon Liu

NOTE: Limits classified according to item 7.4.1.

Test result of EN 61000-3-2



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Urms =	230.1V	Freq =	50.091	Range:	2 A
Irms =	0.240A	Ipk =	1.173A	cf =	4.882
P =	21.40W	S =	55.28VA	pf =	0.387
THDi =	214 %	THDu =	0.10 %	Class A	

Test - Time : 5min (100 %)

Test completed, Result: PASSED

Order	Freq. [Hz]	Iavg [A]	Irms [A]	Irms% [%]	Irms%L [%]	Imax [A]	Imax% [%]	Imax%L [%]	Limit [A]	Status
1	50	0.1014	0.1028	42.785		0.1104	45.935			
2	100	0.0000	0.0010	0.4065	0.0904	0.0023	0.9654	0.2148	1.0800	
3	150	0.0865	0.0873	36.331	3.7948	0.0953	39.685	4.1451	2.3000	
4	200	0.0000	0.0012	0.5081	0.2839	0.0024	1.0163	0.5678	0.4300	
5	250	0.0843	0.0851	35.417	7.4634	0.0928	38.618	8.1380	1.1400	
6	300	0.0000	0.0013	0.5589	0.4476	0.0024	1.0163	0.8138	0.3000	
7	350	0.0809	0.0817	33.994	10.606	0.0889	36.992	11.541	0.7700	
8	400	0.0000	0.0016	0.6606	0.6900	0.0026	1.0671	1.1146	0.2300	
9	450	0.0764	0.0771	32.114	19.287	0.0837	34.858	20.935	0.4000	
10	500	0.0000	0.0017	0.7114	0.9288	0.0026	1.0671	1.3932	0.1840	
11	550	0.0711	0.0718	29.878	21.751	0.0776	32.317	23.526	0.3300	
12	600	0.0000	0.0018	0.7622	1.1942	0.0027	1.1179	1.7514	0.1533	
13	650	0.0649	0.0654	27.236	31.157	0.0707	29.421	33.657	0.2100	
14	700	0.0000	0.0018	0.7622	1.3932	0.0027	1.1179	2.0434	0.1314	
15	750	0.0581	0.0586	24.390	39.063	0.0630	26.220	41.992	0.1500	
16	800	0.0000	0.0018	0.7622	1.5922	0.0027	1.1179	2.3353	0.1150	
17	850	0.0511	0.0516	21.494	39.014	0.0552	22.967	41.688	0.1324	
18	900	0.0000	0.0018	0.7622	1.7912	0.0024	1.0163	2.3883	0.1022	
19	950	0.0441	0.0444	18.496	37.522	0.0471	19.614	39.789	0.1184	
20	1000	0.0000	0.0017	0.7114	1.8576	0.0023	0.9654	2.5210	0.0920	
21	1050	0.0370	0.0374	15.549	34.863	0.0393	16.362	36.686	0.1071	
22	1100	0.0000	0.0016	0.6606	1.8974	0.0021	0.8638	2.4812	0.0836	
23	1150	0.0303	0.0305	12.703	31.196	0.0319	13.262	32.568	0.0978	
24	1200	0.0000	0.0015	0.6098	1.9107	0.0018	0.7622	2.3883	0.0767	
25	1250	0.0240	0.0242	10.061	26.855	0.0249	10.366	27.669	0.0900	
26	1300	0.0000	0.0013	0.5589	1.8974	0.0016	0.6606	2.2424	0.0708	
27	1350	0.0184	0.0184	7.6728	22.119	0.0188	7.8252	22.559	0.0833	
28	1400	0.0000	0.0011	0.4573	1.6718	0.0015	0.6098	2.2291	0.0657	
29	1450	0.0134	0.0134	5.5894	17.307	0.0135	5.6402	17.464	0.0776	
30	1500	0.0000	0.0009	0.3557	1.3932	0.0012	0.5081	1.9903	0.0613	
31	1550	0.0092	0.0093	3.8618	12.782	0.0094	3.9126	12.950	0.0726	
32	1600	0.0000	0.0006	0.2541	1.0615	0.0010	0.4065	1.6984	0.0575	
33	1650	0.0060	0.0061	2.5407	8.9518	0.0062	2.5915	9.1309	0.0682	
34	1700	0.0000	0.0005	0.2033	0.9023	0.0007	0.3049	1.3534	0.0541	
35	1750	0.0000	0.0040	1.6768	6.2663	0.0042	1.7276	6.4562	0.0643	
36	1800	0.0000	0.0004	0.1524	0.7165	0.0006	0.2541	1.1942	0.0511	
37	1850	0.0000	0.0034	1.4228	5.6207	0.0035	1.4736	5.8214	0.0608	
38	1900	0.0000	0.0002	0.1016	0.5042	0.0005	0.2033	1.0084	0.0484	
39	1950	0.0000	0.0037	1.5244	6.3477	0.0040	1.6768	6.9824	0.0577	
40	2000	0.0000	0.0002	0.1016	0.5307	0.0005	0.2033	1.0615	0.0460	

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Definitions of Abbreviations

Urms	***	Actual total Voltage in Volt RMS
Irms	***	Actual total Current in Ampere RMS
Ipk	***	Actual Peak value of the Current in Ampere
cf	***	Actual Crest Factor (Ipk/Irms)
P	***	Actual Active Power in Watt
S	***	Actual Apparent Power in VA (Urms*Irms)
pf	***	Actual Power Factor (P/S)
THDi	***	Actual Total Harmonic Current Distortion in %
THDu	***	Actual Total Harmonic Voltage Distortion in %
THC	***	Actual Total Harmonic Current in Ampere
PHC	***	Actual Partial Harmonic Current in Ampere

Individual measurements for 2nd to 40th order:

Iavg		Average value of the Individual Harmonic Current in Ampere RMS
Irms	***	Actual Individual Harmonic Current in Ampere RMS
Irms%	***	Actual Individual Harmonic Current in percentage of the actual total RMS Current
Irms%L	***	Actual Individual Harmonic Current in percentage of the applicable Limit
Imax		Maximum Individual Harmonic Current in Ampere RMS
Imax%		Maximum Individual Harmonic Current in percentage of the actual total RMS Current
Imax%lim		Maximum Individual Harmonic Current in percentage of the applicable Limit
Limit Irms		Individual Limit (100%) for the selected Class in Ampere RMS

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.5. VOLTAGE FLUCTUATION AND FLICKER MEASUREMENT

7.5.1. LIMITS OF VOLTAGE FLUCTUATION AND FLICKER MEASUREMENT

TEST ITEM	LIMIT	REMARK
P_{st}	1.0	P_{st} means short-term flicker indicator.
P_{lt}	0.65	P_{lt} means long-term flicker indicator.
T_{dt} (ms)	500	T_{dt} means maximum time that dt exceeds 3 %.
d_{max} (%)	4%	d_{max} means maximum relative voltage change.
dc (%)	3.3%	dc means relative steady-state voltage change

7.5.2. TEST INSTRUMENTS

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
H/F Measurement System	EMC Partner	HAR1000-1P	189	08/13/2014
Digital Power Meter	Protronix	1201	201091	No Calibration Required
Software	HARCS V4.19			


NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

7.5.3. TEST PROCEDURE (please refer to measurement standard or CCS SOP PA-030)

- The EUT was placed on the top of a wooden table 0.8 meters above the ground and operated to produce the most unfavorable sequence of voltage changes under normal operating conditions.
- During the flick measurement, the measure time shall include that part of whole operation cycle in which the EUT produce the most unfavorable sequence of voltage changes. The observation period for short-term flicker indicator is 10 minutes and the observation period for long-term flicker indicator is 2 hours.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

7.5.4. TEST SETUP



- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

7.5.5. TEST RESULTS


Observation Period (Tp)	30mins	**Test Mode**	Operating
Environmental Conditions	25°C, 51% RH, 1001mbar	**Tested by**	Julon Liu

TEST PARAMETER	MEASUREMENT VALUE	LIMIT	REMARK
P_{st}	0.07	1.0	Pass
P_{lt}	0.07	0.65	Pass
T_{dt} (ms)	0	500	Pass
d_{max} (%)	0	4%	Pass
dc (%)	0.02	3.3%	Pass

Note: None.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Test result of EN 61000-3-3



Actual Flicker (Fli):	**0.00**
Short-term Flicker (Pst):	**0.07**
Limit (Pst):	1.00
Long-term Flicker (Plt):	**0.07**
Limit (Plt):	0.65
Maximum Relative Volt. Change (dmax):	**0.00%**
Limit (dmax):	4.00%
Relative Steady-state Voltage Change (dc):	**0.02%**
Limit (dc):	3.00%
Maximum Interval exceeding 3.00% (dt):	**0.00ms**
Limit (dt>Lim):	200ms

Flicker Emission - IEC 61000-3-3 , EN 61000-3-3 , (EN60555-3)

2013/9/25 20:56:03

Urms =	229.9	V	P =	17.77	W
Irms =	0.188	A	pf =	0.412	

Range:	2 A
V-nom:	230 V
TestTime:	30 min (100%)

ETKD-IPHONE01-B01

Test completed, Result: PASSED

HAR-1000 EMC-Partner

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

8 IMMUNITY TEST

8.1. GENERAL DESCRIPTION

Product Standard	EN 55024: 2010	
	Test Type	Minimum Requirement
Basic Standard, Specification, and Performance Criterion required	IEC 61000-4-2	Electrostatic Discharge – ESD: 8kV air discharge, 4kV Contact discharge, Performance Criterion B
	IEC 61000-4-3	Radio-Frequency Electromagnetic Field Susceptibility Test – RS: 80 ~1000 MHz, 3V/m, 80% AM(1kHz), Performance Criterion A
	IEC 61000-4-4	Electrical Fast Transient/Burst - EFT, AC Power Port: 1kV DC Power Port: 0.5kV Signal Ports and Telecommunication Ports: 0.5kV Performance Criterion B
	IEC 61000-4-5	Surge Immunity Test: 1.2/50 μs Open Circuit Voltage, 8/20 μs Short Circuit Current, 10/700 μs Open Circuit Voltage, AC Power Port ~ line to line: 1kV, line to earth (ground): 2kV DC Power Port ~ line to earth: 0.5kV Signal Ports and Telecommunication Ports ~ line to ground: 1kV Performance Criterion B
	IEC 61000-4-6	Conducted Radio Frequency Disturbances Test – CS: 0.15 ~ 80 MHz, 3Vrms, 80% AM, 1kHz, Performance Criterion A
	IEC 61000-4-8	Power frequency magnetic field immunity test 50 Hz or 60 Hz, 1A/m, Performance Criterion A
	IEC 61000-4-11	Voltage Dips: i) >95% reduction for 0.5 period, Performance Criterion B ii) 30% reduction for 25 period, Performance Criterion C Voltage Interruptions: >95% reduction for 250 period Performance Criterion C

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

8.2. GENERAL PERFORMANCE CRITERIA DESCRIPTION

Criteria A:	The apparatus shell continues to operate as intended without operator intervention. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. The performance level may be replaced by a permissible loss of performance. If the manufacturer does not specify the minimum performance level or the permissible performance loss, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.
Criteria B:	After test, the apparatus shell continues to operate as intended without operator intervention. No degradation of performance or loss of function is allowed, after the application of the phenomenon below a performance level specified by the manufacturer, when the apparatus is used as intended. The performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed. However, no change of operating state if stored data is allowed to persist after the test. If the manufacturer does not specify the minimum performance level or the permissible performance loss, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.
Criteria C:	Temporary loss of function is allowed, provided the functions is self-recoverable or can be restored by the operation of controls by the user in accordance with the manufacturer instructions. Functions, and/or information stored in non-volatile memory, or protected by a battery backup, shall not be lost.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

8.3. ELECTROSTATIC DISCHARGE (ESD)

8.3.1. TEST SPECIFICATION

Basic Standard:	IEC 61000-4-2
Discharge Impedance:	330 ohm / 150 pF
Discharge Voltage:	Air Discharge: 2 ; 4 ; 8 kV (Direct) Contact Discharge: 2 ; 4 kV (Direct/Indirect)
Polarity:	Positive & Negative
Number of Discharge:	Air Discharge: min. 10 times at each test point for each polarity Contact Discharge: min. 200 times in total
Discharge Mode:	Single Discharge 1 second minimum

8.3.2. TEST INSTRUMENT

IMMUNITY SHIELDED ROOM				
Name of Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Due**
ESD Generator	Teseq	NSG 437	249	12/18/2013
Aneroid Barometer	Sato	7610-20	89090	11/04/2013
Thermo-Hygro meter	TECPEL	DTM-303	080269	04/28/2014

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

8.3.3. TEST PROCEDURE (please refer to measurement standard or CCS SOP PA-022)

The discharges shall be applied in two ways:

a) Contact discharges to the conductive surfaces and coupling planes:
   The EUT shall be exposed to at least 200 discharges, 100 each at negative and positive polarity, at a minimum of four test points. One of the test points shall be subjected to at least 50 indirect discharges to the center of the front edge of the **H**orizontal **C**oupling **P**lane (**HCP**). The remaining three test points shall each receive at least 50 direct contact discharges. If no direct contact test points are available, then at least 200 indirect discharges shall be applied in the indirect mode. Test shall be performed at a maximum repetition rate of one discharge per second.


b) Air discharges at slots and apertures and insulating surfaces:
   On those parts of the EUT where it is not possible to perform contact discharge testing, the equipment should be investigated to identify user accessible points where breakdown may occur. Such points are tested using the air discharge method. This investigation should be restricted to those area normally handled by the user. A minimum of 10 single air discharges shall be applied to the selected test point for each such area.

The basic test procedure was in accordance with IEC 61000-4-2:

a) The EUT was located 0.1 m minimum from all side of the **HCP** (dimensions 1.6m x 0.8m).
b) The support units were located another table 30 cm away from the EUT, but direct support unit was/were located at same location as EUT on the HCP and keep at a distance of 10 cm with EUT.
c) The time interval between two successive single discharges was at least 1 second.
d) Contact discharges were applied to the non-insulating coating, with the pointed tip of the generator penetrating the coating and contacting the conducting substrate.
e) Air discharges were applied with the round discharge tip of the discharge electrode approaching the EUT as fast as possible (without causing mechanical damage) to touch the EUT. After each discharge, the ESD generator was removed from the EUT and re-triggered for a new single discharge. The test was repeated until all discharges were complete.
f) At least ten single discharges (in the most sensitive polarity) were applied at the front edge of each **HCP** opposite the center point of each unit of the EUT and 0.1 meters from the front of the EUT. The long axis of the discharge electrode was in the plane of the **HCP** and perpendicular to its front edge during the discharge.
g) At least ten single discharges (in the most sensitive polarity) were applied to the center of one vertical edge of the **V**ertical **C**oupling **P**lane (**VCP**) in sufficiently different positions that the four faces of the EUT were completely illuminated. The **VCP** (dimensions 0.5m x 0.5m) was placed vertically to and 0.1 meters from the EUT.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

8.3.4. TEST SETUP



Ground Reference Plane

- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

NOTE:

TABLE-TOP EQUIPMENT

The configuration consisted of a wooden table 0.8 meters high standing on the **G**round **R**eference **P**lane. The **GRP** consisted of a sheet of aluminum at least 0.25mm thick, and 2.5 meters square connected to the protective grounding system. A **H**orizontal **C**oupling **P**lane (1.6m x 0.8m) was placed on the table and attached to the **GRP** by means of a cable with 940k ¸ total impedance. The equipment under test, was installed in a representative system as described in section 7 of IEC 61000-4-2, and its cables were placed on the **HCP** and isolated by an insulating support of 0.5mm thickness. A distance of 1-meter minimum was provided between the EUT and the walls of the laboratory and any other metallic structure.

FLOOR-STANDING EQUIPMENT

The equipment under test was installed in a representative system as described in section 7 of IEC 61000-4-2, and its cables were isolated from the Ground Reference Plane by an insulating support of 0.1-meter thickness. The GRP consisted of a sheet of aluminum that is at least 0.25mm thick, and 2.5 meters square connected to the protective grounding system and extended at least 0.5 meters from the EUT on all sides.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

8.3.5. TEST RESULTS

Temperature	19°C	Humidity	40% RH
Pressure	1002mbar	Tested By	Julon Liu
Required Passing Performance		Criterion B	

Air Discharge							
Test Points	Test Levels			Results			
	± 2 KV	± 4 KV	± 8 KV	Pass	Fail	Performance Criterion	Observation
Front	☐	☐	☐	☐	☐	☐A ☐B	Note ☐1 ☒2
Back	☐	☐	☐	☐	☐	☐A ☐B	Note ☐1 ☒2
Left	☐	☐	☐	☐	☐	☐A ☐B	Note ☐1 ☒2
Right	☐	☐	☐	☐	☐	☐A ☐B	Note ☐1 ☒2
Top	☐	☐	☐	☐	☐	☐A ☐B	Note ☐1 ☒2

Contact Discharge							
Test Points	Test Levels			Results			
	± 2 KV	± 4 KV	± 8 KV	Pass	Fail	Performance Criterion	Observation
Front	☒	☒	☐	☒	☐	☒A ☐B	Note ☒1 ☐2
Back	☒	☒	☐	☒	☐	☒A ☐B	Note ☒1 ☐2
Left	☒	☒	☐	☒	☐	☒A ☐B	Note ☒1 ☐2
Right	☒	☒	☐	☒	☐	☒A ☐B	Note ☒1 ☐2
Top	☒	☒	☐	☒	☐	☒A ☐B	Note ☒1 ☐2

Please refer to ESD test photo on next page for detail discharge point

Discharge To Horizontal Coupling Plane							
Side of EUT	Test Levels			Results			
	± 2 KV	± 4 KV	± 8 KV	Pass	Fail	Performance Criterion	Observation
Front	☒	☒	☐	☒	☐	☒A ☐B	Note ☒1 ☐2
Back	☒	☒	☐	☒	☐	☒A ☐B	Note ☒1 ☐2
Left	☒	☒	☐	☒	☐	☒A ☐B	Note ☒1 ☐2
Right	☒	☒	☐	☒	☐	☒A ☐B	Note ☒1 ☐2


Discharge To Vertical Coupling Plane							
Side of EUT	Test Levels			Results			
	± 2 KV	± 4 KV	± 8 KV	Pass	Fail	Performance Criterion	Observation
Front	☒	☒	☐	☒	☐	☒A ☐B	Note ☒1 ☐2
Back	☒	☒	☐	☒	☐	☒A ☐B	Note ☒1 ☐2
Left	☒	☒	☐	☒	☐	☒A ☐B	Note ☒1 ☐2
Right	☒	☒	☐	☒	☐	☒A ☐B	Note ☒1 ☐2

NOTE: 1. There was no change compared with initial operation during the test.
2. Not applicable(Metal Case).

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

The Photo for Discharge Points of EUT

Front



Back



Red Dot —Air Discharged
Blue Dot —Contact Discharged

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Left




Right



Red Dot —Air Discharged
Blue Dot —Contact Discharged

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Top



Red Dot —Air Discharged
Blue Dot —Contact Discharged

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

8.4. RADIATED, RADIO-FREQUENCY, ELECTROMAGNETIC FIELD (RS)

8.4.1. TEST SPECIFICATION

Basic Standard:	IEC 61000-4-3
Frequency Range:	80 MHz ~1000 MHz
Field Strength:	3 V/m
Modulation:	1kHz Sine Wave, 80%, AM Modulation
Frequency Step:	1 % of preceding frequency value
Polarity of Antenna:	Horizontal and Vertical
Test Distance:	3 m
Antenna Height:	1.5m

8.4.2. TEST INSTRUMENT

844 RS Chamber				
Name of Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Due**
Calibration of Field	N/A	Chamber#RS	80-1000MHz	04/15/2014
Signal Generator	Agilent	E4421B	MY43350597	05/30/2014
Electric Field Probe	AR	FL7006	0338955	04/08/2014
RF Power Meter	Boonton	4242-01-02	14357	03/11/2014
Amplifier	AR	500W1000A	320994	No Calibration Required
Direction Coupler	AR	DC6180A	312189	No Calibration Required
Broadband Antenna	AR	AT1080	311819	No Calibration Required
Thermo-Hygro meter	TFA	N/A	NO.6	11/11/2013
Software	Emcware Ver. 2.6.0.16			

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. N.C.R.= No Calibration required

8.4.3. TEST PROCEDURE (please refer to measurement standard or CCS SOP PA-023)

The test procedure was in accordance with IEC 61000-4-3

a) The testing was performed in a fully anechoic chamber. The transmit antenna was located at a distance of 3 meters from the EUT.


b) The frequency range is swept from 80 MHz to 1000 MHz, with the signal 80% amplitude modulated with a 1kHz sine-wave. The rate of sweep did not exceed 1.5×10^{-3} decade/s, where the frequency range is swept incrementally, the step size was 1% of preceding frequency value.

c) The dwell time at each frequency shall be not less than the time necessary for the EUT to be able to respond.

d) The test was performed with the EUT exposed to both vertically and horizontally polarized fields on each of the four sides.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

8.4.4. TEST SETUP



- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

NOTE:

TABLETOP EQUIPMENT

The EUT installed in a representative system as described in section 7 of IEC 61000-4-3 was placed on a non-conductive table 0.8 meters in height. The system under test was connected to the power and signal wire according to relevant installation instructions.

FLOOR STANDING EQUIPMENT

The EUT installed in a representative system as described in section 7 of IEC 61000-4-3 was placed on a non-conductive wood support 0.1 meters in height. The system under test was connected to the power and signal wire according to relevant installation instructions.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

8.4.5. TEST RESULTS

Temperature	28°C	**Humidity**	49% RH
Pressure	1005mbar	**Dwell Time**	3 sec.
Tested By	Julon Liu	**Required Passing Performance**	**Criterion A**

Frequency (MHz)	Polarity	Azimuth	Field Strength (V/m)	Performance Criterion	Observation	Result
80 ~ 1000	V&H	0	3	☒A ☐B	Note	PASS
80 ~ 1000	V&H	90	3	☒A ☐B	Note	PASS
80 ~ 1000	V&H	180	3	☒A ☐B	Note	PASS
80 ~ 1000	V&H	270	3	☒A ☐B	Note	PASS

NOTE: There was no change compared with the initial operation during the test.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

8.5. ELECTRICAL FAST TRANSIENT (EFT)

8.5.1. TEST SPECIFICATION

Basic Standard:	IEC 61000-4-4
Test Voltage:	AC Power Port: 1kV Signal Ports and Telecommunication Ports: 0.5kV
Polarity:	Positive & Negative
Impulse Frequency:	5 kHz
Impulse Wave-shape:	5/50 ns
Burst Duration:	15 ms
Burst Period:	300 ms
Test Duration:	Not less than 1 min.

8.5.2. TEST INSTRUMENT

Immunity Shield Room				
Name of Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Due**
EMC Immunity Tester	EMC Partner	TRANSIENT 2000	1117	03/10/2014
Capacitive Clamp	EMC-Partner	CN-EFT1000	589	07/25/2014
Software	Genecs Ver. 3.27			

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. N.C.R.= No Calibration required

8.5.3. TEST PROCEDURE (please refer to measurement standard or CCS SOP PA-024)

a) Both positive and negative polarity discharges were applied.


b) The length of the " hot wire " from the coaxial output of the EFT generator to the terminals on the EUT should not exceed 0.5 meter.


c) The duration time of each test sequential was 1 minute.

d) The transient/burst waveform was in accordance with IEC 61000-4-4, 5/50ns.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

8.5.4. TEST SETUP





- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

NOTE:

TABLETOP EQUIPMENT

The configuration consisted of a wooden table (0.1m high) standing on the Ground Reference Plane. The GRP consisted of a sheet of aluminum (at least 0.25mm thick and 2.5m square) connected to the protective grounding system. A minimum distance of 0.5m was provided between the EUT and the walls of the laboratory or any other metallic structure.

FLOOR STANDING EQUIPMENT

The EUT installed in a representative system as described in section 7 of IEC 61000-4-4 and its cables, were isolated from the Ground Reference Plane by an insulating support that is 0.1-meter thick. The GRP consisted of a sheet of aluminum (at least 0.25mm thick and 2.5m square) connected to the protective grounding system.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

8.5.5. TEST RESULTS

Temperature	24°C	Humidity	44% RH
Pressure	1001mbar	Tested By	Julon Liu
Required Passing Performance		Criterion B	

Test Point	Polarity	Test Level (kV)	Performance Criterion	Observation	Result
L	+/-	1	☒A ☐B	Note ☒1 ☐2	PASS
N	+/-	1	☒A ☐B	Note ☒1 ☐2	PASS
L – N	+/-	1	☒A ☐B	Note ☒1 ☐2	PASS
PE	+/-	1	☒A ☐B	Note ☒1 ☐2	PASS
L – PE	+/-	1	☒A ☐B	Note ☒1 ☐2	PASS
N – PE	+/-	1	☒A ☐B	Note ☒1 ☐2	PASS
L – N – PE	+/-	1	☒A ☐B	Note ☒1 ☐2	PASS
RJ45	+/-	0.5	☒A ☐B	Note ☒1 ☐2	PASS

NOTE: 1. There was no change compared with initial operation during the test.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

8.6. SURGE IMMUNITY TEST

8.6.1. TEST SPECIFICATION

Basic Standard:	IEC 61000-4-5
Wave-Shape:	Combination Wave 1.2/50 μs Open Circuit Voltage 8/20 μs Short Circuit Current 10/700 μs Open Circuit Voltage
Test Voltage:	AC Power Port~ line to line: 1kV, line to ground: 2kV Signal Ports and Telecommunication Ports: 1kV
Surge Input/Output:	AC Power Line: L-N / L-PE / N-PE Signal Line: L-G
Generator Source Impedance:	2 ohm between networks 12 ohm between network and ground 42 ohm between network and ground
Polarity:	Positive/Negative
Phase Angle:	0° / 90° / 180° / 270°
Pulse Repetition Rate:	1 time / min. (maximum)
Number of Tests:	5 positive and 5 negative at selected points

8.6.2. TEST INSTRUMENT

Immunity Shield Room				
Name of Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Due**
EMC Immunity Tester	EMC Partner	TRANSIENT 2000	1117	03/10/2014
CDN	EMC Partner	CDN-UTP8	CDN-UTP8-1505	03/10/2014
Software	Genecs Ver. 3.27			

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. N.C.R.= No Calibration required

8.6.3. TEST PROCEDURE (please refer to measurement standard or CCS SOP PA-025)


a) For EUT power supply:
The surge is applied to the EUT power supply terminals via the capacitive coupling network. Decoupling networks are required in order to avoid possible adverse effects on equipment not under test that may be powered by the same lines, and to provide sufficient decoupling impedance to the surge wave. The power cord between the EUT and the coupling/decoupling networks was shorter than 2 meters in length.


b) For test applied to unshielded un-symmetrically operated interconnection lines of EUT:
The surge was applied to the lines via the capacitive coupling. The coupling / decoupling networks didn't influence the specified functional conditions of the EUT. The interconnection line between the EUT and the coupling/decoupling networks was shorter than 2 meters in length.

c) For test applied to unshielded symmetrically operated interconnection / telecommunication lines of EUT:
The surge was applied to the lines via gas arrestors coupling. Test levels below the ignition point of the coupling arrestor were not specified. The interconnection line between the EUT and the coupling/decoupling networks was shorter than 2 meters in length.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

8.6.4. TEST SETUP





- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

8.6.5. TEST RESULTS

Temperature	24°C	**Humidity**	45% RH
Pressure	1000mbar	**Tested By**	Julon Liu
Required Passing Performance		**Criterion B**	

Test Point	Polarity	Test Level (kV)	Performance Criterion	Observation	Result
L - N	+/-	1	☒**A** ☐**B**	**Note** ☒**1** ☐**2**	PASS
L - PE	+/-	2	☒**A** ☐**B**	**Note** ☒**1** ☐**2**	PASS
N - PE	+/-	2	☒**A** ☐**B**	**Note** ☒**1** ☐**2**	PASS
RJ45	+/-	1	☒**A** ☐**B**	**Note** ☒**1** ☐**2**	PASS

NOTE: 1. There was no change compared with initial operation during the test.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

8.7. CONDUCTED RADIO FREQUENCY DISTURBANCES (CS)

8.7.1. TEST SPECIFICATION

Basic Standard:	IEC 61000-4-6
Frequency Range:	0.15 MHz ~ 80 MHz
Field Strength:	3 Vrms
Modulation:	1kHz Sine Wave, 80%, AM Modulation
Frequency Step:	1 % of preceding frequency value
Coupled cable:	Power Mains, Unshielded; RJ45 Line, Unshielded
Coupling device:	CDN-M3 (3 wires); CDN-T8

8.7.2. TEST INSTRUMENT

CS Room				
Name of Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Due**
CWS Generator	EM Test	CWS 500N1	V0395105080	10/01/2013
CDN (EUT)	Teseq	CDN M016	35820	06/21/2014
CDN	Teseq	CDN M016	35821	06/21/2014
CDN	Teseq	CDN T400A	25674	01/17/2014
CDN	Teseq	CDN T800	26155	02/04/2014
Attenuator	EMCI	SA3NL	10006F	No Calibration Required
Software	icd.control Ver. 5.1.9			

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. N.C.R.= No Calibration required

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

8.7.3. TEST PROCEDURE (please refer to measurement standard or CCS SOP PA-026)

The EUT shall be tested within its intended operating and climatic conditions.


The test shell performed with the test generator connected to each of the coupling and decoupling devices in turn, while the other non-excited RF input ports of the coupling devices are terminated by a 50-ohm load resistor.

The frequency range was swept from 150 kHz to 80 MHz, using the signal level established during the setting process and with a disturbance signal of 80 % amplitude. The signal was modulated with a 1 kHz sine wave, pausing to adjust the RF signal level or the switch coupling devices as necessary. The sweep rate was 1.5 x 10^{-3} decades/s. Where the frequency range is swept incrementally, the step size was 1 % of preceding frequency value from 150 kHz to 80 MHz.

The dwell time at each frequency was less than the time necessary for the EUT to be exercised, and able to respond. Sensitive frequencies such as clock frequency(ies) and harmonics or frequencies of dominant interest, was analyzed separately.

Attempts was made to fully exercise the EUT during testing, and to fully interrogate all exercise modes selected for susceptibility.

8.7.4. TEST SETUP



Note: 1. The CDNs and / or EM clamp used for real test depends on ports and cables configuration of EUT.
2. The EUT clearance from any metallic obstacles shall be at least 0.5m

- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

NOTE:
TABLE-TOP AND FLOOR-STANDING EQUIPMENT
The equipment to be tested is placed on an insulating support of 0.1 meters height above a ground reference plane. All relevant cables shall be provided with the appropriate coupling and decoupling devices at a distance between 0.1 meters and 0.3 meters from the projected geometry of the EUT on the ground reference plane.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

8.7.5. TEST RESULTS

Temperature	25°C	Humidity	51% RH
Pressure	1001mbar	Tested By	Julon Liu
Required Passing Performance		Criterion A	

Frequency Band (MHz)	Field Strength (Vrms)	Cable	Injection Method	Performance Criterion	Observation	Result
0.15 ~ 80	3	AC Power Line (0.3m)	CDN-M3	☒A ☐B	Note ☒1 ☐2	PASS
0.15 ~ 80	3	RJ 45 Line (0.3m)	CDN-T8	☒A ☐B	Note ☒1 ☐2	PASS

NOTE: 1. There was no change compared with initial operation during the test.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

8.8. POWER FREQUENCY MAGNETIC FIELD

8.8.1. TEST SPECIFICATION

Basic Standard:	IEC 61000-4-8
Frequency Range:	50Hz
Field Strength:	1 A/m
Observation Time:	1 minute
Inductance Coil:	Rectangular type, 1mx1m

8.8.2. TEST INSTRUMENT

Immunity Shield Room				
Name of Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Due**
Induction Coil Interface	Schaffner	INA 2141	6009	No Calibration Required
5KVA Power Source	Teseq	5001IX-208-TSQ	1207A03643	No Calibration Required
AC/DC Clamp Meter	Lutron	CM-9930R	I.200121	06/04/2014
Magnetic Field Meter	Sypris	4080	0247	03/11/2014

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. N.C.R.= No Calibration required

8.8.3. TEST PROCEDURE (please refer to measurement standard or CCS SOP PA-027)

a. The equipment is configured and connected to satisfy its functional requirements. It shall be placed on the GRP with the interposition of a 0.1m-thick insulating support.


b. The equipment cabinets shall be connected to the safety earth directly on the GRP via the earth terminal of the EUT.

c. The power supply, input and output circuits shall be connected to the sources of power supply, control and signal.

d. The cables supplied or recommended by the equipment manufacturer shall be used. 1 meter of all cables used shall be exposed to the magnetic field.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

8.8.4. TEST SETUP



- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

NOTE:
TABLETOP EQUIPMENT
The equipment shall be subjected to the test magnetic field by using the induction coil of standard dimension (1 m x 1 m). The induction coil shall then be rotated by 90 degrees in order to expose the EUT to the test field with different orientations.

FLOOR-STANDING EQUIPMENT
The equipment shall be subjected to the test magnetic field by using induction coils of suitable dimensions. The test shall be repeated by moving and shifting the induction coils, in order to test the whole volume of the EUT for each orthogonal direction. The test shall be repeated with the coil shifted to different positions along the side of the EUT, in steps corresponding to 50 % of the shortest side of the coil. The induction coil shall then be rotated by 90 degrees in order to expose the EUT to the test field with different orientations.

8.8.5. TEST RESULTS

Temperature	N/A	**Humidity**	N/A
Pressure	N/A	**Tested By**	N/A
Required Passing Performance		**Criterion A**	

DIRECTION	Field Strength (A/m)	Performance Criterion	OBSERVATION	RESULTS
X	1	A	Note	N/A
Y	1	A	Note	N/A
Z	1	A	Note	N/A

NOTE: There is no any sensitive part for magnetic field test. Applicable only to equipment containing susceptible to magnetic field.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

8.9. VOLTAGE DIPS & VOLTAGE INTERRUPTIONS

8.9.1. TEST SPECIFICATION

Basic Standard:	IEC 61000-4-11
Test duration time:	Minimum three test events in sequence
Interval between event:	Minimum 10 seconds
Phase Angle:	0^o / 180^o
Test cycle:	3 times

8.9.2. TEST INSTRUMENT

Immunity shielded room				
Name of Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Due**
EMC Immunity Tester	EMC Partner	TRANSIENT 2000	1117	03/10/2014
AC/DC Clamp Meter	Lutron	CM-9930R	I.200121	06/04/2014
Software	Genecs Ver. 3.27			


NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. N.C.R.= No Calibration required

8.9.3. TEST PROCEDURE (please refer to measurement standard or CCS SOP PA-028)

1. The EUT and support units were located on a wooden table, 0.8 m away from ground floor.
2. Setting the parameter of tests and then perform the test software of test simulator.
3. Conditions changes to occur at 0 degree crossover point of the voltage waveform.
4. Recording the test result in test record form.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

8.9.4. TEST SETUP



- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

8.9.5. TEST RESULTS

Temperature	25°C	**Humidity**	43% RH
Pressure	1001mbar	**Tested By**	Julon Liu
Required Passing Performance	**Criterion B: >95% reduction 0.5 period** **Criterion C: 30% reduction 25 period & >95% reduction 250 period**		

Test Power: 230Vac, 50Hz				
Voltage (% Reduction)	**Duration (Period)**	**Performance Criterion**	**Observation**	**Test Result**
>95	0.5	☒**A** ☐**B** ☐**C**	**Note** ☒**1** ☐**2**	PASS
30	25	☒**A** ☐**B** ☐**C**	**Note** ☒**1** ☐**2**	PASS
>95	250	☐**A** ☐**B** ☒**C**	**Note** ☐**1** ☒**2**	PASS


NOTE: 1. There was no change compared with initial operation during and after the test. No unintentional response was found during the test.
2. EUT shut down, it could not become normal except reinstalled by operator.

This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

9 PHOTOGRAPHS OF THE TEST CONFIGURATION

CONDUCTED EMISSION TEST







This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

CONDUCTED EMISSION TEST AT TELECOMMUNICATION PORTS

RJ45 Telecom Port with ISN (10Mbps & 100Mbps & 1Gbps)





This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

RADIATED EMISSION TEST





This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Harmonic & Flicker Test



ESD Test



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

RS Test



EFT Test



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

EFT For I/O Test



Surge Test



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Surge For I/O Test



CS Test



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

CS For I/O Test



Voltage Dips / Interruptions Test



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.