



SPORTON LAB.

Certificate No: EC402416

CERTIFICATE OF COMPLIANCE

EQUIPMENT : Rugged Tablet Computer

MODEL NO. : xxxRTC-900B-WBGzxxx-xxxx

1. xxx=TF-(TF: Toxic Free) or blank

2. z is blank or H,blank means without 3G function;

H means with 3G function

3. xxx is for marketing purpose

4. xxx=SW revision, ex: 1110=rev1, x:0~9

APPLICANT : AAEON Technology Inc.

5F, No. 135, Lane 235, Pao Chiao Rd.,

Taipei, Taiwan



I HEREBY

CERTIFY THAT:

The equipment is in accordance with the procedures are given in **Directive 2004/108/EC.**

The equipment was **Passed** the test performed according to

EN 55022:2010/AC:2011 Class B,

EN 61000-3-2:2006/A1:2009 and /A2:2009, EN 61000-3-3:2008 and

EN 55024:2010 (IEC 61000-4-2 Edition 2.0 2008-12,

IEC 61000-4-3 Edition 3.2 2010-04, IEC 61000-4-4 Edition 3.0 2012-04,

IEC 61000-4-5 Edition 2.0 2005-11, IEC 61000-4-6 Edition 3.0 2008-10

IEC 61000-4-8 Edition 2.0 2009-09, IEC 61000-4-11 Edition 2.0 2004-03)

The test was carried out on **Nov. 27, 2014** SPORTON INTERNATIONAL INC. LAB.

Kero Kuo

Assistant Manager



CE EMC TEST REPORT

according to

**European Standard EN 55022:2010/AC:2011 Class B,
EN 61000-3-2:2006/A1:2009 and /A2:2009, EN 61000-3-3:2008 and
EN 55024:2010 (IEC 61000-4-2 Edition 2.0 2008-12,
IEC 61000-4-3 Edition 3.2 2010-04, IEC 61000-4-4 Edition 3.0 2012-04,
IEC 61000-4-5 Edition 2.0 2005-11, IEC 61000-4-6 Edition 3.0 2008-10,
IEC 61000-4-8 Edition 2.0 2009-09, IEC 61000-4-11 Edition 2.0 2004-03)**

Equipment : Rugged Tablet Computer

Model No. : xxxRTC-900B-WBGzxxx-xxxx

1. xxx=TF-(TF: Toxic Free) or blank

2. z is blank or H, blank means without 3G function;

H means with 3G function

3. xxx is for marketing purpose

4. xxxx=SW revision, ex: 1110=rev1, x:0~9

Applicant : AAEON Technology Inc.

5F, No. 135, Lane 235, Pao Chiao Rd.,

Hsin-Tien Dist., New Taipei City,

Taiwan, R.O.C

Statement

- The test result refers exclusively to the test presented test model / sample.
- Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.
- This test report is only applicable to European Community.

SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.





Table of Contents

History of this test report.....4

CERTIFICATE OF COMPLIANCE.....5

1. General Description of Equipment under Test.....6

 1.1. Applicant.....6

 1.2. Manufacturer6

 1.3. Basic Description of Equipment under Test6

 1.4. Feature of Equipment under Test6

2. Test Configuration of Equipment under Test7

 2.1. Test Manner7

 2.2. Description of Test System9

 2.3. Connection Diagram of Test System for AC Powerline Conducted Emission11

 2.4. Connection Diagram of Test System for Radiated Emission12

3. Test Software13

4. General Information of Test.....14

 4.1. Test Facility14

 4.2. Test Voltage14

 4.3. Measurement Procedure.....14

 4.4. Test in Compliance with14

 4.5. Frequency Range Investigated15

 4.6. Test Distance15

5. Conducted Emissions Measurement16

 5.1. Limits for conducted disturbance at mains terminals and telecommunication ports16

 5.2. Test Procedures.....17

 5.3. Typical Test Setup Layout of AC Powerline Conducted Emissions18

 5.4. Test Result of AC Powerline Conducted Emission19

 5.5. Photographs of Conducted Power line Test Configuration21

6. Radiated Emission Measurement22

 6.1. Limits for radiated disturbance22

 6.2. Test Procedures.....23

 6.3. Typical Test Setup Layout of Radiated Emissions24

 6.4. Test Result of Radiated Emission for Below 1GHz.....25

 6.5. Photographs of Radiated Emission (Below 1GHz) Test Configuration29

 6.6. Test Result of Radiated Emission for Above 1GHz30

 6.7. Photographs of Radiated Emission (From 1GHz to 6GHz) Test Configuration32

7. Harmonic Current Emissions Measurement.....33

 7.1. Standard.....33

 7.2. Test Procedure.....33

 7.3. Test Equipment Settings33

 7.4. Typical Test Setup Layout of Harmonic Current Emissions33

 7.5. Test Result of Harmonic Current Emissions34

8. Voltage Fluctuations and Flicker Measurement.....35

 8.1. Standard.....35

 8.2. Test Procedure.....35

 8.3. Test Equipment Settings35

 8.4. Typical Test Setup Layout of Voltage Fluctuations and Flicker35



8.5. Test Result of Voltage Fluctuation and Flicker.....36

8.6. Photographs of Voltage Fluctuation and Flicker Test37

9. Electrostatic Discharge Immunity Measurement (ESD)38

9.1. Test Setup39

9.2. Test Setup for Tests Performed in Laboratory39

9.3. ESD Test Procedure40

9.4. Test Severity Levels41

9.5. Test Points42

9.6. Photographs of Test Points44

9.7. Photographs of Electrostatic Discharge Immunity Test45

10. Radio Frequency Electromagnetic Field Immunity Measurement (RS).....47

10.1. Test Record48

10.2. Test Setup.....49

10.3. Test Procedure49

10.4. Test Severity Levels.....50

10.5. Photographs of Radio Frequency Electromagnetic Field Immunity Test.....51

11. Electrical Fast Transient/Burst Immunity Measurement (EFT/BURST)53

11.1. Test Record54

11.2. Test setup55

11.3. Test on Power Line56

11.4. Test on Communication Lines56

11.5. Test Procedure56

11.6. Test Severity Levels.....57

11.7. Photographs of Electrical Fast Transient/Burst Immunity Test58

12. Surge Immunity Measurement59

12.1. Test Record60

12.2. Test Severity Levels.....61

12.3. Test Procedure61

12.4. Operating Condition.....62

12.5. Photographs of Surge Immunity Test63

13. Conducted Disturbances Induced by Radio-Frequency Field Immunity Measurement (CS)64

13.1. Test Record64

13.2. Test Severity Levels.....65

13.3. Operating Condition.....65

13.4. Test Procedure65

13.5. Photographs of CS Immunity Test66

14. Power Frequency Magnetic Field immunity Measurement (PFMF).....67

14.1. Test Record67

14.2. Test Setup.....67

14.3. Photographs of Power Frequency Magnetic Field Immunity Tests.....68

15. Voltage Dips and Voltage Interruptions Immunity Measurement (DIP)70

15.1. Test Record of Voltage Interruption71

15.2. Test Record of Voltage Dips71

15.3. Testing Requirement and Procedure71

15.4. Test Conditions71

15.5. Operating Condition.....71

15.6. Photographs of Voltage Dips and Voltage Interruption Immunity Tests72

16. List of Measuring Equipment Used73



17. Uncertainty of Test Site77
Appendix A. Photographs of EUT..... A1 ~ A47



History of this test report

Original Report Issue Date: Jan. 07, 2015

No additional attachment.

Additional attachments were issued as in the following record:

Report No.	Version	Issue Date	Description



CERTIFICATE OF COMPLIANCE

according to

**European Standard EN 55022:2010/AC:2011 Class B,
EN 61000-3-2:2006/A1:2009 and /A2:2009, EN 61000-3-3:2008 and
EN 55024:2010 (IEC 61000-4-2 Edition 2.0 2008-12,
IEC 61000-4-3 Edition 3.2 2010-04, IEC 61000-4-4 Edition 3.0 2012-04,
IEC 61000-4-5 Edition 2.0 2005-11, IEC 61000-4-6 Edition 3.0 2008-10,
IEC 61000-4-8 Edition 2.0 2009-09, IEC 61000-4-11 Edition 2.0 2004-03)**

Equipment : Rugged Tablet Computer
Model No. : xxxRTC-900B-WBGzxxx-xxxx
1. xxx=TF-(TF: Toxic Free) or blank
2. z is blank or H, blank means without 3G function;
H means with 3G function
3. xxx is for marketing purpose
4. xxxx=SW revision, ex: 1110=rev1, x:0~9

Applicant : AAEON Technology Inc.
5F, No. 135, Lane 235, Pao Chiao Rd.,
Hsin-Tien Dist., New Taipei City,
Taiwan, R.O.C

I HEREBY CERTIFY THAT :

The measurements shown in this test report were made in accordance with the procedures given in **EUROPEAN COUNCIL DIRECTIVE 2004/108/EC**. The equipment was **passed** the test performed according to **European Standard EN 55022:2010/AC:2011 Class B, EN61000-3-2:2006/A1:2009 and A2:2009, EN 61000-3-3:2008 and EN 55024:2010 (IEC 61000-4-2 Edition 2.0 2008-12, IEC 61000-4-3 Edition 3.2 2010-04, IEC 61000-4-4 Edition 3.0 2012-04, IEC 61000-4-5 Edition 2.0 2005-11, IEC 61000-4-6 Edition 3.0 2008-10, IEC 61000-4-8 Edition 2.0 2009-09, IEC 61000-4-11 Edition 2.0 2004-03)**. The product sample received on Oct. 27, 2014 and completely tested on **Nov. 27, 2014** at **SPORTON International Inc. LAB.**

Kero Kuo / Assistant Manager

SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



1. General Description of Equipment under Test

1.1. Applicant

AAEON Technology Inc.

5F, No. 135, Lane 235, Pao Chiao Rd., Hsin-Tien Dist., New Taipei City, Taiwan, R.O.C

1.2. Manufacturer

Same as 1.1

1.3. Basic Description of Equipment under Test

Equipment : Rugged Tablet Computer
xxxRTC-900B-WBGzxxx-xxxx
1. xxx=TF-(TF: Toxic Free) or blank
Model No. : 2. z is blank or H, blank means without 3G function;
H means with 3G function
3. xxx is for marketing purpose
4. xxxx=SW revision, ex: 1110=rev1, x:0~9
Trade Name : AAEON
Power Supply Type : From switching

1.4. Feature of Equipment under Test

Please refer to user manual.



2. Test Configuration of Equipment under Test

2.1. Test Manner

- a. During testing, the interface cables and equipment positions were varied according to European Standard EN 55022 .
- b. The complete test system included LCD Monitor”24” *1, USB 2.0 Flash Disk*1, Earphone*1, microSD Card*1, SIM Card*1, EASY Card*1, Notebook*1, AP Router*1, Base Station*1, and EUT for EMI test.
- c. The complete test system included LCD Monitor”24” *1, USB 2.0 Flash Disk*1, Earphone*1, microSD Card*1, SIM Card*1, EASY Card*1, Notebook*1, AP Router*1, Base Station*1, GPS Signal*1 and EUT for EMS test.
- d. The equipment under test were performed the following test modes:

Test Items	Description of test modes
AC Conducted Emission	Mode 1: R/W, play mp3,HDMI+VGA 1280*800 60Hz,earphone,BT+WiFi,WCDMA 2100 Band 1 Link, adapter Mode 2: R/W, play mp4,HDMI 1920*1200 60Hz,speaker,BT+WiFi,WCDMA 2100 Band 1 idle, adapter Mode 3: R/W, play photo+mp3,VGA 1280*800 60Hz,speaker,BT+WiFi,WCDMA 2100 Band 1 Link, adapter (Vertical) Mode 4: R/W,CCD(rear),HDMI+VGA 1024*768 60Hz,earphoner,BT+WiFi,WCDMA 2100 Band 1 Link, adapter Mode 5: R/W,CCD(front),HDMI+VGA 1280*800 60Hz,earphoner,BT+WiFi,WCDMA 2100 Band 1 Link, adapter Mode 6: R/W,VGA 1280*800 60Hz,GPS,earphoner,BT+WiFi,WCDMA 2100 Band 1 Link,adapter The following test mode was referred to pretest worst case “Mode 1” as AC Conducted Emission final test result.
Radiated Emissions Below 1GHz	Mode 1: R/W, play mp3,HDMI+VGA 1280*800 60Hz,earphone,BT+WiFi,WCDMA 2100 Band 1 Link, adapter Mode 2: R/W, play mp4,HDMI 1920*1200 60Hz,speaker,BT+WiFi,WCDMA 2100 Band 1 idle, adapter Mode 3: R/W, play photo+mp3,VGA 1280*800 60Hz,speaker,BT+WiFi,WCDMA 2100 Band 1 Link, adapter (Vertical) Mode 4: R/W,CCD(rear),HDMI+VGA 1024*768 60Hz,earphoner,BT+WiFi,WCDMA 2100 Band 1 Link, adapter Mode 5: R/W,CCD(front),HDMI+VGA 1280*800 60Hz,earphoner,BT+WiFi,WCDMA 2100 Band 1 Link, adapter Mode 6: R/W,VGA 1280*800 60Hz,GPS,earphoner,BT+WiFi,WCDMA 2100 Band 1 Link,battery The following test mode was referred to pretest worst case “Mode 1” for Radiated Emission final test result.
Radiated Emissions Above 1GHz	Mode 1: R/W, play mp3,HDMI+VGA 1280*800 60Hz,earphone,BT+WiFi,WCDMA 2100 Band 1 Link, adapter
Flicker Emissions	Mode 1: R/W, play mp3,CCD,GPS,NFC,HDMI+VGA 1280*800 60Hz,earphone,BT+WiFi+WCDMA2100 Band 1 Link,adapter
EMS	Mode 1: R/W, play mp3,CCD,GPS,NFC,HDMI+VGA 1280*800 60Hz,earphone,BT+WiFi+WCDMA2100 Band1 Link,adapter Mode 2: R/W, VGA 1280*800 60Hz,NFC,CCD,GPS,BT+WiFi+ WCDMA2100 Band1 idle, battery



Test Items	Description of test modes
Flicker Emissions	Mode 1: R/W, play mp3,CCD,GPS,NFC,HDMI+VGA 1280*800 60Hz,earphone,BT+WiFi+WCDMA2100 Band1 Link, adapter
EMS	Mode 1: R/W, play mp3,CCD,GPS,NFC,HDMI+VGA 1280*800 60Hz,earphone,BT+WiFi+WCDMA2100 Band1 Link, adapter Mode 2: R/W, VGA 1280*800 60Hz,NFC,CCD,GPS,BT+WiFi+WCDMA2100 Band1 Link, battery

- e. Frequency range investigated: Conduction 150 kHz to 30 MHz, Radiation 30 MHz to 6,000 MHz.
- f. Frequency range investigated immunity test: CS 150 kHz to 80 MHz, RS 80 MHz to 1,000 MHz.



2.2. Description of Test System

< EMI >

Conducted Emission and Radiated emission below 1GHz

No.	Peripheral	Manufacturer	Model Number	Cable / Spec. Description
Local				
1	LCD Monitor"24"	DELL	U2410F	HDMI Cable, D-Shielded, 2.0m
2	USB 2.0 Flash Disk	TRANSCEND	JetFlash V85	-
3	Earphone	i-Acon	HOH-323-BK	Audio Cable, Non-Shielded, 2.0m
4	Micro SD Card	TRANSCEND	16GB	-
5	SIM Card	R&S	Chunghwa Telecom	-
6	EASY Card	EASY CARD	N/A	-
Remote				
7	Notebook	DELL	E5520	-
8	AP Router	D-LINK	DIR-600B5	-
9	Base Station	R&S	CMU200	-

Radiated emission above 1GHz

No.	Peripheral	Manufacturer	Model Number	Cable / Spec. Description
Local				
1	LCD Monitor"24"	DELL	2408WFPB	HDMI Cable, D-Shielded, 2.0m
2	USB 2.0 Flash Disk	TRANSCEND	JetFlash V85	-
3	Earphone	i-Acon	HOH-323-BK	Audio Cable, Non-Shielded, 2.0m
4	Micro SD Card	Transcend	8GB	-
5	SIM Card	R&S	Chunghwa Telecom	-
6	EASY Card	EASY CARD	N/A	-
Remote				
7	Notebook	DELL	VOSTRO 3350	-
8	AP Router	ASUS	RT-AC66U	-
9	Base Station	R&S	CMU200	-




< EMS > Mode 1

No.	Peripheral	Manufacturer	Model Number	Cable / Spec. Description
Local				
1	Micro SD Card	TRANSCEND	8GB	-
2	SIM Card	R&S	N/A	-
3	EASY Card	EASY CARD	N/A	-
4	LCD Monitor	DELL	U2410F	HDMI Cable, Shielded, 1.8m
5	Earphone	INTOPIC	SR-MK02	Audio Cable, Non-Shielded, 1.8m
6	USB 2.0 Flash Disk	TRANSCEND	JetFlash V85	-
Remote				
7	Notebook	DELL	VOSTRO 3350	-
8	AP Router	ASUS	RT-AC66U	-
9	GPS Signal	WELNAVIGATE.INC	GS50	-
10	Base Station	R&S	CMU200	-


< EMS > Mode 2

No.	Peripheral	Manufacturer	Model Number	Cable / Spec. Description
Local				
1	Micro SD Card	TRANSCEND	8GB	-
2	SIM Card	R&S	N/A	-
3	EASY Card	EASY CARD	N/A	-
Remote				
4	Notebook	DELL	VOSTRO 3350	-
5	AP Router	ASUS	RT-AC66U	-
6	GPS Signal	WELNAVIGATE.INC	GS50	-
7	Base Station	R&S	CMU200	-

2.3. Connection Diagram of Test System for AC Powerline Conducted Emission



2.4. Connection Diagram of Test System for Radiated Emission





3. Test Software

<EMI>

Mode 1

One executive program was used as the test software under Win 8.

The programs were executed as follows:

- a. EUT executed "WinEMC" Test" to demonstrate "H pattern" on the Monitor.
- b. EUT executed "WinEMC" to carry out continuous R/W function from USB Flash Disk and Micro SD Card.
- c. EUT executed "Media player" to play audio sound via speaker or earphone.
- d. EUT turned on Camera function to record audio and video signal.
- e. EUT turned on wireless link function to maintain connection with the AP Router.
- f. EUT turned on BT function to maintain connection with the remote notebook.
- g. EUT executed "Proxy TAP16.6" and turned on NFC function to link with the Easy Card.
- h. EUT opened 3G function to maintain connection with Base station.

< EMS >

Mode 1 :

One executive program was used as the test software under Win 8.

The programs were executed as follows:

- a. EUT executed "WinEMC" Test" to demonstrate "H pattern" on the Monitor.
- b. EUT executed "WinEMC" to carry out continuous R/W function from USB Flash Disk and Micro SD Card.
- c. EUT executed "Media player" to play audio sound via speaker or earphone.
- d. EUT opened Camera function to record audio and video signal.
- e. EUT opened wireless link function to maintain connection with the AP Router.
- f. EUT opened BT function to maintain connection with the remote notebook.
- g. EUT executed "Proxy TAP16.6" opened NFC function to link with the Easy Card.
- h. EUT opened 3G function to maintain connection with Base station.
- i. EUT executed "GPS viewer" opened GPS function to continuous researching.

Mode 2 :

One executive program was used as the test software under Win 8.

The programs were executed as follows.

- a. EUT executed "WinEMC" Test" to demonstrate "H pattern" on the Panel.
- b. EUT executed "WinEMC" to carry out continuous R/W function Micro SD Card.
- c. EUT executed "Media player" to play audio sound via speaker or headset.
- d. EUT opened Camera function to record audio and video signal.
- e. EUT opened wireless link function to maintain connection with the AP Router.
- f. EUT opened BT function to maintain connection with the remote notebook.
- g. EUT executed "Proxy TAP16.6" opened NFC function to link with the Easy Card.
- h. EUT opened 3G function to maintain connection with Base station.
- i. EUT executed "GPS viewer" opened GPS function to continuous researching.



4. General Information of Test

4.1. Test Facility

<EMI>

Test Site : SPORTON INTERNATIONAL INC.

Test Site Location : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei 114, Taiwan, R.O.C.
TEL : 886-2-2631-4739
FAX : 886-2-2631-9740

Test Site No. : CO01-NH / OS02-NH

Test Site : SPORTON INTERNATIONAL INC.

Test Site Location : No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiag,
Tao Yuan Hsien, Taiwan, R.O.C.
TEL : 886-3-327-3456
FAX : 886-3-327-0973

Test Site No. : 03CH04-HY

<EMS>

Test Site Location : No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiag,
Tao Yuan Hsien, Taiwan, R.O.C.
TEL : 886-3-327-3456
FAX : 886-3-327-0973

4.2. Test Voltage

AC 230V / 50Hz

4.3. Measurement Procedure

EMI Test : European Standard EN 55022 Class B
Harmonics Test : European Standard EN 61000-3-2
Voltage Fluctuations Test : European Standard EN 61000-3-3
EMS Test : European Standard EN 55024
(ESD: IEC 61000-4-2, RS: IEC 61000-4-3, EFT: IEC 61000-4-4, SURGE: IEC 61000-4-5,
CS: IEC 61000-4-6, Power Frequency Magnetic Field: IEC 61000-4-8, DIPS: IEC 61000-4-11)

4.4. Test in Compliance with

EMI Test : European Standard EN 55022 Class B
Harmonics Test : European Standard EN 61000-3-2
Voltage Fluctuations Test : European Standard EN 61000-3-3
EMS Test : European Standard EN 55024
(ESD: IEC 61000-4-2, RS: IEC 61000-4-3, EFT: IEC 61000-4-4, SURGE: IEC 61000-4-5,
CS: IEC 61000-4-6, Power Frequency Magnetic Field: IEC 61000-4-8, DIPS: IEC 61000-4-11)



4.5. Frequency Range Investigated

- a. Conducted emission test: from 150 kHz to 30 MHz
- b. Radiated emission test: from 30 MHz to 6,000 MHz
- c. Radio frequency electromagnetic field immunity test: 80-1000 MHz

4.6. Test Distance

- a. The test distance of radiated emission test from antenna to EUT is 10 M (from 30MHz~1GHz).
- b. The test distance of radiated emission test from antenna to EUT is 3 M (from 1GHz~6GHz).
- c. The test distance of radio frequency electromagnetic field immunity test from antenna to EUT is 3 M.



5. Conducted Emissions Measurement

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 kHz and return leads of the EUT according to the methods defined in European Standard EN 55022 Clause 9. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meter above the ground plane as shown in section 6.4. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position producing maximum conducted emissions.

5.1. Limits for conducted disturbance at mains terminals and telecommunication ports

Limits for conducted disturbance at mains terminals

Frequency range (MHz)	Class A Limits dB(μ V)		Class B Limits dB(μ V)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 to 0.50	79	66	66 - 56	56 - 46
0.50 to 5	73	60	56	46
5 to 30	73	60	60	50

NOTE: The limits decrease linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Limits for conducted disturbance at telecommunication ports

Frequency range (MHz)	Class B			
	Voltage limits dB (μ V)		Current limits dB (μ A)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 to 0.50	84 - 74	74 - 64	40 - 30	30 - 20
0.50 to 30	74	64	30	20


NOTE: The limits decrease linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.



5.2. Test Procedures

- a. The EUT was warmed up for 15 minutes before testing started.
- b. The EUT was placed on a desk 0.8 meter height from the metal ground plane and 0.4 meter from the conducting wall of the shielding room and it was kept at least 0.8 meter from any other grounded conducting surface.
- c. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- d. Connect Telecommunication port to ISN (Impedance Stabilization Network).
- e. All the support units are connect to the other LISN.
- f. The LISN provides 50 ohm, coupling impedance for the measuring instrument.
- g. The CISPR states that a 50 ohm, 50 microhenry LISN should be used.
- h. Both sides of AC line were checked for maximum conducted interference.
- i. The frequency range from 150 kHz to 30 MHz was searched.
- j. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

5.3. Typical Test Setup Layout of AC Powerline Conducted Emissions




- a. AMN is 80 cm from the EUT and at least 80 cm from other units and other metal planes.
- b. EUT is connected to one artificial mains network (AMN).
- c. All other units of a system are powered from a second AMN. A multiple outlet strip can be used for multiple mains cords.
- d. Rear of EUT to be flushed with rear of table top.
- e. Peripherals shall be placed at a distance of 10 cm from each other and from the controller, except for the monitor which, if this is an acceptable installation practice, shall be placed directly on the top of the controller.
- f. If cables, which hang closer than 40 cm to the horizontal metal ground plane, cannot be shortened to appropriate length, the excess shall be folded back and forth forming a bundle 30 cm to 40 cm long.
- g. Mains cords and signal cables shall be positioned for their entire lengths, as far as possible, at 40 cm from the vertical reference plane.
- h. Cables of hand operated devices, such as keyboards, mice, etc. shall be placed as for normal usage.



5.4. Test Result of AC Powerline Conducted Emission

Test Mode	Mode 1	Test Site No.	CO01-NH
Test Frequency	0.15 MHz ~ 30 MHz	Test Engineer	Willy
Temperature	22 °C	Relative Humidity	53 %
Note: 1. Corrected Reading (dB μ V) = LISN Factor + Cable Loss + Read Level = Level			
2. All emissions not reported here are more than 10 dB below the prescribed limit.			
■ The test was passed at the minimum margin that marked by the frame in the following data			


Line



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.154	36.14	-19.64	55.78	25.46	10.58	0.10	AVERAGE
2	0.154	47.75	-18.03	65.78	37.07	10.58	0.10	QP
3	0.229	38.22	-24.26	62.48	27.57	10.55	0.10	QP
4	0.229	27.68	-24.80	52.48	17.03	10.55	0.10	AVERAGE
5	0.567	32.76	-13.24	46.00	22.13	10.50	0.14	AVERAGE
6	0.567	37.68	-18.32	56.00	27.05	10.50	0.14	QP
7	3.190	38.72	-17.28	56.00	27.93	10.58	0.20	QP
8	3.190	32.31	-13.69	46.00	21.52	10.58	0.20	AVERAGE
9	5.805	31.17	-18.83	50.00	20.28	10.65	0.24	AVERAGE
10	5.805	36.55	-23.45	60.00	25.66	10.65	0.24	QP
11	13.408	45.49	-14.51	60.00	34.39	10.81	0.30	QP
12	13.408	36.07	-13.93	50.00	24.97	10.81	0.30	AVERAGE



Neutral



	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.177	40.31	-24.32	64.64	30.13	10.08	0.10	QP
2	0.177	29.06	-25.57	54.64	18.88	10.08	0.10	AVERAGE
3	0.213	31.64	-21.45	53.09	21.46	10.08	0.10	AVERAGE
4	0.213	39.07	-24.02	63.09	28.89	10.08	0.10	QP
5	0.541	33.72	-22.28	56.00	23.50	10.08	0.13	QP
6	0.541	28.39	-17.61	46.00	18.17	10.08	0.13	AVERAGE
7	3.190	40.24	-15.76	56.00	29.88	10.15	0.20	QP
8	3.190	33.52	-12.48	46.00	23.16	10.15	0.20	AVERAGE
9	6.488	30.80	-19.20	50.00	20.31	10.23	0.25	AVERAGE
10	6.488	36.44	-23.56	60.00	25.95	10.23	0.25	QP
11	13.558	48.04	-11.96	60.00	37.38	10.37	0.30	QP
12	13.558	42.55	-7.45	50.00	31.89	10.37	0.30	AVERAGE


5.5. Photographs of Conducted Power line Test Configuration

- The photographs show the configuration that generates the maximum emission.

FRONT VIEW



REAR VIEW



6. Radiated Emission Measurement

Radiated emissions from 30 MHz to 6,000 MHz were measured with a bandwidth of 120 kHz for 30 MHz to 1,000 MHz and 1 MHz for above 1GHz according to the methods defines in European Standard EN 55022, Clause 10. The EUT was placed on a nonmetallic stand, 0.8 meter above the ground plane, as shown in section 7.4. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions.

6.1. Limits for radiated disturbance

Limits for radiated disturbance at a measuring distance of 10 m

Frequency range (MHz)	Class A	Class B
	Quasi-peak limits dB(µV/m)	Quasi-peak limits dB(µV/m)
30 to 230	40	30
230 to 1000	47	37

Limits for radiated disturbance at a measuring distance of 3 m

Frequency range (MHz)	Class A		Class B	
	Average limit dB(µV/m)	Peak limit dB(µV/m)	Average limit dB(µV/m)	Peak limit dB(µV/m)
1000 to 3000	56	76	50	70
3000 to 6000	60	80	54	74



6.2. Test Procedures

For Below 1GHz


- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 10 meters from the interference-receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a half wave dipole and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.

For above 1GHz


- a. Same test set up as below 1GHz radiated testing.
- b. The EUT was set 3 meters from the interference-receiving antenna which was mounted on the top of a variable height antenna tower.
- c. There should be absorber placed between the EUT and Antenna and its located size should let the test site meet CISPR16-1-4 requirement.
- d. The table was rotated 360 degrees to determine the position of the highest radiation.
- e. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.
- f. Set the DRG Horn Antenna at 1M height, then run the turn table to get the maximum noise reading from Horizontal and Vertical polarity separately.
- g. When EUT locating on the turn-table, and its height is over 172cm (Antenna's 3dB beam width of 6GHz is 27°), the DRG Horn Antenna must be raised up and descended down, then turning around the turn-table to get the maximum noise reading of the Horizontal and Vertical polarity separately. Note the maximum raise up height is same as the top of EUT.
- h. If emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

6.3. Typical Test Setup Layout of Radiated Emissions

For Below 1GHz



For above 1GHz




Remark: When EUT's height is over 172cm, h_{max} = top of EUT



6.4. Test Result of Radiated Emission for Below 1GHz

Test mode	Mode 1	Test Site No.	OS02-NH
Test frequency	30 MHz ~ 1000 MHz	Test Engineer	Chas
Temperature	20 °C	Relative Humidity	54 %
Note: 1. Emission level (dB μ V/m) = 20 log Emission level (μ V/m)			
2. Corrected Reading : Antenna Factor + Cable Loss + Read Level – Preamp Factor = Level			
■ The test was passed at the minimum margin that marked by the frame in the following data			


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	38.820	26.05	-3.95	30.00	42.55	14.41	0.87	31.78	QP	---	---
2	66.680	25.92	-4.08	30.00	50.14	6.44	1.11	31.77	QP	---	---
3	119.960	26.80	-3.20	30.00	44.75	12.21	1.44	31.60	Peak	---	---
4	185.530	26.79	-3.21	30.00	47.13	9.33	1.79	31.46	QP	---	---
5	189.510	26.65	-3.35	30.00	46.95	9.35	1.81	31.46	QP	---	---
6	189.510	25.65	-4.35	30.00	45.95	9.35	1.81	31.46	Peak	---	---
7	196.600	26.77	-3.23	30.00	46.97	9.40	1.84	31.44	QP	---	---




Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	270.400	20.73	-16.27	37.00	37.12	12.73	2.19	31.31	Peak	---	---
2	432.000	32.67	-4.33	37.00	44.80	16.40	2.84	31.37	Peak	---	---
3	499.200	33.35	-3.65	37.00	43.95	17.64	3.09	31.33	Peak	---	---
4	675.200	33.49	-3.51	37.00	41.83	19.21	3.70	31.25	Peak	---	---
5	772.800	32.81	-4.19	37.00	39.96	20.12	3.94	31.21	Peak	---	---
6	900.000	34.93	-2.07	37.00	40.42	21.33	4.29	31.11	QP	100	180




Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	119.960	22.20	-7.80	30.00	40.15	12.21	1.44	31.60	Peak	---	---
2	147.990	23.74	-6.26	30.00	43.00	10.70	1.59	31.55	Peak	---	---
3	200.060	24.22	-5.78	30.00	44.38	9.42	1.85	31.43	Peak	---	---



Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	240.000	29.72	-7.28	37.00	47.30	11.74	2.04	31.36	Peak	---	---
2	311.200	29.41	-7.59	37.00	44.76	13.57	2.36	31.28	Peak	---	---
3	432.000	30.99	-6.01	37.00	43.12	16.40	2.84	31.37	Peak	---	---
4	499.200	32.36	-4.64	37.00	42.96	17.64	3.09	31.33	Peak	---	---
5	630.400	31.90	-5.10	37.00	40.45	19.12	3.57	31.24	Peak	---	---
6	773.600	33.81	-3.19	37.00	40.95	20.13	3.94	31.21	Peak	---	---
7	900.000	33.32	-3.68	37.00	38.81	21.33	4.29	31.11	Peak	---	---


6.5. Photographs of Radiated Emission (Below 1GHz) Test Configuration

- The photographs show the configuration that generates the maximum emission.
Mode 1

FRONT VIEW



REAR VIEW






6.6. Test Result of Radiated Emission for Above 1GHz

Test mode	Mode 1	Test Site No.	03CH04-HY
Test frequency	1GHz ~ 6GHz	Test Engineer	Ou Yen Liang
Temperature	22°C	Relative Humidity	51%
Note: 1. Emission level (dBμV/m) = 20 log Emission level (μV/m)			
2. Corrected Reading : Antenna Factor + Cable Loss + Read Level – Preamp Factor = Level			
■ The test was passed at the minimum margin that marked by the frame in the following data			


Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1470.000	47.98	-22.02	70.00	52.16	25.76	33.83	3.88	100	198	Peak
2	1470.000	36.58	-13.42	50.00	40.76	25.76	33.83	3.88	100	198	Average
3 @	1612.000	44.58	-5.42	50.00	48.37	25.87	33.70	4.04	100	179	Average
4	1612.000	48.09	-21.91	70.00	51.88	25.87	33.70	4.04	100	179	Peak
5	1862.000	50.55	-19.45	70.00	53.85	26.02	33.58	4.26	100	196	Peak
6	1862.000	38.79	-11.21	50.00	42.09	26.02	33.58	4.26	100	196	Average
7	2006.000	39.84	-10.16	50.00	42.85	26.10	33.52	4.41	100	185	Average
8	2006.000	49.09	-20.91	70.00	52.10	26.10	33.52	4.41	100	185	Peak
9 @	2134.000	46.53	-3.47	50.00	49.21	26.43	33.64	4.52	100	150	Average
10	2134.000	50.27	-19.73	70.00	52.95	26.43	33.64	4.52	100	150	Peak
11	2670.000	55.84	-14.16	70.00	57.24	27.63	34.09	5.06	100	192	Peak
12 @	2670.000	46.12	-3.88	50.00	47.52	27.63	34.09	5.06	100	192	Average



Horizontal




	Freq	Level	Over	Limit	ReadAntenna	Preamp	Cable	Ant	Table	
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Pos	Pos	Remark
			dB	dBuV/m	dBuV	dB/m	dB	cm	deg	
1	1470.000	45.07	-24.93	70.00	49.25	25.76	33.83	---	---	Peak
2	1598.000	48.74	-21.26	70.00	52.59	25.86	33.71	100	236	Peak
3	1598.000	43.40	-6.60	50.00	47.25	25.86	33.71	100	236	Average
4	1748.000	50.56	-19.44	70.00	54.10	25.95	33.64	100	176	Peak
5	1748.000	38.07	-11.93	50.00	41.61	25.95	33.64	100	176	Average
6	1876.000	54.24	-15.76	70.00	57.53	26.03	33.58	100	252	Peak
7	1876.000	40.49	-9.51	50.00	43.78	26.03	33.58	100	252	Average
8 @	2132.000	44.58	-5.42	50.00	47.26	26.43	33.64	100	226	Average
9	2132.000	50.96	-19.04	70.00	53.64	26.43	33.64	100	226	Peak
10	2668.000	43.18	-6.82	50.00	44.58	27.63	34.09	100	192	Average
11	2668.000	54.99	-15.01	70.00	56.39	27.63	34.09	100	192	Peak

6.7. Photographs of Radiated Emission (From 1GHz to 6GHz) Test Configuration

- The photographs show the configuration that generates the maximum emission

Mode 1

FRONT VIEW



REAR VIEW



7. Harmonic Current Emissions Measurement

7.1. Standard

- Standard : EN 61000-3-2

7.2. Test Procedure


The measurement of harmonic currents shall be performed as follows:

- for each harmonic order, measure the 1.5 s smoothed r.m.s. harmonic current in each DFT time window as defined in EN / IEC 61000-4-7: 2002.
- calculate the arithmetic average of the measured values from the DFT time windows, over the entire observation period Short cyclic ($T_{cycle} \leq 2.5$ min). Because of synchronisation to meet the requirements for repeatability in 5%.

7.3. Test Equipment Settings

Harmonic Parameters	Setting
Line Voltage	230 V
Line Frequency	50 Hz
Current Measurement Range	High
Measurement Delay	10.0 seconds
Test Duration	10.0 minutes
Class determination Pre-test Duration	10.0 seconds

7.4. Typical Test Setup Layout of Harmonic Current Emissions





7.5. Test Result of Harmonic Current Emissions

Mode 1

Voltage (Vrms): 229.60
I_Peak (Amps): 0.635
I_Fund (Amps): 0.048
Power (Watts): 9.1

Frequency(Hz): 50.00
I_RMS (Amps): 0.097
Crest Factor: 6.881
Power Factor: 0.449

As specified on clause 7 of EN 61000-3-2:2006/A1:2009 and /A2:2009, the limits are not specified for equipment with a rated power of 75W or less.

8. Voltage Fluctuations and Flicker Measurement

8.1. Standard

- Product Standard : EN 61000-3-3

8.2. Test Procedure


The equipment shall be tested under the conditions of **Clause 5**.

The total impedance of the test circuit, excluding the appliance under test, but including the internal impedance of the supply source, shall be equal to the reference impedance. The stability and tolerance of the reference impedance shall be adequate to ensure that the overall accuracy of $\pm 8\%$ is achieved during the whole assessment procedure.

8.3. Test Equipment Settings

Flicker Parameters	Setting
Line Voltage	230 V
Line Frequency	50 Hz
Measurement Delay	10.0 seconds
Pst Integration Time	10.0 minutes
Pst Integration Periods	1
Test Duration	10.0 minutes

8.4. Typical Test Setup Layout of Voltage Fluctuations and Flicker





8.5. Test Result of Voltage Fluctuation and Flicker

Test mode	Mode 1
Final Test Result	PASS
Temperature	25 °C
Relative Humidity	45 %
Atmospheric Pressure	102 kPa
Test Date	Nov. 27, 2014
Test Engineer	Eric

Mode 1

Vrms at the end of test (Volt):	229.66			
Highest dt (%):	0.22	Test limit (%):	3.30	Pass
Time(mS) > dt:	0.0	Test limit (mS):	500.0	Pass
Highest dc (%):	0.00	Test limit (%):	3.30	Pass
Highest dmax (%):	0.15	Test limit (%):	4.00	Pass
Highest Pst (10 min. period):	0.073	Test limit:	1.000	Pass


8.6. Photographs of Voltage Fluctuation and Flicker Test

Mode 1

FRONT VIEW



REAR VIEW






9. Electrostatic Discharge Immunity Measurement (ESD)

Test mode	Mode 1
Final Test Result	PASS
Pass Performance Criteria	B ±2 / ±4 / ±8 kV for air discharge
	A ±2 / ±4 kV for contact discharge
Required Performance Criteria	B ±2 / ±4 / ±8 kV for air discharge
	B ±2 / ±4 kV for contact discharge
Basic Standard	IEC 61000-4-2
Product Standard	EN 55024:2010
Level	3 for air discharge
	2 for contact discharge
Test Voltage	±2 / ±4 / ±8 kV for air discharge
	±2 / ±4 kV for contact discharge
Discharge Impedance	330 ohm / 150 pF
Temperature	22 °C
Relative Humidity	41 %
Atmospheric Pressure	102 kPa
Test Date	Nov. 27, 2014
Test Engineer	Eric
Observation	The test points, please refer to section 9.5.

Test mode	Mode 2
Final Test Result	PASS
Pass Performance Criteria	A ±2 / ±4 / ±8 kV for air discharge
	A ±2 / ±4 kV for contact discharge
Required Performance Criteria	B ±2 / ±4 / ±8 kV for air discharge
	B ±2 / ±4 kV for contact discharge
Basic Standard	IEC 61000-4-2
Product Standard	EN 55024:2010
Level	3 for air discharge
	2 for contact discharge
Test Voltage	±2 / ±4 / ±8 kV for air discharge
	±2 / ±4 kV for contact discharge
Discharge Impedance	330 ohm / 150 pF
Temperature	22 °C
Relative Humidity	41 %
Atmospheric Pressure	102 kPa
Test Date	Nov. 27, 2014
Test Engineer	Eric
Observation	The test points, please refer to section 9.5.

9.1. Test Setup



The test setup consists of the test generator, EUT and auxiliary instrumentation necessary to perform DIRECT and INDIRECT application of discharges to the EUT as applicable, in the follow manner:

- a. CONTACT DISCHARGE to the conductive surfaces and to coupling plane;
- b. AIR DISCHARGE at insulating surfaces.

The preferred test method is that of type tests performed in laboratories and the only accepted method of demonstrating conformance with this standard. The EUT was arranged as closely as possible to arrangement in final installed conditions.

9.2. Test Setup for Tests Performed in Laboratory

A ground reference plane was provided on the floor of the test site. It was a metallic sheet (copper or aluminum) of 0.25 mm, minimum thickness; other metallic may be used but they shall have at least 0.65 mm thickness. In the SPORTON EMC LAB., we provided 1 mm thickness aluminum ground reference plane or 1 mm thickness stainless steel ground reference plane. The minimum size of the ground reference plane is 1 m x 1 m, the exact size depending on the dimensions of the EUT. It was connected to the protective grounding system.

The EUT was arranged and connected according to its functional requirements. A distance of 1 m minimum was provided between the EUT and the wall of the Lab., and any other metallic structure. In cases where this length exceeds the length necessary to apply the discharges to the selected points, the excess length shall, where possible, be placed non-inductively off the ground reference plane and shall not come closer than 0.2 m to other conductive parts in the test setup.

Where the EUT is installed on a metal table, the table was connected to the reference plane via a cable with a 470k ohm resistor located at each end, to prevent a build-up of charge. The test setup was consist a wooden table, 0.8 m high, standing on the ground reference plane. A HCP, 1.6 m x 0.8 m, was placed on the table. The EUT and cables was isolated from the HCP by an insulating support 0.5 mm thick. The VCP size, 0.5 m x 0.5 m.



9.3. ESD Test Procedure

- a. In the case of air discharge testing the climatic conditions shall be within the following ranges:
 - ambient temperature: 15 °C to 35 °C;
 - relative humidity : 30 % to 60 %;
 - atmospheric pressure : 86 kPa (860 mbar) to 106 kPa (1060 mbar).
- b. Test programs and software shall be chosen so as to exercise all normal modes of operation of the EUT. The use of special exercising software is encouraged, but permitted only where it can be shown that the EUT is being comprehensively exercised.
- c. The test voltage shall be increased from the minimum to the selected test severity level, in order to determine any threshold of failure. The final severity level should not exceed the product specification value in order to avoid damage to the equipment.
- d. The test shall be performed with both air discharge and contact discharge. On preselected points at least 10 single discharges (in the most sensitive polarity) shall be applied on air discharge. On preselected points at least 25 single discharges (in the most sensitive polarity) shall be applied on contact discharge.
- e. For the time interval between successive single discharges an initial value of one second is recommended. Longer intervals may be necessary to determine whether a system failure has occurred.
- f. In the case of contact discharges, the tip of the discharge electrode shall touch the EUT before the discharge switch is operated.
- g. In the case of painted surface covering a conducting substrate, the following procedure shall be adopted:
 - If the coating is not declared to be an insulating coating by the equipment manufacturer, then the pointed tip of the generator shall penetrate the coating so as to make contact with the conducting substrate.
 - Coating declared as insulating by the manufacturer shall only be submitted to the air discharge.
 - The contact discharge test shall not be applied to such surfaces.
- h. In the case of air discharges, the round discharge tip of the discharge electrode shall be approached as fast as possible (without causing mechanical damage) to touch the EUT. After each discharge, the ESD generator (discharge electrode) shall be removed from the EUT. The generator is then retriggered for a new single discharge. This procedure shall be repeated until the discharges are completed. In the case of an air discharge test, the discharge switch, which is used for contact discharge, shall be closed.



9.4. Test Severity Levels

9.4.1. Contact Discharge

Level	Test Voltage (kV) of Contact discharge
1	±2
2	±4
3	±6
4	±8
X	Specified
Remark : "X" is an open level.	

9.4.2. Air Discharge

Level	Test Voltage (kV) of Air Discharge
1	±2
2	±4
3	±8
4	±15
X	Specified
Remark : "X" is an open level.	

9.5. Test Points

9.5.1. Test Result of Air Discharge

Mode1

Test Method	No. of Discharges	Air Discharge/Round Tip						Test Record
		+2kV	-2kV	+4kV	-4kV	+8kV	-8kV	
Case	10	A	A	A	A	A	A	No influencing
Power Switching	10	A	A	A	A	A	A	No influencing
HDMI Port	10	A	A	A	A	A	A	No influencing
USB Port	10	A	A	A	A	A	A	No influencing
Micro SD Card Port	10	A	A	A	A	A	A	No influencing
Camera	10	A	A	A	A	A	A	No influencing
Earphone Port	10	A	A	A	A	B	B	Note ¹
SIM Card Port	10	A	A	A	A	A	A	No influencing
DC Input Jack	10	A	A	A	A	A	A	No influencing
Panel	10	A	A	A	A	A	A	No influencing
Remark	Note ¹ : During the test, the EUT would be interfered and generate noise at $\pm 8kV$ Earphone Port. After the test, the equipment continued to operate as intended without operator intervention.							

Mode2

Test Method	No. of Discharges	Air Discharge/Round Tip						Test Record
		+2kV	-2kV	+4kV	-4kV	+8kV	-8kV	
Case	10	A	A	A	A	A	A	No influencing
Power Switching	10	A	A	A	A	A	A	No influencing
Micro SD Card Port	10	A	A	A	A	A	A	No influencing
Camera	10	A	A	A	A	A	A	No influencing
SIM Card Port	10	A	A	A	A	A	A	No influencing
Panel	10	A	A	A	A	A	A	No influencing



9.5.2. Test Result of Contact Discharge

Direct discharge

Mode1 & Mode2

Test Method	No. of Discharges	Contact Discharge/Pointed Tip				Test Record
		+2kV	-2kV	+4kV	-4kV	
Screw	25	A	A	A	A	Normal

Indirect discharge to HCP and VCP

Mode1 & Mode2

Test Method	No. of Discharges	Contact Discharge/Pointed Tip				Test Record
		+2kV	-2kV	+4kV	-4kV	
HCP (At Front)	25	A	A	A	A	Normal
HCP (At Left)	25	A	A	A	A	Normal
HCP (At Right)	25	A	A	A	A	Normal
HCP (At Rear)	25	A	A	A	A	Normal
VCP (At Front)	25	A	A	A	A	Normal
VCP (At Left)	25	A	A	A	A	Normal
VCP (At Right)	25	A	A	A	A	Normal
VCP (At Rear)	25	A	A	A	A	Normal

9.6. Photographs of Test Points

Test Points



Top View



Bottom View



Side View



9.7. Photographs of Electrostatic Discharge Immunity Test

Mode 1

FRONT VIEW



REAR VIEW



Mode 2

FRONT VIEW



REAR VIEW





10. Radio Frequency Electromagnetic Field Immunity Measurement (RS)

Test mode	Mode 1&2
Final Test Result	PASS
Pass Performance Criteria	A
Required Performance Criteria	A
Basic Standard	IEC 61000-4-3
Product Standard	EN 55024:2010
Level	2
Frequency Range	80-1000 MHz
Field Strength	3 V/m (unmodulated, r.m.s) 80% AM (1 kHz)
Temperature	25 °C
Relative Humidity	45 %
Atmospheric Pressure	102 kPa
Test Date	Nov. 27, 2014
Test Engineer	Eric
Observation	Normal




10.1. Test Record

Frequency Band: 80-1000 MHz

Sides of the EUT have been exposed to the field	Antenna positioned	Test field strength Level	Test field strength (V/m)	Test Record
Front	Vertical	2	3	Normal (No influencing)
	Horizontally	2	3	Normal (No influencing)
Left	Vertical	2	3	Normal (No influencing)
	Horizontally	2	3	Normal (No influencing)
Back	Vertical	2	3	Normal (No influencing)
	Horizontally	2	3	Normal (No influencing)
Right	Vertical	2	3	Normal (No influencing)
	Horizontally	2	3	Normal (No influencing)

10.2. Test Setup



NOTE : The SPORTON 7m x 4m x 4m semi-anechoic chamber is compliance with the sixteen point's uniform field requirement as stated in IEC 61000-4-3 Section 6.2.

The procedure defined in this part requires the generation of electromagnetic fields within which the test sample is placed and its operation observed. To generate fields that are useful for simulation of actual (field) conditions may require significant antenna drive power and the resultant high field strength levels. To comply with local regulations and to prevent biological hazards to the testing personnel, it is recommended that these tests be carried out in a shielded enclosure or semi-anechoic chamber.

10.3. Test Procedure

- The equipment to be tested is placed in the center of the enclosure on a wooden table. The equipment is then connected to power and signal leads according to pertinent installation instructions.
- The bilog antenna which is enabling the complete frequency range of 80-1000MHz is placed 3m away from the equipment. The required field strength is determined by placing the field strength meter(s) on top of or directly alongside the equipment under test and monitoring the field strength meter via a remote field strength indicator outside the enclosure while adjusting the continuous-wave to the applicable antennae.
- The test is normally performed with the generating antenna facing each of four sides of the EUT. The polarization of the field generated by the broadband (bilog) antenna necessitates testing each position twice, once with the antenna positioned vertically and again with the antenna positioned horizontally.
- The dwell time at each frequency shall not be less than the time necessary for the EUT to be exercised, and able to respond. Sensitive frequencies e.g. clock frequency(ies) and harmonics or frequencies of dominant interest shall be analyzed separately.
- At each of the above conditions, the frequency range is swept 80-1000MHz, pausing to adjust the R.F. signal level or to switch oscillators and antenna. The rate of sweep is in the order of 1.5×10^{-3} decades/s. The sensitive frequencies or frequencies of dominant interest may be discretely analyzed.



10.4. Test Severity Levels

Frequency Band : 80-1000MHz

Level	Test field strength (V/m)
1	1
2	3
3	10
X	Specified
Remark : "X" is an open class.	

10.5. Photographs of Radio Frequency Electromagnetic Field Immunity Test

Mode 1

FRONT VIEW



REAR VIEW



Mode 2**FRONT VIEW****REAR VIEW**



11. Electrical Fast Transient/Burst Immunity Measurement (EFT/BURST)

Test mode	Mode 1
Final Test Result	PASS
Pass Performance Criteria	B
Required Performance Criteria	B
Basic Standard	IEC 61000-4-4
Product Standard	EN 55024:2010
Level	on input power ports -- 2
Test Voltage	on input power ports -- $\pm 0.5 / \pm 1.0$ kV
Impulse wave shape	5/50 ns (Tr/Th)
Impulse frequency	5 kHz
Test Repetition Rate	1 time / minute
Temperature	25 °C
Relative Humidity	45 %
Atmospheric Pressure	102 kPa
Test Date	Nov. 27, 2014
Test Engineer	Eric
Observation	Normal




11.1. Test Record

■ on Input power ports:

Mode 1

Test Location	Polarity	Test Level	Voltage (Peak)	Test Record
L+N+PE	+	2	1.0 kV	Note ¹
	-	2	1.0 kV	Note ¹
Remark	Note ¹ : During AC Input power test, the EUT would be interfered and generate noise. After the test, the equipment continued to operate as intended without operator intervention.			

11.2. Test setup



Key

- / length between clamp and the EUT to be tested (should be 0,5 m ± 0,05 m)
- (A) location for supply line coupling
- (B) location for signal lines coupling

IEC 901/04

The EUT was placed on a ground reference plane and was insulated from it by an insulating support about 0.1 m thick. If the EUT is table-top equipment, it was located approximately 0.8 m above the GRP. The GRP was a metallic sheet (copper or aluminum) of 0.25 mm, minimum thickness; other metallic may be used but they shall have at least 0.65 mm thickness. It shall project beyond the EUT by at least 0.1 m on all sides and connected to the protective earth. In the SPORTON EMC LAB., We provided 1 mm thickness aluminum ground reference plane or 1 mm thickness stainless steel ground reference plane. The minimum size of the ground reference plane is 1 m x 1 m, the exact size depending on the dimensions of the EUT. It was connected to the protective grounding system. The EUT was arranged and connected according to its functional requirements. The minimum distance between the EUT and other conductive structures, except the GRP. Beneath the EUT, was more than 0.5 m. using the coupling clamp, the minimum distance between the coupling plates and all other conductive structures, except the GRP. Beneath the EUT, was more than 0.5 m. The length of the signal and power lines between the coupling device and the EUT was 0.5 m or less.



11.3. Test on Power Line

- a. The EFT/B-generator was located on the GRP. The length from the EFT/B-generator to the EUT as not exceeds 0.5 m.
- b. The EFT/B-generator provides the ability to apply the test voltage in a non-symmetrical condition to the power supply input terminals of the EUT.

11.4. Test on Communication Lines

- a. The coupling clamp is composed of a clamp unit for housing the cable (length more than 3 m), and was placed on the GRP.
- b. The coupling clamp provides the ability of coupling the fast transient/bursts to the cable under test.

11.5. Test Procedure

- a. In order to minimize the effect of environmental parameters on test results, the climatic conditions when test is carrying out shall comply with the following requirements:
 - ambient temperature: 15 °C to 35 °C;
 - relative humidity : 45 % to 75 %;
 - atmospheric pressure : 86 kPa (860 mbar) to 106 kPa (1060 mbar).
- b. In order to minimize the effect of environmental parameters on test results, the electromagnetic environment of the laboratory shall not influence the test results.
- c. The variety and diversity of equipment and systems to be tested make it difficult to establish general criteria for the evaluation of the effects of fast transients/bursts on equipment and systems.
- d. The test results may be classified on the basic of the operating conditions and the functional specification of the equipment under test, according to the following performance criteria :
 - Normal performance within the specification limits.
 - Temporary degradation or loss of function or performance which is self-recoverable.
 - Temporary degradation or loss of function or performance which requires operator intervention or system reset.
 - Degradation or loss of function which is not recoverable due to damage of equipment (components).



11.6. Test Severity Levels

The following test severity levels are recommended for the fast transient/burst test :

Open circuit output test voltage $\pm 10\%$		
Level	On Input power ports	On signal port and telecommunication ports
1	0.5 kV	0.25 kV
2	1.0 kV	0.50 kV
3	2.0 kV	1.00 kV
4	4.0 kV	2.00 kV
X	Specified	Specified

Remark : " X " is an open level.
The level is subject to negotiation between the user and the manufacturer or is specified by the manufacturer.

11.7. Photographs of Electrical Fast Transient/Burst Immunity Test

Mode 1

FRONT VIEW



REAR VIEW





12. Surge Immunity Measurement

Test mode	Mode 1
Final Test Result	PASS
Pass Performance Criteria	<u>A</u> for Input Power Port
Required Performance Criteria	B for Input power ports,
Basic Standard	IEC 61000-4-5:2005
Product Standard	EN 55024:2010
Surge wave form (Tr/Th)	1,2/50 (8/20) μ s for input power ports
Level	on input power ports -- 3
Test Voltage	on Input Power Port -- $\pm 1.0 / \pm 2.0$ kV
Phase Angle	0°, 90°, 180°, 270°
Number of surges	5 positive and 5 negative pulses
Pulse Repetition Rate	1 time / min. (maximum)
Temperature	25 °C
Relative Humidity	45 %
Atmospheric Pressure	102 kPa
Test Date	Nov. 26, 2014
Test Engineer	Eric
Observation	Please refer to section 12.1



12.1. Test Record

■ on Input power ports:

Test Location	Voltage (kV)	Polarity	Phase Angle				Test Record
			0°	90°	180°	270°	
L - N	1.0	+	A	A	A	A	Normal (No influencing)
		-	A	A	A	A	Normal (No influencing)
L - PE	2.0	+	A	A	A	A	Normal (No influencing)
		-	A	A	A	A	Normal (No influencing)
N - PE	2.0	+	A	A	A	A	Normal (No influencing)
		-	A	A	A	A	Normal (No influencing)

12.2. Test Severity Levels

Level	Open-circuit test voltage, $\pm 10\%$, kV
1	0.5
2	1.0
3	2.0
4	4.0
x	Specified
Remark : " X " is an open level. This level can be specified in the product specification.	

12.3. Test Procedure

- a. Climatic conditions

The climatic conditions shall comply with the following requirements :

 - ambient temperature : 15 °C to 35 °C
 - relative humidity : 10 % to 75 %
 - atmospheric pressure : 86 kPa to 106 kPa (860 mbar to 1060 mbar).
- b. Electromagnetic conditions

The electromagnetic environment of the laboratory shall not influence the test results.
- c. The test shall be performed according the test plan that shall specify the test set-up with
 - generator and other equipment utilized;
 - test level (voltage/current);
 - generator source impedance;
 - internal or external generator trigger;
 - number of tests : at least five positive and five negative at the selected points;
 - repetition rate : maximum 1/min.
 - inputs and outputs to be tested;
 - representative operating conditions of the EUT;
 - sequence of application of the surge to the circuit;
 - phase angle in the case of a.c. power supply;
 - actual installation conditions, for example :
 - AC : neutral earthed,
 - DC : (+) or (-) earthed to simulated the actual earthing conditions.
- d. If not otherwise specified the surges have to be applied synchronized to the voltage phase at the zero-crossing and the peak value of the a.c. voltage wave (positive and negative).
- e. The surges have to be applied line to line and line(s) and earth. When testing line to earth, the test voltage has to be applied successively between each of the lines and earth, if there is no other specification.
- f. The test procedure shall also consider the non-linear current-voltage characteristics of the



equipment under test. Therefore the test voltage has to be increased by steps up to the test level specified in the product standard or test plan.

- g. All lower levels including the selected test level shall be satisfied. For testing the secondary protection, the output voltage of the generator shall be increased up to the worst-case voltage breakdown level (let-through level) of the primary protection.
- h. If the actual operating signal sources are not available, they may be simulated. Under no circumstances may the test level exceed the product specification. The test shall be carried out according to the test plan.
- i. To find all critical points of the duty cycle of the equipment, a sufficient number of positive and negative test pulses shall be applied. For acceptance test previously unstressed equipment shall be used to the protection devices shall be replaced.

12.4. Operating Condition

Full system


12.5. Photographs of Surge Immunity Test

Mode1

FRONT VIEW



REAR VIEW





13. Conducted Disturbances Induced by Radio-Frequency Field Immunity Measurement (CS)

Test mode	Mode 1
Final Test Result	PASS
Pass Performance Criteria	A
Required Performance Criteria	A
Basic Standard	IEC 61000-4-6
Product Standard	EN 55024:2010
Level	2
Test Voltage	3 V (unmodulated, r.m.s), 80% AM (1 kHz)
Frequency Range	0.15 MHz to 80 MHz
Test Port	on Input Power Port
Dwell time	2.9 seconds
Frequency step size	1 %
Coupling mode	CDN M016 M3 for AC power Port
Temperature	25 °C
Relative Humidity	45 %
Atmospheric Pressure	102 kPa
Test Date	Nov. 27, 2014
Test Engineer	Eric
Observation	Normal

13.1. Test Record

Mode 1

Test Port	Test field strength level	Test field strength (V rms)	Test Record
Input power port	2	3	Normal (No influencing)



13.2. Test Severity Levels

Level	Voltage Level (EMF)
1	1 V rms
2	3 V rms
3	10 V rms
x	Specified

Remark : " X " is an open level.
This level can be specified in the product specification.

13.3. Operating Condition

Full system

13.4. Test Procedure

- a. The EUT shall be operated within its intended climatic conditions. The temperature and relative humidity should be recorded.
- b. This test method test can be performed without using a sell shielded enclosure. This is because the disturbance levels applied and the geometry of the setups are not likely to radiated a high amount of energy, especially at the lower frequencies. If under certain circumstances the radiated energy is too high, a shielded enclosure has to be used.
- c. The test shall be performed with the test generator connected to each of the coupling and decoupling devices in turn while the other non-excited RF-input ports of the coupling devices are terminated by a 50 ohm load resistor.
- d. The frequency range is swept from 150 kHz to 80 MHz, using the signal levels established during the setting process, and with the disturbance signal 80% amplitude modulated with a 1kHz sine wave, pausing to adjust the RF-signal level or to switch coupling devices as necessary. The rate of sweep shall no exceed 1.5×10^{-3} decades/s. Where the frequency is swept incrementally, the step size shall no exceed 1% of the start and thereafter 1% of the preceding frequency value.
- e. The dwell time at each frequency shall not be less than the time necessary for the EUT to be exercised, and able to respond. Sensitive frequencies e.g. clock frequency(ies) and harmonics or frequencies of dominant interest shall be analyzed separately.
- f. In cases of dispute, the test procedure using a step size not exceeding 1% of the start and thereafter 1% of preceding frequency value shall take precedence.
- g. Attempts should be made to fully exercise the EUT during testing, and to fully interrogate all exercise modes selected for susceptibility.
- h. The use of special exercising programs is recommended.
- i. Testing shall be performed according to a Test Plan, which shall be included in the test report.
- j. It may be necessary to carry out some investigatory testing in order to establish some aspects of the test plan.

13.5. Photographs of CS Immunity Test

Mode 1

FRONT VIEW



REAR VIEW




14. Power Frequency Magnetic Field immunity Measurement (PFMF)

Test mode	Mode 1&2
Final Test Result	PASS
Pass Performance Criteria	A
Required Performance Criteria	A
Basic Standard	IEC 61000-4-8
Product Standard	EN 55024:2010
Temperature	25 °C
Relative Humidity	45 %
Atmospheric Pressure	102 kPa
Test Date	Nov. 27, 2014
Test Engineer	Eric
Observation	Please refer to section 14.1

14.1. Test Record

Power Frequency Magnetic Field	Testing duration	Coil Orientation	Test Record
50/60Hz,1A/m	1.0 Min	X-axis	Normal (No influencing)
50/60Hz,1A/m	1.0 Min	Y-axis	Normal (No influencing)
50/60Hz,1A/m	1.0 Min	Z-axis	Normal (No influencing)

14.2. Test Setup



EUT : Equipment under test G : Test Generator

14.3. Photographs of Power Frequency Magnetic Field Immunity Tests

Mode 1

FRONT VIEW



REAR VIEW



Mode 2**FRONT VIEW****REAR VIEW**



15. Voltage Dips and Voltage Interruptions Immunity Measurement (DIP)

Test mode	Mode 1
Final Test Result	PASS
Pass Performance Criteria	<u>A</u> or voltage interruption, <u>A</u> for voltage dips
Required Performance Criteria	C for voltage interruption, C/B for voltage dips
Basic Standard	IEC 61000-4-11
Product Standard	EN 55024:2010
Test Port	Input power ports
Temperature	25 °C
Relative Humidity	45 %
Atmospheric Pressure	102 kPa
Test Date	Nov. 27, 2014
Test Engineer	Eric
Observation	Please refer to section 15.1 and 15.2

**15.1. Test Record of Voltage Interruption**

Voltage (V)	Performance Criterion (Phase Angle)		Reduction Voltage	Duration (Periods)
	0°	180°		
100/240	A	A	>95 %	5000 ms

15.2. Test Record of Voltage Dips

Voltage (V)	Performance Criterion (Phase Angle)		Reduction Voltage	Duration (Periods)
	0°	180°		
100/240	A	A	30 %	500 ms
100/240	A	A	>95 %	10ms

15.3. Testing Requirement and Procedure

The test was based on IEC 61000-4-11

15.4. Test Conditions

- Source voltage and frequency : 100/240V, 50Hz, Single phase.
- Test of interval : 10 sec.
- Level and duration : Sequency of 3 dips/interrupts.
- Voltage rise (and fall) time : 1 ~ 5 μ s.

15.5. Operating Condition

Full system


15.6. Photographs of Voltage Dips and Voltage Interruption Immunity Tests

Mode1

FRONT VIEW



REAR VIEW





16. List of Measuring Equipment Used

<EMI>

<Conducted Emission >

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Receiver	R&S	ESCS 30	100357	9 kHz - 2.75 GHz	Jun. 13, 2014	Conduction (CO01-NH)
LISN	SCHAFFNER	NNB41	06/10024	9kHz - 30MHz	Dec. 05, 2013	Conduction (CO01-NH)
LISN	KYORITSU	KNW-407	8-1010-15	9kHz - 30MHz	N/A	Conduction (CO01-NH)
Power Filter	CORCOM	MR12030	N/A	30A*2	N/A	Conduction (CO01-NH)
RF Cable-CON	Suhner Switzerland	RG223/U	CB004	9kHz - 30MHz	Dec. 11, 2013	Conduction (CO01-NH)

Note: Calibration Interval of instruments listed above is one year. NCR: No calibration request.

✧

**< Radiated Emission below 1GHz >**

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Open Area Test Site	SPORTON	OATS-10	OS02-NH	30 MHz - 1 GHz 10m, 3m	Dec. 30, 2013	Radiation (OS02-NH)
Amplifier	BURGEON	BPA-530	100203	0.01 MHz - 3 GHz	May. 19, 2014	Radiation (OS02-NH)
Receiver	R&S	ESCI	100497	9 kHz - 3 GHz	Apr. 24, 2014	Radiation (OS02-NH)
Bilog Antenna	CHASE	CBL6122B	2884	30 MHz - 2 GHz	Feb. 28, 2014	Radiation (OS02-NH)
Turn Table	EMCO	2080	9508-1805	0 - 360 degree	N/A	Radiation (OS02-NH)
Antenna Mast	ETS	2075-2	2385	1 m - 4 m	N/A	Radiation (OS02-NH)
RF Cable-R10m	MIYAZAKI	5DFB	CB044	30 MHz - 1 GHz	Aug. 29, 2014	Radiation (OS02-NH)

Note: Calibration Interval of instruments listed above is one year. NCR: No calibration request.

< Radiated Emission above 1GHz >

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
3m Semi Anechoic Chamber	TDK	SAC-3M	03CH04-HY	1 GHz ~ 6 GHz 3m	May. 16, 2014	Radiation (03CH04-HY)
Receiver	R&S	ESU	100422	20Hz ~ 26.5GHz	Jun. 19, 2014	Radiation (03CH04-HY)
Amplifier	Agilent	8449B	3008A02326	1GHz ~ 26.5GHz	May. 22, 2014	Radiation (03CH04-HY)
Horn Antenna	SCHWARZBECK	BBHA9120	BBHA9120D1130	1 GHz ~ 18 GHz	Sep.16, 2014	Radiation (03CH04-HY)
Turn Table	Chaintek	3000	MF7802056	0 ~ 360 degree	NCR	Radiation (03CH04-HY)
Antenna Mast	MF	MF-7802	MF780208163	1 m ~ 4 m	NCR	Radiation (03CH04-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	CB063-HF	1 GHz ~ 40 GHz	Nov.20 , 2013	Radiation (03CH04-HY)

Note: Calibration Interval of instruments listed above is one year. NCR: No calibration request.



< EMS >

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
ESD Simulator	KEYTEK	MZ-15/EC	0711355	Air: 0 ~15kV Contact: 0 ~ 8kV	Apr. 28, 2014	ESD (ES01-HY)
EFT Generator	TESEQ	FTM3425	0180	0 ~ 4kV	Jan. 02, 2014	EFT (EX01-HY)
SURGE Generator	TESEQ	CWN 3650	0429	0 ~ 6 kV/2Ω 0~ 6 kV/12Ω	Jan. 02, 2014	SURGE (EX01-HY)
Conducted Immunity Test System	TESEQ	NSG4070	34293	9kHz ~ 1GHz	Jul. 07, 2014	CS (CS03-HY)
Attenuator	BIRD	100-SA-MFB-06	0232	150kHz ~ 230MHz	Jul. 09, 2014	CS (CS03-HY)
Coupling and Decoupling Network	SCHAFFNER	CDN M016	16672	150kHz ~ 230MHz	Jul. 04, 2014	CS (CS03-HY)
Magnetic field Immunity Loop	FCC (KEYTEK)	F-1000-4-8-G-1 25A	05004	30A/CONTINUOUS 100A/2Hrs 230A/30SEC	Nov. 03, 2014	PFMF (CS03-HY)
Magnetic Generator	FCC (KEYTEK)	F-1000-4-8/9/10 -L-1M	03004	30A/CONTINUOUS 100A/2Hrs 230A/30SEC	Nov. 03, 2014	PFMF (CS03-HY)
DIP Generator	TESEQ	VAR 3005-S16	0804	230VA/50Hz/60Hz 0%Open/5S 0%Short/5S 40%/0.10S 70%/0.01S	Jan. 02, 2014	DIP (EX01-HY)
Harmonic/Flicker Test System	SCHAFFNER	CCN1000-1	72471	4000VA 16A PEAK	Jan. 29, 2014	Harmonics, Flicker (EX01-HY)

Note: Calibration Interval of instruments listed above is one year.

**< EMS > RS**

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RS immunity Test system	ROHDE& SCHWARZ	RSF	RS-01	80M~3GHz	Mar. 14, 2014	RS (RS01-HY)
Amplifier	AMPLIFIER& RESEARCH	250W 1000AM	0332909	80MHz ~ 1GHz	Apr. 08, 2014	RS (RS01-HY)
DUAL DIRECTIONAL COUPLER	AMPLIFIER& RESEARCH	DC6180A	312453	0.08 ~ 1GHz	Oct. 20, 2014	RS (RS01-HY)
INTEGRATED MEASUREMENT SYSTEM	ROHDE& SCHWARZ	IMS	100007	9kHz ~ 3GHz	Mar. 26, 2014	RS (RS01-HY)
NRP-Z91 POWER SENSOR 6GHZ	ROHDE& SCHWARZ	NRP-Z91 1168.8004.02	100095	9kHz ~ 3GHz	Mar. 26, 2014	RS (RS01-HY)
Antenna	FRANKONIA	BTA-L	02002L	26MHz ~ 1GHz	May 05, 2014	RS (RS01-HY)
Probe	ETS-LINDGREN	HI-6005	00052473	0.1MHz ~ 5GHz	Feb. 05, 2014	RS (RS01-HY)



17. Uncertainty of Test Site

Emission Test Measurement Uncertainty

Test Items	Test Site No.	Uncertainty	Remark
Conducted Emissions	CO01-NH	± 2.6dB	Confidence levels of 95%
Radiated Emissions below 1GHz	OS0-NH	± 3.0dB	Confidence levels of 95%
Radiated Emissions above 1GHz	03CH04-HY	± 4.8dB	Confidence levels of 95%

Immunity Test Measurement Uncertainty

◆ ESD Immunity (IEC 61000-4-2)

Negative Discharge Current

From Standard			
2kV	First Peak Current	Current at 30ns	Current at 60ns
Nominal	7.5	4	2
Min	6.75	2.8	1.4
Max	8.25	5.2	2.6
Tolerance in %	10%	30%	30%

From calibration certificate					
Measured First Peak Current	1st Peak Worst case. +5%	Measured Current at 30ns	30ns Worst case. +5%	Measured Current at 60ns	60ns Worst case. -5%
7.48	7.85	4.2	4.41	2.01	2.11
	6.75		2.8		1.4
	8.25		5.2		2.6

From Standard			
4kV	First Peak Current	Current at 30ns	Current at 60ns
Nominal	15	8	4
Min	13.5	5.6	2.8
Max	16.5	10.4	5.2
Tolerance in %	10%	30%	30%

First Peak Current	1st Peak Worst case. +5%	Measured Current at 30ns	30ns Worst case. +5%	Measured Current at 60ns	60ns Worst case. +5%
15.12	15.88	8.03	8.43	3.68	3.86
	13.5		5.6		2.8
	16.5		10.4		5.2

From Standard			
6kV	First Peak Current	Current at 30ns	Current at 60ns
Nominal	22.5	12	6
Min	20.25	8.4	4.2
Max	24.75	15.6	7.8
Tolerance in %	10%	30%	30%

First Peak Current	1st Peak Worst case. -5%	Measured Current at 30ns	30ns Worst case. +5%	Measured Current at 60ns	60ns Worst case. +5%
22.78	23.92	12.37	12.99	5.45	5.72
	20.25		8.4		4.2
	24.75		15.6		7.8



Negative Discharge Current

From Standard				From calibration Certificate					
8kV	First Peak Current	Current at 30ns	Current at 60ns	First Peak Current	1st Peak Worst case. +5%	Measured Current at 30ns	30ns Worst case. +5%	Measured Current at 60ns	60ns Worst case. +5%
	Nominal	30	16	8	30.26	31.77	16.13	16.94	7.39
Min	27	11.2	5.6		27		11.2		5.6
Max	33	20.8	10.4		33		20.8		10.4
Tolerance in %	10%	30%	30%						

Negative Discharge Voltage

Standard Parameters				Measured Values
Indicated Voltage.	Tolerance.	Max.	Min.	
kV	%	kV	kV	kV
2	10	2.20	1.80	2.05
4	10	4.40	3.60	4.027
6	10	6.60	5.40	5.955
8	10	8.80	7.20	7.916
15	10	16.50	13.50	14.839

Negative Rise Time

Standard Parameters		Measured Values			
T max.	T min	Indicated Voltage.	Measured Rise Time.	Worst Case max. +6%	Worst Case min. -6%
1ns	0.7ns	2kV	0.851	0.902	0.799
		4kV	0.780	0.268	0.733
		6kV	0.750	0.795	0.705
		8kV	0.772	0.818	0.726

It has been demonstrated that the ESD generator meets the specified requirements in the standard with at least a 95% confidence



◆ RF Radiated Immunity (IEC 61000-4-3)

Symbol	Source of Uncertainty	Value	Probability distribution	Divisor	$u_i(y)$
F_{SM}	Felds Strength monitor	1.5	Normal 2	2.000	0.75
FS_{AW}	Field Strength acceptability window	0.50	Rectangular	1.732	0.29
PAH	Power Amplifier Harmonics	0.50	Rectangular	1.732	0.29
R_S	Measurement System Repeatability	0.50	normal 1	1.000	0.50
R_{EUT}	Repeatability of EUT	0.00	normal 1	1.000	0.00
$u_c(F_S)$	Combined Standard Uncertainty	-	normal	-	0.83
$U(F_S)$	Expanded Uncertainty	-	normal k= 2		1.66

Specified Level (V/m)	Test level (V/m)
For 1 Volts	1.25
For 3 Volts	3.33
For 10 Volts	11.22

◆ EFT/BURST Immunity (IEC 61000-4-4)

Voltage Output

Standard Parameters				Measured Values
Indicated Voltage.	Tolerance.	Max.	Min.	
kV	%	kV	kV	kV
0.5	10	0.55	0.45	0.489
1	10	1.1	0.9	1.006
2	10	2.2	1.8	2.016
4	10	4.4	3.6	3.830
- 0.5	10	- 0.55	- 0.45	- 0.489
- 1	10	- 1.1	- 0.9	- 0.972
- 2	10	- 2.2	- 1.8	- 1.961
- 4	10	- 4.4	- 3.6	- 3.770



Spike frequency

Standard Parameters					Measured Values
Indicated Voltage.		Tolerance.	Max.	Min.	
kV	kHz	%	kHz	kHz	kHz
0.5	5	10	5.5	4.5	5.00
1	5	10	5.5	4.5	4.98
2	5	10	5.5	4.5	4.98
4	2.5	10	2.75	2.25	2.49
4	5	10	5.5	4.5	5.01

Burst width

Standard Parameters					Measured Values
Indicated Voltage.		Tolerance.	Max.	Min.	
kV	ms	%	ms	ms	ms
0.5	15	20	18	12	14.97
1	15	20	18	12	14.94
2	15	20	18	12	14.91
4	15	20	18	12	14.95

Burst period

Standard Parameters					Measured Values
Indicated Voltage.		Tolerance.	Max.	Min.	
kV	ms	%	ms	ms	ms
0.5	300	20	360	240	299.7
1	300	20	360	240	300.5
2	300	20	360	240	299.2
4	300	20	360	240	300.2

It has been demonstrated that the EFT/BURST generator meets the specified requirements in the standard with at least a 95% confidence

◆ **Surge Immunity (IEC 61000-4-5)**

Surge Voltage Output

Standard Parameters				Measured Values
Indicated Voltage.	Tolerance.	Max.	Min.	
kV	%	kV	kV	kV
0.5	10	0.55	0.45	0.488
1	10	1.1	0.9	0.964
2	10	2.2	1.8	1.984
4	10	4.4	3.6	3.94
6	10	6.6	5.4	5.91
- 0.5	10	- 0.55	- 0.45	- 0.484
- 1	10	- 1.1	- 0.9	- 0.977
- 2	10	- 2.2	- 1.8	- 1.992
- 4	10	- 4.4	- 3.6	- 3.95
- 6	10	- 6.6	- 5.4	- 5.91

Output Wave

Standard Parameters			Measured Values
+ 6 kV			
	Max.	Min.	
Rise Time	1.56 μ s	0.84 μ s	1.24 μ s
Duration Time	60 μ s	40 μ s	52.83 μ s
+ 6 kV			
Rise Time	1.56 μ s	0.84 μ s	1.30 μ s
Duration Time	60 μ s	40 μ s	54.72 μ s

It has been demonstrated that the Surge generator meets the specified requirements in the standard with at least a 95% confidence



◆ RF Conducted Immunity (IEC 61000-4-6)

Symbol	Source of Uncertainty	Value	Probability distribution	Divisor	$u_i(y)$
S_A	Spectrum Analyzer	1.50	Rectangular	1.732	0.87
C_C	Current coil Calibration	1.00	normal 2	2.000	0.50
M	Mismatch	-0.5	U-shaped	1.414	-0.35
M	Mismatch	-0.3	U-shaped	1.414	-0.35
R_S	Measurement System Repeatability	0.50	normal 1	1.000	0.50
R_{EUT}	Repeatability of EUT	0.00	normal 1	1.000	0.00
$u_c(F_S)$	Combined Standard Uncertainty	-	normal	-	1.57
$U(F_S)$	Expanded Uncertainty	-	normal k= 2		3.14

Specified Level (V)	Test level (V)
For 1 Volts	1.30
For 3 Volts	3.88
For 10 Volts	12.15

◆ Magnetic Field Immunity (IEC 61000-4-8)

Current output

Standard Parameters					Measured Values	
Magnetic Field Strength	Output Current	Tolerance.	Max.	Min.		
A/m	A	%	A	A		
1	6	5	6.3	3.8		A
3	50	5	52.5	47.5		6.1
10	180	5	189	171	49.0	
					188.0	

It has been demonstrated that the Magnetic generator meets the specified requirements in the standard with at least a 95% confidence



◆ Voltage Variation Immunity (IEC 61000-4-11)

Short Dip period

Standard Parameters				
Degree	Duration	Tolerance.	Max.	Min.
	ms	%	ms	ms
90	4	5	4.2	3.8
180	8	5	8.4	7.6
270	12	5	12.6	11.4
360	16	5	16.8	15.2

Measured Values
ms
4.17
8.33
12.50
16.67


Long Dip period

Standard Parameters				
Degree	Duration	Tolerance.	Max.	Min.
	ms	%	ms	ms
90	16	5	16.8	15.2
180	50	5	55	45
270	100	5	110	90
360	150	5	165	135


Measured Values
ms
16.38
50.04
99.64
149.3



It has been demonstrated that the Dip generator meets the specified requirements in the standard with at least a 95% confidence

APPENDIX A. Photographs of EUT





















































NFC Module





































WLAN and Bluetooth Module




















WWAN Module





















WLAN Ant.



WLAN Ant.






WLAN Ant.







WWAN Ant.








Bluetooth Ant.



Bluetooth Ant.



Bluetooth Ant.

