

P5 Verification Test Plan

Release No: 09P010014

Product Model	FOX-81
Description	Multi-Purpose & Waterproof Panel PC with 8.4" TFT LCD
Test Configuration	<input checked="" type="checkbox"/> New product <input checked="" type="checkbox"/> System : FOX-81 <input checked="" type="checkbox"/> PCB : GENE-9455 A1.0 <input checked="" type="checkbox"/> BIOS : FOX-81 BIOS Rev 1.0(09/02/2009) <input checked="" type="checkbox"/> Riser Card : N/A <input checked="" type="checkbox"/> Inverter :HWA YOUN.QF82V4.90IS <input checked="" type="checkbox"/> Daughter Board : N/A <input checked="" type="checkbox"/> I/O Board :PER-T102.Rev.A1.1 <input checked="" type="checkbox"/> Power Board : PER-P15DRev.A1.0 <input checked="" type="checkbox"/> LCD : AUO.G084SN05 V7 8.4" <input checked="" type="checkbox"/> Touch Panel : Mildex 8.4" 4wire <input checked="" type="checkbox"/> M/B Chipset <input checked="" type="checkbox"/> North Bridge : Intel 945GSE <input checked="" type="checkbox"/> South Bridge : Intel ICH7-M <input checked="" type="checkbox"/> VGA Chipset : Intel 945GSE integrated VGA <input checked="" type="checkbox"/> Audio Chipset : Realtek ALC655 <input checked="" type="checkbox"/> Ethernet Chipset :Intel 82574L <input checked="" type="checkbox"/> I/O Chipset : ITE8781 <input checked="" type="checkbox"/> TV Chipset : N/A <input checked="" type="checkbox"/> Remark : QE P5 Report for FOX-81
Test Result Summary	
<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail <input type="checkbox"/> Pass with Deviation Comment: _____ _____	

2009/09/04

Issue date

Wenyuan Yang

Manager

Eva Yeh

Test Engineer

Summary Table of contents:

Summary Table of contents	2
Platform Information	3
1. I/O Peripheral Function Test	4
2. Timer Accuracy Test	7
3. Network HUB / LAN Connection Test	8
4. Hardware compatibility	8
5. O.S. Compatibility Test	13
6. BIOS Function Test	14
7. Performance Test	15

There are 3 test results in this document; they are described as follows:

Pass: Function worked perfectly

Fail: Function failed and must be modified in the next version

N/A: Outside of specification or no test equipment

Platform Information:

Item	Device Information
System	FOX-81
PCB Model / Version	Gene 9455 A1.0
BIOS / Version	FOX-81 BIOS Rev 1.0(09/02/2009)
CPU Type	Intel(R) Atom(TM) CPU N270 1.6GHz
Memory Type	DSL DDRII 667 1GB. ELPIDA(64MX8).E5108A(X)-6E-E
SATA	N/A
Primary IDE Master	N/A
Primary IDE Slave	N/A
SATA DOM	InnoDisk SATADOM H Type 4GB
CRT	N/A
LCD	AUO.G084SN05 V7 8.4"
Compact Flash	N/A
Riser Card	N/A
Inverter	HWA YOUN.QF82V4.90IS
Daughter Board	N/A
I/O Board	PER-T102.Rev.A1.1
Touch Panel	Mildex 8.4" 4wire
Operating System	Windows XP Professional English Version V2002 Service Pack 3
Power Supply	DC Input: SINPRO MPU100-108 Input:100-240V~47-63Hz 1.25-0.5A Output : 24V 4.16A

Test Result for Certification

1. I/O Peripheral Function Test

I/O Peripheral Function Test –I/O Function	Result		
	Pass	Fail	N/A
Floppy Connector / Driver A:			X
Primary IDE Master			X
Primary IDE Slave			X
Secondary IDE Master			X
Secondary IDE Slave			X
Third IDE Master			X
Third IDE Slave			X
RAID 0 Function Test			X
RAID 1 Function Test			X
SATA1 / Serial ATA Connector 1			X
SATA2 / Serial ATA Connector 2	X		
SATA3 / Serial ATA Connector 3			X
SATA4 / Serial ATA Connector 4			X
Compact Flash – Type I			X
Compact Flash – Type II			X
DOC (Disk On Chip)			X
DOM (Disk On Module) – 40 Pin			X
DOM (Disk On Module) – 44 Pin			X
COM 1-232	X		
COM 2-232	X		
COM 2-422	X		
COM 2-485	X		
COM 2-Ring /+5V /+12V			X
COM 3-232			X
COM 4-232			X
COM 5-232			X
COM 6-232			X
PS/2 Mouse & Keyboard (Internal)			X
PS/2 Mouse & Keyboard (External)			X
Audio Connector	X		
Audio 7.1 Channel / S/P DIF			X
LPT 1			X
LPT 2			X
SIR / 115.2 Kbps			X
FIR / 4M bps			X
USB 1/2 Ports			X
USB 3/4 Ports	X		
USB 5/6 Ports			X
USB 7/8 Ports			X
USB 2.0 1/2 Ports	X		
USB 2.0 3/4 Ports			X

USB 2.0 5/6 Ports			X
USB 2.0 7/8 Ports			X
DIO Connector			X
Card Bus			X
PC/104			X
PC/104-Plus			X
PCI-104			X
CD-In Connector			X
TFT TTL LCD			X
TFT LVDS LCD	X		
CRT			X
TV-out / S Terminal			X
TV-out / AV Terminal			X
DVI			X
HDMI			X
Component Video : Y/ Pb /Pr			X
Touch Screen – 4 Wire	X		
Touch Screen – 5 Wire			X
Touch Screen – 8 Wire			X
DIMM Slots	X		
Watchdog IRQ n			X
Watchdog Software Control	X		
CPU FAN Connector			X
System FAN Connector			X
Front Panel	Result		
	Pass	Fail	N/A
Power On Button	X		
IDE LED			X
External Buzzer			X
On Board Buzzer	X		
Power LED			X
Reset Switch			X
Keyboard Lock			X
Jumpers Function	Result		
	Pass	Fail	N/A
ATX simulates AT			X
Audio Out Selection (W/O & W/ Amplifier)			X
LCD Power Select			X
COM1-Ring/5V/12V Selection			X
COM2-Ring/5V/12V Selection			X
COM2 RS-232/422/485 Selection (Depends on BIOS)			X
COM3-Ring/5V/12V Selection			X
COM4-Ring/5V/12V Selection			X
Clear CMOS	X		
Touch Screen Operating Mode Selection			X
Clock Shift of TFT LCD			X

Power Connector & Function		Result		
		Pass	Fail	N/A
5V only Power for Big 4P				X
ATX Power Connector				X
ATX Power_12V Connector				X
AT Power Connector				X
Big 4P Power Connector				X
Mini 4P Power Connector				X
External Power Connector		X		
Option ATX Power Connector (PS-ON / +5VSB)				X
LAN Connector & Function		Result		
		Pass	Fail	N/A
LAN Link / Speed LED	LAN1			X
	LAN2			X
LAN Active LED	LAN1			X
	LAN2			X
LAN 10/100 Ethernet		X		
LAN 1G Ethernet		X		
PCI Connector & Function		Result		
		Pass	Fail	N/A
Mini PCI Slots				X
PCI Slots				X
PCI Express				X
Mini PCI Express card				X
Express card				X
OSD Control Function		Result		
		Pass	Fail	N/A
POWER Button		X		
Brightness Control		X		

2. Timer Accuracy Test

System Clock & RTC Clock Test				
Test Method	Margin for error	Result		
		Pass	Fail	N/A
RTC Clock in Power On Mode	±3 second during 24 hours	X		
RTC Clock in Power Off Mode	±3 second during 24 hours	X		
Watchdog Timer Test		Result		
		Pass	Fail	N/A
Time-out Interval	10 sec	X		
	60 sec	X		
	255 sec	X		

3. Network HUB / LAN Connection Test

Location		LED Type				Result		
						Pass	Fail	N/A
LAN1 LED		Link / Speed LED						X
		Active LED						X
LAN2 LED		Link / Speed LED						X
		Active LED						X
Location	Speed	HUB Type	Cable Length	HUB Speed	Onboard LAN Speed	Result		
						Pass	Fail	N/A
Onboard LAN1	10/100/1000 Mbps	D-Link DGS-1008T	100M	1GBps	1000	X		
		Accton DeskTop-3005	100M	100 MBps	100	X		
		SVEC FD916H (10 Mbps HUB)	100M	10 MBps	10	X		
Onboard LAN2	10/100/1000 Mbps	D-Link DGS-1008T	100M	1GBps	1000			X
		Accton DeskTop-3005	100M	100 MBps	100			X
		SVEC FD916H (10 Mbps HUB)	100M	10 MBps	10			X

4. Hardware Compatibility

CPU Compatible Test							
CPU Type		FSB	Prime95 Version	Result			
				Pass	Fail	N/A	
Intel(R) Atom(TM) CPU N270 1.6GHz		533MHz	V.256	X			
		MHz	V.256				
Memory Compatibility Test							
Memory Brand	Memory Chipset	Frequency	Size	MemTest86 Version	Result		
					Pass	Fail	N/A
DSL DDRII 1GB	ELPIDA(64MX8).E5108A(X)-6E-E	667	1GB	V3.5	X		
Audio Basic Function Test					Result		
					Pass	Fail	N/A
System Sound							X
CD_In							X
CD_In Sound Recorder							X
Play Sound Recorder							X
Line Out					X		
Line In							X
Line In Sound Record							X
MIC Speaker					Dynamic		X
					Condenser		X

MIC Sound Recorder		Dynamic			X
		Condenser			X
Audio 5.1 Channel with S/P DIF Function Test			Result		
			Pass	Fail	N/A
2-channel mode for stereo speaker output					X
4-channel mode for 4 speaker output					X
6-channel mode for 5.1 speaker output					X
8-channel mode for 7.1 speaker output					X
S/P DIF function Test		Input			X
		Output			X
On Board TV Function Test			Result		
			Pass	Fail	N/A
NTSC	AV Terminal				X
PAL					X
NTSC	S Terminal				X
PAL					X
On Board LCD Function Test					
TFT LCD	Type		Voltage	Result	
				Pass	Fail
LVDS	AUO.G084SN05 V7 / 8.4" / 800x600 18bit		3.3V	X	
	AUO G065VN01 V.0 / 6.5" / 640x480 / 24bit (4:3)		3.3V		X
	Data Image 7" / 800*480 / 18bit (16:9)		3.3V		X
	AU G084SN05 V.3 / 8.4" / 800*600 / 18bit (4:3)		3.3V		X
	AU G150XG01 V.0 / 15" / 1024*768 / 18bit (4:3)		3.3V		X
	AU M150XN07 V.2 / 15" / 1024x768 / 24bit (4:3)		3.3V		X
	Toshiba /12.1"/1280 x 768 x 18bit (16:9)		3.3V		X
	AU M170EG01 / 17" / 1280*1024 / 48bit (4:3)		5V		X
	AU M170XW01 V.1 / 17" / 1280x768 / 24bit (16:9)		5V		X
	AUO T260XW02 / 26" / 1366x768 / 24bit		5V		X
	AU M201UN02 V.5 / 20.1" / 1600x1200x48bit		5V		X
	AUO T370HW01 / 37" / 1920x1080 / 48bit		5V		X
	AUO M190PW01 V0 / 19" / 1440X900/48 bit		5V		X
TTL	Toshiba LTM10C209A / 10.4" / 640*480 / 18bit (4:3)		5V		X
	NEC NL8060AC31-12 / 12.1" / 800*600 / 18bit (4:3)		3.3/5V		X
	Sharp LQ121S1DG11 / 12.1" / 800*600 / 18bit (4:3)		3.3V		X
	LG LM151X2-C2TH / 15.1" / 1024x768 / 18bit (4:3)		3.3V		X
	Fujitsu FLC38XGC6V-06 / 15" / 1024*768 / 36bit (4:3)		5V		X
PCI Slot Function (PCI Adapter Card) Test					
Model		Type		Result	
				Pass	Fail
CHAINTECH NVIDIA GeForce4 MX440-8X		VGA Card			X
Creative Sound BLASTER Live5.1		Sound Card			X
Takram DC-395U V1.02		SCSI Card			X
ADAPTEC Ultra160 SCSI ASC-29160		SCSI Card			X
I-VIEW CP-1400AS (with Age STD-477FAI CCD)		Capture Card			X

Intel GD82559 10/100 Mbps Fast Ethernet Adapter	LAN Card			X
3Com 3C905C-TXM ETHERLINK 10/100 PCI	LAN Card			X
D-Link DWL-520+ Wireless LAN	LAN Card			X
ADAPTEC 1420SA RoHS 4-Port SATA II RAID	RAID Card			X
LEMEL MD V1456VQH-P2 PCI MODEM Card	Modem Card			X
D-Link DU-520 USB 2.0	USB Hub Card			X
Tekram TR-822 Serial ATA 150 [SA-001] + SATA HDD Seagate ST3120026AS 120GB	SATA Card			X
ISA Slot Function Test	Result			
	Pass	Fail	N/A	
NE2000 Compatible LAN Card (RTL8019AS)				X
Adaptec AHA-1510/20/22B SCSI Card				X
PCI-Express Function Test				
	Model	Result		
		Pass	Fail	N/A
SUNIX SATA1414 VER 1.1 PCI-Express x1 SATA Card				X
SksKonnnect SK-9E21D 10/100/1000 Base-T Adapter PCI-Express x1 LAN Card				X
Adaptec AAR-1430SA SATAII HostRAID Controllers PCI-Express x4 RAID Card				X
ASUS EAX1600PRO/TD/256M/A (ATI Chipset) PCI-Express x16 VGA Card				X
WinFast PX6200 TC TDH PCI-Express x16 VGA Card				X
HDD Compatibility Test				
	Model	Result		
		Pass	Fail	N/A
Seagate / ST3160815A / 160GB /PATA-100				X
Fujitsu MHY2080BH 80GB 2.5" HDD / ATA-133 / SATA				X
Western Digital/WD8800AAJS / 80GB / SATA II				X
HITACHI HDP725025GLA380 / 250GB / SATA 3.0Gb/s				X
IDE Cable Function test				
	IDE Model	Result		
		Pass	Fail	N/A
40 Pin Cable ATA100				X
44 Pin Cable ATA33				X
80 Pin Cable ATA100				X
USB Function Test				
USB Basic Function Test	Result			
	Pass	Fail	N/A	
USB Controller	X			
USB 2.0 Controller	X			
USB Keyboard Support	X			
USB Mouse Support	X			
USB 1.1 Compatible Test	Result			
	Pass	Fail	N/A	

USB 1.1 Compatible Test		X			
USB 2.0 Compatible Test		Result			
		Pass	Fail	N/A	
USB 2.0 Compatible Test		X			
USB 2.0 Function Test		Result			
		Pass	Fail	N/A	
Install Windows XP Professional from HighSpeed Device: USB2.0 DRW-1604P-D/WHT/G/ASUS		X			
Floppy Disk Controller Function Test		Result			
		Pass	Fail	N/A	
Copy and compare file between C: and A / B:				X	
Change Floppy to None value				X	
Swap FDD				X	
Peripheral Compatibility-Storage Device					
Model	Interface	Result			
		Pass	Fail	N/A	
FUJITSU MCB3064SS	SCSI			X	
IOMega ZIP 100 parallel port	Parallel			X	
IOMega ZIP100MB Internal ATAPI Drive	IDE			X	
DOC				X	
Type-I CF	Fix / PIO Mode			X	
Type-I CF	Fix / UDMA Mode			X	
Digital I/O Connector Test		Result			
		Pass	Fail	N/A	
Input Address: BF				X	
Output Address: 33				X	
VCC: (5V) , Position : (801)				X	
DIO-1 Function Test				X	
DIO-2 Function Test				X	
Adapter Compatibility- Industry Control Card PC/104, PC/104+, PCI-104 Modules					
Interface	Model	Type	Result		
			Pass	Fail	N/A
PC/104	AAEON PCM-5600	Modem Module			X
	AAEON PCM-3115B	PCMCIA Module			X
PC/104+	AAEON PCM-3430	SCSI Module			X
PCI-104	AAEON PCM-FA00	Mini-PCI Converter			X
	AAEON PCM-3794	SCSI Module			X
	AAEON PCM-3730	Intel 82559 LAN Module			X
PCI/104 Express	AAEON PER-123				X
On-Board SCSI Function Test					
Model	Interface	Result			
		Pass	Fail	N/A	
RICOH MP7060S	SCSI-CDROM 24X			X	

Fujitsu MCB3064SS	SCSI-MO Device			X
Seagate 32155W	SCSI-HDD 2.15GB			X
IBM DNES-309170	SCSI-HDD 9GB			X
Seagate ST39205LW/P	9GB / Ultra160 / LVD			X
On-Board RAID Function Test				
Model	Interface	Result		
		Pass	Fail	N/A
Set SATA HDDs as RAID 0	SATA			X
Set SATA HDDs as RAID 1	SATA			X
Set SATA HDDs as RAID 10	SATA			X
Set SATA HDDs as RAID 5	SATA			X
COM Function Test		Result		
		Pass	Fail	N/A
COM Port Burn In Test		X		
Disk On Module [DOM] Compatibility Test				
Model	Interface	Result		
		Pass	Fail	N/A
Transcend / TS512MDOM40V / 512MB	IDE 40 Pin			X
Transcend / TS512MDOM44V / 512MB	IDE 44 Pin			X
Mini PCI Card Compatibility Test				
Model	Interface	Result		
		Pass	Fail	N/A
PCI 10/100 LAN Mini PCI Card (Model:PER-C10L)	LAN			X
GM-101 WLAN 11b/g 54Mbps Mini PCI Card (Model: VNT6655AM)	WLAN			X
COM/LPT Ports & RS-232/422/485 Function Test		Result		
		Pass	Fail	N/A
RS-422 for COM2		X		
RS-485 for COM2		X		
COM1		X		
COM2		X		
COM3				X
COM4				X
COM5				X
COM6				X
LPT1				X
LPT2				X
Card Bus(PCMCIA) Compatibility Function Test				
Model		Result		
		Pass	Fail	N/A
Intel PRO/Wireless 2011B LAN PC Card (WPC2011BWW)				X

PQI 16MB Compact Flash Adapter (64MB PQI CF Card inserting)			X
Kingston datapack DP-PCM2 / 2GB (PC Card TypeII HDD)			X
PCi GW-NS54SG Cardbus Adapter Wireless LAN Type-II			X

5. O.S. Compatibility Test

Installation Operation System Compatibility Test		Result			
		Pass	Fail	N/A	
Windows XP Professional English Version V2002 Service Pack 3		X			
Utility and Driver Test					
OS	Drivers Version		Result		
			Pass	Fail	N/A
Windows XP Professional English Version V2002 Service Pack 3	Chipset Software	Intel (R) Chipset Device Software 9.0.0.1008	X		
	Graphics Media	Mobile Intel (R) 945 Express Chipset Family 6.14.10.4926(2/15/2008)	X		
	LAN Driver	Intel(R) 82574L Gigabit Network Connection 10.3.49.0(8/5/2008)	X		
	Audio Driver	Realtek AC'97 Audio 5.10.0.6280(1/23/2008)	X		
	Touch Screen Driver	PenMount 6000 USB 2.1.0.0(5/13/2008)	X		

6. BIOS Function Test

Test Item	Result		
	Pass	Fail	N/A
Memory Beep Test			X
Standard CMOS Setup Test	X		
Boot Sequence Test	X		
Power Management Test			
APM Power Management Test			X
ACPI Power Management Test	X		
Power On Function Test			X
Wake Up Event Test	X		
Power On after Power Failure Test	X		
CMOS Backup / Clear CMOS Test	X		
Boot ROM Test (PXE)	X		
Supervisor / User Password Test	X		
LCD Function Test	X		
TV Standard Function Test			X
Init Display First Function Test			X
On-Chip Serial ATA Function Test(SATA Only)	X		
SATA Mode-IDE/RAID Function Test			X
PC Health Status			

Voltage Monitor Test	X		
FAN Speed Monitor Test			X
Temperature Monitor Test	X		
Swap Floppy Drive & Boot up Floppy Seek Function Test			X
USB Onboard Device Function Test	X		
COM Address / IRQ Test	X		
LPT Address / IRQ Test			X
BIOS AWDFLASH Program Test	X		

7. Performance Test

Platform Information

System	FOX-81
PCB Model / Version	Gene-9455 A1.0
BIOS	FOX-81 BIOS Rev 0.3.1(04/22/2009)
Operating System	Windows XP Professional V2002 Service Pack 3
CPU	Intel (R) Atom(TM) CPU N270 1.6GHz
Memory	DSL DDRII 667 512MB. ELPIDA(64MX8).E5108A(X)-6E-E.DSL.D2SE64081XG30AA
SATA HDD	N/A
Primary IDE Master	N/A
Primary IDE Slave	N/A
CRT	N/A
LCD	AUO.G084SN05 V7 8.4"
Compact Flash	Transcend CF Card 4GB for Industrial TS4GCF133
Backplane	N/A
Riser Card	N/A
Chipset Software	Intel (R) Chipset Device Software 9.0.0.1008
Graphics Media	Mobile Intel (R) 945 Express Chipset Family 6.14.10.4926(2/15/2008)
LAN Driver	Intel(R) 82574L Gigabit Network Connection 10.3.49.0(8/5/2008)
Audio Driver	Realtek AC'97 Audio 5.10.0.6280(1/23/2008)
Touchscreen Driver	PenMount 6000 USB 2.1.0.0(5/13/2008)
Power Supply	DC Input: SINPRO MPU100-108 Input:100-240V~47-63Hz 1.25-0.5A Output : 24V 4.16A

Test result:

Testing Software	Result	Unit
PCMark2002		

CPU	2643	
Memory	6035	
HDD	297	
Final Reality V1.01—BenchMark Test		
2D image	19.29	
3D	4.06	
Bus transfer	31.64	
Overall	12.76	Reality marks
3Dmark2001		
3DMark2001SE Build 330_Benchmark mode	2721	

Test Result:

Testing Software	Result	Unit
PCMark05		
PCMark	1064	PCMarks
CPU	1482	
Memory	2382	
Graphics	449	
HDD	806	
3Dmark2003 v360		
3Dmark Score	685	
CPU Score	241	

Remark: Please uses below two performance software to test main board if the chipset is new enough.
(ex. Intel Core 2 Duo CPU)