Power Consumption

Platform Information:

PCB Model & Version	PCM-6894 Rev.A0.2 BIOS Rev 0.6(07/19/2002)
CPU Type & FSB	Pentium III 1G / 133
Memory Type	INFINEDN HYB39S64800CT-75 / PC133 /128MB
DOC Type	M-System DOC2000 ☐4MB ☐8MB ☐16MB ☐32MB ☐___MB
Power Supply	Seasonic SSG-250G / 250W
VGA Card (Chipset)	OnBoard Silicon Motion Lynx3DM / Driver Ver.4.12.01.0034

Operating System Environment :

DOS 6.22	Config.sys Device=c:\dos\setup.exe Device=c:\dos\power.exe dos=high files=30 Autoexec.bat c:dos\smartdrv.exe/x @ echo off path c:\dos set temp=c:\dos

A. Power Consumption Test :

Test Software (DOS Mode):

Test Software	**QAPlus/Fe 5.5（Run QAPlusfe.exe/ Memory module test programming）**

Test Result:

Mode Type	**CPU TYPE**					Current
	PIII 1.4G 133 FSB	PIII 1G 133 FSB	PIII 850 100 FSB	Celeron 1G 100 FSB	VIA C3 800 133 FSB	
Normal Mode(+5V)	5.92	6.63	5.16	6.02	2.63	Amp/Max
Suspend Mode(+5V)	5.29	2.62	1.82	1.88	1.61	Amp/Max
Normal Mode(+12V)	0.19	0.18	0.20	0.18	0.21	Amp/Max
Suspend Mode(+12V)	0.17	0.15	0.18	0.15	0.19	Amp/Max
Normal Mode(+3.3V)	N/A	N/A	N/A	N/A	N/A	Amp/Max
Suspend Mode(+3.3V)	N/A	N/A	N/A	N/A	N/A	Amp/Max