

COM-SKHB6

PCB Rev. A0.2

Temperature/Humidity Test Report

Report NO:

Summary	<p><input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail</p> <p>Note : There is/are ____ defect(s) not list in the report, please check it in the DTS Website.</p> <p><input type="checkbox"/> Pass with Deviation</p> <p>Comment:</p>

Issue date

2015-12-30

Approval

Richard Wu

Test Engineer

James Yang

Test item list

1. *Test item list* ----- 2
2. *Configuration of EUT* ----- 3
3. *Temp./humidity power on/off test* ----- 4
4. *Temperature variation operation test* ----- 5
5. *Cold start and hot start test* ----- 6

Testing Result

Num	Test item list	Result	Remark
1	Temp./humidity power on/off test	Pass	
2	Temperature variation operation test	Pass	
3	Cold start and hot start test	Pass	

Configuration of EUT

Test Product: COM-SKHB6 A0.2

Sample Configuration & Quantity Under Test:

1. CPU: Intel® Core 6th Gen i7-6822EQ
2. VGA: Intel® HD Graphics 530
3. DDR4 Sodimm: DSL 2133Mhz 8GB (D4SS12082SH21A-A)
4. BIOS Rev. : CSKHAM0B
5. SATA HDD: Hitachi 2.5" 5400RPM 120GB (HTS541612J9SA00)
6. Power Supply: EMACS HG2-6400P 400W
7. Test Software: Win 8.1 X64/ PassMark BurnInTest Pro v8.0
8. Monitor: CMV CM-922D
9. Carrier BD: COME W2 A1.0
10. Heat-sink: COM-SKHB6 heat-spreader +Cooler.FAN for COM-QM77



Temp./humidity power on/off test


Test Date: 2015/12/25~2015/12/26

Test Site: AAEON Taichung Internal Lab

Test Standard: Reference IEC 68-2-30 Testing procedures
Test Db: Damp Heat Test

Test Equipment:
Programmable Temperature & Humidity Chamber
TERCHY. TECH. CORP.
Model: MHU-150LB
Date of Calibration: 2015/03/16
Serial Number: 961138

Temperature & Humidity Power On/Off Test:



Test Result:

No issues were found during the temperature & humidity power on/off test.

Test Method	Actual	Successful	Failure rate
Power On/Off	1739	1739	0%
Note: Failure rate need to under 0.0%.			

Temperature variation operation test

Test Date: 2015/12/29~2015/012/30


Test Site: AAEON Taichung Internal Lab

Test Standard: Reference IEC 68-2-14 Testing procedures
Test N: Change of temperature Test

Test Equipment:
Programmable Temperature & Humidity Chamber
TERCHY. TECH. CORP.
Model: MHU-150LB
Date of Calibration: 2015/03/16
Serial Number: 961138

Temperature & Humidity Cycle Test:

1. Test Low Temperature: 0°C (1~2 cycles)
-5°C (3rd cycle)
2. Test High Temperature: 60°C (1~2 cycles)
65°C (3rd cycle)
3. Test dwell time: 4Hrs (1~2 cycles)
2Hrs (3rd cycle)
4. Temperature slope: 2°C/min
5. Test cycle: 3 cycles
6. Test Environment Curve:



Test Result:

No issues were found during the temperature variation operation test.

Cold start and hot start test


Test Date: 2015/12/31

Test Site: AAEON Taichung Internal Lab

Test Standard: Reference IEC 68-2-14 Testing procedures
Test N: Change of temperature Test

Test Equipment:
Programmable Temperature & Humidity Chamber
TERCHY. TECH. CORP.
Model: MHU-150LB
Date of Calibration: 2015/03/16
Serial Number: 961138

Test Condition:



Parameters	Description
T1	-5°C
T2	65°C
t1	1 hrs
t2	2 hrs
t4, t5	30 mins
t, t3	2°C/min
n(Cycle)	1

t,t3 = temperature slope

t,t1 : Power Off

t2 : Power on/off test 10 times (on 2 min / off 5 min)

t3,t4 : Run PassMark Burn In Test

t5 : Win 8.1 Software restart 2 times

Test Software: Window 8.1 64bit

Test Result:

- a. No issues were found during the cold start test.
- b. No issues were found during the hot start test.