

EPC-CV1

Temperature/Humidity Test Report

Report NO: 12IP020005

Summary	<p><input checked="" type="checkbox"/> Pass</p> <p><input type="checkbox"/> Fail</p> <p>Note : There is/are ____ defect(s) not list in the report, please check it in the DTS Website.</p> <p><input type="checkbox"/> Pass with Deviation</p>
---------	---

Issue date

2012-12-11

Approval

Tom Lin

Test Engineer

Matthew Chi

Test item list

-
1. *Test item list* ----- 2
 2. *Configuration of EUT* ----- 3
 3. *Temp./humidity power on/off test* ----- 4
 4. *Temperature variation operation test* ----- 5
 5. *Cold start and hot start test* ----- 6

Testing Result


Num	Test item list	Result	Remark
1	Temp./humidity power on/off test	Pass	
2	Temperature variation operation test	Pass	
3	Cold start and hot start test	Pass	

Configuration of EUT

Test Product: EPC-CV1 A1.01

Sample Configuration & Quantity Under Test:

1. CPU: Intel Atom N2600 1.6GHz
2. BIOS: 0201 X64(11/15/2012)
3. Chipset: INTEL Cedarview
4. Memory: DSL 4G DDR3 1066 SEC K4B2G0846C
5. HDD: TOSHIBA 2"5 SATA MK1676GSX 160GB
6. Test Software: Windows 7 64Bit/ Run PassMark Burn In Test 7.0 Pro
7. AT Power Supply: ZIPPY HG2-6400P
8. Heat Sink:



Temp./humidity power on/off test

Test Date: 12-05 ~ 06-2012

Test Site: AAEON QE Dept.

Test Standard: Refer to IEC 68-2-30 Testing procedures
Test Db: Damp Heat Test


Test Equipment:
 Programmable Temperature & Humidity Chamber
 K.SON. INS. TECH. CORP.
 Model: THS-B6T-150+LN2
 Date of Calibration: 10/13/11
 Serial Number: 6487KT

Temperature & Humidity Power On/Off Test:

Testing Specification:

Sep	Temperature(°C)	Humidity(%RH)	Duration(H:MM)
1	25	50	00:30
2	25	50	00:30
3	25	90	01:00
4	25	90	00:30
5	55	90	08:30
6	55	90	08:00
7	-10	0	04:50
8	-10	0	05:23
9	25	50	01:47
10	25	50	08:00

Test Curve:



Test Result:

Test Method	Actual	Successful	Failure rate
Power On/Off	1204/times	1204/times	0.0 %
Note: Failure rate must be under 0.2%.			

Temperature variation operation test

Test Date: 12-06~10 -2012

Test Site: AAEON QE Dept.


Test Standard: Refer to IEC 68-2-14 Testing procedures
Test N: Change of temperature Test

Test Equipment:

Programmable Temperature & Humidity Chamber
K.SON. INS. TECH. CORP.
Model: THS-B6T-150+LN2
Date of Calibration: 10/13/11
Serial Number: 6487KT

Temperature & Humidity Cycle Test:

1. Test Low Temperature: -10°C (1~2 cycles)
-15°C (3rd cycle)
2. Test High Temperature: 50°C (1~2 cycles)
55°C (3rd cycle)
3. Test dwell time: 4Hrs (1~2 cycles)
4Hrs (3rd cycle)
4. Temperature slope: 2°C/min
5. Test cycle: 3 cycles
6. Test Environment Curve:



Test Result:

No issues were found during the temperature variation operation test.

Cold start and hot start test


Test Date: 12-10 ~11-2012

Test Site: AAEON QE Dept.

Test Standard: Refer to IEC 68-2-14 Testing procedures
Test N: Change of temperature Test

Test Equipment:
 Programmable Temperature & Humidity Chamber
 K.SON. INS. TECH. CORP.
 Model: THS-B6T-150+LN2
 Date of Calibration: 10/13/11
 Serial Number: 6487KT

Test Condition:



Parameters	Description
T1	-15°C
T2	55°C
t1	1 hrs
t2	2 hrs
t4, t5	30 min
t, t3	2°C/min
n (Cycle)	1

t,t3 = temprature slope
 t, t1: Power Off
 t2: Power on/off test 10 times (on 2 min / off 5min)
 t3,t4: Run PassMark Burn In Test
 t5: Windows 7 Software restart test 2 times
 Test Software:Windows 7

Test Result:

- a. No issues were found during the cold start test.
- b. No issues were found during the hot start test.