

# IMBA-Q170A

## Temperature/Humidity Test Report

Report NO: 17IP020010

Summary	<p><input checked="" type="checkbox"/> <b>Pass</b></p> <p><input type="checkbox"/> <b>Fail</b> Note : There is/are ___ defect(s) not list in the report, please check it in the DTS Website.</p> <p><input type="checkbox"/> <b>Pass with Deviation</b> Comment: _____</p>
---------	--

Issue date

QE Manager

Test Engineer

2017-08-16

KJ Wang

Ben Sun

# Test item list

- 
1. *Test item list* ----- 2
  2. *Configuration of EUT* ----- 3
  3. *Temp./humidity power on/off test* ----- 4
  4. *Temperature variation operation test* ----- 5
  5. *Cold start and hot start test* ----- 6

## Testing Result

Num	Test item list	Result	Remark
1	Temp./humidity power on/off test	Pass	
2	Temperature variation operation test	Pass	
3	Cold start and hot start test	Pass	

# Configuration of EUT

## Test Product: IMBA-Q170A A1.0

### Sample Configuration & Quantity Under Test:

1. CPU: Intel Core i7-6700 3.4GHz
2. BIOS Ver.: R0.3(AQH0AM03)
3. Chipset: Intel Q170A
4. Memory: Innodisk DDR4-2400 16GB \* 4
5. USB Flash: Transcend 4GB (For DOS Mode Power On/Off Test)
6. 2.5" SATA HDD: TOSHIBA MK1676GSX 160G
7. Test Software: Windows 10 / Run PassMark Burn In Test 8.1 Pro
8. ATX Power Supply: DSA400P-C
9. CPU Cooler:



# Temp./humidity power on/off test

**Test Date:** 08-11~ 12-2017

**Test Site:** AAEON QE Dept.

**Test Standard:** Refer to IEC 68-2-30 Testing procedures  
 Test Db: Damp Heat Test  
 Refer to IEC 68-2-1 Testing procedures  
 Test Ad: Cold Test

**Test Equipment:**

Programmable Temperature & Humidity Chamber: (K.SON. INS. TECH. CORP.)  
 Model: THS-D7TS-100+LN2  
 Date of Calibration: 09/10/16  
 Due date of Calibration: 09/09/17  
 Serial Number: A0004


**Temperature & Humidity Power On/Off Test:**

1. Test High Temp./Humidity: 60°C @90%RH
2. Test Low Temperature: 0°C
3. Test Time: 24Hours / Cycle
4. Test Cycle: 1 Cycles
5. Test Software: DOS Mode / Run Boot Up Record Program ver 1.41

**Testing Specification:**

Step	Temperature (°C)	Humidity (%RH)	Duration (HH:MM)
1	25	50	00:30
2	25	50	00:30
3	25	90	01:00
4	25	90	00:30
5	60	90	03:30
6	60	90	03:00
7	0	0	04:50
8	0	0	05:23
9	25	50	01:47
10	25	50	03:00

**Test Curve:**



**Test Result:**

	Actual	Successful	Failure rate	Test Result
Power On/Off	1113/times	1113/times	0 %	Pass

**Note:** 1. Failure rate need to under 0%.  
 2. Power on/off fixture setting: on - 40 sec / off - 40 sec

# Temperature variation operation test

**Test Date:** 08-14 ~ 15-2017


**Test Site:** AAEON QE Dept.

**Test Standard:** Refer to IEC 68-2-14 Testing procedures  
Test N: Change of temperature Test

**Test Equipment:**  
Programmable Temperature & Humidity Chamber: (K.SON. INS. TECH. CORP.)  
Model: THS-D7TS-100+LN2  
Date of Calibration: 09/10/16  
Due date of Calibration: 09/09/17  
Serial Number: A0004

## Temperature & Humidity Cycle Test:

1. Test Low Temperature: 0°C (1~3 cycles)
2. Test High Temperature: 60°C (1~3 cycles)
3. Test dwell time: 4Hrs (1~2 cycles)  
2Hrs (3<sup>rd</sup> cycle)
4. Temperature slope: 2°C/min
5. Test cycle: 3 cycles
6. Test Environment Curve:



## Test Result:

No issues were found during the temperature variation operation test.

# Cold start and hot start test


**Test Date:** 08-10 ~ 11-2017

**Test Site:** AAEON QE Dept.

**Test Standard:** Refer to IEC 68-2-14 Testing procedures  
Test N: Change of temperature Test

**Test Equipment:**  
Programmable Temperature & Humidity Chamber: (K.SON. INS. TECH. CORP.)  
Model: THS-D7TS-100+LN2  
Date of Calibration: 09/10/16  
Due date of Calibration: 09/09/17  
Serial Number: A0004

**Test Condition:**



Parameters	Description
T1	0°C
T2	60°C
t1	1 hrs
t2	2 hrs
t4, t5	30 min
t, t3	2°C/min
n (Cycle)	1

t,t3 = temperature slope  
t, t1: Power Off  
t2: Power on/off test 10 times (on 2 min / off 5min)  
t3,t4: Run PassMark Burn In Test  
t5: Windows 10 Software restart test 2 times  
Test Software:Windows 10

**Test Result:**

- a. No issues were found during the cold start test.
- b. No issues were found during the hot start test.