

# AAEON

**AAEON Technology INC.**  
ISO-9001/ISO-14001 Certified  
Industrial Automation PCs

## **SBC-556**

# **Environment Test Report**

**Release Date : Apr.08.1999**

---

**Issue Stamp**

---

**QA Manager**

---

**QE Manager**

---

**Test Engineer**

# Environment

**Model Name :** SBC-556

**Test Date :** 99-03-30

**Test Site :** AAEON QE Dept.

**Performed by :** Wenyuan Yang

**Test Standard :**

Select	NO.	Description
√	IEC 68-2-30	Test DB : Damp Heat Test
√	IEC 68-2-61	Test Z/ABD : Climatic Sequence Test

**Testing Item :**

Temperature & Humidity Cycle  
Test Temperature & Humidity Power On/Off Test

**Additional Test Peripheral :**

Configuration	Model
Test Software	AMIDIAG 5.11
Test Fixture	Power on/off(110V) Fixture

**Testing Equipment :**

Programmable Temperature & Humidity Chamber  
Model : Ths-D4L+-100  
S/N : 1241  
Date of Calibration : 07-10-1998

**Sample Configuration & Quantity Under Test :**


Use SBC-556 Half-size CPU Card with the following options installed .  
1.CPU : Intel Pentium MMX 233MHZ  
2.RAM : 16MB\*2  
3.Chipset : SIS 5582  
4.VGA Chipset : C&T 69000  
5.I/O Chipset : Winbond W83877TF

**Test Result :**

Standard	Description	Result
IEC 68-2-30	Temperature & Humidity Power On/Off Test	Pass
IEC 68-2-61	Temperature & Humidity Cycle Test(Run AMIDIAG 5.11)	Pass


# Environment

## Temperature & Humidity Power On/Off Test




# Environment

## Temperature & Humidity Power On/Off Test



# Environment

Temperature & Humidity Cycle Test(Run AMIDIAG 5.11)



# Environment

Temperature & Humidity Cycle Test (Run AMIDIAG 5.11)

