



A4EON **Technology INC.**  
ISO-9001/ISO-14001 Certified  
Industrial Automation PCs

**PCM-4898**

**QE Compatibility Test Report**

**Release Date :Aug. 14, 2000**

---

**Issue Stamp**

---

**QA Manager**

---

**QE Manager**

---

**Test Engineer**

## Summary of contents :

<b>Cover Sheet</b> .....	<b>1</b>
<b>Summary of contents</b> .....	<b>2</b>
<b>1. Margin</b> .....	<b>3</b>
Includes temperature, DC voltage and IDE cable length tests.	
<b>2. Stability</b> .....	<b>4</b>
Includes burn-in and booting tests .	
A. Burn-In Testing(25°C/24hrs).....	4
B. Burn-In Testing(Climatic Sequence/48hrs).....	4
C. Booting Testing(25°C).....	4
D. Booting Testing(Damp Heat,Cyclic/24hrs).....	4
<b>3. Performance</b> .....	<b>5</b>
Includes performance indexes using various performance test software programs .	
<b>4. Power consumption data</b> .....	<b>6</b>
Includes +5V current rate .	
<b>5. Hardware compatibility</b> .....	<b>7</b>
Includes CPU , DRAM , adapter card and HDD compatibility tests.	
<b>A. Component Compatibility- CPU</b> .....	<b>7</b>
B. Component Compatibility- DRAM SIMM Module.....	7
C. Adapter Compatibility- VGA.....	7
D. Adapter Compatibility- LAN.....	8
E. Adapter Compatibility- SCSI Card.....	8
F. Adapter Compatibility- Other Card.....	8
G. Peripheral Compatibility- HDD Device.....	8
H. Peripheral Compatibility- Storage Device.....	9
I. Peripheral Compatibility- Others.....	9
J. Peripheral Compatibility- Input Device.....	10
K. On_Board Network Hardware (physical) Compatibility.....	10
<b>6. Software compatibility</b> .....	<b>12</b>
Includes various OS and application software tests.	
A. O.S. Compatibility- Windows 95.....	12
B. O.S. Compatibility- Windows 98.....	13
B-1. Microsoft Windows 98 Hardware Compatibility Test(HCT).....	14
C. O.S. Compatibility- Windows NT R4.0.....	15
D. O.S. Compatibility- DOS and DOS Utility Compatibility Testing.....	17
E. Word Processing/Spread Sheet Compatibility Testing.....	18
F. Business Graphics/DTP/DB Compatibility Testing.....	20

**There are 3 test results in this document; they are described as follows:**

**Pass:** It worked perfectly

**Fail:** Test failed, and to be modified in the next version

**N/A:** Outside of specifications or no test equipment

**The test report would be tested and updated after version changed.**

**Quality Engineering Department of AAEON TECHNOLOGY INC.**

1F, No.6, Alley 6, Lane 45, Pao-Hsin Rd,

Hsin-Tien City, Taipei, Taiwan , ROC

Tel: 886-2-29121234

Fax:886-2-29130792

886-2-29130774

# 1. Margin Testing

## System Information:

DRAM/SDRAM Capacity & BRAND(SIMM Qty)	Brand: NEC D4516821AG-A10-9NF <input type="checkbox"/> 16 <input checked="" type="checkbox"/> 32 <input type="checkbox"/> 64 <input type="checkbox"/> 128MB <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> SDRAM <input type="checkbox"/> SODIMM <input type="checkbox"/> _____ Qty: <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4
System BIOS Version	<input checked="" type="checkbox"/> Award <input type="checkbox"/> AMI Ver: 4.51PG
O.S. Environment	<input checked="" type="checkbox"/> MSDOS6.22 <input type="checkbox"/> _____
VGA Card	<input checked="" type="checkbox"/> OnBoard NS Geode CS5530A
DOC Type	M-System DOC2000 <input type="checkbox"/> 4MB <input type="checkbox"/> 8MB <input checked="" type="checkbox"/> 16MB <input type="checkbox"/> 24MB <input type="checkbox"/> __ MB

## Test Result:

High Temperature: 2 Hours							
Testing CPU: Cyrix GXm-266P	<input type="checkbox"/> COM1 LB	<input type="checkbox"/> COM2 LB	<input type="checkbox"/> LPT LB				
Test Program:	<input checked="" type="checkbox"/> QAPlus/FE V5.29	<input type="checkbox"/> AMIDIAG V4.50					
<input type="checkbox"/> 55°C	<input type="checkbox"/> 60°C	<input type="checkbox"/> 65°C	<input checked="" type="checkbox"/> 70°C	<input type="checkbox"/> 75°C	<input type="checkbox"/> 80°C	<input type="checkbox"/> 85°C	

Low Temperature: 2 Hours							
Testing CPU: Cyrix GXm-266P	<input type="checkbox"/> COM1 LB	<input type="checkbox"/> COM2 LB	<input type="checkbox"/> LPT LB				
Test Program:	<input checked="" type="checkbox"/> QAPlus/FEV5.29	<input type="checkbox"/> AMIDIAG V4.50	<input type="checkbox"/> 5°C	<input type="checkbox"/> 0°C			
<input type="checkbox"/> -5°C	<input checked="" type="checkbox"/> -10°C	<input type="checkbox"/> -15°C	<input type="checkbox"/> -20°C	<input type="checkbox"/> -25°C	<input type="checkbox"/> -30°C	<input type="checkbox"/> -35°C	<input type="checkbox"/> -40°C

High Voltage: 2 Hours/25°C							
Testing CPU: Cyrix GXm-266P	<input type="checkbox"/> COM1 LB	<input type="checkbox"/> COM2 LB	<input type="checkbox"/> LPT LB				
Test Program:	<input checked="" type="checkbox"/> QAPlus/FE V5.29	<input type="checkbox"/> AMIDIAG V4.50					
<input type="checkbox"/> A Grade: 5.20V	<input checked="" type="checkbox"/> B grade: 5.25V	<input type="checkbox"/> C Grade: 5.30V	<input type="checkbox"/> D Grade: 5.35V	<input type="checkbox"/> E Grade: 5.4V			

Low Voltage: 2 Hours/25°C							
Testing CPU: Cyrix GXm-266P	<input type="checkbox"/> COM1 LB	<input type="checkbox"/> COM2 LB	<input type="checkbox"/> LPT LB				
Test Program:	<input checked="" type="checkbox"/> QAPlus/FE V5.29	<input type="checkbox"/> AMIDIAG V4.50					
<input type="checkbox"/> A Grade: 4.80V	<input checked="" type="checkbox"/> B grade: 4.75V	<input type="checkbox"/> C Grade: 4.70V	<input type="checkbox"/> D Grade: 4.65V	<input type="checkbox"/> E Grade: 4.6V			

## 2 . Stability Testing

### System Information:

DRAM/SDRAM Capacity & BRAND(SIMM Qty)	Brand: NEC D4516821AG-A10-9NF <input type="checkbox"/> 16 <input checked="" type="checkbox"/> 32 <input type="checkbox"/> 64 <input type="checkbox"/> 128MB <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> SDRAM <input type="checkbox"/> SODIMM <input type="checkbox"/> Qty: <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4
System BIOS Version	<input checked="" type="checkbox"/> Award <input type="checkbox"/> AMI Ver:4.51PG
O.S. Environment	<input checked="" type="checkbox"/> MSDOS6.22 <input type="checkbox"/>
VGA Card	<input checked="" type="checkbox"/> OnBoard NS Geode CS5530A
DOC Type	M-System DOC2000 <input type="checkbox"/> 4MB <input type="checkbox"/> 8MB <input checked="" type="checkbox"/> 16MB <input type="checkbox"/> 24MB <input type="checkbox"/> MB

### A. Burn-In Testing (24Hours)

Test Condition : Under Room Temp. 25°C

Test Software	Pass	Fail	Note
QAPlus/FE V5.29	✓		

### B. Burn-In Testing (48 Hours)

Test Condition : Burn-In Under Temp. 0°C ~ 60°C (IEC-68-2-61)

Test Software	Pass	Fail	Note
QAPlus/FE V5.29	✓		

### C. Booting Testing

Test Condition : Under Room Temp. 25°C

Test Method	Actual	Successful	Failure rate	On time	Off Time	Note
Power On/Off 1000Times	1000	1000	0 %	20 Sec	5 Sec	
KB Reset 20 Times	20	20	0 %	20 Sec	5 Sec	

### D. Burn-In Booting Testing (24 Hours)

Test Condition : Burn-In Under Temp. -0°C ~ 60°C (IEC-68-2-30)

Test Method	Actual	Successful	Failure rate	On time	Off Time	Note
Power On/Off	1365	1363	0.15%	50 Sec	50 Sec	

### 3 . Performance Testing

#### System Information:

DRAM/SDRAM Capacity & BRAND(SIMM Qty)	Brand: HYNDAI HY57V658020 TC-10 <input type="checkbox"/> 8 <input type="checkbox"/> 16 <input type="checkbox"/> 32 <input checked="" type="checkbox"/> 64 <input checked="" type="checkbox"/> 128MB <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> SDRAM <input type="checkbox"/> SODIMM <input type="checkbox"/> _____ Qty: <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4
System BIOS Version	<input checked="" type="checkbox"/> Award <input type="checkbox"/> AMI Ver: 4.51PG
O.S. Environment	<input checked="" type="checkbox"/> MSDOS6.22 <input checked="" type="checkbox"/> Windows 98 <input type="checkbox"/> Windows NT <input type="checkbox"/>
VGA Card	<input checked="" type="checkbox"/> OnBoard NS Geode CS5530A
VGA Memory	<input type="checkbox"/> 256K <input type="checkbox"/> 512K <input type="checkbox"/> 1M <input checked="" type="checkbox"/> 3M <input type="checkbox"/> 4M <input type="checkbox"/>
HDD Type	<input type="checkbox"/> Max <input type="checkbox"/> Sea <input type="checkbox"/> Con <input checked="" type="checkbox"/> IBM <input type="checkbox"/> Fuj : DPTA-372050
VGA Testing Mode	1024X768X256c (For WinStone & WinBench)
Driver or Utility	<input checked="" type="checkbox"/> VGA <input type="checkbox"/> HDD <input checked="" type="checkbox"/> Others : Intel 82559ER LAN

#### Operating System Environment (DOS Mode)

Config.sys	Autoexec.bat
Device=c:\dos\himem.sys dos=high,umb files=35 Buffers=40	Prompt \$p\$g c:\dos\smartdrv.exe /x

#### Testing Software

Testing Utility	CPU Type				Unit
	Cyrix GXM GXm-233GP	Cyrix GXM GXm-266GP	NS Geode GX1-300P 1.69k	NS Geode GXLV-233 1k	
<b>LandMark Speed 2.0</b>					
CPU	734.29	890.46	1030.41	743.21	MHz
FPU	1991.70	2381.12	2763.05	1980.64	MHz
VIDEO	13284	16115	18904	13284	Chs/sec
<b>Norton 8.0</b>					
SI	448.7	541.1	629.1	453.1	ID
<b>Power Meter 2.02</b>					
MIPS Test	67.7	83.6	94.8	71.1	Mips
<b>WinStone 99 v1.2</b>					
Business Graphic Winstone99	7.11	7.99	8.85	7.11	
<b>WinBench 99</b>					
H.E. Graphic WinMark 99	76.2	88.6	99.9	76.8	MP/s
Business Graphic WinMark99	26.4	30.4	34.5	26.6	TB/s
CPUMark 99	7.24	8.41	9.37	7.26	
<b>Coretest V3.02</b>					
DTR (Buffered Read)	5920	6256	6480	5936	KB/Sec
Performance ID	43.69	45.69	46.9	43.79	
<b>Wintech V1.2</b>					
Overall WinTach RPM	116.55	134.70	151.71	115.64	

**System Information:**

DRAM/SDRAM Capacity & BRAND(SIMM Qty)	Brand: HYNDAI HY57V658020 TC-10 <input type="checkbox"/> 8 <input type="checkbox"/> 16 <input type="checkbox"/> 32 <input type="checkbox"/> 64 <input checked="" type="checkbox"/> 128MB <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> SDRAM <input type="checkbox"/> SODIMM <input type="checkbox"/> Qty: <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4
System BIOS Version	<input checked="" type="checkbox"/> Award <input type="checkbox"/> AMI Ver: 4.51PG
O.S. Environment	<input checked="" type="checkbox"/> MSDOS6.22 <input checked="" type="checkbox"/> Windows 98 <input type="checkbox"/> Windows NT <input type="checkbox"/>
VGA Card	<input checked="" type="checkbox"/> OnBoard NS Geode CS5530A
VGA Memory	<input type="checkbox"/> 256K <input type="checkbox"/> 512K <input type="checkbox"/> 1M <input checked="" type="checkbox"/> 3M <input type="checkbox"/> 4M <input type="checkbox"/>
HDD Type	<input type="checkbox"/> Max <input type="checkbox"/> Sea <input type="checkbox"/> Con <input checked="" type="checkbox"/> IBM <input type="checkbox"/> Fuj : DPTA-372050
VGA Testing Mode	1024X768X256c (For WinStone & WinBench)
Driver or Utility	<input checked="" type="checkbox"/> VGA <input type="checkbox"/> HDD <input checked="" type="checkbox"/> Others : Intel 82559ER LAN

**Operating System Environment (DOS Mode)**

Config.sys	Autoexec.bat
Device=c:\dos\himem.sys dos=high,umb files=35 Buffers=40	Prompt \$p\$g c:\dos\smartdrv.exe /x

**Testing Software**

Testing Utility	CPU Type			Unit
	NS Geode G1-266P 2.2k	NS Geode G1-200P 1k+2.7k		
<b>LandMark Speed 2.0</b>				
CPU	888.09	616.26		MHz
FPU	2385.29	1655.47		MHz
VIDEO	16115	10922		Chs/sec
<b>Norton 8.0</b>				
SI	540.8	376.4		ID
<b>Power Meter 2.02</b>				
MIPS Test	83.6	58.0		Mips
<b>WinStone 99 v1.2</b>				
Business Graphic Winstone99	8.01	6.43		
<b>WinBench 99</b>				
H.E. Graphic WinMark 99	88.4	70.5		MP/s
Business Graphic WinMark99	30.3	24		TB/s
CPUMark 99	8.39	6.43		
<b>Coretest V3.02</b>				
DTR (Buffered Read)	6256	5696		KB/Sec
Performance ID	45.69	42.36		
<b>Wintech V1.2</b>				
Overall WinTach RPM	135.24	107.04		

## 4 . Power Consumption

### System Information:

DRAM Type & Capacity	NEC D4564841G5-A80-9JF 128MB
VGA Card	Onboard NS Geode CS5530A
DOC or Floppy	M-Systems DOC 16MB
O.S.	DOS6.22

### Operating System Environment (DOS Mode)

Config.sys	Autoexec.bat
Device=c:\dos\himem.sys dos=high,umb files=35 Buffers=40	Prompt \$p\$g c:\dos\smartdrv.exe /x

### Test Software (DOS Mode):

Test Software	Landmark Speed V.2.0(Speed200.exe)
---------------	------------------------------------

### Test Result:

#### ATX Power

Mode Type	CPU Type				Unit
	Cyrix GXM GXm-233GP	Cyrix GXM GXm-266GP	NS Geode GX1-300P R393 : 1.69k	NS Geode GXLV-233 R393 : 1k	
Normal Mode(+5V)	2.12	1.94	1.78	2.06	amp/max
Doze Mode(+5V)	2.12	1.94	1.78	2.06	amp/max
Standby Mode(+5V)	1.01	1.01	1.03	1.01	amp/max

Mode Type	CPU Type				Unit
	NS Geode G1-266 R393 : 2.2k	NS Geode G1-200 R393 : 1k+2.7k			
Normal Mode(+5V)	1.61	1.40			amp/max
Doze Mode(+5V)	1.61	1.40			amp/max
Standby Mode(+5V)	1.02	0.97			amp/max

Normal Model is measured while open system

Doze Model VGA controller is still enabled

STANDBY Model VGA controller is still enabled

## 5 . Hardware Compatibility

### A. Component Compatibility- CPU

#### CPU Device List:

Brand	Device Model	Pass	Fail	Note
Cyrix	GXm-233GP	✓		2.9V
Cyrix	GXm-266GP	✓		2.9V
NS Geode	GXLV-233P	✓		2.2V
NS Geode	G1-300P	✓		2V
NS Geode	G1-266P	✓		1.8V
NS Geode	G1-200P	✓		1.6V

### B. Component Compatibility- DRAM DIMM Module

#### DRAM DIMM Model List:

Brand	Device Model	Pass	Fail	Note
HYNDAI	HY57V658020 TC-10 128MB	✓		
NEC	D4564841G5-A80-9JF 128MB	✓		
NEC	D4564841G5-A10-9JF 128MB	✓		
LGS	GM72V661641CT7J 64MB	✓		
HITACHI	5264805DTTA60 PC100-222-60 64MB	✓		
HYNDAI	HY57V1291620 TC-10S 64MB	✓		
HYNDAI	HY57V129160 LTC-10S 64MB	✓		
NEC	D4564841G5-A10-9JF 64MB	✓		
NEC	D4564841G5-A60-9JF 64MB	✓		
NEC	D4564841G5-A80-9JF 64MB	✓		
HYNDAI	HY57V168010D TC-10S 32MB	✓		
NEC	D4516821AG-A10-9NF 32MB	✓		
MICRO	MT48LC2M8A1 TG -10S 32MB	✓		
SIEMENS	HYB39S16800A7 -10 32MB	✓		
MITSUBISHI	M2V64S40BTP 32MB	✓		
MITSUBISHI	M5M4V16S30DTP 32MB	✓		
HITACHI	HM5216805TT10H 16MB	✓		
NEC	D4516821AG5-A10-9NF 16MB	✓		

### C. Adapter Compatibility- VGA Card

#### VGA Adapter List:

Brand	Device Model	Pass	Fail	Note
Onboard VGA	NS Geode CS5530A	✓		

### D. Adapter Compatibility- LAN Card

#### Action:

1. Load ODI Driver (Lsl,lpxodi,Vlm Or Netx)	2. Login To Server System
3. Transfer Data Between SRV And WK(Mulity Task)	4. logout

#### LAN Adapter List:

Brand	Device Model	Pass	Fail	Note
Intel	82557	✓		
Intel	82559	✓		

Intel	EtherExpress™ PRO/100 (ISA)	✓		
D-Link	DFE-530TX	✓		
REL	RTL8139A	✓		
3 COM	3C905B-TX	✓		
3 COM	3C509B(ISA)	✓		

## E. Adapter Compatibility- SCSI Card

### SCSI Adapter List:

Brand	Device Model	Pass	Fail	Note
Adaptec	AHA-2940U/UW	✓		
Adaptec	AHA-1520	✓		
Adaptec	AHA-2940U	✓		
Adaptec	AHA-2940U2W	✓		

## F. Adapter Compatibility- Other Card

### Adapter Card List:

Brand	Device Model	Pass	Fail	Note
<b>MPEG Card</b>				
YUAN	MPG-200C DVD MPEG-2	✓		
<b>Modem Card (PCI)</b>				
SmartLink	5634PEW 56000bps Win modem	✓		

## G. Peripheral Compatibility-HDD Device

### HDD List:

Brand	Device Model	Pass	Fail	Note
Quantum	3240AT 3.2GB	✓		
Quantum	1700AT 1.7GB	✓		
Seagate	ST34520A 4GB	✓		
Seagate	ST51270A 1.2GB	✓		
Quantum	Bigfoot 4.0AT 4GB	✓		
Western Digital	WD Caviar 28400 8.4GB	✓		
Western Digital	WD Caviar 26400 6.4GB	✓		
FUJITSU	MPC 3032AT 3.2GB	✓		
IBM	DTLA-307045 40GB	✓		
IBM	DPTA-372050 20GB	✓		
Seagate	ST31230N 1.0GB SCSI	✓		
Seagate	ST34520LW 4.3GB SCSI			
Seagate	ST34520W 4.3GB SCSI			

## H. Peripheral Compatibility- Storage Device

### Device List:

Brand	Device Model	Pass	Fail	Note
<b>CD/ROM</b>				
TEAC	CD-540E 40X	✓		
CREATIVE	CD2423E 24X	✓		
PIONEER	DR-A24X 24X	✓		

<b>SONY</b>	CDU-4811-81 48X	✓		
<b>PIONEER</b>	DVD-A03S	✓		
<b>ZIP</b>				
<b>lomega</b>	Z100P2	✓		
<b>LS-120</b>				
<b>Panasonic</b>	LKM-F934-1	✓		
<b>Fax/Modem</b>				
<b>Cyber Lander</b>	Rock Modem E210 V.90 56K	✓		
<b>LEMEL</b>	MD336RSVD 56K	✓		

## I. Peripheral Compatibility- Others Device List:

Brand	Device Model	Pass	Fail	Note
<b>RS-485 Port</b>				
<b>Adventech</b>	Adam 401	✓		
<b>USB Port</b>				
<b>WINTEK</b>	AM-767-U USB Mouse	✓		
<b>DEXIN</b>	A2U800A USB Mouse	✓		
<b>Solidtek</b>	ACK-298 USB Keyboard	✓		
<b>BTC</b>	7932 USB Keyboard	✓		
<b>Vcam</b>	CU-98 USB Camara	✓		
<b>Tekom</b>	TekCam P35U USB Camara	✓		
<b>HP</b>	ScanJet 4200C USB Scanner	✓		
<b>EPSON</b>	STYLUS COLOR740 USB Printer	✓		
<b>HP</b>	PhotoSmart P1000	✓		
<b>lomega</b>	Z100USB			
<b>Parallel Port</b>				
<b>EPSON</b>	STYLUS COLOR740	✓		
<b>HP</b>	PhotoSmart P1000			
<b>IR Port</b>				
<b>ACTiSYS</b>	ACT-IR210L	✓		

## J. Peripheral Compatibility- Input Device Input Device List:

Brand	Device Model	Pass	Fail	Note
<b>Keyboard</b>				
<b>Acer</b>	6511-TW1C/B	✓		
<b>Mouse</b>				
<b>DEXIN</b>	K3P800A	✓		
<b>LOGITECH</b>	M-M35	✓		

**K. On Board Network Hardware (physical) Compatibility****System Information(Client Site):**

Board System	<input checked="" type="checkbox"/> MB-668
DRAM/SDRAM Capacity & BRAND(SIMM Qty)	Brand: NEC D4564841G5-A80-9JF <input type="checkbox"/> 8 <input type="checkbox"/> 16 <input type="checkbox"/> 32 <input type="checkbox"/> 64 <input checked="" type="checkbox"/> 128MB <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> SDRAM <input type="checkbox"/> SODIMM <input type="checkbox"/> Qty: <input type="checkbox"/> 1 <input checked="" type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4
SYSTEM BIOS Ver.	<input checked="" type="checkbox"/> AWARD <input type="checkbox"/> AMI Ver: _____
O.S. Environment	<input checked="" type="checkbox"/> DOS6.22 <input checked="" type="checkbox"/> WINNT _____ <input type="checkbox"/> NOVELL _____ <input type="checkbox"/> _____
VGA Card	<input checked="" type="checkbox"/> OnBoard C&T 69000
POWER SUPPLY	<input type="checkbox"/> MPU-250W <input type="checkbox"/> SSH-250G <input type="checkbox"/> SSH-350G <input checked="" type="checkbox"/> ST-250AF
IDE HDD TYPE	<input type="checkbox"/> Max <input type="checkbox"/> Sea <input type="checkbox"/> Con <input type="checkbox"/> Qua <input type="checkbox"/> Fuj <input checked="" type="checkbox"/> IBM : DHEA-34330
LAN CARD	<input checked="" type="checkbox"/> OnBoard: RTL 8139B
CD-ROM TYPE	<input type="checkbox"/> NEC <input type="checkbox"/> PANASONIC <input checked="" type="checkbox"/> PIONEER <input type="checkbox"/> CREATIVE : DVD-A035
Cable/Cable Length	CAT5 100M

**System Information(Server Site):**

Board System	<input checked="" type="checkbox"/> MB-668
DRAM/SDRAM Capacity & BRAND(SIMM Qty)	Brand: LGS GM72V661641CT7J <input type="checkbox"/> 8 <input type="checkbox"/> 16 <input type="checkbox"/> 32 <input checked="" type="checkbox"/> 64MB <input type="checkbox"/> 128MB <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> SDRAM <input type="checkbox"/> SODIMM <input type="checkbox"/> Qty: <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4
SYSTEM BIOS Ver.	<input checked="" type="checkbox"/> AWARD <input type="checkbox"/> AMI Ver: 4.51PG
VGA Card	<input checked="" type="checkbox"/> OnBoard Cyrix CX5530
O.S. Environment	<input checked="" type="checkbox"/> DOS6.22 <input checked="" type="checkbox"/> WINNT _____ <input checked="" type="checkbox"/> NOVELL 4.11 <input type="checkbox"/> _____
IDE HDD TYPE	<input type="checkbox"/> Max <input type="checkbox"/> Sea <input type="checkbox"/> Con <input checked="" type="checkbox"/> Qua <input type="checkbox"/> Fuj <input type="checkbox"/> IBM : Bigfoot 4.0AT
LAN CARD	<input checked="" type="checkbox"/> OnBoard: RTL-8139B
CPU Type	<input checked="" type="checkbox"/> Intel <input type="checkbox"/> Cyrix <input type="checkbox"/> AMD : Celeron 366 MHz
CD-ROM TYPE	<input type="checkbox"/> NEC <input type="checkbox"/> PANASONIC <input type="checkbox"/> PIONEER <input checked="" type="checkbox"/> CREATIVE : CD2423E
Cable/Cable Length	CAT5 100M

**HUB Type: D-Link DES1008 10/100 Fast Ethernet Switch****Test Result:**

SUBJECT	Network Hardware Function Testing			
Test Item	Pass	Fail	Note	
Transceiver	✓			
Receiver	✓			
CRC error	✓			
Collision back-off generation	✓			
Auto-negotiation	✓			
100M Base-TX full duplex	✓			
100M Base-TX half duplex	✓			
10M Base-T full duplex	✓			
10M Base-T half duplex	✓			
SUBJECT	Network Operation System Function Testing			
Test Item	Pass	Fail	Note	
NetWare 4.11	✓			
Windows NT 4.0	✓			
Linux Unix	✓			
SUBJECT	Network Performance Testing			
Test Item	Result		Note	
NWTEST 24HR	Pass			

SUBJECT	Workstation Application Function Testing			
Test Item	Pass	Fail	Note	
Dos 6.22 for IPXODI	✓			

Dos 6.22 for package driver	✓		
Windows 3.1 for IPXODI	✓		
Windows 3.1 for package driver	✓		
WFW 3.11 for NDIS 2.0/3.0	✓		
WFW 3.11 for NDIS 3.0/ODI	✓		
Windows 95 for IPX/SPX	✓		
Windows 95 for NetBEUI	✓		
Windows 95 for TCP/IP	✓		
Windows 98 for IPX/SPX	✓		
Windows 98 for NetBEUI	✓		
Windows 98 for TCP/IP	✓		
Windows NT 4.0 for IPX/SPX	✓		
Windows NT 4.0 for NetBEUI	✓		
Windows NT 4.0 for TCP/IP	✓		
Transfer Data Between SRV And WK	✓		Mulity Task 12 Hours(NOTE 1.)

Note : 1.Mulity Task is that transfers files(copy/verify/delet) and VCD in the same time.

## 6 . Software Compatibility

### A. O.S. Compatibility-Windows 95

#### System Information:

DRAM/SDRAM Capacity & BRAND(SIMM Qty)	Brand:NEC D4564841G5-A80-9JF <input type="checkbox"/> 8 <input type="checkbox"/> 16 <input type="checkbox"/> 32 <input checked="" type="checkbox"/> 64 <input type="checkbox"/> 128MB <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> SDRAM <input type="checkbox"/> SODIMM <input type="checkbox"/> Qty: <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4
System BIOS Version	<input checked="" type="checkbox"/> Award <input type="checkbox"/> AMI Ver: 4.51PG
VGA Card & BIOS	<input checked="" type="checkbox"/> OnBoard Cyrix CX5530
VGA Memory Capacity & Brand	Brand: NS Geode CS5530A Built-in <input type="checkbox"/> 60ns <input type="checkbox"/> 70ns <input type="checkbox"/> ns <input type="checkbox"/> DRAM <input type="checkbox"/> VRAM <input type="checkbox"/> 256K <input type="checkbox"/> 512K <input type="checkbox"/> 1M <input checked="" type="checkbox"/> 3M <input type="checkbox"/> 4M
CPU Type	<input type="checkbox"/> Intel <input checked="" type="checkbox"/> Cyrix <input type="checkbox"/> AMD: GXm-266P
HDD Type	<input type="checkbox"/> Max <input checked="" type="checkbox"/> WD <input type="checkbox"/> Con <input type="checkbox"/> Qua <input type="checkbox"/> Fuj : Caviar26400 6.4GB
CD-ROM Type	<input type="checkbox"/> NEC <input type="checkbox"/> Panasonic <input type="checkbox"/> Pioneer <input checked="" type="checkbox"/> Creative : CD2423E
Driver or Utility	<input checked="" type="checkbox"/> VGA <input type="checkbox"/> HDD <input checked="" type="checkbox"/> Others : Intel 82559ER LAN

#### VGA Driver Testing:

Resolution	Color	SF	LF	Pass	Fail	Note
640X480	256	—	—	✓		
	32K	—	—	✓		
800X600	256	✓	✓	✓		
	32K	✓	✓	✓		
1024X768	256	✓	✓	✓		
	32K	✓	✓	✓		
1280X1024	256	✓	✓	✓		

#### Test Results:

Test Item	Pass	Fail	Note
<b>Installation From CD-ROM</b>			
Install to IDE HDD	✓		Testing CPU: GXm-266P
<b>Boot</b>			
Boot Normal	✓		
Boot Logged (\BOOTLOG.TXT)	✓		
Boot Safe Mode	✓		
Boot Safe Mode & Network	✓		
Boot Step By Step Confirmation	✓		
Boot Command Prompt Only	✓		
Boot Safe Mode Command Prompt	✓		
<b>Function Test</b>			
Serial Mouse	✓		
FDD Format/Copy/Read/Write	✓		
PS/2 Mouse	✓		
System Clock	✓		
<b>Keyboard Function Test</b>			
Alt+F4 Quit a Program	✓		
Ctrl+Esc Display the Start Menu	✓		
Alt+Tab Switch To Last Windows	✓		
Ctrl+Alt+Del Close Program	✓		
F8 Start up Boot Up Menu	✓		
F4 Boot Up from Previous	✓		
<b>Shutdown</b>			
Shutdown the Computer	✓		
Shutdown Restart	✓		
Shutdown to MS-DOS Mode	✓		
Close all Prog. & Login Other User	✓		

**B. O.S. Compatibility-Windows 98****System Information:**

DRAM/SDRAM Capacity & BRAND(SIMM Qty)	Brand:NEC D4564841G5-A80-9JF <input type="checkbox"/> 8 <input type="checkbox"/> 16 <input type="checkbox"/> 32 <input type="checkbox"/> 64 <input checked="" type="checkbox"/> 128MB <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> SDRAM <input type="checkbox"/> SODIMM <input type="checkbox"/> Qty: <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4
System BIOS Version	<input checked="" type="checkbox"/> Award <input type="checkbox"/> AMI Ver: 4.51PG
VGA Memory Capacity & Brand	Brand: Cyrix 5530 Built-in <input type="checkbox"/> 60ns <input type="checkbox"/> 70ns <input type="checkbox"/> ns <input type="checkbox"/> DRAM <input type="checkbox"/> VRAM <input type="checkbox"/> 256K <input type="checkbox"/> 512K <input type="checkbox"/> 1M <input checked="" type="checkbox"/> 3M <input type="checkbox"/> 4M
CPU Type	<input type="checkbox"/> Intel <input checked="" type="checkbox"/> Cyrix <input type="checkbox"/> AMD: GXm-266P
HDD Type	<input type="checkbox"/> Max <input checked="" type="checkbox"/> WD <input type="checkbox"/> Con <input type="checkbox"/> Qua <input type="checkbox"/> Fuj : Caviar26400 6.4GB
CD-ROM Type	<input type="checkbox"/> NEC <input type="checkbox"/> Panasonic <input type="checkbox"/> Pioneer <input checked="" type="checkbox"/> Creative : CD2423E
Driver or Utility	<input checked="" type="checkbox"/> VGA <input type="checkbox"/> HDD <input checked="" type="checkbox"/> Others : Intel 82559ER LAN

**VGA Driver Testing:**

Resolution	Color	SF	LF	Pass	Fail	Note
640X480	16	—	—	✓		
	256	—	—	✓		
	32K	—	—	✓		
800X600	256	✓	✓	✓		
	32K	✓	✓	✓		
1024X768	256	✓	✓	✓		
	32K	✓	✓	✓		
1280X1024	256	✓	✓	✓		

**Test Results:**

Test Item	Pass	Fail	Note
<b>Installation From CD-ROM</b>			
Install to IDE HDD	✓		Testing CPU: Cyrix GXm-266P
<b>Boot</b>			
Boot Normal	✓		
Boot Logged (\BOOTLOG.TXT)	✓		
Boot Safe Mode	✓		
Boot Safe Mode & Network	✓		
Boot Step By Step Confirmation	✓		
Boot Command Prompt Only	✓		
Boot Safe Mode Command Prompt	✓		
<b>Function Test</b>			
Serial Mouse	✓		
FDD Format/Copy/Read/Write	✓		
PS/2 Mouse	✓		
System Clock	✓		
<b>Keyboard Function Test</b>			
Alt+F4 Quit a Program	✓		
Ctrl+Esc Display the Start Menu	✓		
Alt+Tab Switch To Last Windows	✓		
Ctrl+Alt+Del Close Program	✓		
F8 Start up Boot Up Menu	✓		
F4 Boot Up from Previous	✓		
<b>Shutdown</b>			
Shutdown the Computer	✓		

Shutdown Restart	✓		
Shutdown to MS-DOS Mode	✓		
Close all Prog. & Login Other User	✓		

## B-1. Microsoft Windows 98 Hardware Compatibility Test(HCT)

### System Information:

DRAM/SDRAM Capacity & BRAND(SIMM Qty)	Brand: NEC D451228841G5-A10-9JF <input type="checkbox"/> 32 <input type="checkbox"/> 64 <input checked="" type="checkbox"/> 128 <input type="checkbox"/> 256MB <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> SDRAM <input type="checkbox"/> SODIMM <input type="checkbox"/> Qty: <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4
System BIOS Version	<input checked="" type="checkbox"/> Award <input type="checkbox"/> AMI Ver: 4.51PG
VGA Card & BIOS	<input checked="" type="checkbox"/> OnBoard Cyrix CX5530
VGA Memory Capacity & Brand	Brand: Cyrix CX5530 Built-in <input type="checkbox"/> 60ns <input type="checkbox"/> 70ns <input type="checkbox"/> ns <input type="checkbox"/> DRAM <input type="checkbox"/> VRAM <input type="checkbox"/> 256K <input type="checkbox"/> 512K <input type="checkbox"/> 1M <input checked="" type="checkbox"/> 3M <input type="checkbox"/> 4M
CPU Type	<input checked="" type="checkbox"/> Intel <input type="checkbox"/> Cyrix <input type="checkbox"/> AMD: Cyrix GXm-266P
HDD Type	<input type="checkbox"/> Max <input checked="" type="checkbox"/> WD <input type="checkbox"/> Con <input type="checkbox"/> Qua <input type="checkbox"/> Fuj : Caviar 26400 6.4GB
CD-ROM Type	<input type="checkbox"/> NEC <input type="checkbox"/> Panasonic <input type="checkbox"/> Pioneer <input checked="" type="checkbox"/> Creative : CD2423E
Keyboard TYPE	Acer 6511-TW1C/B
FDD TYPE	TEAC FD-235HF
Mouse	LOGITECH M-CQ38
LAN CARD	Intel 82559ER
Driver or Utility	<input checked="" type="checkbox"/> VGA <input type="checkbox"/> HDD <input checked="" type="checkbox"/> Others : Intel 82559ER LAN

### Test Result:

HCT 7.6 Features Test	Pass	Fail	Remark
Virtual Dos Mach	✓		
DMPS Test	✓		
Video Playback	✓		
Extended BIOS Parameter Block	✓		
MCI CD Test	✓		
BCT API Test	✓		
INT 13 Extension	✓		
Disk(Stress) Individual Drive	✓		
Disk -CD (Stress)	✓		
Disk (Stress)	✓		
Coprocessor(Stress)	✓		
Net Class Dynamic	✓		
PCI I/O Space	✓		
PCI 2.1 (BIOS)	✓		
PCI 2.1 (Card)	✓		
Unreported I/O	✓		
Unreported Memory	✓		
PnP BIOS	✓		
APM 1.2	✓		
Media Class Dynamic Config	✓		
Wave Drift	✓		

## C. O.S. Compatibility-Windows NT R4.0

**System Information:**

DRAM/SDRAM Capacity & BRAND(SIMM Qty)	Brand: HYNDAI HY57V168010D TC-10S <input type="checkbox"/> 16 <input checked="" type="checkbox"/> 32 <input type="checkbox"/> 64 <input type="checkbox"/> 128MB <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> SDRAM <input type="checkbox"/> SODIMM <input type="checkbox"/> Qty: <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4
System BIOS Version	<input checked="" type="checkbox"/> Award <input type="checkbox"/> AMI Ver: 4.51PG
VGA Card & BIOS	<input checked="" type="checkbox"/> OnBoard Cyrix CX5530
VGA Memory Capacity & Brand	Brand: Cyrix CX5530 Built-in <input type="checkbox"/> 60ns <input type="checkbox"/> 70ns <input type="checkbox"/> ns <input type="checkbox"/> DRAM <input type="checkbox"/> VRAM <input type="checkbox"/> 256K <input type="checkbox"/> 512K <input type="checkbox"/> 1M <input checked="" type="checkbox"/> 3M <input type="checkbox"/> 4M
CPU Type	<input checked="" type="checkbox"/> Intel <input type="checkbox"/> Cyrix <input type="checkbox"/> AMD : Cyrix GXm-266P
HDD Type	<input type="checkbox"/> Max <input checked="" type="checkbox"/> Sea <input type="checkbox"/> Con <input type="checkbox"/> Qua <input type="checkbox"/> Fuj : ST34520A 4GB
CD-ROM Type	<input type="checkbox"/> NEC <input checked="" type="checkbox"/> TEAC <input type="checkbox"/> Pioneer <input type="checkbox"/> Creative : CD-532E 32X
Driver or Utility	<input checked="" type="checkbox"/> VGA <input type="checkbox"/> HDD <input checked="" type="checkbox"/> Others : Intel 82559ER LAN

**VGA Driver Testing:**

Resolution	Color	SF	LF	Pass	Fail	Note
640X480	256	—	—	✓		
	32K	—	—	✓		
	64K	—	—	✓		
800X600	256	✓	✓	✓		
	32K	✓	✓	✓		
	64K	✓	✓	✓		
1024X768	256	✓	✓	✓		
	32K	✓	✓	✓		
1280X1024	256	✓	✓	✓		

**Test Results:**

Test Item	Pass	Fail	Note
<b>Installation From CD-ROM</b>			
Install to IDE HDD	✓		Testing CPU: Cyrix GXm-266P
<b>Boot</b>			
Boot to Windows NT	✓		
Boot to MS-DOS	✓		
Last known good configuration	✓		
Original Configuration	✓		
Shutdown	✓		
Shutdown & Restart	✓		
<b>CPU/Memory/File System</b>			
Memory size less than 64MB	✓		
Memory size Larger than 64MB	✓		
Virtual memory	✓		
System tasking settings	✓		
FAT	✓		
NTFS	✓		
Network	✓		
System clock	✓		
Task switching	✓		
<b>Function Test</b>			
Serial Mouse	✓		
FDD Format/Copy/Read/Write	✓		
PS/2 Mouse	✓		
System Clock	✓		
<b>Keyboard Function Test</b>			
CapLock,NumLock,ScrLock	✓		

<b>Ctrl+Alt+Del</b>	✓		
<b>Ctrl+Esc,Alt+Tab/Esc/Space</b>	✓		
<b>Alt+Tab,Alt+Esc,Alt+Space</b>	✓		
<b>Ctrl+Alt+Pause/Print Screen</b>	✓		
<b>Ctrl+Alt+F1~F12</b>	✓		
<b>COM Port</b>			
<b>Serial Mouse</b>	✓		
<b>Security/Audit/Control</b>			
<b>User manager</b>	✓		
<b>Server manager</b>	✓		
<b>Disk administrator</b>	✓		
<b>Performance monitor</b>	✓		
<b>User profile editor</b>	✓		
<b>Event Viewer</b>	✓		
<b>Windows NT Diagnostics</b>	✓		

**D. O.S. Compatibility-DOS and DOS Utility Compatibility Testing****System Information:**

DRAM/SDRAM Capacity & BRAND(SIMM Qty)	Brand: HYNDAI HY57V658020 TC-10 <input type="checkbox"/> 16 <input type="checkbox"/> 32 <input type="checkbox"/> 64 <input checked="" type="checkbox"/> 128MB <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> SDRAM <input type="checkbox"/> SODIMM <input type="checkbox"/> Qty: <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4
System BIOS Version	<input checked="" type="checkbox"/> Award <input type="checkbox"/> AMI Ver: 4.51PG
VGA Card & BIOS	<input checked="" type="checkbox"/> OnBoard Cyrix CX5530
VGA Memory Capacity & Brand	Brand: Cyrix CX5530 Built-in <input type="checkbox"/> 60ns <input type="checkbox"/> 70ns <input type="checkbox"/> ns <input type="checkbox"/> DRAM <input type="checkbox"/> VRAM <input type="checkbox"/> 256K <input type="checkbox"/> 512K <input type="checkbox"/> 1M <input checked="" type="checkbox"/> 3M <input type="checkbox"/> 4M
CPU Type	<input type="checkbox"/> Intel <input checked="" type="checkbox"/> Cyrix <input type="checkbox"/> AMD: Cyrix GXm-266P
HDD Type	<input type="checkbox"/> Max <input type="checkbox"/> Sea <input type="checkbox"/> Con <input checked="" type="checkbox"/> Qua <input type="checkbox"/> Fuj : 1700AT 1.7GB
CD-ROM Type	<input type="checkbox"/> NEC <input type="checkbox"/> Panasonic <input checked="" type="checkbox"/> Pioneer <input type="checkbox"/> Creative : DVD-A03S
Driver or Utility	<input type="checkbox"/> VGA <input type="checkbox"/> HDD <input checked="" type="checkbox"/> Others : Intel 82559ER LAN

**Test Results:**

Test Item	Pass	Fail	Note
<b>Installation From FDD</b>			
Install to IDE HDD	✓		Testing CPU: Cyrix GXm-266P
<b>Function Test</b>			
Sysinfo Check (Before DOS Initialed )	✓		
System Clock(Compare to RTC CLK)	✓		
DOS Prompt	✓		
FDD Format/Copy/Read/Write	✓		
Serial Mouse	✓		
<b>DOS Commander</b>			
MSD.COM	✓		
EDIT.COM	✓		
EMM386.EXE	✓		
HIMEN.SYS	✓		
<b>Norton Commander</b>			
Key F1~F10 Function	✓		
Key Alt+F1~F10 Function	✓		
Key Ctrl+F1~F10 Function	✓		
<b>Telex</b>			
Setup Function	✓		
Connect with E288MX Fax	✓		
Dialing Function	✓		
File Upload Function	✓		
File Download Function	✓		
<b>ET Ver3.53</b>			
Installation Testing	✓		
16 Font Mode	✓		
24 Font Mode	✓		
Key: Ctrl+Esc Function	✓		
Sethrc Function	✓		
<b>ET 2000</b>			
Installation Testing	✓		
16 Font Mode	✓		
24 Font Mode	✓		
Key: Ctrl+Esc Function	✓		
Sethrc Function	✓		
ETFree Function	✓		

## E. Word Processing/Spread Sheet Compatibility Testing

### System Information:

DRAM/SDRAM Capacity & BRAND(SIMM Qty)	Brand: HYNDAI HY57V658020 TC-10 <input type="checkbox"/> 16 <input type="checkbox"/> 32 <input type="checkbox"/> 64 <input checked="" type="checkbox"/> 128MB <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> SDRAM <input type="checkbox"/> SODIMM <input type="checkbox"/> Qty: <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4
System BIOS Version	<input checked="" type="checkbox"/> Award <input type="checkbox"/> AMI Ver: 4.51PG
VGA Card & BIOS	<input checked="" type="checkbox"/> OnBoard Cyrix CX5530
VGA Memory Capacity & Brand	Brand: C&T69000 Built-in <input type="checkbox"/> 60ns <input type="checkbox"/> 70ns <input type="checkbox"/> ns <input type="checkbox"/> DRAM <input type="checkbox"/> VRAM <input type="checkbox"/> 256K <input type="checkbox"/> 512K <input type="checkbox"/> 1M <input checked="" type="checkbox"/> 3M <input type="checkbox"/> 4M
CPU Type	<input type="checkbox"/> Intel <input checked="" type="checkbox"/> Cyrix <input type="checkbox"/> AMD: Cyrix GXm-266P
HDD Type	<input type="checkbox"/> Max <input checked="" type="checkbox"/> WD <input type="checkbox"/> Con <input type="checkbox"/> Qua <input type="checkbox"/> Fuj : Caviar 26400 6.4GB
CD-ROM Type	<input type="checkbox"/> NEC <input type="checkbox"/> Panasonic <input type="checkbox"/> Pioneer <input checked="" type="checkbox"/> Creative : CD2423E
Driver or Utility	<input checked="" type="checkbox"/> VGA <input type="checkbox"/> HDD <input checked="" type="checkbox"/> Others : Intel 82559ER LAN

### Test Results:

Test Item	Pass	Fail	Note
<b>Ami Pro 3.1</b>			
File Function	✓		
Edit Function	✓		
View Function	✓		
Style Function	✓		
Page Function	✓		
Frame Function	✓		
Tools Function	✓		
Windows Function	✓		
Help Function	✓		
<b>MS Word 6.0c</b>			
File Function	✓		
Edit Function	✓		
View Function	✓		
Insert Function	✓		
Format Function	✓		
Tools Function	✓		
Table Function	✓		
Windows Function	✓		
Help Function	✓		
<b>WordPerfect 6.1</b>			
File Function	✓		
Edit Function	✓		
View Function	✓		
Insert Function	✓		
Format Function	✓		
Table Function	✓		
Graphics Function	✓		
Tools Function	✓		
Windows Function	✓		
Help Function	✓		
<b>MS Works 3.0b</b>			
File Function	✓		
Edit Function	✓		
View Function	✓		
Insert Function	✓		
Format Function	✓		
Tools Function	✓		
Windows Function	✓		
Help Function	✓		
<b>Lotus 1-2-3 R5</b>			
File Function	✓		

<b>Edit Function</b>	✓		
<b>View Function</b>	✓		
<b>Style Function</b>	✓		
<b>Tools Function</b>	✓		
<b>Range Function</b>	✓		
<b>Windows Function</b>	✓		
<b>Help Function</b>	✓		
<b>MS Excel 5.0c</b>			
<b>File Function</b>	✓		
<b>Edit Function</b>	✓		
<b>View Function</b>	✓		
<b>Insert Function</b>	✓		
<b>Format Function</b>	✓		
<b>Tools Function</b>	✓		
<b>Data Function</b>	✓		
<b>Windows Function</b>	✓		
<b>Help Function</b>	✓		
<b>Quattro Pro 6.01</b>			
<b>File Function</b>	✓		
<b>Edit Function</b>	✓		
<b>View Function</b>	✓		
<b>Block Function</b>	✓		
<b>Notebook Function</b>	✓		
<b>Graphics Function</b>	✓		
<b>Tools Function</b>	✓		
<b>Windows Function</b>	✓		
<b>Help Function</b>	✓		

## F. Business Graphics/DTP/DB Compatibility Testing

### System Information:

DRAM/SDRAM Capacity & BRAND(SIMM Qty)	Brand: HYNDAI HY57V658020 TC-10 <input type="checkbox"/> 16 <input type="checkbox"/> 32 <input type="checkbox"/> 64 <input checked="" type="checkbox"/> 128MB <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> SDRAM <input type="checkbox"/> SODIMM <input type="checkbox"/> Qty: <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4
System BIOS Version	<input checked="" type="checkbox"/> Award <input type="checkbox"/> AMI Ver: 4.51PG
VGA Card & BIOS	<input checked="" type="checkbox"/> OnBoard Cyrix CX5530
VGA Memory Capacity & Brand	Brand: Cyrix CX5530 Built-in <input type="checkbox"/> 60ns <input type="checkbox"/> 70ns <input type="checkbox"/> ns <input type="checkbox"/> DRAM <input type="checkbox"/> VRAM <input type="checkbox"/> 256K <input type="checkbox"/> 512K <input type="checkbox"/> 1M <input checked="" type="checkbox"/> 3M <input type="checkbox"/> 4M
CPU Type	<input type="checkbox"/> Intel <input checked="" type="checkbox"/> Cyrix <input type="checkbox"/> AMD: Cyrix GXm-266P
HDD Type	<input type="checkbox"/> Max <input checked="" type="checkbox"/> WD <input type="checkbox"/> Con <input type="checkbox"/> Qua <input type="checkbox"/> Fuj : Caviar 26400 6.4GB
CD-ROM Type	<input type="checkbox"/> NEC <input type="checkbox"/> Panasonic <input type="checkbox"/> Pioneer <input checked="" type="checkbox"/> Creative : CD2423E
Driver or Utility	<input checked="" type="checkbox"/> VGA <input type="checkbox"/> HDD <input checked="" type="checkbox"/> Others : Intel 82559ER LAN

### Test Results:

Test Item	Pass	Fail	Note
<b>PageMaker 5.0a</b>			
File Function	✓		
Edit Function	✓		
Utilities Function	✓		
Layout Function	✓		
Type Function	✓		
Element Function	✓		
Windows Function	✓		
Help Function	✓		
<b>CorelDraw 5.0E2</b>			
File Function	✓		
Edit Function	✓		
View Function	✓		
Layout Function	✓		
Arrange Function	✓		
Effects Function	✓		
Text Function	✓		
Special Function	✓		
Help Function	✓		
<b>PowerPoint 4.0c</b>			
File Function	✓		
Edit Function	✓		
View Function	✓		
Insert Function	✓		
Format Function	✓		
Tools Function	✓		
Draw Function	✓		
Windows Function	✓		
Help Function	✓		
<b>DBase 5.0</b>			
File Function	✓		
Edit Function	✓		
View Function	✓		
Report Function	✓		
Program Function	✓		
Table Function	✓		
Properties Function	✓		
Help Function	✓		
<b>Paradox 5.0</b>			
File Function	✓		
Edit Function	✓		
View Function	✓		

<b>Table Function</b>	✓		
<b>Query Function</b>	✓		
<b>Properties Function</b>	✓		
<b>Tools Function</b>	✓		
<b>Record Function</b>	✓		
<b>Windows Function</b>	✓		
<b>Help Function</b>	✓		
<b>Access 2.0</b>			
<b>File Function</b>	✓		
<b>Edit Function</b>	✓		
<b>View Function</b>	✓		
<b>Security Function</b>	✓		
<b>Format Function</b>	✓		
<b>Record Function</b>	✓		
<b>Windows Function</b>	✓		
<b>Help Function</b>	✓		