



AAEON Technology INC.
ISO-9001/ISO-14001 Certified
Industrial Automation PCs

SBC-658 A0.1

QE Compatibility Test Report

Release Date : July. 27, 2000

Issue Stamp

QA Manager

QE Manager

Test Engineer

Summary of contents :

1. Cover Sheet	1
2. Summary of contents	2
3. Margin	3
Includes temperature, DC voltage and IDE cable length tests.	
4. Stability	4
Includes burn-in and booting tests .	
A. Burn-In Testing(25°C/24hrs).....	4
B. Burn-In Testing(Climatic Sequence/48hrs).....	4
C. Booting Testing(25°C).....	4
D. Booting Testing(Damp Heat,Cyclic/24hrs).....	4
5. Performance	5
Includes performance indexes using various performance test software programs .	
6. Power consumption data	6
Includes +5V current rate .	
7. Hardware compatibility	7
Includes CPU , DRAM , adapter card and HDD compatibility tests.	
A. Component Compatibility- CPU.....	7
B. Component Compatibility- DRAM SIMM Module.....	7
C. Adapter Compatibility- VGA.....	7
D. Adapter Compatibility- LAN.....	8
E. Adapter Compatibility- SCSI Card.....	8
F. Adapter Compatibility- Other Card.....	8
G. Adapter Compatibility- Industry Control Card.....	9
H. Peripheral Compatibility- HDD Device.....	9
I. Peripheral Compatibility- Storage Device.....	9
J. Peripheral Compatibility- Storage Device.....	10
K. Peripheral Compatibility- Input Device.....	10
L. On_Board Network Hardware (physical) Compatibility.....	11
8. Software compatibility	12
Includes various OS and application software tests.	
A. O.S. Compatibility- OS/2 Warp 4.0 (English Version).....	12
B. O.S. Compatibility- Linux RedHat 6.0 (kernel 2.2.14).....	13
C. O.S. Compatibility- Windows 3.1.....	14
D. O.S. Compatibility- Windows 95.....	15
E. O.S. Compatibility- Windows 98.....	17
E-1. Microsoft Windows 98 Hardware Compatibility Test(HCT).....	19
F. O.S. Compatibility- Windows NT R4.0.....	20
G. O.S. Compatibility- DOS and DOS Utility Compatibility Testing.....	22

There are 3 test results in this document; they are described as follows:

Pass: It worked perfectly

Fail: Test failed, and to be modified in the next version

N/A: Outside of specifications or no test equipment

The test report would be tested and updated after version changed.

Quality Engineering Department of AAEON TECHNOLOGY INC.

1F, No.6,Alley 6, Lane 45,Pao-Hsin Rd,

Hsin-Tien City, Taipei, Taiwan , ROC

Tel: 886-2-29121234

Fax:886-2-29130792

886-2-29130774

1. Margin Testing

System Information:

DRAM/SDRAM Capacity & BRAND(SIMM Qty)	Brand: D4516821AG5-A10-9NF <input type="checkbox"/> 8 <input type="checkbox"/> 16 <input checked="" type="checkbox"/> 32 <input type="checkbox"/> 64 <input type="checkbox"/> 128MB <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> SDRAM <input type="checkbox"/> SODIMM <input type="checkbox"/> _____ Qty: <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4
System BIOS Version	<input checked="" type="checkbox"/> Award <input type="checkbox"/> AMI Ver: V 4.51
O.S. Environment	<input checked="" type="checkbox"/> MSDOS6.22 <input type="checkbox"/> _____
VGA Card	<input checked="" type="checkbox"/> OnBoard <input type="checkbox"/> C&T 69000
DOC Type	M-System DOC2000 <input type="checkbox"/> 4MB <input checked="" type="checkbox"/> 8MB <input type="checkbox"/> 16MB <input type="checkbox"/> 24MB <input type="checkbox"/> __MB

Test Result:

High Temperature: 2 Hours			
Testing CPU: Celeron 400	<input type="checkbox"/> COM1 LB	<input type="checkbox"/> COM2 LB	<input type="checkbox"/> LPT LB
Test Program:	<input checked="" type="checkbox"/> QAPlus/FE V5.4	<input type="checkbox"/> AMIDIAG V4.50	
<input checked="" type="checkbox"/> 55°C	<input checked="" type="checkbox"/> 60°C	<input checked="" type="checkbox"/> 65°C	<input checked="" type="checkbox"/> 70°C <input type="checkbox"/> 75°C <input type="checkbox"/> 80°C <input type="checkbox"/> 85°C

Low Temperature: 2 Hours			
Testing CPU: Celeron 400	<input type="checkbox"/> COM1 LB	<input type="checkbox"/> COM2 LB	<input type="checkbox"/> LPT LB
Test Program:	<input checked="" type="checkbox"/> QAPlus/FEV5.4	<input type="checkbox"/> AMIDIAG V4.50	<input checked="" type="checkbox"/> 5°C <input checked="" type="checkbox"/> 0°C
<input type="checkbox"/> -5°C	<input type="checkbox"/> -10°C	<input type="checkbox"/> -15°C	<input type="checkbox"/> -20°C <input type="checkbox"/> -25°C <input type="checkbox"/> -30°C <input type="checkbox"/> -35°C <input type="checkbox"/> -40°C

High Voltage: 2 Hours/25°C			
Testing CPU: Celeron 366	<input type="checkbox"/> COM1 LB	<input type="checkbox"/> COM2 LB	<input type="checkbox"/> LPT LB
Test Program:	<input checked="" type="checkbox"/> QAPlus/FE V5.4	<input type="checkbox"/> AMIDIAG V4.50	
<input checked="" type="checkbox"/> AGrade: 5.20V	<input checked="" type="checkbox"/> BGrade: 5.25V	<input type="checkbox"/> CGrade: 5.30V	<input type="checkbox"/> DGrade: 5.35V <input type="checkbox"/> EGrade: 5.4V

Low Voltage: 2 Hours/25°C			
Testing CPU: Celeron 366	<input type="checkbox"/> COM1 LB	<input type="checkbox"/> COM2 LB	<input type="checkbox"/> LPT LB
Test Program:	<input checked="" type="checkbox"/> QAPlus/FE V5.4	<input type="checkbox"/> AMIDIAG V4.50	
<input checked="" type="checkbox"/> AGrade: 4.85V	<input checked="" type="checkbox"/> BGrade: 4.75V	<input type="checkbox"/> CGrade: 4.70V	<input type="checkbox"/> DGrade: 4.65V <input type="checkbox"/> EGrade: 4.6V

2 . Stability Testing

System Information:

DRAM/SDRAM Capacity & BRAND(SIMM Qty)	Brand: D4516821AG5-A10-9NF <input type="checkbox"/> 8 <input type="checkbox"/> 16 <input checked="" type="checkbox"/> 32 <input type="checkbox"/> 64 <input type="checkbox"/> 128MB <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> SDRAM <input type="checkbox"/> SODIMM <input type="checkbox"/> Qty: <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4
System BIOS Version	<input checked="" type="checkbox"/> Award <input type="checkbox"/> AMI Ver: V 4.51
O.S. Environment	<input checked="" type="checkbox"/> MSDOS6.22 <input type="checkbox"/>
VGA Card	<input checked="" type="checkbox"/> OnBoard <input type="checkbox"/> C&T 69000
DOC Type	M-System DOC2000 <input type="checkbox"/> 4MB <input checked="" type="checkbox"/> 8MB <input type="checkbox"/> 16MB <input type="checkbox"/> 24MB <input type="checkbox"/> MB

A. Burn-In Testing (24Hours)

Test Condition : Under Room Temp. 25°C

Test Software	Pass	Fail	Note
QAPluse 5.4	✓		

B. Burn-In Testing (48 Hours)

Test Condition : Burn-In Under Temp. 0°C ~ 60°C (IEC-68-2-61)

Test Software	Pass	Fail	Note
QAPluse 5.4	✓		

C. Booting Testing

Test Condition : Under Room Temp. 25°C

Test Method	Actual	Successful	Failure rate	On time	Off Time	Note
Power On/Off 1000Times	1000	1000	0 %	55 Sec	5 Sec	
KB Reset 20 Times	20	20	0 %	45 Sec	3 Sec	
H/W Reset 1000Times	1000	1000	0 %	55 Sec	5 Sec	

D. Burn-In Booting Testing (24 Hours)

Test Condition : Burn-In Under Temp. 0°C ~ 60°C (IEC-68-2-30)

Test Method	Actual	Successful	Failure rate	On time	Off Time	Note
Power On/Off	1329	1328	0.07 %	55 Sec	5 Sec	

3 . Performance Testing

System Information:

DRAM/SDRAM Capacity & BRAND(SIMM Qty)	Brand: D45128841G5-A10-9JF <input type="checkbox"/> 8 <input type="checkbox"/> 16 <input type="checkbox"/> 32 <input type="checkbox"/> 64 <input checked="" type="checkbox"/> 256MB <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> SDRAM <input type="checkbox"/> SODIMM <input type="checkbox"/> Qty: <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4
System BIOS Version	<input checked="" type="checkbox"/> Award <input type="checkbox"/> AMI Ver: V 4.51
O.S. Environment	<input checked="" type="checkbox"/> MSDOS6.22 <input checked="" type="checkbox"/> Windows 98 <input type="checkbox"/> Windows NT <input type="checkbox"/>
VGA Card	<input checked="" type="checkbox"/> OnBoard <input type="checkbox"/> C&T 69000
VGA Memory	<input type="checkbox"/> 256K <input type="checkbox"/> 512K <input type="checkbox"/> 1M <input checked="" type="checkbox"/> 2M <input type="checkbox"/> 4M <input type="checkbox"/>
HDD Type	<input type="checkbox"/> Max <input type="checkbox"/> Sea <input type="checkbox"/> Con <input checked="" type="checkbox"/> Qua <input type="checkbox"/> Fuj : K13600AT
Testing Feature	<input type="checkbox"/> 32 bits Transfer <input checked="" type="checkbox"/> Block Mode <input type="checkbox"/> DMA Mode
VGA Testing Mode	1024X768X256c (For WinStone & WinBench)
Driver or Utility	<input checked="" type="checkbox"/> VGA <input type="checkbox"/> HDD <input type="checkbox"/> Others :

Operating System Environment (DOS Mode)

Config.sys	Autoexec.bat
Device=c:\dos\himem.sys dos=high,umb files=35 Buffers=40	Prompt \$p\$g c:\dos\smartdrv.exe /x

Testing Software

Testing Utility	CPU Type					Unit
	Celeron 500	Celeron 533	Pentium III 550	Pentium III 600	Pentium III 700	
LandMark Speed 2.0						
CPU	3163.05	3373.95	3435.62	3795.77	4428.45	MHz
FPU	8962.80	9560.43	10444.54	10664.53	12441.99	MHz
VIDEO	16384	16384	11430	16948	33Chr/sec	Chs/sec
Norton 8.0						
SI	191.2	28.3	54.8	141.6	90.6	ID
Power Meter 2.02						
MIPS Test	237.0	258.5	284.4	284.4	355.5	Mips
WinStone 2000						
HighEnd Graphic WinStone 99	24.2	25	31	31.7	34	
Business Graphic Winstone 99	19.9	20.2	29.4	24.3	25.2	
WinBench 2000						
H.E. Graphic WinMark 99	354 ^{2.3}	366 ^{2.3}	341 ^{2.3}	436 ^{2.3}	479 ^{2.3}	MP/s
Business Graphic WinMark 99	108 ^{2.3}	111 ^{2.3}	98.1 ^{2.3}	133 ^{2.3}	142 ^{2.3}	TB/s
CPUmark 99	34.9 ^{3.13}	36.6 ³	51.2 ^{3.13}	55.2 ³	62.8 ^{3.13}	
FPU Winmark	2670 ³	2860 ³	2970 ³	3240 ³	3780 ³	
Coretest V3.02						
DTR (Buffered Read)	7680	7712	9056	9072	9632	KB/Sec
Performance ID	53.04	53.23	60.44	61.33	64.76	
Wintech V1.2						
Overall WinTach RPM	656.68	669.36	725.60	804.06	838.2	

4 . Power Consumption

System Information:

DRAM Type & Capacity	MT48LC2M8A1
VGA Card	OnBoard C&T 69000
DOC or Floppy	M-System DOC2000
VGA Testing Mode	Blank Screen
O.S.	DOS 6.22

Operating System Environment (DOS Mode)

Config.sys	Autoexec.bat
Device=c:\dos\himem.sys dos=high,umb files=35 Buffers=40	Prompt \$p\$g c:\dos\smartdrv.exe /x

Test Software (DOS Mode):

Test Software	Landmark Speed V.2.0(Speed200.exe)
---------------	------------------------------------

Test Result:

Mode Type	Celeron CPU						Pentium III CPU			Unit
	300	366	400	433	500	533	550	600	700	
Normal Mode(+5V)	4.44	4.72	4.97	4.97	5.33	5.87	4.62	4.86	5.19	amp/max
Standby Mode(+5V)	3.28	3.6	3.59	4.03	4.54	4.99	3.41	4.11	4.42	amp/max
Suspend Mode(+5V)	3.12	3.4	3.44	3.84	4.32	4.85	3.25	4.07	4.29	amp/max
HD Power Down(+5V)	1.97	1.9	1.97	2.03	2.12	2.16	2.12	2.26	2.29	amp/max

Note :

- 1.STANDBY Model all function off.
- 2.The unit of current is A .

5 . Hardware Compatibility

A. Component Compatibility- CPU

CPU Device List:

Brand	Device Model	Pass	Fail	Note
Celeron	Socket 370 300MHz	✓		
Celeron	Socket 370 366MHz	✓		
Celeron	Socket 370 400MHz	✓		
Celeron	Socket 370 433MHz	✓		
Celeron	Socket 370 500MHz	✓		
Celeron	Socket 370 533MHz	✓		
Pentium III	Socket 370 550MHz 0.18 μ	✓		
Pentium III	Socket 370 600MHz 0.18 μ	✓		
Pentium III	Socket 370 700MHz 0.18 μ	✓		

B. Component Compatibility- DRAM SIMM Module

DRAM SIMM Model List:

Brand	Device Model	Pass	Fail	Note
Hitachi	HM5216805T10H16M 16MB	✓		
NEC	D4564841G5-A10-9JF 64MB	✓		
Micron	MT48LC2M8A1 32MB	✓		
LGS	GM72V661641CT7J 64MB	✓		
SIEMENS	HYB39S16800AT-10 32MB	✓		
NEC	D4516821AG5-A10-9NF 32MB	✓		
Hyundai	HY57V168010D TC-10S 32MB	✓		
NEC	D4564841G5 A80-9JF 64MB	✓		
NEC	D4564841G5 A80-9JF 128MB	✓		
NEC	D4516821AG5-A10-9NF 16MB	✓		
NEC	D4516821AG5-A10-9NF 32MB	✓		
NEC	D45128841G5-A10-9JF 256MB	✓		
Hyundai	HY57V1291620 LTC-10S 64MB	✓		
Hitachi	5264805DTTA60 64MB	✓		
NEC	D4516821AG5-A10-9NF 16MB	✓		

C. Adapter Compatibility- VGA Card

VGA Adapter List:

Brand	Device Model	Pass	Fail	Note
VGA Card	S3/Trio64 V2	✓		
VGA Card	S3 Vision 968	✓		
VGA Card	3D Blaster Savage4	✓		
On Board	C&T 69000	✓		

D. Adapter Compatibility- LAN Card**Action:**

1. Load ODI Driver (Lsl,lpxodi,Vlm Or Netx)	2. Login To Server System
3. Transfer Data Between SRV And WK(Mulity Task)	4. logout

LAN Adapter List:

Brand	Device Model	Pass	Fail	Note
3COM	3C509B ISA(10Mbps)	✓		
3COM	3C905-TX PCI(10/100Mbps)	✓		
Intell	EP-320x Rec.3B PCI(10/100Mbps)	✓		
OnBoard	Intel 82559er 100Mbps	✓		

E. Adapter Compatibility- SCSI Card**SCSI Adapter List:**

Brand	Device Model	Pass	Fail	Note
SCSI Adapter	AHA-2940UW	✓		
SCSI Adapter	AHA-1520B	✓		
SCSI Adapter	AHA-2940U2WK ULTRA-2-WIDE	✓		

F. Adapter Compatibility- Other Card**Adapter Card List:**

Brand	Device Model	Pass	Fail	Note
MPEG Card				
YUAN	DVD MPEG-2	✓		
Sound Card				
Sound Card	Creative SB16 PNP/CT2980 ISA	✓		
Sound Card	Blaster Vibra 16XV	✓		

G. Adapter Compatibility- Industry Control Card**Industry Control Adapter List:**

Brand	Device Model	Pass	Fail	Note
ISA CARD				
AAEON	RDC-1020N	✓		
AAEON	RDC-1010A	✓		
104 Module				
AAEON	PCM-3115(PCMCIA 2 SLOTS)	✓		
AAEON	PCM-3420 (SCSI)	✓		
AAEON	PCM-3840-BARE (Extend DOC)	✓		

H. Peripheral Compatibility-HDD Device**HDD List:**

Brand	Device Model	Pass	Fail	Note
Seagate	ST34520LW 4.5GB 7200RPM	✓		
IBM	DNES-309170 9GB	✓		
Quantum	Big-Foot TX4000AT	✓		
Maxtor	91021U2 10GB ULTRA DMA/66	✓		
Quantum	K13600AT 13GB Fireball	✓		
IBM	DPTA-372050	✓		

I. Peripheral Compatibility- Storage Device**Device List:**

Brand	Device Model	Pass	Fail	Note
CD/ROM				
GENUNE	50X	✓		
SAMPO	36X	✓		
CREATIVE	24X	✓		
ZIP				
IOMEGA	ZIP 100MB Parallel Port	✓		
IOMEGA	ZIP 100MB USB Port	✓		
LS-120				
LS-120	LKM-F934-1	✓		
Fax/Modem				
Modem	LEMEL 33.6 FAX/MODEM	✓		
Modem	Cyber Lander 2000 56K	✓		

J. Peripheral Compatibility- Others**Device List:**

Brand	Device Model	Pass	Fail	Note
RS-485 Port				
Adam	ADAM-4011	✓		
USB Port				
SCANNER	HP SJ4200C	✓		
ZIP	IOMEGA ZIP 100MB	✓		
Mouse	Dexin 800dpi A2U800A	✓		
Vcam	Capture	✓		
Tekcam	P35u	✓		
BTC	7932 Keyboard	✓		
HP	PhotoSmart P1000 Printer	✓		
Parallel Port				
HP	PhotoSmart P1000 Printer	✓		
ZIP	IOMEGA ZIP 100MB Parallel Port	✓		
MP3 radio	IMars Digital Stereo Player			

K. Peripheral Compatibility- Input Device**Input Device List:**

Brand	Device Model	Pass	Fail	Note
Keyboard				
BTC	7932 Keyboard	✓		
Acer	6311-TW	✓		
Mouse				
Dexin	Mouse	✓		
Logitech	MouseMan	✓		
Logitech	Serial Mouse	✓		

L. On Board Network Hardware (physical) Compatibility**System Information(Client Site):**

DRAM/SDRAM Capacity & BRAND(SIMM Qty)	Brand: D4564841G5 A80-9JF <input type="checkbox"/> 8 <input type="checkbox"/> 16 <input type="checkbox"/> 32 <input checked="" type="checkbox"/> 64 <input type="checkbox"/> 128MB <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> SDRAM <input type="checkbox"/> SODIMM <input type="checkbox"/> Qty: <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4
SYSTEM BIOS Ver.	<input checked="" type="checkbox"/> AWARD <input type="checkbox"/> AMI Ver: V 4.51
O.S. Environment	<input checked="" type="checkbox"/> DOS6.22 <input type="checkbox"/> WINNT <input type="checkbox"/> NOVELL V 5.0
VGA Card	<input checked="" type="checkbox"/> OnBoard C&T 69000
POWER SUPPLY	<input type="checkbox"/> MPU-250W <input checked="" type="checkbox"/> SSH-250G <input type="checkbox"/> SSH-350G <input type="checkbox"/> ST-250AF
IDE HDD TYPE	<input checked="" type="checkbox"/> Max <input type="checkbox"/> Sea <input type="checkbox"/> Con <input type="checkbox"/> Qua <input type="checkbox"/> Fuj <input type="checkbox"/> IBM : 91021U2 10GB
SCSI HDD TYPE	<input type="checkbox"/> Max <input type="checkbox"/> Sea <input type="checkbox"/> Con <input type="checkbox"/> Qua <input type="checkbox"/> Fuj <input type="checkbox"/> IBM:
LAN CARD	<input checked="" type="checkbox"/> OnBoard: Intell 82559er
CD-ROM TYPE	<input type="checkbox"/> NEC <input type="checkbox"/> PANASONIC <input type="checkbox"/> PIONEER <input checked="" type="checkbox"/> SAMPO :36X
Cable/Cable Length	

System Information(Server Site):

Board System	<input checked="" type="checkbox"/> NOVELL V 5.0
DRAM/SDRAM Capacity & BRAND(SIMM Qty)	Brand: 5264805DTTA60 <input type="checkbox"/> 8 <input type="checkbox"/> 16 <input type="checkbox"/> 32 <input checked="" type="checkbox"/> 64 <input type="checkbox"/> 128MB <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> SDRAM <input type="checkbox"/> SODIMM <input type="checkbox"/> Qty: <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4
SYSTEM BIOS Ver.	<input checked="" type="checkbox"/> AWARD <input type="checkbox"/> AMI Ver: V 4.51
VGA Card	<input checked="" type="checkbox"/> DOS6.22 <input type="checkbox"/> WINNT <input checked="" type="checkbox"/> NOVELL V 5.0
O.S. Environment	<input checked="" type="checkbox"/> OnBoard C&T 69000
IDE HDD TYPE	<input type="checkbox"/> MPU-250W <input checked="" type="checkbox"/> SSH-250G <input type="checkbox"/> SSH-350G <input type="checkbox"/> ST-250AF
SCSI HDD TYPE	<input type="checkbox"/> Max <input type="checkbox"/> Sea <input type="checkbox"/> Con <input checked="" type="checkbox"/> Qua <input type="checkbox"/> Fuj <input type="checkbox"/> IBM : Big-Foot TX4000AT
LAN CARD	<input type="checkbox"/> Max <input type="checkbox"/> Sea <input type="checkbox"/> Con <input type="checkbox"/> Qua <input type="checkbox"/> Fuj <input type="checkbox"/> IBM:
CPU Type	<input checked="" type="checkbox"/> OnBoard: Intell 82559
CD-ROM TYPE	<input type="checkbox"/> NEC <input type="checkbox"/> PANASONIC <input type="checkbox"/> PIONEER <input checked="" type="checkbox"/> GENUNE :50X
Cable/Cable Length	

HUB Type:**Test Result:**

SUBJECT Network Hardware Function Testing				
Test Item	Pass	Fail	Note	
Transceiver	✓			
Receiver	✓			
CRC error	✓			
Collision back-off generation	✓			
Auto-negotiation	✓			
100M Base-TX half duplex	✓			
10M Base-T half duplex	✓			
SUBJECT Network Operation System Function Testing				
Windows NT 4.0	✓			
SUBJECT Network Performance Testing				
NWTEST 24HR	Pass			
SUBJECT Workstation Application Function Testing				
Windows 98 for TCP/IP	✓			
Windows NT 4.0 for IPX/SPX	✓			
Windows NT 4.0 for NetBEUI	✓			
Windows NT 4.0 for TCP/IP	✓			

Note : 1.Mulity Task is that transfers files(copy/verify/delete) and VCD in the same time.

6 . Software Compatibility

A. O.S. Compatibility-OS/2 Warp 4.0 (English Version)

System Information:

DRAM/SDRAM Capacity & BRAND(SIMM Qty)	Brand: D4564841G5 A80-9JF <input type="checkbox"/> 8 <input type="checkbox"/> 16 <input type="checkbox"/> 32 <input checked="" type="checkbox"/> 64 <input type="checkbox"/> 128MB <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> SDRAM <input type="checkbox"/> SODIMM <input type="checkbox"/> Qty: <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4
Cache Memory Capacity & Brand	Brand: <input type="checkbox"/> 60ns <input type="checkbox"/> 70ns <input type="checkbox"/> ns <input type="checkbox"/> PB <input type="checkbox"/> 128K <input type="checkbox"/> 256K <input type="checkbox"/> 512K <input type="checkbox"/>
System BIOS Version	<input checked="" type="checkbox"/> AWARD <input type="checkbox"/> AMI Ver: V 4.51
VGA Card & BIOS	<input checked="" type="checkbox"/> OnBoard C&T 69000 <input type="checkbox"/> BIOS:
VGA Memory Capacity & Brand	Brand: <input type="checkbox"/> 60ns <input type="checkbox"/> 70ns <input type="checkbox"/> ns <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> VRAM <input type="checkbox"/> 256K <input type="checkbox"/> 512K <input type="checkbox"/> 1M <input checked="" type="checkbox"/> 2M <input type="checkbox"/> 4M <input type="checkbox"/>
CPU Type	Celeron 400MHz
HDD Type	<input type="checkbox"/> Max <input type="checkbox"/> Sea <input type="checkbox"/> Con <input checked="" type="checkbox"/> Qua <input type="checkbox"/> Fuj : Big-Foot TX4000AT
CD-ROM Type	<input type="checkbox"/> NEC <input type="checkbox"/> Panasonic <input type="checkbox"/> Pioneer <input checked="" type="checkbox"/> SAMPO :36X
Driver or Utility	<input type="checkbox"/> VGA <input type="checkbox"/> HDD <input type="checkbox"/> Others :

Test Results:

Test Item	Pass	Fail	Note
Installation From CD-ROM + Boot-Disk			
Install to IDE HDD	✓		Testing CPU: Celeron 400MHz
SCSI HDD with AHA-1542 <input type="checkbox"/> CP <input type="checkbox"/> CF			Testing CPU:
SCSI HDD with AHA- <input type="checkbox"/> 2940UW <input type="checkbox"/> 2940W			Testing CPU:
Boot			
Boot to DOS	✓		
Boot to OS/2 (FAT)	✓		
Boot Up - Without K.B.	✓		
Shutdown	✓		
Function Test			
Task Switching	✓		
Multi-Task Test	✓		
System Clock	✓		
Command Prompts Test			
WIN-OS/2 Full Screen	✓		
WIN-OS/2 Windows	✓		
OS/2 Full Screen	✓		
OS/2 Windows	✓		
DOS Full Screen	✓		
DOS Windows	✓		
DOS from Drive A	✓		
Keyboard Function Test			
Ctrl+Alt+Del	✓		
Alt+Tab	✓		
Alt+Esc	✓		
Ctrl+Esc	✓		
Alt+F4	✓		

B. O.S. Compatibility -Linux RedHat 6.0 (kernel 2.2.14)**System Information:**

DRAM/SDRAM Capacity & BRAND(SIMM Qty)	Brand: D4564841G5-A80-9JF <input type="checkbox"/> 16 <input type="checkbox"/> 32 <input type="checkbox"/> 64 <input checked="" type="checkbox"/> 128 <input type="checkbox"/> 256MB <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> SDRAM <input type="checkbox"/> SODIMM <input type="checkbox"/> _____ Qty: <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4
Cache Memory Capacity & Brand	Brand: <input type="checkbox"/> 60ns <input type="checkbox"/> 70ns <input type="checkbox"/> ns <input type="checkbox"/> PB <input type="checkbox"/> 128K <input type="checkbox"/> 256K <input type="checkbox"/> 512K <input type="checkbox"/>
System BIOS Version	<input checked="" type="checkbox"/> Award <input type="checkbox"/> AMI Ver:
VGA Card & BIOS	<input checked="" type="checkbox"/> OnBoard C&T 69000 <input type="checkbox"/> BIOS:
LAN CARD	<input checked="" type="checkbox"/> OnBoard: Intel 82559er
VGA Memory Capacity & Brand	Brand: <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> VRAM <input type="checkbox"/> 256K <input type="checkbox"/> 512K <input type="checkbox"/> 1M <input checked="" type="checkbox"/> 2M <input type="checkbox"/> 4M
CPU Type	Celeron 500MHZ
HDD Type	<input checked="" type="checkbox"/> Max <input type="checkbox"/> Sea <input type="checkbox"/> Con <input type="checkbox"/> Qua <input type="checkbox"/> WD :91021U2
CD-ROM Type	<input checked="" type="checkbox"/> NEC <input type="checkbox"/> Panasonic <input type="checkbox"/> Pioneer <input type="checkbox"/> Creative :E151483
Driver or Utility	<input type="checkbox"/> VGA <input checked="" type="checkbox"/> LAN e100-1.0.0

Test Results:

Test Item	Pass	Fail	Note
Subject Installation to HDD			
Install from IDE HDD			
Install from CD-ROM	✓		
Subject Base Function			
Default Booting	✓		
Failsafe Booting	✓		
Gnome work plane	✓		
KDE work plane	✓		
Reboot	✓		
Logout	✓		
Halt	✓		
Subject Xf86config Setup(3.3.3.1)			
Xf86config	✓		BIOS adjust to 1024x768 VGA Mode
XF86Setup	✓		
X -probeonly >	✓		
Subject X Windows Function			
Netscape 4.51	✓		
Work space switching	✓		
Ctrl+alt+back space	✓		
Ctrl+alt+F1	✓		
Ctrl+alt+F7	✓		
Ctrl+alt +/-	✓		
Subject Xterm Function			
Dmesg	✓		
adduser ` passwd	✓		
Ping	✓		
ls ` cp ` rm ` mv ` tar ` gzip	✓		
mkdir ` rmdir	✓		
Subject Mount Function			
Floppy ` CD-ROM ` HD	✓		
MSDOS FAT	✓		
Windows 98 FAT	✓		

C. O.S. Compatibility-Windows 3.1

System Information:

DRAM/SDRAM Capacity & BRAND(SIMM Qty)	Brand: HYB39S16800AT-10 <input type="checkbox"/> 8 <input type="checkbox"/> 16 <input checked="" type="checkbox"/> 32 <input type="checkbox"/> 64 <input type="checkbox"/> 128MB <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> SDRAM <input type="checkbox"/> SODIMM <input type="checkbox"/> Qty: <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4
Cache Memory Capacity & Brand	Brand: <input type="checkbox"/> 60ns <input type="checkbox"/> 70ns <input type="checkbox"/> ns <input type="checkbox"/> PB <input type="checkbox"/> 128K <input type="checkbox"/> 256K <input type="checkbox"/> 512K <input type="checkbox"/>
System BIOS Version	<input checked="" type="checkbox"/> AWARD <input type="checkbox"/> AMI Ver: V 4.51
VGA Card & BIOS	<input checked="" type="checkbox"/> OnBoard C&T 69000 <input type="checkbox"/> BIOS:
VGA Memory Capacity & Brand	Brand: <input type="checkbox"/> 60ns <input type="checkbox"/> 70ns <input type="checkbox"/> ns <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> VRAM <input type="checkbox"/> 256K <input type="checkbox"/> 512K <input type="checkbox"/> 1M <input checked="" type="checkbox"/> 2M <input type="checkbox"/> 4M <input type="checkbox"/>
CPU Type	Celeron 366MHz
HDD Type	<input checked="" type="checkbox"/> Max <input type="checkbox"/> Sea <input type="checkbox"/> Con <input type="checkbox"/> Qua <input type="checkbox"/> Fuj : 91021U2 10GB
CD-ROM Type	<input type="checkbox"/> NEC <input type="checkbox"/> Panasonic <input type="checkbox"/> Pioneer <input checked="" type="checkbox"/> GENUNE :50X
Driver or Utility	<input checked="" type="checkbox"/> VGA <input type="checkbox"/> HDD <input type="checkbox"/> Others :

VGA Driver Testing:

Resolution	Color	SF	LF	Pass	Fail	Note
640X480	256			✓		
	32K			✓		
	64K			✓		
	16.7M			✓		
800X600	256			✓		
	32K			✓		
	64K			✓		
1024X768	32K			✓		
	64K			✓		
1280X1024	256			✓		

Test Results:

Test Item	Pass	Fail	Note
Installation From FDD			
Install to IDE HDD	✓		Testing CPU: Celeron 366Hz
SCSI HDD with AHA-1542 <input type="checkbox"/> CP <input type="checkbox"/> CF Card			Testing CPU:
SCSI HDD with AHA- <input type="checkbox"/> 2940UW <input type="checkbox"/> 2940W			Testing CPU:
Keyboard Function Test			
Ctrl+Alt+Del	✓		
Alt+Tab	✓		
Alt+Esc	✓		
Alt-F4	✓		
Function Test			
Virtual Memory	✓		
System Clock	✓		
DOS Prompt	✓		
Real Mode & Protect Mode Switch	✓		
Task Switching	✓		
FDD Format/Copy/Read/Write	✓		
Serial Mouse	✓		
PS/2 Mouse	✓		

D. O.S. Compatibility-Windows 95**System Information:**

DRAM/SDRAM Capacity & BRAND(SIMM Qty)	Brand: D4564841G5 A80-9JF <input type="checkbox"/> 8 <input type="checkbox"/> 16 <input type="checkbox"/> 32 <input type="checkbox"/> 64 <input checked="" type="checkbox"/> 128MB <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> SDRAM <input type="checkbox"/> SODIMM <input type="checkbox"/> Qty: <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4
Cache Memory Capacity & Brand	Brand: <input type="checkbox"/> 60ns <input type="checkbox"/> 70ns <input type="checkbox"/> ns <input type="checkbox"/> PB <input type="checkbox"/> 128K <input type="checkbox"/> 256K <input type="checkbox"/> 512K <input type="checkbox"/>
System BIOS Version	<input checked="" type="checkbox"/> AWARD <input type="checkbox"/> AMI Ver: V 4.51
VGA Card & BIOS	<input checked="" type="checkbox"/> OnBoard C&T 69000 <input type="checkbox"/> BIOS:
VGA Memory Capacity & Brand	Brand: <input type="checkbox"/> 60ns <input type="checkbox"/> 70ns <input type="checkbox"/> ns <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> VRAM <input type="checkbox"/> 256K <input type="checkbox"/> 512K <input type="checkbox"/> 1M <input checked="" type="checkbox"/> 2M <input type="checkbox"/> 4M <input type="checkbox"/>
CPU Type	Celeron 433Hz
HDD Type	<input checked="" type="checkbox"/> Max <input type="checkbox"/> Sea <input type="checkbox"/> Con <input type="checkbox"/> Qua <input type="checkbox"/> Fuj : 91021U2 10GB
CD-ROM Type	<input type="checkbox"/> NEC <input type="checkbox"/> Panasonic <input type="checkbox"/> Pioneer <input checked="" type="checkbox"/> GENUNE :50X
Driver or Utility	<input checked="" type="checkbox"/> VGA <input type="checkbox"/> HDD <input type="checkbox"/> Others :

VGA Driver Testing:

Resolution	Color	SF	LF	Pass	Fail	Note
640X480	256			✓		
	32K			✓		
	64K			✓		
	16.7M			✓		
800X600	256			✓		
	32K			✓		
	64K			✓		
1024X768	32K			✓		
	64K			✓		
	256			✓		
1280X1024	256			✓		
1600X1200	256			✓		

Test Results:

Test Item	Pass	Fail	Note
Installation From CD/ROM			
Install to IDE HDD	✓		Testing CPU: Celeron 433Hz
SCSI HDD with AHA-1542 <input type="checkbox"/> CP <input type="checkbox"/> CF			Testing CPU:
SCSI HDD with AHA- <input type="checkbox"/> 2940UW <input type="checkbox"/> 2940W			Testing CPU:
Boot			
Boot Normal	✓		
Boot Logged (\BOOTLOG.TXT)	✓		
Boot Safe Mode	✓		
Boot Safe Mode & Network	✓		
Boot Step By Step Confirmation	✓		
Boot Safe Mode Command Prompt	✓		
Function Test			
Serial Mouse	✓		
FDD Format/Copy/Read/Write	✓		
PS/2 Mouse	✓		
System Clock	✓		
Keyboard Function Test			
Alt+F4 Quit a Program	✓		
Ctrl+Esc Display the Start Menu	✓		
Alt+Tab Switch To Last Windows	✓		
Ctrl+Alt+Del Close Program	✓		
F8 Start up Boot Up Menu	✓		
F4 Boot Up from Previous	✓		

Shutdown			
Shutdown the Computer	✓		
Shutdown Restart	✓		
Shutdown to MS-DOS Mode	✓		
Close all Prog. & Login Other User	✓		

E. O.S. Compatibility-Windows 98**System Information:**

DRAM/SDRAM Capacity & BRAND(SIMM Qty)	Brand: D45128841G5-A10-9JF <input type="checkbox"/> 8 <input type="checkbox"/> 16 <input type="checkbox"/> 32 <input type="checkbox"/> 64 <input checked="" type="checkbox"/> 256MB <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> SDRAM <input type="checkbox"/> SODIMM <input type="checkbox"/> Qty: <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4
Cache Memory Capacity & Brand	Brand: <input type="checkbox"/> 60ns <input type="checkbox"/> 70ns <input type="checkbox"/> ns <input type="checkbox"/> PB <input type="checkbox"/> 128K <input type="checkbox"/> 256K <input type="checkbox"/> 512K <input type="checkbox"/>
System BIOS Version	<input checked="" type="checkbox"/> AWARD <input type="checkbox"/> AMI Ver: V 4.51
VGA Card & BIOS	<input checked="" type="checkbox"/> OnBoard C&T 69000 <input type="checkbox"/> BIOS:
VGA Memory Capacity & Brand	Brand: <input type="checkbox"/> 60ns <input type="checkbox"/> 70ns <input type="checkbox"/> ns <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> VRAM <input type="checkbox"/> 256K <input type="checkbox"/> 512K <input type="checkbox"/> 1M <input checked="" type="checkbox"/> 2M <input type="checkbox"/> 4M <input type="checkbox"/>
CPU Type	Pentium III 550
HDD Type	<input checked="" type="checkbox"/> IBM <input type="checkbox"/> Sea <input type="checkbox"/> Con <input type="checkbox"/> Qua <input type="checkbox"/> Fuj : DPTA-372050
CD-ROM Type	<input type="checkbox"/> NEC <input type="checkbox"/> Panasonic <input type="checkbox"/> Pioneer <input checked="" type="checkbox"/> GENUNE :50X
Driver or Utility	<input checked="" type="checkbox"/> VGA <input type="checkbox"/> HDD <input type="checkbox"/> Others :

VGA Driver Testing:

Resolution	Color	SF	LF	Pass	Fail	Note
640X480	256			✓		
	32K			✓		
	64K			✓		
	16.7M			✓		
800X600	256			✓		
	32K			✓		
1024X768	64K			✓		
	32K			✓		
	64K			✓		
	256			✓		
1280X1024	256			✓		
1600X1200	256			✓		

Test Results:

Test Item	Pass	Fail	Note
Installation From CD/ROM			
Install to IDE HDD	✓		Testing CPU: Pentium III 550
SCSI HDD with AHA-1542 <input type="checkbox"/> CP <input type="checkbox"/> CF			Testing CPU:
SCSI HDD with AHA- <input type="checkbox"/> 2940UW <input type="checkbox"/> 2940W			Testing CPU:
Boot			
Boot Normal	✓		
Boot Logged (\BOOTLOG.TXT)	✓		
Boot Safe Mode	✓		
Boot Step By Step Confirmation	✓		
Boot Command Prompt Only	✓		
Boot Safe Mode Command Prompt	✓		
Function Test			
Serial Mouse	✓		
FDD Format/Copy/Read/Write	✓		
PS/2 Mouse	✓		
System Clock	✓		
Keyboard Function Test			
Alt+F4 Quit a Program	✓		
Ctrl+Esc Display the Start Menu	✓		
Alt+Tab Switch To Last Windows	✓		
Ctrl+Alt+Del Close Program	✓		
F8 Start up Boot Up Menu	✓		

F4 Boot Up from Previous	✓		
Shutdown			
Shutdown the Computer	✓		
Shutdown Restart	✓		
Shutdown to MS-DOS Mode	✓		
Close all Prog. & Login Other User	✓		

E-1.Microsoft Windows 98 Hardware Compatibility Test(HCT)**System Information:**

DRAM/SDRAM Capacity & BRAND(SIMM Qty)	Brand: D45128841G5-A10-9JF <input type="checkbox"/> 8 <input type="checkbox"/> 16 <input type="checkbox"/> 32 <input type="checkbox"/> 64 <input checked="" type="checkbox"/> 256MB <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> SDRAM <input type="checkbox"/> SODIMM <input type="checkbox"/> Qty: <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4
Cache Memory Capacity & Brand	Brand: <input type="checkbox"/> 60ns <input type="checkbox"/> 70ns <input type="checkbox"/> ns <input type="checkbox"/> PB <input type="checkbox"/> 128K <input type="checkbox"/> 256K <input type="checkbox"/> 512K <input type="checkbox"/>
System BIOS Version	<input checked="" type="checkbox"/> AWARD <input type="checkbox"/> AMI Ver: V 4.51
VGA Card & BIOS	<input checked="" type="checkbox"/> OnBoard C&T 69000 <input type="checkbox"/> BIOS:
VGA Memory Capacity & Brand	Brand: <input type="checkbox"/> 60ns <input type="checkbox"/> 70ns <input type="checkbox"/> ns <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> VRAM <input type="checkbox"/> 256K <input type="checkbox"/> 512K <input type="checkbox"/> 1M <input checked="" type="checkbox"/> 2M <input type="checkbox"/> 4M <input type="checkbox"/>
CPU Type	Pentium III 550
HDD Type	<input checked="" type="checkbox"/> IBM <input type="checkbox"/> Sea <input type="checkbox"/> Con <input type="checkbox"/> Qua <input type="checkbox"/> Fuj : DPTA-372050
CD-ROM Type	<input type="checkbox"/> NEC <input type="checkbox"/> Panasonic <input type="checkbox"/> Pioneer <input checked="" type="checkbox"/> GENUNE :50X
Keyboard TYPE	ACER 6511-TW1C/B
FDD TYPE	Panasonic JU-257A606P
Mouse	PS/2 mouse
LAN CARD	OnBoard Intell 82559er
Driver or Utility	<input checked="" type="checkbox"/> VGA <input type="checkbox"/> HDD <input checked="" type="checkbox"/> Others :LAN 82559er

Test Result:

HCT 7.6 Features Test	Pass	Fail	Remark
Virtual Dos Mach	✓		
DMPS Test	✓		
Video Playback	✓		
Extended BIOS Parameter Block	✓		
MCI CD Test	✓		
BCT API Test	✓		
INT 13 Extension	✓		
Disk(Stress) Individual Drive	✓		
Disk -CD (Stress)	✓		
Disk (Stress)	✓		
Coprocessor(Stress)	✓		
Net Class Dynamic	✓		
PCI I/O Space	✓		
PCI 2.1 (BIOS)	✓		
PCI 2.1 (Card)		✓	
Unreported I/O	✓		
Unreported Memory	✓		
PnP BIOS	✓		
APM 1.2	✓		
Media Class Dynamic Config	✓		
Wave Drift	✓		

F. O.S. Compatibility-Windows NT R4.0**System Information:**

DRAM/SDRAM Capacity & BRAND(SIMM Qty)	Brand: HY57V1291620 LTC-10S <input type="checkbox"/> 8 <input type="checkbox"/> 16 <input type="checkbox"/> 32 <input checked="" type="checkbox"/> 64 <input type="checkbox"/> 128MB <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> SDRAM <input type="checkbox"/> SODIMM <input type="checkbox"/> Qty: <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4
Cache Memory Capacity & Brand	Brand: <input type="checkbox"/> 60ns <input type="checkbox"/> 70ns <input type="checkbox"/> ns <input type="checkbox"/> PB <input type="checkbox"/> 128K <input type="checkbox"/> 256K <input type="checkbox"/> 512K <input type="checkbox"/>
System BIOS Version	<input checked="" type="checkbox"/> AWARD <input type="checkbox"/> AMI Ver: V 4.51
VGA Card & BIOS	<input checked="" type="checkbox"/> OnBoard C&T 69000 <input type="checkbox"/> BIOS:
VGA Memory Capacity & Brand	Brand: <input type="checkbox"/> 60ns <input type="checkbox"/> 70ns <input type="checkbox"/> ns <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> VRAM <input type="checkbox"/> 256K <input type="checkbox"/> 512K <input type="checkbox"/> 1M <input checked="" type="checkbox"/> 2M <input type="checkbox"/> 4M <input type="checkbox"/>
CPU Type	Celeron 400Hz
HDD Type	<input checked="" type="checkbox"/> IBM <input type="checkbox"/> Sea <input type="checkbox"/> Con <input type="checkbox"/> Qua <input type="checkbox"/> Fuj : DPTA-372050
CD-ROM Type	<input type="checkbox"/> NEC <input type="checkbox"/> Panasonic <input type="checkbox"/> Pioneer <input checked="" type="checkbox"/> GENUNE :50X
Driver or Utility	<input checked="" type="checkbox"/> VGA <input type="checkbox"/> HDD <input type="checkbox"/> Others :

VGA Driver Testing:

Resolution	Color	SF	LF	Pass	Fail	Note
640X480	256			✓		
	32K			✓		
	64K			✓		
	16.7M			✓		
800X600	256			✓		
	32K			✓		
	64K			✓		
1024X768	32K			✓		
	64K			✓		
	256			✓		
1280X1024	256			✓		
1600X1200	256			✓		

Test Results:

Test Item	Pass	Fail	Note
Installation From CD-ROM			
Install to IDE HDD	✓		Testing CPU: Celeron 400Hz
SCSI HDD with AHA-1542 <input type="checkbox"/> CP <input type="checkbox"/> CF			Testing CPU:
SCSI HDD with AHA- <input type="checkbox"/> 2940UW <input type="checkbox"/> 2940W			Testing CPU:
SCSI HDD			
SCSI CD-ROM Drive			
Boot			
Boot to Windows NT	✓		
Boot to MS-DOS	✓		
Shutdown	✓		
Shutdown & Restart	✓		
CPU/Memory/File System			
Memory size less than 64MB	✓		
Memory size Larger than 64MB	✓		
Virtual memory	✓		
System tasking settings	✓		
FAT	✓		
Nwtwork	✓		
System clock	✓		
Task switching	✓		

Function Test			
Serial Mouse	✓		
FDD Format/Copy/Read/Write	✓		
PS/2 Mouse	✓		
System Clock	✓		
Keyboard Function Test			
CapLock,NumLock,ScrLock	✓		
Ctrl+Alt+Del	✓		
Ctrl+Esc,Alt+Tab/Esc/Space	✓		
Alt+Tab,Alt+Esc,Alt+Space	✓		
Ctrl+Alt+Pause/Print Screen	✓		
Ctrl+Alt+F1~F12	✓		
COM Port			
Serial Mouse	✓		
Security/Audit/Control			
User manager	✓		
Server manager	✓		
Disk administrator	✓		
Performance monitor	✓		
User profile editor	✓		
Event Viewer	✓		
Windows NT Diagnostics	✓		

G. O.S. Compatibility-DOS and DOS Utility Compatibility Testing

System Information:

DRAM/SDRAM Capacity & BRAND(SIMM Qty)	Brand: HY57V168010D TC-10S <input type="checkbox"/> 8 <input type="checkbox"/> 16 <input checked="" type="checkbox"/> 32 <input type="checkbox"/> 64 <input type="checkbox"/> 128MB <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> SDRAM <input type="checkbox"/> SODIMM <input type="checkbox"/> Qty: <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4
Cache Memory Capacity & Brand	Brand: <input type="checkbox"/> 60ns <input type="checkbox"/> 70ns <input type="checkbox"/> ns <input type="checkbox"/> PB <input type="checkbox"/> 128K <input type="checkbox"/> 256K <input type="checkbox"/> 512K <input type="checkbox"/>
System BIOS Version	<input checked="" type="checkbox"/> AWARD <input type="checkbox"/> AMI Ver: V 4.51
VGA Card & BIOS	<input checked="" type="checkbox"/> OnBoard C&T 69000 <input type="checkbox"/> BIOS:
VGA Memory Capacity & Brand	Brand: <input type="checkbox"/> 60ns <input type="checkbox"/> 70ns <input type="checkbox"/> ns <input type="checkbox"/> DRAM <input checked="" type="checkbox"/> VRAM <input type="checkbox"/> 256K <input type="checkbox"/> 512K <input type="checkbox"/> 1M <input checked="" type="checkbox"/> 2M <input type="checkbox"/> 4M <input type="checkbox"/>
CPU Type	Celeron 300MHz
HDD Type	<input checked="" type="checkbox"/> Qua <input type="checkbox"/> Sea <input type="checkbox"/> Con <input type="checkbox"/> Max <input type="checkbox"/> Fuj : TX4000AT
CD-ROM Type	<input type="checkbox"/> NEC <input type="checkbox"/> Panasonic <input type="checkbox"/> Pioneer <input checked="" type="checkbox"/> GENUNE :50X
Driver or Utility	<input checked="" type="checkbox"/> VGA <input type="checkbox"/> HDD <input type="checkbox"/> Others :

Test Results:

Test Item	Pass	Fail	Note
Installation From FDD			
Install to IDE HDD	✓		Testing CPU: Celeron 300Hz
SCSI HDD with AHA-1542 <input type="checkbox"/> CP <input type="checkbox"/> CF Card			Testing CPU:
SCSI HDD with AHA- <input type="checkbox"/> 2940UW <input type="checkbox"/> 2940W			Testing CPU:
Function Test			
Sysinfo Check (Before DOS Initialed)	✓		
System Clock(Compare to RTC CLK)	✓		
DOS Prompt	✓		
FDD Format/Copy/Read/Write	✓		
Serial Mouse	✓		
DOS Commander			
MSD.COM	✓		
EDIT.COM	✓		
EMM386.EXE	✓		
HIMEN.SYS	✓		
Norton Commander			
Key F1~F10 Function	✓		
Key Alt+F1~F10 Function	✓		
Key Ctrl+F1~F10 Function	✓		
ET Ver3.53			
Installation Testing	✓		
16 Font Mode	✓		
24 Font Mode	✓		
Key: Ctrl+Esc Function	✓		
Sethrc Function	✓		