



FCC CFR47 PART 15 DIGITAL DEVICE

TEST REPORT

FOR

Industrial PC

MODEL: SBC-659 (N)

REPORT NUMBER: 01E9417

ISSUE DATE: May 4, 2001

Prepared for

**AAEON TECHNOLOGY INC.
5F, NO. 135, LANE 235, PAO CHIAO RD.,
HSIN-TIEN CITY, TAIPEI, TAIWAN, R. O. C.**

Prepared by

**COMPLIANCE ENGINEERING SERVICES, INC.
No. 199, CHUNG SHENG ROAD
HSIN TIEN CITY, TAIPEI, TAIWAN R.O.C.
TEL: (02) 2217-0894
FAX: (02) 2217-1254**

NVLAP[®]

LAB CODE: SL2-IN-E-0005



**FCC, VCCI, CISPR, CE
UL, CSA, TÜV, VDE**

**U.S.A. : P.O.BOX 612650, SAN JOSE, CA 95161-2650
TAIPEI : P.O.BOX 17-82, HSIN TIEN, TAIWAN, R.O.C.**

TABLE OF CONTENTS	PAGE
1. VERIFICATION OF COMPLIANCE.....	1
2. PRODUCT DESCRIPTION.....	2
3. TESTED SYSTEM DETAILS.....	2
4. TEST FACILITY.....	3
5. ACCREDITATION AND LISTING.....	3
6. MEASUREMENT INSTRUMENTATION.....	4
7. MEASURING INSTRUMENT CALIBRATION.....	4
8. UNITS OF MEASUREMENT.....	4
9. ANTENNAS.....	5
10. CLASSIFICATION OF DIGITAL DEVICE.....	5
11. RADIATED EMISSION LIMITS.....	5
12. CONDUCTED EMISSION LIMITS.....	6
13. CONDUCTED EMISSION TEST PROCEDURE.....	6
14. RADIATED EMISSION TEST PROCEDURE.....	7
15. AMBIENT CONDITIONS.....	7
16. SYSTEM TEST CONFIGURATION.....	8
17. EQUIPMENT MODIFICATIONS.....	8
18. EUT SETUP PHOTOS.....	9
19. TEST EQUIPMENT LIST.....	11
20. CORRECTION FACTOR.....	12
21. TEST RESULT SUMMARY.....	14
APPENDICES	16
.EXTERNAL I/O CABLE CONSTRUCTION DESCRIPTION	
.CONFIGURATION BLOCK DIAGRAM	
.CONDUCTED EMISSION PLOT	
.RADIATED EMISSION DATA	

1. VERIFICATION OF COMPLIANCE



COMPANY NAME: AAEON TECHNOLOGY INC.
5F, NO. 135, LANE 235, PAO CHIAO RD.,
HSIN-TIEN CITY, TAIPEI, TAIWAN, R. O. C.

CONTACT PERSON: MILO WANG / ENGINEER

TELEPHONE NO: +886-2-8919-1234

MODEL NO/NAME: SBC-659 (N)

SERIAL NO: N/A

DATE TESTED: April 27, 2001

TYPE OF EQUIPMENT:	INFORMATION TECHNOLOGY EQUIPMENT (ITE)
MEASUREMENT DISTANCE:	() 3 METER (x) 10 METER
TECHNICAL LIMIT:	CLASS A
FCC RULES:	PART 15
MEASUREMENT PROCEDURE	ANSI C63.4:92 / EN55022
EQUIPMENT AUTHORIZATION PROCEDURE	VERIFICATION
MODIFICATION MADE ON EUT	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
DEVIATIONS FROM MEASUREMENT PROCEDURE	<input type="checkbox"/> YES (refer to section 21 for comments) <input checked="" type="checkbox"/> NO
RADIATED EMISSION TEST RESULT	-2.05 dB @ 166.171MHz / HORIZONTAL
CONDUCTED EMISSION TEST RESULT	-27.29 dB @ 0.150MHz / L1

The above equipment was tested by Compliance Engineering Services, Inc. for compliance with the requirements set forth in the FCC CFR 47, PART 15. The results of testing in this report apply to the product/system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved By

Acknowledged By


RICK YEO / EMC MANAGER
COMPLIANCE ENGINEERING SERVICES

MILO WANG / ENGINEER
AAEON TECHNOLOGY INC.

2. PRODUCT DESCRIPTION

CHASSIS TYPE	METAL
LIST OF EACH OSC. OR XTAL. FREQ. (FREQ.>=1 MHz)	Y1=25MHz; Y2=14.318MHz Y3=25MHz; Y5=14.318MHz
CPU SPEEDS TESTED	PENTIUM-III 933MHz (133MHz X 7)
POWER REQUIREMENTS	INPUT: 100-127V; 5A; 60Hz OUTPUT: 3.3/5/12V
POWER SUPPLY/NAME/MODEL/S.N.	ENHANCE / ENP-1815

3. TESTED SYSTEM DETAILS

The Model names for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

Host Computer (EUT)

Device Type	Manufacturer	Model Number	Serial Number	FCC ID / DoC
HDD	QUANTUM	FIREBALL	N/A	N/A
USB CARD	N/A	N/A	N/A	N/A
USB + AUDIO CARD	N/A	PCM-3533	1907353300	N/A
RAM	NEC	SD-64M	N/A	N/A
MAIN-BOARD	UNIC	94V-0	N/A	N/A
CPU	INTEL	PENTIUM-III	N/A	N/A
BACK PLANE	N/A	BP-204SS-P4C	N/A	N/A
CHASSIS	N/A	AEC-204	N/A	N/A

External Peripheral Devices

Device Type	Manufacturer	Model Number	Serial No.	FCC ID / DoC
SPEAKER	SINGVOX	SP-362	N/A	N/A
PLAYER	PANASONIC	RQ-L309GT	N/A	N/A
MICROPHONE	KOKA	DM-510	N/A	N/A
PRINTER	PANASONIC	KX-P1080i	N/A	ACJ5ZL6KX-PI080I
KEYBOARD	CHERRY	MY3000	000659	DoC
USB MOUSE	LOGITECH	M-BB48	LZE93851294	DoC
USB MOUSE	LOGITECH	M-BB48	LZA00354416	DoC
USB MOUSE	LOGITECH	M-BB48	LZA00354333	DoC
PS/2 MOUSE	LOGITECH	M-S34	LZE92901135	DZL211029
MODEM	ACEEX	1414	N/A	IFAXDM1414
MODEM	HAYES	231AA	N/A	DoC
SERVER PC	TOSHIBA	PS253L	31012396J	N/A
MONITOR	SAMSUNG	77BDF	N/A	DoC

4. TEST FACILITY

The open area test sites and conducted measurement facilities used to collect the radiated data are located at No. 199, Chung Sheng Road, Hsin Tien City, Taipei, Taiwan R.O.C. The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

5. ACCREDITATION AND LISTING

The test facilities used to perform radiated and conducted emissions tests are accredited by National Voluntary Laboratory Accreditation Program for the specific scope of accreditation under Lab Code:SL2-IN-E-0005 to perform Electromagnetic Interference tests according to FCC PART 15 AND CISPR 22 requirements. No part of this report may be used to claim or imply product endorsement by BSMI or any agency of the US Government. In addition, the test facilities are listed with Federal Communications Commission (reference no: 31040/SIT(1300F2))

6. MEASUREMENT INSTRUMENTATION

Radiated emissions were measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, ridged waveguide, liner horn. EMI receivers were used for line conducted readings, spectrum analyzers with pre-selectors and quasi-peak detectors were used to perform radiated measurements. Receiving equipment (i.e., receiver, analyzer, quasi-peak adapter, pre-selector) and LISNs conform to CISPR specification for "Radio Interference Measuring Apparatus and Measurement Methods," Publication 16.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

7. MEASURING INSTRUMENT CALIBRATION

The measuring equipment which was utilized in performing the tests documented herein has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment which is traceable to recognized national standards.

8. UNITS OF MEASUREMENT

Measurements of radiated interference are reported in terms of dB(uV/m) at a specified distance. The indicated readings on the spectrum analyzer were converted to dB(uV/m) by use of appropriate conversion factors. Measurements of conducted interference are reported in terms of dB(uV).

The field strength is calculated by adding the Antenna Factor and Cable Factors, then by subtracting the Amplifier Gain from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG$$

Where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

AG = Amplifier Gain

Assume a receiver reading of 52.5 dBuV is obtained. The Antenna Factor of 7.4dB/m and a Cable Factor of 1.1dB is added. The Amplifier Gain of 29 dB is subtracted, giving a field strength of 32 dBuV/m. The 32 dBuV/m value was mathematically converted to its corresponding level in uV/m.

$$FS = 52.5 + 7.4 + 1.1 - 29 = 32 \text{ dBuV/m}$$

$$\text{Level in uV/m} = \text{Common Antilogarithm} [(32 \text{ dBuV/m})/20] = 39.8 \text{ uV/m}$$

9. ANTENNAS

The calibrated antennas used to sample the radiated field strength are mounted on a non-conductive, motorized antenna mast 10 meters from the leading edge of the turn table.

10. CLASSIFICATION OF DIGITAL DEVICE

Class A includes digital devices that are marketed for use in commercial, industrial or business environments, excluding devices which are marketed for use by the general public or are intended to be used in the home.

Class B includes digital devices that are marketed for use in residential environments, notwithstanding use in commercial, business and industrial environments.

Note: The responsible party may also qualify a device intended to be marketed in a commercial, business or industrial environment as Class B device, and in fact is encouraged to do so provided the device complies with the technical specifications for a Class B digital device. In the event that a particular type of device has been found to repeatedly cause harmful interference to radio communications, the Commission may classify such a digital device as a Class B digital device, regardless of its intended use.

11. RADIATED EMISSION LIMITS

FCC PART 15 CLASS B

MEASURING DISTANCE OF 3 METER		
FREQUENCY RANGE (MHz)	FIELD STRENGTH (Microvolts/m)	FIELD STRENGTH (dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

FCC CLASS B ALTERNATIVE DISTANCE (CISPR 22:1993)

MEASURING DISTANCE OF 10 METER		
FREQUENCY RANGE (MHz)	FIELD STRENGTH (Microvolts/m)	FIELD STRENGTH (dBuV/m)
30-88	30	29.5
88-216	45	33.0
216-960	60	35.6
960-1000	150	43.5
ABOVE 1000	150	43.5

Note: Limits extrapolated 20dB/decade

FCC PART 15 CLASS A

MEASURING DISTANCE OF 10 METER		
FREQUENCY RANGE (MHz)	FIELD STRENGTH (Microvolts/m)	FIELD STRENGTH (dBuV/m)
30-88	90	39.1
88-216	150	43.5
216-960	210	46.4
Above 960	300	49.5

12. CONDUCTED EMISSION LIMITS

CLASS B

FREQUENCY RANGE	FIELD STRENGTH (Microvolts)	FIELD STRENGTH (dBuV)
450kHz-30MHz	250	48

CLASS A

FREQUENCY RANGE	FIELD STRENGTH (Microvolts)	FIELD STRENGTH (dBuV)
450kHz-1.705MHz	1000	60
1.705MHz - 30MHz	3000	69.54

13. CONDUCTED EMISSION TEST PROCEDURE

The EUT is located so that the distance between the boundary of the EUT and the closest surface to the LISN is 0.8m.

EUT test configuration is according to Section 7 of ANSI C63.4/1992.

Conducted disturbance shall be measured between the phase lead and the ground, and between the neutral lead and the ground. The frequency 0.450 - 30 MHz shall be investigated.

Set the EMI receiver to PEAK detector setting and sweep continuously over the frequency range to be investigated. Set resolution bandwidth to 9kHz minimum. Connect EMI receiver input cable to LINE 1 RF measurement connection on the LISN. Connect a 50ohm terminator to the unused RF connection on the LISN. For each mode of EUT operation, maximize emissions readings by manipulating cable and wire positions. Record the configuration for each EUT power cord which produces emissions closest to the limit. Repeat the same procedure for LINE 2 of each EUT power cord.

14. RADIATED EMISSION TEST PROCEDURE

The EUT and all other support equipment are placed on a wooden table 80 cm above the ground screen. Antenna to EUT distance is either 3 meters or 10 meters (Class B or Class A). During the test, the table is rotated 360 degrees to maximize emissions, and the antenna is positioned from 1 to 4 meters above the ground screen to further maximize emissions. The antenna is polarized in both vertical and horizontal positions.

EUT test configuration is according to Section 8 of ANSI C63.4/1992.

Monitor the frequency range of interest at a fixed antenna height and EUT azimuth. Frequency span should be small enough to easily differentiate between broadcast stations and intermittent ambients. Rotate EUT 360 degrees to maximize emissions received from EUT. If emission increases by more than 1 dB, or if another emission appears that is greater by 1 dB, return to azimuth where maximum occurred and perform additional cable manipulation to further maximize received emission.

Move antenna up and down to further maximize suspected highest amplitude signal. If emission increased by 1 dB or more, or if another emission appears that is greater by 1dB or more, return to antenna height where maximum signal was observed and manipulate cables to produce highest emissions, noting frequency and amplitude.

15. AMBIENT CONDITIONS

The ambient conditions at the time of final tests were as follows:

	Radiated Emission	Conducted Emission
Temperature	22 °C	21 °C
Humidity	85 %	84 %

16. SYSTEM TEST CONFIGURATION

The equipment under test was configured and operated in a manner which tended to maximize its emission characteristics in a typical application. Power and signal distribution, ground, interconnecting cabling and physical placement of equipment simulated the typical application and usage insofar as practicable.


SOFTWARE USED DURING THE TESTS	
Operating System	WINDOWS 98
File Name	EMITEST.EXE
Program Sequence	1. WINDOWS 98 BOOTS SYSTEM. 2. RUN EMITEST.EXE TO ACTIVATE ALL PERIPHERALS AND DISPLAY "H" PATTERN ON MONITOR SCREEN.

17. EQUIPMENT MODIFICATIONS


To achieve compliance to CLASS A levels, the following change(s) were made during compliance testing:

NOT APPLICABLE

18. EUT SETUP PHOTOS



Radiated Emission Setup Photos (Worst Emission Position)



Conducted Emission Setup Photos (Worst Emission Position)

19. TEST EQUIPMENT LIST

Equipment	Manuf.	Model No.	Serial No.	Site	Cal Date	Due Date
EMI TEST DISPLAY	ROHDE & SCHWARZ	DSAI-D 804.8932.52	827832/001	D	11/00	11/01
EMI TEST RF UNIT	ROHDE & SCHWARZ	ESBI-RF/1005.4300.52	827832/003	D	11/00	11/01
AMPLIFIER	T.E.C.	PA-102	43685	D	05/00	05/01
ANTENNA	EMCO	3142	1310	D	06/00	06/01
LISN	FISHER CUSTOM	FCC-LISN-50/250-25-2	107	D	07/00	07/01
LISN(EUT)	EMCO	3825/2	1435	D	01/01	01/02
CABLE	TIME MICROWAVE	LMR-400	N-TYPE02	D	12/00	12/01
SPECTRUM ANALYZER	H.P.	8566B	2937A06102	E	12/00	12/01
SPECTRUM DISPLAY	H.P.	85662A	2848A18276	E	12/00	12/01
QUASI-PEAK DETECTOR	H.P.	85650A	2811A01439	E	12/00	12/01
AMPLIFIER	H.P.	8447D B	1644A02328	E	05/00	05/01
ANTENNA	EMCO	3142	1212	E	09/00	09/01
TEST RECEIVER	ROHDE & SCHWARZ	ESHS20	840455/006	E	03/01	03/02
LISN	SOLAR	8012-50-R-24-BNC	8305114	E	07/00	07/01
LISN(EUT)	EMCO	3825/2	1842	E	01/01	01/02
CABLE	TIME MICROWAVE	LMR-400	N-TYPE01	E	12/00	12/01
ANTENNA (1-18GHz)	EMCO	3115	5761	D/E	02/01	02/02
AMPLIFIER (1-26GHz)	MITEQ	NSP2600-44	646455	D/E	02/01	02/02
CABLE (1-26.5G)	FLEXCO	FC195	N/A	D/E	02/01	02/02

20. CORRECTION FACTOR

OATS NO. E

FREQ (MHZ)	ANTENNA 3 METER			ANTENNA 10 METER			SITE E
	HORI.	VERT.	CABLE LOSS (dB)	HORI.	VERT.	CABLE LOSS (dB)	AMP GAIN (dB)
30	19.01	19.01	0.92	17.9	17.9	0.92	27.41
35	15.92	15.92	0.94	14.6	14.6	0.94	27.42
40	12.70	12.70	1.04	12.0	12.0	1.04	27.36
45	10.20	10.20	1.06	9.9	9.9	1.06	27.36
50	8.70	8.70	1.08	8.5	8.5	1.08	27.39
60	7.20	7.20	1.15	7.4	7.4	1.15	27.36
70	6.95	6.95	1.22	5.9	5.9	1.22	27.34
80	7.63	7.63	1.31	4.6	4.6	1.31	27.34
90	8.52	8.52	1.45	5.8	5.8	1.45	27.28
100	9.05	9.05	1.50	8.5	8.5	1.50	27.42
120	7.65	7.65	1.69	7.3	7.3	1.69	27.26
125	7.70	7.70	1.70	6.9	6.9	1.70	27.31
140	8.32	8.32	1.82	6.9	6.9	1.82	27.21
150	9.21	9.21	1.84	8.6	8.6	1.84	27.24
160	9.65	9.65	1.92	9.9	9.9	1.92	27.08
175	9.86	9.86	2.02	11.1	11.1	2.02	27.00
180	10.10	10.10	2.04	11.3	11.3	2.04	27.04
200	10.30	10.30	2.22	11.0	11.0	2.22	26.93
250	12.85	12.85	2.51	12.3	12.3	2.51	26.94
300	14.10	14.10	2.72	13.1	13.1	2.72	26.85
400	16.55	16.55	3.29	15.5	15.5	3.29	27.26
500	18.75	18.75	3.85	18.1	18.1	3.85	27.34
600	20.85	20.85	4.32	20.4	20.4	4.32	27.23
700	22.86	22.86	4.73	21.6	21.6	4.73	26.83
800	23.10	23.10	5.10	21.9	21.9	5.10	26.58
900	24.31	24.31	5.58	23.2	23.2	5.58	26.55
1000	25.01	25.01	5.74	23.9	23.9	5.74	26.85
1100	25.64	25.64		25.0	25.0		27.82
1200	26.56	26.56		26.3	26.3		27.70
1300	26.75	26.75		26.3	26.3		
1400	27.85	27.85		27.4	27.4		
1500	28.12	28.12		27.6	27.6		
1600	29.25	29.25		28.7	28.7		
1700	29.75	29.75		28.3	28.3		
1800	29.90	29.90		29.7	29.7		
1900	29.95	29.95		29.0	29.0		
2000	31.52	31.52		30.8	30.8		

FREQ (MHZ)	ANTENNA 1 METER			ANTENNA 3 METER			AMP GAIN (dB)
	HORI. (dB)	VERT. (dB)	CABLE LOSS (dB)	HORI. (dB)	VERT. (dB)	CABLE LOSS (dB)	
1000	24.20	24.20	2.50	24.10	24.10	2.50	38.00
1500	25.70	25.70	3.00	25.40	25.40	3.00	38.00
2000	27.70	27.70	3.60	27.30	27.30	3.60	37.90
2500	28.80	28.80	4.00	28.40	28.40	4.00	37.70
3000	30.80	30.80	4.50	30.20	30.20	4.50	36.80
3500	31.90	31.90	4.70	31.20	31.20	4.70	36.90
4000	33.20	33.20	5.20	32.70	32.70	5.20	36.70
4500	33.00	33.00	5.50	32.40	32.40	5.50	36.50
5000	34.30	34.30	5.90	33.50	33.50	5.90	36.60
5500	34.80	34.80	6.20	34.20	34.20	6.20	36.80
6000	35.10	35.10	6.70	34.40	34.40	6.70	36.90
6500	35.30	35.30	7.00	34.40	34.40	7.00	36.90
7000	36.30	36.30	7.20	35.40	35.40	7.20	36.60
7500	37.50	37.50	7.60	36.70	36.70	7.60	36.00
8000	38.00	38.00	7.80	37.20	37.20	7.80	35.70
8500	38.60	38.60	8.10	37.90	37.90	8.10	36.00
9000	38.70	38.70	8.30	38.20	38.20	8.30	35.00
9500	38.20	38.20	8.70	37.70	37.70	8.70	33.90
10000	38.60	38.60	8.90	37.90	37.90	8.90	33.40
10500	38.60	38.60	9.00	38.00	38.00	9.00	33.70
11000	38.90	38.90	9.40	38.30	38.30	9.40	34.10
11500	39.30	39.30	9.70	38.70	38.70	9.70	34.30
12000	39.20	39.20	9.80	39.20	39.20	9.80	34.20
12500	39.30	39.30	10.10	38.90	38.90	10.10	34.80
13000	40.10	40.10	10.40	39.30	39.30	10.40	34.40
13500	41.20	41.20	10.80	40.50	40.50	10.80	36.20
14000	42.20	42.20	11.00	41.90	41.90	11.00	36.40
14500	41.40	41.40	11.10	42.30	42.30	11.10	36.50
15000	39.70	39.70	11.50	40.50	40.50	11.50	36.80
15500	38.40	38.40	11.70	38.30	38.30	11.70	37.30
16000	38.30	38.30	11.80	37.80	37.80	11.80	37.50
16500	39.60	39.60	12.00	38.50	38.50	12.00	37.60
17000	42.50	42.50	12.40	41.40	41.40	12.40	37.30
17500	45.60	45.60	12.70	44.00	44.00	12.70	36.60
18000	46.20	46.20	12.80	45.70	45.70	12.80	36.40
19000							
21000							
24000							
26000							

21. TEST RESULT SUMMARY

Preliminary Radiated Emission Tests were performed at the 10 meter open area test site. CCS test procedure no:CCSUE2001B and the procedure listed in ANSI C63.4 /1992 section 8.3.1.1. were used. The following preliminary tests were conducted to determine the worst mode of operation and configuration.

Preliminary Radiated Emission Test			
Frequency Range Investigated		30 MHz TO 5000 MHz	
Mode of operation	Date	Data Report No.	Worst Mode
NORMAL MODE	04/27/01	9417F# (12, 15)	<input checked="" type="checkbox"/>
1-5G	04/27/01	9417F# (22, 30)	<input type="checkbox"/>

Final Radiated Emission Test was conducted by operating the worst mode as indicated above.

OATS No: E / 10 M		Data Report No. 9417F# (12, 15)		Date 04/27/01		Tested By: MICHAEL HUNG	
Six Highest Radiated Emission Readings							
Frequency Range Investigated				30 MHz TO 5000 MHz			
Freq (MHz)	Meter Reading (dBuV)	C.F. (dB/m)	Corrected Reading (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Reading Type P/Q/A	Pol. H/V
166.170	47.20	-11.75	35.45	40.00	-4.55	Q	V
186.830	44.10	-10.68	33.42	40.00	-6.58	P	V
199.997	48.60	-10.69	37.91	40.00	-2.09	Q	V
232.690	50.70	-9.76	40.94	47.00	-6.06	P	V
166.171	49.70	-11.75	37.95	40.00	-2.05	P	H
224.990	43.50	-10.00	33.51	40.00	-6.49	P	H

C.F.(Correction Factor)=Antenna Factor + Cable Loss + Attenuator(6dB)
- Amplifier Gain

Corrected Reading = Metering Reading + C.F.

Margin=Corrected Reading - Limits

P=Peak Reading

H=Horizontal Polarization/Antenna

Q=Quasi-peak

V=Vertical Polarization/Antenna

A=Average Reading

Comments: **N/A**

Preliminary Conducted Emission Tests were performed according to CCS test procedure no:CCSUE2002B and ANSI C63.4/1992 section 7.2.3. The following preliminary tests were conducted to determine the worst mode of operation.

Preliminary Conducted Emission Test			
Frequency Range Investigated		150 kHz TO 30 MHz	
Mode of operation	Date	Data Report No.	Worst Mode
NORMAL MODE	04/27/01	9417E# (8, 16)	<input checked="" type="checkbox"/>

Final Conducted Emission Test was conducted by operating the worst mode as indicated above.

Conducted Room	Data Report No. 9417E# (8, 16)		Date 04/27/01		Tested By: MICHAEL HUNG		
Six Highest Conducted Emission Readings							
Frequency Range Investigated				150 kHz TO 30 MHz			
Freq (MHz)	Meter Reading (dBuV)	C.F. (dB)	Corrected Reading (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Reading Type (P/Q/A)	Line (L1/L2)
0.150	51.68	0.03	51.71	79.00	-27.29	P	L1
0.263	45.88	0.05	45.93	79.00	-33.07	P	L1
7.852	38.91	0.25	39.16	73.00	-33.84	P	L1
7.935	39.99	0.25	40.25	73.00	-32.75	P	L1
0.150	48.89	0.03	48.92	79.00	-30.08	P	L2
20.056	38.10	0.48	38.58	73.00	-34.42	P	L2

C.F.(Correction Factor)=Insertion Loss + Cable Loss

Corrected Reading = Metering Reading + C.F.

Margin=Corrected Reading - Limits

P=Peak Reading

L1=Hot

Q=Quasi-peak

L2=Neutral

A=Average Reading

Comments: **N/A**

APPENDICES

EXTERNAL I/O CABLE CONSTRUCTION DESCRIPTION

CONFIGURATION BLOCK DIAGRAM

CONDUCTED EMISSION PLOT

RADIATED EMISSION DATA

External I/O Cable Construction Description

NO: 1	CABLE Name: 9	Number of I/O ports of this type: 1
I/O Port: PS/2 MOUSE		Type of Cable used: Un-Shielded
Cable Connector Type: Molded		Data Traffic Generated: Yes
Bundled During Tests: No		Cable Length: 1.8 M
Remarks: N/A		

NO: 2~4	CABLE Name: 7, 5, 69	Number of I/O ports of this type: 3
I/O Port: USB MOUSE		Type of Cable used: Un-Shielded
Cable Connector Type: Molded		Data Traffic Generated: Yes
Bundled During Tests: No		Cable Length: 1.8 M
Remarks: N/A		

NO: 5	CABLE Name: 13	Number of I/O ports of this type: 1
I/O Port: USB KEYBOARD		Type of Cable used: Shielded
Cable Connector Type: Molded		Data Traffic Generated: Yes
Bundled During Tests: No		Cable Length: 1.8 M
Remarks: N/A		

NO: 6	CABLE Name: 27	Number of I/O ports of this type: 1
I/O Port: MICROPHONE		Type of Cable used: Un-Shielded
Cable Connector Type: Molded		Data Traffic Generated: Yes
Bundled During Tests: Yes		Cable Length: 2.8 M
Remarks: N/A		

NO: 7	CABLE Name: 24	Number of I/O ports of this type: 1
I/O Port: PLAYER		Type of Cable used: Un-Shielded
Cable Connector Type: Molded		Data Traffic Generated: Yes
Bundled During Tests: No		Cable Length: 1.5 M
Remarks: N/A		

NO: 8	CABLE Name: 42	Number of I/O ports of this type: 1
I/O Port: SPEAKER		Type of Cable used: Un-Shielded
Cable Connector Type: Molded		Data Traffic Generated: Yes
Bundled During Tests: No		Cable Length: 1.1 M
Remarks: N/A		

NO: 9	CABLE Name: 50	Number of I/O ports of this type: 1
I/O Port: SERIAL MODEM		Type of Cable used: Shielded
Cable Connector Type: Metal		Data Traffic Generated: Yes
Bundled During Tests: Yes		Cable Length: 1.4 M
Remarks: N/A		

NO: 10	CABLE Name: N/A	Number of I/O ports of this type: 1
I/O Port: SERIAL MODEM		Type of Cable used: Shielded
Cable Connector Type: Metal		Data Traffic Generated: Yes
Bundled During Tests: No		Cable Length: 1 M
Remarks: N/A		


NO: 11	CABLE Name: N/A	Number of I/O ports of this type: 1
I/O Port: MONITOR		Type of Cable used: Shielded
Cable Connector Type: Molded		Data Traffic Generated: Yes
Bundled During Tests: Yes		Cable Length: 1.5 M
Remarks: A Ferrite bead on the cable of EUT end		

NO: 12	CABLE Name: 60	Number of I/O ports of this type: 1
I/O Port: PARALLEL PRINTER		Type of Cable used: Shielded
Cable Connector Type: Molded		Data Traffic Generated: Yes
Bundled During Tests: Yes		Cable Length: 1.9 M
Remarks: N/A		

NO: 13~17	CABLE Name: N/A	Number of I/O ports of this type: 5
I/O Port: AC Power Cord		Type of Cable used: Un-Shielded
Cable Connector Type: Molded		Cable Length: 1.8 M
Bundled During Tests: No (Radiation), Yes (Line Conduction)		
Remarks: N/A		


NO: 18, 19	CABLE Name: N/A	Number of I/O ports of this type: 2
I/O Port: LAN CABLE / CABLE LOAD		Type of Cable used: Un-Shielded
Cable Connector Type: Molded		Cable Length: 30/1 M
Bundled During Tests: 18: NO, 19: YES		
Remarks: N/A		

Configuration Block Diagram



Data#: 8 File#: 9417e.emi

Date: 04-27-2001 Time: 21:29:48



(CCS E-Site)


Trace: 7

Ref Trace:

Condition: LINE
 Report No. : 01E9417
 Test Engr. : MICHAEL HUNG
 Company : AAEON TECHNOLOGY INC.
 EUT : SBC-659 (N)
 Test Config : EUT/ALL PERIPHERALS
 Type of Test: EN55022 CLASS A
 Mode of Op. : INTEL P-III 933MHZ/133MHZ

Data#: 16 File#: 9417e.emi

Date: 04-27-2001 Time: 21:37:14



(CCS E-Site)

Trace: 15

Ref Trace:

Condition: NEUTRAL
Report No. : 01E9417
Test Engr. : MICHAEL HUNG
Company : AAEON TECHNOLOGY INC.
EUT : SBC-659 (N)
Test Config : EUT/ALL PERIPHERALS
Type of Test: EN55022 CLASS A
Mode of Op. : INTEL P-III 933MHZ/133MHZ

Data#: 12 File#: 9417f.emi
CCS E-Site

Date: 2001-4-27 Time: 22:52:38

Condition: VERTICAL
Report No. : 01E9417
Test Engr. : MICHAEL HUNG
Company : AAEON TECHNOLOGY INC.
EUT : SBC-659 (N)
Test Config : EUT/ALL PERIPHERALS
Type of Test: EN55022 CLASS A
Mode of Op. : INTEL P-III
: CPU=933MHZ/133MHZ

Page: 1

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1	30.460	36.50	-5.59	30.91	40.00	-9.09	Peak
2	37.600	39.80	-9.48	30.32	40.00	-9.68	Peak
3	49.550	44.20	-14.81	29.39	40.00	-10.61	Peak
4	61.260	43.00	-16.11	26.89	40.00	-13.11	Peak
5	77.680	49.70	-18.31	31.39	40.00	-8.61	Peak
6	110.590	43.30	-14.82	28.48	40.00	-11.52	Peak
7	132.944	43.10	-15.62	27.48	40.00	-12.52	Peak
8	150.020	47.10	-13.80	33.30	40.00	-6.70	Peak
9	166.170	47.20	-11.75	35.45	40.00	-4.55	QP
10	176.940	42.20	-10.84	31.36	40.00	-8.64	Peak
11	186.570	42.20	-10.68	31.52	40.00	-8.48	Peak
12	186.830	44.10	-10.68	33.42	40.00	-6.58	Peak
13	199.997	48.60	-10.69	37.91	40.00	-2.09	QP
14	211.290	43.50	-10.38	33.12	40.00	-6.88	Peak
15	232.690	50.70	-9.76	40.94	47.00	-6.06	Peak
16	249.990	45.90	-9.16	36.74	47.00	-10.26	Peak
17	287.510	40.80	-8.31	32.49	47.00	-14.51	Peak
18	300.000	46.40	-8.03	38.37	47.00	-8.63	Peak
19	325.060	37.10	-7.27	29.83	47.00	-17.17	Peak
20	332.340	42.00	-7.09	34.91	47.00	-12.09	Peak
21	350.100	41.90	-6.63	35.27	47.00	-11.73	Peak
22	399.997	32.90	-5.47	27.43	47.00	-19.57	Peak
23	498.527	39.30	-2.45	36.85	47.00	-10.15	Peak
24	565.006	37.70	-0.46	37.24	47.00	-9.76	Peak
25	664.718	35.00	1.86	36.86	47.00	-10.14	Peak
26	764.430	33.70	3.23	36.93	47.00	-10.07	Peak

Data#: 15 File#: 9417f.emi
CCS E-Site

Date: 2001-4-27 Time: 23:28:21

Condition: HORIZONTAL
Report No. : 01E9417
Test Engr. : MICHAEL HUNG
Company : AAEON TECHNOLOGY INC.
EUT : SBC-659 (N)
Test Config : EUT/ALL PERIPHERALS
Type of Test: EN55022 CLASS A
Mode of Op. : INTEL P-III
: CPU=933MHZ/133MHZ

Page: 1

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1	50.360	41.20	-14.81	26.39	40.00	-13.61	Peak
2	68.800	42.00	-17.11	24.89	40.00	-15.11	Peak
3	80.920	45.30	-18.19	27.11	40.00	-12.89	Peak
4	120.000	44.70	-15.24	29.46	40.00	-10.54	Peak
5	150.100	46.30	-13.80	32.50	40.00	-7.50	Peak
6	166.171	49.70	-11.75	37.95	40.00	-2.05	Peak
7	224.990	43.50	-10.00	33.51	40.00	-6.49	Peak
8	250.030	47.10	-9.16	37.94	47.00	-9.06	Peak
9	265.880	48.60	-8.77	39.83	47.00	-7.17	Peak
10	324.990	39.90	-7.27	32.63	47.00	-14.37	Peak
11	365.610	43.80	-6.36	37.44	47.00	-9.56	Peak
12	450.030	35.70	-3.60	32.11	47.00	-14.90	Peak
13	465.290	35.80	-3.23	32.57	47.00	-14.43	Peak
14	565.010	37.80	-0.46	37.34	47.00	-9.66	Peak
15	627.910	36.20	0.97	37.17	47.00	-9.83	Peak
16	830.891	34.50	3.78	38.28	47.00	-8.72	Peak