



FCC CLASS A COMPLIANCE REPORT

for

Electromagnetic Emissions

of

CPU Board

Trade Name : N/A
Model Number : PCM-5894(N)
Serial Number : N/A
Report Number : 010212-F
Date : March 30, 2001

Prepared for :

AAEON Technology Inc.
5F, No. 135, Lane 235, Pao Chiao Rd., Hsin-Tien City,
Taipei, Taiwan, R.O.C.

Prepared by :



C&C LABORATORY, CO., LTD.

#B1, 1st Fl., Universal Center,
No. 183, Sec. 1, Tatung Rd., Hsi Chih,
Taipei Hsien, Taiwan, R.O.C.

TEL: (02)8642-1150

FAX: (02)8642-2256

**This report shall not be reproduced, except in full, without the written approval of
C&C Laboratory, Co., Ltd.**



TABLE OF CONTENTS

DESCRIPTION	PAGE
VERIFICATION OF COMPLIANCE	3
SYSTEM DESCRIPTION	4
PRODUCT INFORMATION	5
SUPPORT EQUIPMENT	6
MEASUREMENT PROCEDURE & LIMIT (LINE CONDUCTED EMISSION TEST)	7
MEASUREMENT PROCEDURE & LIMIT (RADIATED EMISSION TEST)	9
SUMMARY DATA	12
TEST FACILITY	17
TEST EQUIPMENT	18
BLOCK DIAGRAM OF TEST SETUP	21
APPENDIX 1 PHOTOGRAPHS (TEST SETUP OF LINE CONDUCTED EMISSION TEST)	21
APPENDIX 2 PHOTOGRAPHS (TEST SETUP OF RADIATED EMISSION TEST)	24
APPENDIX 3 PHOTOGRAPHS OF EUT	26



VERIFICATION OF COMPLIANCE

Equipment Under Test: CPU Board

Trade Name: N/A

Model Number: PCM-5894(N)

Serial Number: N/A

Applicant:
AAEON Technology Inc.
5F, No. 135, Lane 235, Pao Chiao Rd., Hsin-Tien City,
Taipei, Taiwan, R.O.C.

Manufacturer:
AAEON Technology Inc.
5F, No. 135, Lane 235, Pao Chiao Rd., Hsin-Tien City,
Taipei, Taiwan, R.O.C.

Type of Test: FCC Class A

Measurement Procedure: ANSI C63.4: 1992

File Number: 010212-F

Date of test: March 19 ~ 25, 2001

Deviation: According applicant declaration this EUT is a class A product, and to be marketed in industrial environment only.

Condition of Test Sample: Normal

The above equipment was tested by C&C Laboratory, Co., Ltd. for compliance with the requirements set forth in the FCC Rules and Regulations Part 15, Subpart B and the measurement procedure according to ANSI C63.4. This said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment are within the compliance requirements.

The test results of this report relate only to the tested sample identified in this report.

Authorized Signatory

Responsible Party

Officer of the Responsible Party



SYSTEM DESCRIPTION

EUT Test Program:

1. EMI test program was loaded and executed in Windows mode.
2. Data was sent to Monitor filling the screen with upper case of “H” patterns.
3. Test program sequentially exercised all related I/O’s of EUT and sent “H” patterns to all out ports EUT.
4. Communication test program was loaded and executed to communicate with remote side.
5. EUT sent data to Notebook PC on remote side via UTP cable.
6. Repeat 2 to 5. Test program is self-repeating throughout the test.



PRODUCT INFORMATION

Housing Type: Metal case
EUT Power Rating: 100-127/200-240VAC, 50/60Hz, 5/2.5A
AC Power during Test 120VAC/60Hz
Power Supply Manufacturer: Enhance
Power Supply Model Number: ENP-1815
AC Power Cord Type: Unshielded, 1.8m (Detachable)
DC Power Cable Type: N/A
CPU Manufacture: AMD **Type:** K6-2(366MHz)
OSC/Clock Frequencies: 66MHz
Memory Capacity: **Install:** 32MB
HDD Manufacturer: Maxtor **Model:** 72700AP
Chassis Manufacturer: **Model:** ARC-6100B
I/O Board Type: On Board

I/O Port of EUT

I/O PORT TYPES	Q'TY	TESTED WITH
1) Parallel Port	1	1
2) Serial Port	4	4
3) Video Port	1	1
4) PS/2 Keyboard Port	1	1
5) PS/2 Mouse Port	1	1
6) LAN Port	1	1
7) USB Port	2	2
8) AT Port	1	1



SUPPORT EQUIPMENT

No.	Equipment	Model #	Serial #	FCC ID	Trade Name	Data Cable	Power Cord
1.	Monitor	GDM-17SE2T	7139819	AK8GDM17SE2T	SONY	Shielded, 1.8m (with two cores)	Unshielded, 1.8m
2.	Modem	2400	94-364-176272	DK467GSM24	Computer Peripherals	Shielded, 1.8m	Unshielded, 1.5m
3.	Print	2225C	3137S01428	DSI6XU2225	HP	Shielded, 1.8m	Unshielded, 1.5m
4.	AT Keyboard	KB-9000	9809052512	LFCACEKEY1	ACEKEY	Shielded, 1.5m	N/A
5.	PS/2 Keyboard	SK-2502C	M990543850	FCC DoC	HP	Shielded, 1.8m	N/A
6.	PS/2 Mouse	M-S34	LZC84314453	DZL211029	Logitech	Shielded, 1.8m	N/A
7.	USB Mouse	M-BB48	LZE92250243	FCC DoC	Logitech	Shielded, 1.8m	N/A
8.	USB Mouse	M-BB48	LZE93050164	FCC DoC	Logitech	Shielded, 1.8m	N/A
9.	Mouse	M-MM43	LZE93353024	DoC	Logitech	Shielded, 1.9m	N/A
10.	Mouse	M-MM43	LZE93353074	DoC	Logitech	Shielded, 1.9m	N/A
11.	Mouse	M-MM43	LZE94052771	DoC	Logitech	Shielded, 1.9m	N/A
12.	Notebook (Remote)	365	TZ30518	DoC	Acer	LAN Cable Shielded, 5m	AC I/P: Unshielded, 1.8m DC O/P: Unshielded, 1.8m

Note: All the above equipment/cables were placed in worse case positions to maximize emission signals during emission test.

Grounding: Grounding was in accordance with the manufacturer's requirements and conditions for the intended use.



MEASUREMENT PROCEDURE (PRELIMINARY LINE CONDUCTED EMISSION TEST)

- 1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2) Support equipment, if needed, was placed as per ANSI C63.4.
- 3) All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4) The EUT received AC power through a Line Impedance Stabilization Network (LISN) which supplied power source of 120VAC/60Hz and was grounded to the ground plane.
- 5) All support equipment received power from a second LISN supplying power of 110VAC/60Hz.
- 6) The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7) Analyzer / Receiver scanned from 150kHz to 30MHz for emissions in each of the test modes.
- 8) During the above scans, the emissions were maximized by cable manipulation.
- 9) The following test mode(s) were scanned during the preliminary test:

Mode(s): (customer defined)

- 1. 1024 x 768 Resolution**
- 2. 800 x 600 Resolution**
- 3. 640 x 480 Resolution**

- 10) After the preliminary scan, we found the following test mode(s) producing the highest emission level.

Mode(s): 1.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.



MEASUREMENT PROCEDURE (FINAL LINE CONDUCTED EMISSION TEST)

- 1) EUT and support equipment was set up on the test bench as per step 10 of the preliminary test.
- 2) A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Q.P. mode, then the emission signal was re-checked using an Average detector.
- 3) The test data of the worst case condition(s) was reported on the Summary Data page.

Data Sample:

Freq. MHz	Q.P. Raw dBuV	Average Raw dBuV	Q.P. Limit dBuV	Average Limit dBuV	Q.P. Margin dB	Average Margin dB	Note
x.xx	43.95	---	56	46	-12.05	---	L 1

- | | |
|------------|--|
| Freq. | = Emission frequency in MHz |
| Raw dBuV | = Uncorrected Analyzer/Receiver reading |
| Limit dBuV | = Limit stated in standard |
| Margin dB | = Reading in reference to limit |
| Note | = Current carrying line of reading |
| “---“ | = The emission level complied with the Average limits, with at least 2 dB margin, so no further recheck. |

LINE CONDUCTED EMISSION LIMIT

Frequency	Maximum RF Line Voltage	
	Q.P.	AVERAGE
150kHz-500kHz	79dBuV	66dBuV
500kHz-5MHz	73dBuV	60dBuV
5MHz-30MHz	73dBuV	60dBuV

Note: The lower limit shall apply at the transition frequency.



MEASUREMENT PROCEDURE (PRELIMINARY RADIATED EMISSION TEST)

- 1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2) Support equipment, if needed, was placed as per ANSI C63.4.
- 3) All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4) The EUT received 120VAC/60Hz power source from the outlet socket under the turntable. All support equipment received 110VAC/60Hz power from another socket under the turntable.
- 5) The antenna was placed at 10 meter away from the EUT as stated in ANSI C63.4. The antenna connected to the Analyzer via a cable and at times a pre-amplifier would be used.
- 6) The Analyzer / Receiver quickly scanned from 30MHz to 2000MHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- 7) The following test mode(s) were scanned during the preliminary test:

Mode(s): (customer defined)

- 1. 1024 x 768 Resolution**
- 2. 800 x 600 Resolution**
- 3. 640 x 480 Resolution**

- 8) After the preliminary scan, we found the following test mode(s) producing the highest emission level.

Mode(s): 1.

Then, the EUT and cable configuration, antenna position, polarization and turntable position of the above highest emission level were recorded for reference of final testing.



MEASUREMENT PROCEDURE (FINAL RAIDATED EMISSION TEST)

- 1) EUT and support equipment were set up on the turntable as per step 8 of the preliminary test.
- 2) The Analyzer / Receiver scanned from 30MHz to 2000MHz. Emissions were scanned and measured rotating the EUT to 360 degrees, varying cable placement and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- 3) Recorded at least the six highest emissions. Emission frequency, amplitude, were recorded into a computer (The antenna position, polarization and turntable position were kept in raw data file) in which correction factors were used to calculate the emission level and compare reading to the applicable limit.
- 4) The test data of the worst case condition(s) was reported on the Summary Data page.

Data Sample:

Freq. (MHz)	Raw Data (dBuV/m)	Corr. Factor (dB)	Emiss. Level (dBuV/m)	Limits	Margin (dB)
xx.xx	14.0	11.2	26.2	30	-3.8

Freq.	= Emission frequency in MHz
Raw Data (dBuV/m)	= Uncorrected Analyzer / Receiver reading
Corr. Factor (dB)	= Correction factors of antenna factor and cable loss
Emiss. Level	= Raw reading converted to dBuV/m and CF added
Limit dBuV/m	= Limit stated in standard
Margin dB	= Reading in reference to limit



RADIATED EMISSION LIMIT

Frequency (MHz)	Distance (m)	Maximum Field Strength Limit (dBuV/m)		
		Q.P.	AVERAGE	PEAK
30-230	10	40	/	/
230-1000	10	47	/	/
Above 1000	3	/	60	80

****Note:** “/” means the limit line is not applicable.



SUMMARY DATA

(LINE CONDUCTED TEST)

Model Number: PCM-5894(N)

Location: Site # 4

Tested by: Jack Chen

Test Mode: Mode 1

Test Results: Passed

Temperature: 20°C

Humidity: 69%RH

(The chart below shows the highest readings taken from the final data)

FREQ MHz	Q.P. RAW dBuV	AVG RAW dBuV	Q.P. Limit dBuV	AVG Limit dBuV	Q.P. Margin dB	AVG Margin dB	NOTE
0.150	61.4	---	79.0	66.0	-17.6	---	L1
5.336	24.2	---	73.0	60.0	-48.8	---	L1
6.448	22.3	---	73.0	60.0	-50.7	---	L1
13.044	23.5	---	73.0	60.0	-49.5	---	L1
19.687	25.4	---	73.0	60.0	-47.6	---	L1
29.912	22.4	---	73.0	60.0	-50.6	---	L1
0.150	63.2	---	79.0	66.0	-15.8	---	L2
1.912	22.4	---	79.0	66.0	-56.6	---	L2
11.277	21.1	---	73.0	60.0	-51.9	---	L2
12.094	21.5	---	73.0	60.0	-51.5	---	L2
19.683	23.2	---	73.0	60.0	-49.8	---	L2
26.451	20.8	---	73.0	60.0	-52.2	---	L2

L1 = Line One (Hot side) / L2 = Line Two (Neutral side)

****NOTE: “---” denotes the emission level was or more than 2dB below the Average limit, so no re-check anymore.**



SUMMARY DATA

(RADIATED EMISSION TEST)

Model Number: PCM-5894(N)

Location: Site # 4

Tested by: Jack Chen

Test Mode: Mode 1

Polar: Vertical -- 10m

Detector Function: Quasi-Peak

Test Results: Passed

Temperature: 22^oC

Humidity: 70%RH

(The chart below shows the highest readings taken from the final data)

Freq. (MHz)	Raw Data (dBuV/m)	Corr. Factor (dB)	Emiss. Level (dBuV/m)	Limits	Margin (dB)
111.23	16.2	12.6	28.8	40.0	-11.2
133.40	14.6	12.2	26.8	40.0	-13.2
244.10	17.8	13.5	31.3	47.0	-15.7
402.10	16.2	18.8	35.0	47.0	-12.0
502.10	17.1	20.7	37.8	47.0	-9.2
733.60	13.3	22.7	36.0	47.0	-11.0



SUMMARY DATA

(RADIATED EMISSION TEST)

Model Number: PCM-5894(N)

Location: Site # 4

Tested by: Jack Chen

Test Mode: Mode 1

Polar: Horizontal -- 10m

Detector Function: Quasi-Peak

Test Results: Passed

Temperature: 22⁰C

Humidity: 70%RH

(The chart below shows the highest readings taken from the final data)

Freq. (MHz)	Raw Data (dBuV/m)	Corr. Factor (dB)	Emiss. Level (dBuV/m)	Limits	Margin (dB)
43.20	13.4	14.6	28.0	40.0	-12.0
110.98	12.9	12.6	25.5	40.0	-14.5
166.24	15.9	10.9	26.8	40.0	-13.2
233.60	18.5	12.3	30.8	47.0	-16.2
502.40	16.1	20.7	36.8	47.0	-10.2
733.20	14.1	22.7	36.8	47.0	-10.2



SUMMARY DATA

(RADIATED EMISSION TEST)

Model Number: PCM-5894(N)

Location: 3 meter chamber

Tested by: Jack Chen

Polar: Vertical ---3 m

Test Mode: Mode 1

Detector Function: Pk / A.V.

Test Results: Passed

Temperature: 23⁰C

Humidity: 67%RH

(The chart below shows the highest readings taken from the final data)

Freq. (MHz)	Raw Data (dBuV/m)	Corr. Factor (dB)	Emiss. Level(Pk) (dBuV/m)	Limits Pk	Margin (dB)
1083.00	14.8	26.7	41.5	80.0	-38.5
1096.00	14.4	26.7	41.1	80.0	-38.9
1461.00	14.4	27.9	42.3	80.0	-37.7

Note: In case of peak reading complied with the limit at least 22dB margin, no measurement with A.V. detector required.



SUMMARY DATA

(RADIATED EMISSION TEST)

Model Number: PCM-5894(N)

Location: 3 meter chamber

Tested by: Jack Chen

Polar: Horizontal ---3 m

Test Mode: Mode 1

Detector Function: Pk / A.V.

Test Results: Passed

Temperature: 23°C

Humidity: 67%RH

(The chart below shows the highest readings taken from the final data)

Freq. (MHz)	Raw Data (dBuV/m)	Corr. Factor (dB)	Emiss. Level(Pk) (dBuV/m)	Limits Pk ()	Margin (dB)
1096.00	13.5	26.7	40.2	80.0	-39.8
1461.00	16.1	27.9	44.0	80.0	-36.0
1896.00	10.4	29.4	39.8	80.0	-40.2

Note: In case of peak reading complied with the limit at least 22dB margin, no measurement with A.V. detector required.



TEST FACILITY

- Location:** No. 15, 14 Line, Chin Twu Chi, Lu Chu Hsiang, Taoyuan, Taiwan, R.O.C.
- Description:** There are four 3/10m open area test sites and three line conducted labs for final test.
The Open Area Test Sites and the Line Conducted labs are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 1992 and CISPR 22/EN 55022 requirements.
- Site Filing:** A site description is on file with the Federal Communications Commission, 7435 Oakland Mills Road, Columbia, MD 21046.

Registration also was made with Voluntary Control Council for Interference (VCCI).
- Site Accreditation:** Accredited by NEMKO (Authorization #: ELA 124) for EMC & A2LA (Certificate #: 824.01) for Emission

Also accredited by BSMI for the product category of Information Technology Equipment.
- Instrument Tolerance:** All measuring equipment is in accord with ANSI C63.4 and CISPR 22 requirements that meet industry regulatory agency and accreditation agency requirement.
- Ground Plane:** Two conductive reference ground planes were used during the Line Conducted Emission, one in vertical and the other in horizontal. The dimensions of these ground planes are as below. The vertical ground plane was placed distancing 40 cm to the rear of the wooden test table on where the EUT and the support equipment were placed during test. The horizontal ground plane projected 50 cm beyond the footprint of the EUT system and distanced 80 cm to the wooden test table. For Radiated Emission Test, one horizontal conductive ground plane extended at least 1m beyond the periphery of the EUT and the largest measuring antenna, and covered the entire area between the EUT and the antenna. It has no holes or gaps having longitudinal dimensions larger than one-tenth of a wavelength at the highest frequency of measurement up to 1GHz.

Site # 3 # 4 Line Conducted Test Site: At Shielding Room



TEST EQUIPMENT LIST

Instrumentation: The following list contains equipment used at C & C Laboratory, Co., Ltd. for testing. The equipment conforms to the CISPR 16-1 / ANSI C63.2-1988 Specifications for Electromagnetic Interference and Field Strength Instrumentation from 10kHz to 1.0 / 2.0 GHz.

Equipment used during the tests:

Open Area Test Site: # 1 ; # 2 ; # 3 ; # 4

Open Area Test Site # 1					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL. DUE
Q.P Adaptor	HP	85650A	2811A01399	05/05/2000	05/04/2001
RF Pre-selector	HP	85685A	2947A01064	05/05/2000	05/04/2001
Spectrum Analyzer	HP	8568B	3001A05004	05/05/2000	05/04/2001
S.P.A Display	HP	8568B	3014A18846	05/05/2000	05/04/2001
Precision Dipole	R&S	HZ-12	846932/0004	07/14/2000	07/13/2001
Precision Dipole	R&S	HZ-13	846556/0008	07/14/2000	07/13/2001
Bilog Antenna	CHASE	CBL6112A	2309	02/11/2001	02/10/2002
Turn Table	EMCO	2081-1.21	N/A	N.C.R	N.C.R
Antenna Tower	EMCO	2075-2	9707-2604	N.C.R	N.C.R
Controller	EMCO	2090	N/A	N.C.R	N.C.R
RF Switch	ANRITSU	MP59B	M54367	N.C.R	N.C.R
Site NSA	C&C	N/A	N/A	11/05/2000	11/04/2001

Open Area Test Site # 2					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL. DUE
Spectrum Analyzer	ADVANTEST	R3261C	81720301	09/02/2000	09/01/2001
Pre-Amplifier	HP	8447D	2944A08432	11/28/2000	11/27/2001
EMI Test Receiver	R&S	ESVS10	834468/006	03/24/2000	03/23/2001
Precision Dipole	R&S	HZ-12	846932/0004	07/14/2000	07/13/2001
Precision Dipole	R&S	HZ-13	846556/0008	07/14/2000	07/13/2001
Bilog Antenna	CHASE	CBL 6112B	2635	12/01/2000	11/30/2001
Turn Table	Chance Most	CM-T003-1	T807-6	N.C.R	N.C.R
Antenna Tower	Chance Most	CM-A003-1	A807-6	N.C.R	N.C.R
Controller	Chance Most	N/A	N/A	N.C.R	N.C.R
RF Switch	ANRITSU	MP59B	M76890	N.C.R	N.C.R
Site NSA	C&C Lab.	N/A	N/A	11/11/2000	11/10/2001



Open Area Test Site # 3					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL. DUE
Spectrum Analyzer	ADVANTEST	R3261A	21720279	08/15/2000	08/14/2001
EMI Test Receiver	R&S	ESVS20	838804/004	12/28/2000	12/27/2001
Pre-Amplifier	HP	8447D	2944A09173	02/19/2001	02/18/2002
Precision Dipole	R&S	HZ-12	846932/0004	07/14/2000	07/13/2001
Precision Dipole	R&S	HZ-13	846556/0008	07/14/2000	07/13/2001
Bilog Antenna	CHASE	CBL6112A	2179	12/01/2000	11/30/2001
Turn Table	EMCO	2081-1.21	9709-1885	N.C.R	N.C.R
Antenna Tower	EMCO	2075-2	9707-2060	N.C.R	N.C.R
Controller	EMCO	2090	9709-1256	N.C.R	N.C.R
RF Switch	ANRITSU	MP59B	M53867	N.C.R	N.C.R
Site NSA	C&C	N/A	N/A	11/23/2000	11/22/2001

Open Area Test Site # 4					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL. DUE
Spectrum Analyzer	ADVANTEST	R3261C	71720533	10/26/2000	10/25/2001
Pre-Amplifier	ANRITSU	MH648A	M89145	09/04/2000	09/03/2001
EMI Test Receiver	R&S	ESCS30	847793/012	11/10/2000	11/09/2001
Precision Dipole	R&S	HZ-12	846932/0004	07/14/2000	07/13/2001
Precision Dipole	R&S	HZ-13	846556/0008	07/14/2000	07/13/2001
Bilog Antenna	CHASE	CBL 6112B	2462	01/16/2001	01/15/2002
Turn Table	Chance most	N/A	N/A	N.C.R	N.C.R
Antenna Tower	Chance most	N/A	N/A	N.C.R	N.C.R
Controller	Chance most	N/A	N/A	N.C.R	N.C.R
RF Switch	ANRITSU	MP59B	M51067	N.C.R	N.C.R
Site NSA	C&C Lab.	N/A	N/A	11/24/2000	11/23/2001



3 meter chamber					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL. DUE
Spectrum Analyzer	ADVANTEST	R3271A	85060321	10/04/2000	10/03/2001
Pre-Amplifier	HP	8449B	3008A00965	10/03/2000	10/02/2001
Horn Antenna	EMCO	3115	9602-4659	04/06/2000	04/05/2001
Coaxial Cable	ANOREW	LDF-2-50	79027	09/22/2000	09/21/2001
Turn Table	HD	DS 415	N/A	N.C.R	N.C.R
Antenna Tower	HD	MA 240	N/A	N.C.R	N.C.R
Controller	HD	HD 100	N/A	N.C.R	N.C.R

Conducted Emission Test Site: # 4

Conducted Emission Test Site # 4					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL. DUE
EMI Test Receiver	R&S	ESHS10	843743/015	12/15/2000	12/14/2001
LISN	R&S	ENV 4200	8303261016	11/18/2000	11/17/2001
LISN	EMCO	3825/2	9003/1382	02/08/2001	02/07/2002


The calibrations of the measuring instruments, including any accessories that may effect such calibration, are checked frequently to assure their accuracy. Adjustments are made and correction factors applied in accordance with instructions contained in the manual for the measuring instrument.



BLOCK DIAGRAM OF TEST SETUP

SYSTEM DIAGRAM OF CONNECTIONS BETWEEN EUT AND SIMULATORS

EUT: CPU Board
Trade Name: N/A
Model Number: PCM-5894(N)
Power Cord: Unshielded, 1.8m





APPENDIX 1

PHOTOGRAPHS (TEST SETUP OF LINE CONDUCTED EMISSION TEST)

LINE CONDUCTED EMISSION TEST





APPDENDIX 2

PHOTOGRAPHS (TEST SETUP OF RADIATED EMISSION TEST)

RADIATED EMISSION TEST





APPENDIX 3

PHOTOGRAPHS OF EUT

Front view of EUT



Back view of EUT



Left view of EUT

