



## ENERGY EFFICIENCY CERTIFICATION (EEC):Test Report - Cover Page

**Customer Name:** AAEON TECHNOLOGY INC

**Address:** 5TH FL,135 LANE 235 PAO CHIAO RD HSIN-TIEN,TAIPEI, 231, TAIWAN

**Brand name(s):** AAEON

**Model name(s):** Green Communication System

**Product category:** Desktop Computer

**Electrical Ratings:** I/P: 10-30 V dc, 7.0A

**Representative (tested) Model:** TF-GCS-2500-IF-A10

**Model differences:** N/A

**Construction details:** Electronic components are mounted on PWB, which is enclosed by metal enclosure.

**The Sample(s) tested is(are) compliant with the following applied standards/regulations:**

ENERGY STAR ® : ENERGY STAR Program Requirements Product Specification for Computers, Version 5.2

**UL Project No. - Report ID:** 12CA26448

**Project Handler:** Johnny Hung

**Reviewed by:** Mark Lee / YuMi Lee

**Issued:** 2012-05-30  
(yyyy-mm-dd)

**Revised:** N/A  
(yyyy-mm-dd)

*The information and documentation involving UL Mark services are provided on behalf of Underwriters Laboratories (UL) or any authorized licensee of UL. The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.*



**ATTACHMENT(S)**

- External Power Supply list:

Manufacturer	Brand Name	Model Name	Represents Testing
FSP GROUP INC.	FSP	FSP084-DMAA1	X

*The information and documentation involving UL Mark services are provided on behalf of Underwriters Laboratories (UL) or any authorized licensee of UL. The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.*



Annex A – Unit 1					
Regulatory Body	Test Method, Regulation or Program Evaluated to	Tests to Determine Compliance	Test Limit per Regulation or Program Requirement	Measured Efficiency or Limit Level	Other
EPA – ENERGY STAR	ENERGY STAR Program Requirements for Computers – Test Method (Rev. Aug-2010)	Maximum Calculated Typical Energy Consumption ( $E_{TEC\_MAX}$ ) at 115 V ac/60 Hz	181 kWh (Category B)	170.20 kWh	N/A
EPA – ENERGY STAR	ENERGY STAR Program Requirements for Computers – Test Method (Rev. Aug-2010)	Maximum Calculated Typical Energy Consumption ( $E_{TEC\_MAX}$ ) at 230 V ac/50 Hz	181 kWh (Category B)	174.38 kWh	N/A
EPA – ENERGY STAR	ENERGY STAR Program Requirements for Computers – Test Method (Rev. Aug-2010)	Maximum Calculated Typical Energy Consumption ( $E_{TEC\_MAX}$ ) at 100 V ac/50 Hz	181 kWh (Category B)	172.80 kWh	N/A
EPA – ENERGY STAR	ENERGY STAR Program Requirements for Computers – Test Method (Rev. Aug-2010)	Maximum Calculated Typical Energy Consumption ( $E_{TEC\_MAX}$ ) at 100 V ac/60 Hz	181 kWh (Category B)	173.55 kWh	N/A
Additional Information: See Energy Efficiency Laboratory Data Package of Project No: 12CA26448 for further details and test results See ANNEX for pictures of the unit and further details. N/A = Not Applicable					

The information and documentation involving UL Mark services are provided on behalf of Underwriters Laboratories (UL) or any authorized licensee of UL. The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.



Annex B – Unit 2					
Regulatory Body	Test Method, Regulation or Program Evaluated to	Tests to Determine Compliance	Test Limit per Regulation or Program Requirement	Measured Efficiency or Limit Level	Other
EPA – ENERGY STAR	ENERGY STAR Program Requirements for Computers – Test Method (Rev. Aug-2010)	Maximum Calculated Typical Energy Consumption ( $E_{TEC,MAX}$ ) at 115 V ac/60 Hz	181 kWh (Category B)	160.89 kWh	N/A
EPA – ENERGY STAR	ENERGY STAR Program Requirements for Computers – Test Method (Rev. Aug-2010)	Maximum Calculated Typical Energy Consumption ( $E_{TEC,MAX}$ ) at 230 V ac/50 Hz	181 kWh (Category B)	160.94 kWh	N/A
EPA – ENERGY STAR	ENERGY STAR Program Requirements for Computers – Test Method (Rev. Aug-2010)	Maximum Calculated Typical Energy Consumption ( $E_{TEC,MAX}$ ) at 100 V ac/50 Hz	181 kWh (Category B)	160.39 kWh	N/A
EPA – ENERGY STAR	ENERGY STAR Program Requirements for Computers – Test Method (Rev. Aug-2010)	Maximum Calculated Typical Energy Consumption ( $E_{TEC,MAX}$ ) at 100 V ac/60 Hz	181 kWh (Category B)	160.20 kWh	N/A
Additional Information: See Energy Efficiency Laboratory Data Package of Project No: 12CA26448-Unit2 for further details and test results See ANNEX for pictures of the unit and further details. N/A = Not Applicable					

The information and documentation involving UL Mark services are provided on behalf of Underwriters Laboratories (UL) or any authorized licensee of UL. The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.

## DATA PACKAGE INFORMATION SHEET

Applicant Information	Name / Address:	AAEON TECHNOLOGY INC 5TH FL,135 LANE 235 PAO CHIAO RD HSIN-TIEN,TAIPEI,TAIWAN, 231
-----------------------	-----------------	---

Product Information	Standard(s):	<input checked="" type="checkbox"/> Energy Star Program Requirements for Computers: Version 5.2
		<input type="checkbox"/>
		<input type="checkbox"/>
		<input type="checkbox"/>
	CCNs:	ENVP
Product Name/Type:	Computers	
Models:	TF-GCS-2500-IF-A10	

Test Location Information	DAP and UL: <input type="checkbox"/> CTDp <input type="checkbox"/> TCP <input type="checkbox"/> TPTDP <input type="checkbox"/> WTDP <input checked="" type="checkbox"/> UL	
	Test Location Name/Address:    Underwriters Laboratories Taiwan Co., Ltd. 260 Da-Yeh Road, Peitou Taipei City, Taiwan 112	
	Tests Conducted By**:	Sign    BRUCE YANG
		Print    BRUCE YANG
	**When one person conducts all tests, the printed name and signature can be inserted here instead of on each page containing data.	
	Authorized Signatory or TCP Reviewer:	Sign    --
		Print    --
		Date    --
UL WTDP / WMT Witness:	Sign    --	
	Print    --	

Reviewed & Accepted	Qualified Project Handler:	Sign
		Print

# LIST OF TESTS

## Contents

PRODUCT REFERENCE PAGE .....	6
POWER SUPPLY REFERENCE PAGE .....	7
TECHNICIAN'S REFERENCE GUIDE .....	8
UUT PREPARATION FOR ALL PRODUCTS.....	12
OFF MODE POWER CONSUMPTION TEST .....	15
IDLE MODE POWER CONSUMPTION TEST .....	17
SLEEP MODE POWER CONSUMPTION TEST .....	19
MAXIMUM POWER TEST FOR WORKSTATIONS .....	21
WORKSHEETS.....	23

**Witness Test Data Program (WTDP) Information:****Environment:**

Accommodations and Environmental conditions, including proper power source meet the requirements of the test standard or UL default criteria (ISO/IEC 17025 Clause 5.3.1, 5.3.2, 5.3.3)

Yes  No  N/A

**Equipment:**

Testing is being conducted within the test equipment calibration dates. (See Test Instrument Information Page and ISO/IEC 17025 5.6.2.2)

Yes  No

**Critical Consumables:**

Critical consumables are compliant with test standard requirements. (ISO/IEC 17025 Clause 4.6)

Yes  No  N/A

**Sample Identification:**

Identification of items to be tested has been made (e.g. model no., Serial No., etc.) (See Test Sample Identification page and ISO/IEC 17025 Clause 5.8.2)

Yes  No

**Summary:**

The test facility was deemed to have the environment and capabilities necessary to perform the tests included in this data package.

Yes  No

JH 2012-05-18
------------------

## TEST SAMPLE IDENTIFICATION

The table below is to provide correlation of sample numbers to specific product related information. Refer to this table when a test identifies a test sample by "Sample No." only.

Sample Number	Sample Card Number	Date Received	Manufacturer, Product Identification, Serial Number and Ratings
1377847-1	1377847	2012-05-15	AAEON Technology Inc, Green embedded System, model TF-GCS-2500-IF-A10, rating: 10-30 Vdc, 7.0A
1377847-2	1377847	2012-05-15	FSP Group Inc., External power supply, type FSP084-DMAA1, Rating: I/P: 100-240 V~, 1.3A, 50-60Hz; O/P: 12.0V dc, 7.0A
1377847-3	1377847	2012-05-15	Keyboard
1377847-4	1377847	2012-05-15	Mouse
Sampling Procedure (if used) :			





**PRODUCT REFERENCE PAGE**

Model:	TF-GCS-2500-IF-A10	
Product Coding:	--	
Model Differences:	--	
Base Product:	--	
Electrical Ratings:	Voltage <input type="checkbox"/> Vac <input checked="" type="checkbox"/> Vdc:	10 – 30 Vdc
	Current <input checked="" type="checkbox"/> A <input type="checkbox"/> mA:	7.0 A
	Frequency, Hz:	--
	Power, Watts:	84 W

Unit Configuration	Comments
Product Classification:	<input checked="" type="checkbox"/> Desktop Computer <input type="checkbox"/> Thin Client <input type="checkbox"/> Integrated Desktop Computer <input type="checkbox"/> Workstation <input type="checkbox"/> Notebook Computer <input type="checkbox"/> Small-Scale Server
Product Category (see Tables 3 and 4 provided in this data sheet package):	<input type="checkbox"/> Category A <input type="checkbox"/> Category D <input checked="" type="checkbox"/> Category B <input type="checkbox"/> N/A <input type="checkbox"/> Category C
Processor Type/Model:	Intel, Core i7-620M
Processor Speed/Core (GHz):	2600GHz
# of CPU Cores/Processor Package:	2
# of Discrete Processor Packages Installed:	1
Operating System:	Windows 7
# of HDDs:	TOSHIBA , MK1060GSC , 100GB
RPMs for HDDs:	4200
# of Solid State Drives:	N/A
System Memory (GB):	8 GB
# of DIMMs Installed:	2
Video Card (GPU) Brand/Model:	N/A
Discrete GPU:	N/A
Discrete GPU Frame Buffer Width:	N/A
Video Card Dedicated Non-Shared Memory (MB)	N/A
Ethernet Capable System:	Yes
WOL Enabled from Sleep:	Enabled
WOL Enable from Off:	Enabled
Other:	Test with adopter, FSP084-DMAA1

**POWER SUPPLY REFERENCE PAGE**

Product Type:	<input type="checkbox"/> Internal	<input checked="" type="checkbox"/> External	
Manufacturer:	FSP Group Inc.		
Brand Name:	FSP		
Model Number/Designation:	FSP084-DMAA1		
Nameplate Rating:	Input:	100-240 V~, 1.3A, 50-60Hz	
	Output:	12.0V dc, 7.0A	
UL EEC Certified?	<input type="checkbox"/> Yes	<input type="checkbox"/> No	EEC Certificate #:
EPA Approved Lab certified?	<input type="checkbox"/> Yes	<input type="checkbox"/> No	Lab Info:

- The internal power supply shall meet the applicable requirements from Table 1 provided in this data sheet package. See separate data sheet package for the internal power supply testing.
- The external power supply with integral cooling fans shall meet the applicable requirements from Table 1 provided in this data sheet package. See separate data sheet package for the external power supply testing.
- The external power supply without integral cooling fans shall meet the level V performance requirements under the International Efficiency Marking Protocol and include the level V marking. ~~See separate data sheet package for the external power supply testing.~~

**FSP GROUP INC.**  
全漢企業股份有限公司  
全漢企業股份有限公司  
AC/DC Adapter(직류전원장치)  
電源供應器/電源适配器  
MODEL NO.(모델명) 型號/型号: FSP084-DMAA1  
AC INPUT(交流輸入/交流輸入): 100-240V~, 1.3A, 50-60Hz  
DC OUTPUT(直流輸出/直流輸出):  
12.0V --- 7.0A MAX (84W MAX)  
**CAUTION/주의사항: 警告!**  
**FOR INDOOR USE ONLY.**  
(室內使用/戶內使用)  
For use with information Technology Equipment.  
(適用於資訊類產品/適用於資訊類產品)  
본 제품은 실내용이며, IT제품에 사용하십시오.  
**ATTENTION:**  
Nur innerhalb von Gebäuden benutzen.  
Nur zur Verwendung mit informationstechnischen Einrichtungen.

**UL US LISTED**  
I.T.E. POWER SUPPLY  
E190414  
A/12614EA

**GS**  
TÜV Rheinland  
Product Safety

**CE**  
R43001 A/R46

**RoHS**  
TÜV RT  
PS E  
昭榮電具株式會社

**CCC S&E**

**EFFICIENCY LEVEL: V**

HU10142-10054  
A/S: +82-2-571-6680  
Made in China - Zhonghan Electronics(Shenzhen) Co., Ltd.  
회社/소미포플리온 민항제출  
生濟企業名稱: 仲漢電子(深圳)有限公司  
MADE IN CHINA (中國製造/中國製造) 6LL0906501GP FJ-1

## TECHNICIAN'S REFERENCE GUIDE

### Definitions:

**Desktop Computer:** A computer whose main unit is designed to be located in a permanent location, often on a desk or on the floor. Desktop computers are not designed for portability and are designed for use with an external display, keyboard, and mouse. Desktop computers are intended for a broad range of home and office applications.

**Integrated Desktop Computer:** A desktop computer in which the computing hardware and display are integrated into a single housing, and which is connected to ac mains power through a single cable. Integrated desktop computers come in one of two possible forms: (1) a system where the display and computer are physically combined into a single unit; or (2) a system packaged as a single system where the display is separate but is connected to the main chassis by a dc power cord and both the computer and display are powered from a single power supply. As a subset of desktop computers, integrated desktop computers are typically designed to provide similar functionality as desktop systems.

**Notebook Computer:** A computer designed specifically for portability and to be operated for extended periods of time both with and without a direct connection to an ac mains power source. Notebook computers include an integrated display and are capable of being powered by an integrated battery or other portable power source. In addition, most notebooks use an external power supply and have an integrated keyboard and pointing device. Notebook computers are typically designed to provide similar functionality to desktops, including operation of software similar in functionality as that used in desktops.

**Small-Scale Server:** A computer that typically uses desktop components in a desktop form factor, but is designed primarily to be a storage host for other computers. Small-scale Servers are designed to perform functions such as providing network infrastructure services (e.g., archiving) and hosting data/media. These products are not designed to process information for other systems or run web servers as a primary function.

**Thin Client:** An independently-powered computer that relies on a connection to remote computing resources to obtain primary functionality. Main computing functions (e.g., program execution, data storage, interaction with other Internet resources) are provided by the remote computing resources. Thin Clients covered by this specification are (1) limited to devices with no rotational storage media integral to the computer and (2) designed for use in a permanent location (e.g. on a desk) and not for portability.

**Workstation:** A high-performance, single-user computer typically used for graphics, CAD, software development, financial and scientific applications among other compute intensive tasks. Workstations covered by this specification (a) are marketed as a workstation; (b) provide mean time between failures (MTBF) of at least 15,000 hours (based on either Bellcore TR-NWT-000332, issue 6, 12/97 or field collected data); and (c) support error-correcting code (ECC) and/or buffered memory.

**Typical Energy Consumption (TEC):** A method of testing and comparing the energy performance of computers, which focuses on the typical electricity consumed by a product while in normal operation during a representative period of time.

## TECHNICIAN'S REFERENCE GUIDE (Cont'd)

### Definitions:

**Off Mode:** The lowest power mode which cannot be switched off (influenced) by the user and that may persist for an indefinite time when the appliance is connected to the main electricity supply and used in accordance with the manufacturer's instructions. For systems where ACPI standards are applicable, Off Mode correlates to ACPI System Level S5 state.

**Sleep Mode:** A low power mode that the computer enters automatically after a period of inactivity or by manual selection. A computer with Sleep capability can quickly "wake" in response to network connections or user interface devices with a latency of less than or equal to 5 seconds from initiation of wake event to system becoming fully usable including rendering of display. For systems where ACPI standards are applicable, Sleep Mode most commonly correlates to ACPI System Level S3 (suspend to RAM) state.

**Idle State:** The power state in which the operating system and other software have completed loading, a user profile has been created, activity is limited to those basic applications that the system starts by default, and the computer is not in Sleep Mode.

**Active State:** The power state in which the computer is carrying out useful work in response to a) prior or concurrent user input or b) prior or concurrent instruction over the network. Active State includes active processing, seeking data from storage, memory, or cache, including Idle State time while awaiting further user input and before entering low power modes.

### Significant Digits and Rounding:

All calculations shall be carried out with actual measured or observed values. Only the final result of a calculation shall be rounded. Calculated results shall be rounded to the nearest significant digit as expressed in the corresponding specification limit.

Unless otherwise specified, compliance with specification limits shall be evaluated using exact values without any benefit from further rounding.

## TECHNICIAN'S REFERENCE GUIDE (Cont'd)

### AC Input Power:

Products intended to be powered from AC mains shall be connected to a voltage source appropriate for the intended market, as specified in Table 1 or Table 2.

1. Products shipped with external power supplies (EPSs) shall first be connected to the EPS and then to the voltage source specified in Table 1 or Table 2.

**Table 1: Input Power Requirements for Products with  
Nameplate Rated Power Less Than or Equal to 1500 W**

Market	Voltage	Voltage Tolerance	Maximum Total Harmonic Distortion	Frequency	Frequency Tolerance
North America, Taiwan	115 Vac	+/- 1.0 %	2.0 %	60 Hz	+/- 1.0 %
Europe, Australia, New Zealand	230 Vac	+/- 1.0 %	2.0 %	50 Hz	+/- 1.0 %
Japan	100 Vac	+/- 1.0 %	2.0 %	50 Hz/60 Hz	+/- 1.0 %

**Table 2: Input Power Requirements for Products with  
Nameplate Rated Power Greater than 1500 W**

Market	Voltage	Voltage Tolerance	Maximum Total Harmonic Distortion	Frequency	Frequency Tolerance
North America, Taiwan	115 Vac	+/- 4.0 %	5.0 %	60 Hz	+/- 1.0 %
Europe, Australia, New Zealand	230 Vac	+/- 4.0 %	5.0 %	50 Hz	+/- 1.0 %
Japan	100 Vac	+/- 4.0 %	5.0 %	50 Hz/60 Hz	+/- 1.0 %

**Ambient Temperature:** Ambient temperature shall be from 18°C to 28°C.

**Relative Humidity:** Relative humidity shall be from 10% to 80%.

## TECHNICIAN'S REFERENCE GUIDE (Cont'd)

### Input Meter Considerations:

The power meter shall include the following attributes:

1. Crest Factor: Possesses an available current crest factor of 3 or more at its rated range value.
2. Minimum Frequency Response: 3.0 kHz
3. Minimum Resolution:
  - a. W for measurement values less than 10 W;
  - b. 0.1 W for measurement values from 10 W to 100 W; and
  - c. 1.0 W for measurement values greater than 100 W.

### Measurement Accuracy:

1. Power measurements with a value greater than or equal to 0.5 W shall be made with an uncertainty of less than or equal to 2% at the 95% confidence level.
2. Power measurements with a value less than 0.5 W shall be made with an uncertainty of less than or equal to 0.01 W at the 95% confidence level.

### User Information Requirements:

Based on the informational materials shipped with the product, please confirm the following:

Requirement	Yes/No	
(1) A description of power management settings that have been enabled by default,	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
(2) A description of the timing settings for various power management features, and	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
(3) Instructions for properly waking the product from Sleep Mode.	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
The information materials shipped with the product that contains the above information (1-3) have been reviewed and stored in eCommunications.	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No

Please confirm that the products are shipped with one or more of the following:

Requirement	Yes/No	
(1) A listed of default power management settings.	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
(2) A note stating that default power management settings have been selected for compliance with ENERGY STAR (within 15 min of user inactivity for the display, within 30 min for the computer, if applicable per Table 2), and are recommended by the ENERGY STAR program for optimal energy savings.	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
(3) Information about ENERGY STAR and the benefits of power management, to be located at or near the beginning of the hard copy or electronic user manual, or in a package or box insert.	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
The information materials shipped with the product that contains the above information (1-3) have been reviewed and stored in eCommunications.	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No

Tested by: \_\_\_\_\_ Tested by: \_\_\_\_\_ Test date: 2012-05-22  
signature print  
Sample #: 1377847-1~4 Instrument Code / Range: \_\_\_\_\_

---

## UUT PREPARATION FOR ALL PRODUCTS

Test Method (Rev. Aug-2010)

### METHOD

The unit was connected to a variable ac source of supply as indicated below.

- Desktops, Integrated Desktops, Notebooks, Thin Clients, Small-Scale Servers with Ethernet (IEEE 802.3) capability shall be connected to a live Ethernet network switch and any wireless radios shall be turned off. Computers without Ethernet capability must maintain a live wireless connection to a wireless router or network access point.
- Thin Clients shall be connected to a live server via a live Ethernet (IEEE 802.3) network switch and shall run intended terminal/remote connection software.
- Desktop computers, Small-Scale Servers and Thin Clients shipped without accessories shall be configured with a standard mouse, keyboard and external computer display (if server has display output functionality).
- Integrated Desktop computers shipped without accessories shall be configured with a standard mouse and keyboard.
- Notebook computers without an integrated pointing device or digitizer shall be configured with a mouse.
- Notebook computers shall not be configured with a docking station.
- Notebooks should have the battery pack(s) removed during testing. For systems where operation without a battery pack is not a supported configuration, the test may be performed with fully charged battery pack(s) installed, making sure to report this configuration in the test results.
- Desktops, Integrated Desktop, and Notebook Computers shall be tested with proxying features enabled or disabled as shipped.
- Primary hard drives shall not be power managed ("spun-down") during Idle testing unless containing non-volatile cache integral to the drive (e.g. "hybrid" hard drives or similar non-removable disk caching architectures). Any secondary internal hard drive(s) may be tested with hard drive power management enabled as shipped. If these additional drives are not power managed when shipped to customers, they shall be tested without such features implemented.



Tested by: \_\_\_\_\_ Tested by: \_\_\_\_\_ Test date: 2012-05-22  
signature print  
Sample # : 1377847-1~4 Instrument Code / Range: \_\_\_\_\_

---

**UUT PREPARATION FOR ALL PRODUCTS (Cont'd)**

Test Method (Rev. Aug-2010)

## METHOD

Record the ac voltage and frequency. Boot the computer and wait until the operating system has fully loaded. If necessary, run the initial operating system setup and allow all preliminary file indexing and other one-time/periodic processes to complete.

Record basic information about the computer's configuration – computer type, operating system name and version, processor type and speed, and total and available physical memory, etc.

Record basic information about the video card or graphics chipset (if applicable) - video card/chipset name, frame buffer width, resolution, amount of onboard memory, and bits per pixel.

Record in the following table if the product includes the following power management features in their "as-shipped" condition, subject to the following conditions:

- a. For Thin Clients, the WOL requirement shall apply products designed to receive software updates from a centrally managed network while in Sleep Mode or in Off Mode. Thin Clients whose standard software upgrade framework does not require off-hours scheduling are exempt from the WOL requirement.
- b. For Notebooks, WOL may be automatically disabled when the product is disconnected from ac mains power.
- c. For all products with WOL, directed packet filters shall be enabled and set to an industry standard default configuration.

Shut down the UUT.

Tested by: \_\_\_\_\_ Tested by: \_\_\_\_\_ Test date: 2012-05-22  
signature print  
Sample #: 1377847-1~4 Instrument Code / Range: \_\_\_\_\_

**UUT PREPARATION FOR ALL PRODUCTS (Cont'd)**

Test Method (Rev. Aug-2010)

## RESULTS

Mode or Model Transition	Requirement	Yes/No	
		Yes	No
Sleep Mode	(1) Sleep Mode shall be set to activate after no more than 30 minutes of user inactivity.  (2) The speed of any active 1 Gb/s Ethernet network links shall be reduced when transitioning to Sleep Mode or Off Mode.	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
Display Sleep Mode	(1) Display Sleep Mode shall be set to activate after no more than 15 minutes of user inactivity.	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
Wake on LAN (WOL)	(1) Computers with Ethernet capability shall provide users with an option to enable and disable WOL for Sleep Mode.  (2) Computers with Ethernet capability that are shipped through enterprise channels shall either: (a) be shipped with WOL enabled by default for Sleep Mode, when the computer is operating on ac mains power; or (b) provide users with the ability to enable WOL that is accessible from both the client operating system user interface and over the network.	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
Wake Management	1) Computers with Ethernet capability that are shipped through enterprise channels shall either: (a) be capable of both remote (via network) and scheduled (via real-time clock) wake events from Sleep Mode, and (b) provide clients with the ability to centrally manage (via vendor tools) any wake management settings that are configured through hardware settings if the manufacturer has control over such features.	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No

The power management features  meet  does not meet the requirements outlined in Table 2 provided in this data sheet package.

Tested by: \_\_\_\_\_ Tested by: \_\_\_\_\_ Test date: 2012-05-22  
signature print  
Sample # : 1377847-1~4 Instrument Code / Range: \_\_\_\_\_

**OFF MODE POWER CONSUMPTION TEST**

Test Method (Rev. Aug-2010)

## METHOD

The unit was connected to a variable ac source of supply as indicated below while in the off mode condition.

Computers shall be tested in their "as-shipped" condition for Off Mode. Models that will be shipped with WOL enabled for Off Mode shall be tested with WOL enabled.

With the UUT shut down and in Off, set the meter to begin accumulating true power values at an interval of less than or equal to 1 reading per second. Accumulative power values for 5 additional minutes and record the watt-hour value observed during that 5 minute period using both the "Wh" and time functions on the input meter. The average power consumed over that time period was then calculated.

Off Mode Unit Configuration Details:	
Operating System/Version:	Windows 7
Processor Type and Speed:	Intel core i7-620M, 2.66GHz
Total/Available Physical Memory:	8 GB
Wake On LAN (WOL) Enabled:	Enabled
Other:	Test with adopter, FSP084-DMAA1

Tested by: \_\_\_\_\_ Tested by: \_\_\_\_\_ Test date: 2012-05-22  
signature print  
Sample #: 1377847-1~4 Instrument Code / Range: \_\_\_\_\_

**OFF MODE POWER CONSUMPTION TEST (Cont'd)**

Test Method (Rev. Aug-2010)

## RESULTS

Ambient Temperature, °C 21 Relative Humidity, % 66

Required		Input						Elapsed Time	
V	Hz	V	Hz	A	Wh	Wh Integration time, min	P <sub>OFF</sub> , WATTS***	TIME START	TIME END
100	50	100.4	50	0.1124	0.30187	5	3.62244	00'00"	05'00"
100	60	99.95	60	0.10323	0.30155	5	3.6186	00'00"	05'00"
115	60	115.02	60	0.09423	0.30345	5	3.6414	00'00"	05'00"
230	50	229.86	50	0.0724	0.32073	5	3.84876	00'00"	05'00"

- For Small-Scale Servers**, the measured input power P<sub>off</sub> during the measurement period:  
 exceeded  did not exceed \_\_\_\_\_ Watt(s)\*.

Note (\*) this value is derived from the Equation 5 Worksheet provided in this data sheet package.

The results  comply  do not comply with the ENERGY STAR Program Requirements Product Specification for Computers, Version 5.2.

- For Thin Clients**, the measured input power P<sub>off</sub> during the measurement period:  
 exceeded  did not exceed \_\_\_\_\_ Watt(s)\*\*.

Note (\*\*) this value is derived from the Equation 6 Worksheet provided in this data sheet package.

The results  comply  do not comply with the ENERGY STAR Program Requirements Product Specification for Computers, Version 5.2.

\*\*\* The average power is calculated by the following equation:

$$\text{Avg. Power (Watts)} = (\text{Wh} \times 60 \text{ minutes/hr}) / (\text{Wh Interval, minutes})$$

## Supplemental Information:

- For UUT running Windows, "Off" is defined as selecting "Shut Down" from the start menu.  
 For UUT running Linux, "Off" is defined as typing the "shutdown -h now" command from the Command Line Interface (CLI).  
 Other:

Tested by: \_\_\_\_\_ Tested by: \_\_\_\_\_ Test date: 2012-05-22  
signature print  
Sample #: 1377847-1~4 Instrument Code / Range: \_\_\_\_\_

## IDLE MODE POWER CONSUMPTION TEST

Test Method (Rev. Aug-2010)

### METHOD

Immediately after the off mode power consumption test, switch on the computer and begin recording elapsed time after completing any login activity necessary to fully boot the system. Once logged in with the operating system fully loaded and ready, close any open windows so that the standard operational desktop screen or equivalent ready screen is displayed. Between 5 and 15 minutes after the initial boot or log in, set the meter to begin accumulating true power values at an interval or greater than or equal to 1 reading per second. Accumulate power values for 5 additional minutes and record the watt-hour value value observed during that 5 minute period using both the "Wh" and time functions on the input meter. The average power consumed over that time period was then calculated.

- For Computers with external computer displays (most desktops), use the computer display power management setting to prevent the display from powering down to ensure it stays on for the full length of the Idle Mode Power Consumption Test as described below.
- For Computers with integrated computer displays (notebooks and integrated systems), use the power management settings to set the display to power down after 1 minute.
- For Small-Scale Servers and Thin Clients, if the initial unit tested is less than or equal to the applicable requirements for idle but falls within 10% of that level, one additional unit of the same model with an identical configuration must also be tested.

Idle Mode Unit Configuration Details:	
Operating System/Version:	Windows 7
Processor Type and Speed:	Intel core i7-620M, 2.66GHz
Total/Available Physical Memory:	8 GB
Wake On LAN (WOL) Enabled:	Enabled
Other:	Test with adopter, FSP084-DMAA1

Tested by: \_\_\_\_\_ Tested by: \_\_\_\_\_ Test date: 2012-05-22  
signature print  
Sample #: 1377847-1~4 Instrument Code / Range: \_\_\_\_\_

**IDLE MODE POWER CONSUMPTION TEST (Cont'd)**

Test Method (Rev. Aug-2010)

Ambient Temperature, °C 21 Relative Humidity, % 66

Input								Elapsed Time		
Required		Measured						Elapsed Time		
V	Hz	V	Hz	A	Wh	Wh Integration time, min	P <sub>idle</sub> , Watts***	Verified Screen Power Management Set for 1 minute (Y) Integrated Display Only	Time Start	Time End
100	50	100.37	50	0.7245	3.2716	5	39.2592	YES	00'00"	05'00"
100	60	99.86	60	0.7304	3.3712	5	40.4544	YES	00'00"	05'00"
115	60	114.91	60	0.7363	3.3357	5	40.0284	YES	00'00"	05'00"
230	50	229.76	50	0.3955	3.3294	5	39.9528	YES	00'00"	05'00"

 **For Small-Scale Servers:**

The measured input power P<sub>idle</sub> during the measurement period  exceeded  did not exceed \_\_\_\_\_ Watt(s)\*.

Note (\*) this value is derived from table 10 provided in this data sheet package.

The results  comply  do not comply with the ENERGY STAR Program Requirements Product Specification for Computers, Version 5.2.

 **For Thin Clients:**

The measured input power P<sub>idle</sub> during the measurement period  exceeded  did not exceed \_\_\_\_\_ Watt(s)\*\*.

Note (\*\*) this value is derived from table 11 provided in this data sheet package.

The results  comply  do not comply with the ENERGY STAR Program Requirements Product Specification for Computers, Version 5.2.

\*\*\* The average power is calculated by the following equation:

$$\text{Avg. Power (Watts)} = (\text{Wh} \times 60 \text{ minutes/hr}) / (\text{Wh Interval, minutes})$$

Tested by: \_\_\_\_\_ Tested by: \_\_\_\_\_ Test date: 2012-05-22  
signature Print  
Sample #: 1377847-1~4 Instrument Code / Range: \_\_\_\_\_

## SLEEP MODE POWER CONSUMPTION TEST

Test Method (Rev. Aug-2010)

### METHOD

After completing the idle measurements, measure the time of user inactivity to place both the computer and display in sleep mode.

Then, reset the meter (if necessary) and begin accumulating true power values at an interval of greater than or equal to 1 reading per second. Accumulate power values for 5 additional minutes and record the watt-hour value value observed during that 5 minute period using both the "Wh" and time functions on the input meter. The average power consumed over that time period was then calculated.

- If testing both WOL enabled and WOL disabled for Sleep, wake the computer and change the WOL from Sleep setting through the operating system settings or by other means. Repeat the sleep mode test with the alternate configuration.

Sleep Mode Unit Configuration Details:	
Operating System/Version:	Windows 7
Processor Type and Speed:	Intel core i7-620M, 2.66GHz
Total/Available Physical Memory:	8 GB
Wake On LAN (WOL) Enabled:	Enabled
Other:	Test with adopter, FSP084-DMAA1

Tested by: \_\_\_\_\_ Tested by: \_\_\_\_\_ Test date: 2012-05-22  
signature print

Sample #: 1377847-1~4 Instrument Code / Range: \_\_\_\_\_

**SLEEP MODE POWER CONSUMPTION TEST (Cont'd)**

Test Method (Rev. Aug-2010)

## RESULTS

Ambient Temperature, °C 21 Relative Humidity, % 66

Input									
Required		Measured						Elapsed Time	
V	Hz	V	Hz	A	Wh	Wh Integration time, min	P <sub>sleep</sub> , Watts**	Time Start	Time End
100	50	100.47	50	0.74	2.8884	5	34.6608	00'00"	05'00"
100	60	99.87	60	0.7389	2.8914	5	34.6968	00'00"	05'00"
115	60	115.2	60	0.6423	2.8538	5	34.2456	00'00"	05'00"
230	50	229.82	50	0.347	2.8567	5	34.2804	00'00"	05'00"

 **For Thin Clients:**

The measured input power P<sub>sleep</sub> during the measurement period  exceeded  did not exceed \_\_\_\_\_ Watt(s)\*.

Note (\*) this value is derived from the Equation 7 Worksheet provided in this data sheet package.

The results  comply  do not comply with the ENERGY STAR Program Requirements Product Specification for Computers, Version 5.2.

## Notes:

\*\* The average power is calculated by the following equation:

$$\text{Avg. Power (Watts)} = (\text{Wh} \times 60 \text{ minutes/hr}) / (\text{Wh Interval, minutes})$$



Tested by: \_\_\_\_\_ Tested by: \_\_\_\_\_ Test date: \_\_\_\_\_  
signature print

Sample #: \_\_\_\_\_ Instrument Code / Range: \_\_\_\_\_

## MAXIMUM POWER TEST FOR WORKSTATIONS

Test Method (Rev. Aug-2010)

### Method

Record the ac voltage and frequency. The meter should be able to store and output the maximum power measurement reached during the test.

Run linpack (linx) with the memory allocation set to: \_\_\_\_\_ mb and the number of tests set to: \_\_\_\_\_.

Run specviewperf10/specviewperf10 with multithreading for all tests at the highest resolution supported by the display and graphic card used.

Set the meter to begin accumulating true power values at an interval of less than or equal to 1 reading per second, and begin taking measurements. Accumulate power values until specviewperf and all its instances have completed running. Record the maximum power value attained during the test.

This test must be repeated three times on the same UUT, and all three measurements must fall within a  $\pm 2\%$  tolerance relative to the average of the three measured maximum power values.

### Maximum Mode Unit Configuration Details:

Operating System/Version:	
Processor Type and Speed:	
Total/Available Physical Memory:	
Wake On LAN (WOL) Enabled:	
# of HDDs:	
Other:	

Johnny Hung  
2012-05-18



## WORKSHEETS

Equation 1: Calculation Of Typical Annual Electricity Use ( $E_{TEC}$ ) for Desktop, Integrated Desktop, and Notebook Computers:

$$E_{TEC} = (8760/1000) * (P_{off} * T_{off} + P_{sleep} * T_{sleep} + P_{idle} * T_{idle}),$$

Where all  $P_x$  are power values in watts, all  $T_x$  are mode weightings as specified in Table 5 (for Desktops and Integrated Desktops) or Table 6 (for Notebooks) , and the  $E_{TEC}$  is in units of kWh and represents annual consumption based on mode weightings.

Input		Calculated			
V	Hz	$P_{off}$	$P_{idle}$	$P_{sleep}$	$E_{TEC}$
100	50	3.62244	39.2592	34.6608	170.20
100	60	3.6186	40.4544	34.6968	174.38
115	60	3.6414	40.0284	34.2456	172.80
230	50	3.84876	39.9528	34.2804	173.55

Equation 2: Calculation of Maximum Typical Annual Electricity Use ( $E_{TEC\_MAX}$ ) For Desktop, Integrated Desktop, and Notebook Computers:

$$E_{TEC\_MAX} \text{ (kWh)} = TEC_{BASE} + TEC_{MEMORY} + TEC_{GRAPHICS} + TEC_{STORAGE}$$

Where  $TEC_{BASE}$ ,  $TEC_{MEMORY}$ ,  $TEC_{GRAPHICS}$  and  $TEC_{STORAGE}$  are adders as specified in Table 7 (for Desktops and Integrated Desktops) or Table 8 (for Notebooks).

Calculated				
$TEC_{BASE}$ (kWh)	$TEC_{MEMORY}$ (kWh)	$TEC_{GRAPHICS}$ (kWh)	$TEC_{STORAGE}$ (kWh)	$E_{TEC\_MAX}$ (kWh)
175	6	0	0	181

For Desktops, Integrated Desktop, and Notebook Computers, the calculated  $E_{TEC}$   exceeded  did not exceed  $E_{TEC\_MAX}$  .

The results  comply  do not comply with the ENERGY STAR Program Requirements Product Specification for Computers, Version 5.2.

For Desktops, Integrated Desktop, and Notebook Computers, if the initial unit tested is less than or equal to the applicable requirements for TEC but falls within 10% of that level, one additional unit of the same model with an identical configuration must also be tested.

### WORKSHEETS (Cont'd)

Equation 3: Calculation of Weighted Power Consumption ( $P_{TEC}$ ) for Workstations:

$$P_{TEC} = (P_{off} * T_{off}) + (P_{sleep} * T_{sleep}) + (P_{idle} * T_{idle}),$$

Where all  $P_x$  are power values in watts, all  $T_x$  are mode weightings as specified in Table 9.

Input		Calculated			
V	Hz	$P_{off}$	$P_{idle}$	$P_{sleep}$	$P_{TEC}$

Equation 4: Calculation of Maximum Weighted Power Consumption ( $P_{TEC\_MAX}$ ) for Workstations:

$$P_{TEC\_MAX} (W) \leq 0.28 * \{P_{MAX} + (N_{HDD} * 5)\},$$

Where  $P_{MAX}$  = measured maximum power consumption (W) and  $N_{HDD}$  = number of installed hard disk drives (HDD) or solid state drives (SSD).

$P_{MAX} (W)$	$N_{HDD}$	$P_{TEC\_MAX} (W)$

For Workstations, the calculated  $P_{TEC}$   exceeded  did not exceed  $P_{TEC\_MAX}$ .

The results  comply  do not comply with the ENERGY STAR Program Requirements Product Specification for Computers, Version 5.2.

For Workstations, if the initial unit tested is less than or equal to the applicable requirements for TEC but falls within 10% of that level, one additional unit of the same model with an identical configuration must also be tested.

Johnny Hung 2012-05-18
---------------------------

**WORKSHEETS (Cont'd)**

Equation 5: Calculation of Maximum Off Mode Power Consumption ( $P_{off\_Max}$ ) for Small-Scale Servers:

$$P_{OFF\_MAX} (W) = P_{OFF\_BASE} + P_{OFF\_WOL},$$

Where  $P_{OFF\_WOL}$  shall only be applied to products that offer WOL that is enabled by default upon shipment.

$P_{OFF\_BASE} (W)$	$P_{OFF\_WOL}$	$P_{OFF\_MAX} (W)$

Equation 6: Calculation of Maximum Off Mode Power Consumption ( $P_{off\_Max}$ ) for Thin Clients:

$$P_{OFF\_MAX} (W) = P_{OFF\_BASE} + P_{OFF\_WOL},$$

Where  $P_{OFF\_WOL}$  shall only be applied to products that offer WOL that is enabled by default upon shipment.

$P_{OFF\_BASE} (W)$	$P_{OFF\_WOL}$	$P_{OFF\_MAX} (W)$

Equation 7: Calculation of Maximum Sleep Mode Power Consumption ( $P_{sleep\_Max}$ ) for Thin Clients:

$$P_{SLEEP\_MAX} (W) = P_{SLEEP\_BASE} + P_{SLEEP\_WOL},$$

Where  $P_{SLEEP\_WOL}$  shall only be applied to products that offer WOL that is enabled by default upon shipment.

$P_{SLEEP\_BASE} (W)$	$P_{SLEEP\_WOL}$	$P_{SLEEP\_MAX} (W)$

Johnny Hung  
2012-05-18

**Table 1:**  
**Requirements for Internal Power Supplies and External Power Supplies with Integral Cooling**

<b>Loading Condition (Percentage of Nameplate Output Current)</b>	<b>Minimum Efficiency</b>	<b>Minimum Power Factor</b>
20%	0.82	-
50%	0.85	-
100%	0.82	0.90

**Table 2:  
Power management requirements**

Mode or Mode Transition	Requirement	Desktops	Integrated Desktops	Notebooks	Workstations	Small-scale Servers	Thin Clients
Sleep Mode	(1) Sleep Mode shall be set to activate after no more than 30 minutes of user inactivity. (2) The speed of any active 1 Gb/s Ethernet network links shall be reduced when transitioning to Sleep Mode or Off Mode.	Yes	Yes	Yes	Yes	No	No
Display Sleep Mode	(1) Display Sleep Mode shall be set to activate after no more than 15 minutes of user inactivity.	Yes	Yes	Yes	Yes	Yes	Yes
Wake on LAN (WOL)	(1) Computers with Ethernet capability shall provide users with an option to enable and disable WOL for Sleep Mode. (2) Computers with Ethernet capability that are shipped through enterprise channels shall either: (a) be shipped with WOL enabled by default for Sleep Mode, when the computer is operating on ac mains power; or (b) provide users with the ability to enable WOL that is accessible from both the client operating system user interface and over the network.	Yes	Yes	Yes	Yes	Yes	Yes
Wake Management	(1) Computers with Ethernet capability that are shipped through enterprise channels shall: (a) be capable of both remote (via network) and scheduled (via real-time clock) wake events from Sleep Mode, and (b) provide clients with the ability to centrally manage (via vendor tools) any wake management settings that are configured through hardware settings if the manufacturer has control over such features.	Yes	Yes	Yes	Yes	Yes	Yes

**Table 3:  
Categorization of Desktop and Integrated Desktop Computers**

<b>Category A</b>	All desktop computers that do not meet the definition of Category B, Category C, or Category D below will be considered under Category A for ENERGY STAR qualification.
<b>Category B</b>	To qualify under Category B, desktops <u>must</u> have: <ul style="list-style-type: none"> <li>▪ Equal to 2 Physical Cores; and</li> <li>▪ Greater than or equal to 2 gigabytes (GB) of System Memory.</li> </ul>
<b>Category C</b>	To qualify under Category C, desktops <u>must</u> have: <ul style="list-style-type: none"> <li>▪ Greater than 2 Physical Cores.</li> </ul> <p>In addition to the requirement above, models qualifying under Category C must be configured with a minimum of 1 of the following 2 characteristics:</p> <ul style="list-style-type: none"> <li>▪ Greater than or equal to 2 gigabytes (GB) of System Memory; and/or</li> <li>▪ A Discrete GPU.</li> </ul>
<b>Category D</b>	To qualify under Category D, desktops <u>must</u> have: <ul style="list-style-type: none"> <li>▪ Greater than or equal to 4 Physical Cores.</li> </ul> <p>In addition to the requirement above, models qualifying under Category D must be configured with a minimum of 1 of the following 2 characteristics:</p> <ul style="list-style-type: none"> <li>▪ Greater than or equal to 4 gigabytes (GB) of System Memory; and/or</li> <li>▪ A Discrete GPU with a Frame Buffer Width greater than 128-bit.</li> </ul>

**Table 4:  
Categorization of Notebook Computers**

<b>Category A</b>	All notebook computers that do not meet the definition of Category B or Category C below will be considered under Category A for ENERGY STAR qualification.
<b>Category B</b>	To qualify under Category B, notebooks <u>must</u> have: <ul style="list-style-type: none"> <li>▪ A Discrete GPU.</li> </ul>
<b>Category C</b>	To qualify under Category C, notebooks <u>must</u> have: <ul style="list-style-type: none"> <li>▪ Greater than or equal to 2 Physical Cores;</li> <li>▪ Greater than or equal to 2 gigabytes (GB) of System Memory; and</li> <li>▪ A Discrete GPU with a Frame Buffer Width greater than 128-bit.</li> </ul>



**Table 5:  
Mode Weightings for Desktop and Integrated Desktop Computers**

Mode Weighting	Conventional	Full Network Connectivity			
		Base Capability	Remote Wake	Service Discovery/Name Services	Full Proxying
T <sub>off</sub>	55%	50%	47%	43%	40%
T <sub>sleep</sub>	5%	14%	20%	25%	30%
T <sub>idle</sub>	40%	36%	33%	32%	30%

**Table 6:  
Mode Weightings for Notebook Computers**

Mode Weighting	Conventional	Full Network Connectivity			
		Base Capability	Remote Wake	Service Discovery / Name Services	Full Proxying
T <sub>off</sub>	60%	54%	49%	48%	45%
T <sub>sleep</sub>	10%	18%	24%	26%	30%
T <sub>idle</sub>	30%	28%	27%	26%	25%

**Table 7:  
Maximum TEC Allowances for Desktop and Integrated Desktop Computers**

Product Category	TEC <sub>BASE</sub> (kWh)	TEC <sub>MEMORY</sub> (kWh) Where: $m$ = System Memory (GB)	TEC <sub>GRAPHICS</sub> (kWh)	TEC <sub>STORAGE</sub> (kWh) (Applies <u>once</u> if system has more than one Additional Internal Storage element.)
A	148.0	1.0 (per GB > 2.0)	35.0 (GPU Frame Buffer Width $\leq$ 128-bit)	25.0
			50.0 (GPU Frame Buffer Width > 128-bit)	
B	175.0	1.0 (per GB > 2.0)	35.0 (GPU Frame Buffer Width $\leq$ 128-bit)	25.0
			50.0 (GPU Frame Buffer Width > 128-bit)	
C	209.0	1.0 (per GB > 2.0)	50.0 (GPU Frame Buffer Width > 128-bit)	25.0
D	234.0	1.0 (per GB > 4.0)	50.0 (GPU Frame Buffer Width > 128-bit)	25.0

**Table 8:  
Maximum TEC Allowances for Notebook Computers**

Product Category	TEC <sub>BASE</sub> (kWh)	TEC <sub>MEMORY</sub> (kWh) <i>Where: m = System Memory (GB)</i>	TEC <sub>GRAPHICS</sub> (kWh)	TEC <sub>STORAGE</sub> (kWh) <i>(Applies once if system has more than one Additional Internal Storage element.)</i>
<b>A</b>	40.0	0.4 <i>(per GB &gt; 4.0)</i>	-	3.0
<b>B</b>	53.0	0.4 <i>(per GB &gt; 4.0)</i>	3.0 <i>(GPU Frame Buffer Width &gt; 64-bit)</i>	3.0
<b>C</b>	88.5	0.4 <i>(per GB &gt; 4.0)</i>	-	3.0

**Table 9:  
Mode Weightings for Workstations**

T <sub>OFF</sub>	T <sub>SLEEP</sub>	T <sub>IDLE</sub>
0.35	0.10	0.55

**Table 10:  
Classification & Power Consumption Requirements for Small-scale Servers**

Small-scale Server Classification		Operational Mode Requirements		
Product Category	Category Description	$P_{OFF\ BASE}$ (watts)	$P_{OFF\ WOL}$ (watts)	$P_{IDLE\ MAX}$ (watts)
A	All Small-Scale Servers that do not meet the definition of Category B will be considered under Category A for ENERGY STAR qualification.	2.0	0.7	50.0
B	To qualify under Category B Small-Scale Servers must have: <ul style="list-style-type: none"> <li>Processor(s) with greater than 1 physical core or greater than 1 discrete processor; and</li> <li>Minimum of 1 gigabyte of system memory.</li> </ul>	2.0	0.7	65.0

**Table 11:  
Classification & Power Consumption Requirements for Thin Clients**

Thin Client Classification		Operational Mode Requirements				
Product Category	Category Description	$P_{OFF\ BASE}$ (watts)	$P_{OFF\ WOL}$ (watts)	$P_{SLEEP\ BASE}$ (watts)	$P_{SLEEP\ WOL}$ (watts)	$P_{IDLE\ MAX}$ (watts)
A	All Thin Clients that do not meet the definition of Category B, below, will be considered under Category A for ENERGY STAR qualification.	2.0	0.7	2.0	0.7	12.0
B	To qualify under Category B, Thin Clients must support local multimedia encode/decode.	2.0	0.7	2.0	0.7	15.0

## DATA PACKAGE INFORMATION SHEET

Applicant Information	Name / Address:	AAEON TECHNOLOGY INC 5TH FL,135 LANE 235 PAO CHIAO RD HSIN-TIEN,TAIPEI,TAIWAN, 231
-----------------------	-----------------	---

Product Information	Standard(s):	<input checked="" type="checkbox"/> Energy Star Program Requirements for Computers: Version 5.2
		<input type="checkbox"/>
		<input type="checkbox"/>
		<input type="checkbox"/>
	CCNs:	ENVP
Product Name/Type:	Computers	
Models:	TF-GCS-2500-IF-A10	

Test Location Information	DAP and UL: <input type="checkbox"/> CTDp <input type="checkbox"/> TCP <input type="checkbox"/> TPTDP <input type="checkbox"/> WTDP <input checked="" type="checkbox"/> UL	
	Test Location Name/Address:    Underwriters Laboratories Taiwan Co., Ltd. 260 Da-Yeh Road, Peitou Taipei City, Taiwan 112	
	Tests Conducted By**:	Sign    BRUCE YANG
		Print    BRUCE YANG
	**When one person conducts all tests, the printed name and signature can be inserted here instead of on each page containing data.	
	Authorized Signatory or TCP Reviewer:	Sign    --
		Print    --
		Date    --
UL WTDP / WMT Witness:	Sign    --	
	Print    --	

Reviewed & Accepted	Qualified Project Handler:	Sign    JOHNNY HUNG
		Print    JOHNNY HUNG

# LIST OF TESTS

## Contents

PRODUCT REFERENCE PAGE .....	6
POWER SUPPLY REFERENCE PAGE .....	7
TECHNICIAN'S REFERENCE GUIDE .....	8
UUT PREPARATION FOR ALL PRODUCTS.....	12
OFF MODE POWER CONSUMPTION TEST .....	15
IDLE MODE POWER CONSUMPTION TEST .....	17
SLEEP MODE POWER CONSUMPTION TEST .....	19
MAXIMUM POWER TEST FOR WORKSTATIONS .....	21
WORKSHEETS.....	23

**Witness Test Data Program (WTDP) Information:****Environment:**

Accommodations and Environmental conditions, including proper power source meet the requirements of the test standard or UL default criteria (ISO/IEC 17025 Clause 5.3.1, 5.3.2, 5.3.3)

Yes  No  N/A

**Equipment:**

Testing is being conducted within the test equipment calibration dates. (See Test Instrument Information Page and ISO/IEC 17025 5.6.2.2)

Yes  No

**Critical Consumables:**

Critical consumables are compliant with test standard requirements. (ISO/IEC 17025 Clause 4.6)

Yes  No  N/A

**Sample Identification:**

Identification of items to be tested has been made (e.g. model no., Serial No., etc.) (See Test Sample Identification page and ISO/IEC 17025 Clause 5.8.2)

Yes  No

**Summary:**

The test facility was deemed to have the environment and capabilities necessary to perform the tests included in this data package.

Yes  No

JH 2012-05-24
------------------

## TEST SAMPLE IDENTIFICATION

The table below is to provide correlation of sample numbers to specific product related information. Refer to this table when a test identifies a test sample by "Sample No." only.

Sample Number	Sample Card Number	Date Received	Manufacturer, Product Identification, Serial Number and Ratings
1385063-1	1385063	2012-05-24	AAEON Technology Inc, Green embedded System, model TF-GCS-2500-IF-A10, rating: 10-30 Vdc, 7.0A
1385063-2	1385063	2012-05-24	FSP Group Inc., External power supply, type FSP084-DMAA1, Rating: I/P: 100-240 V~, 1.3A, 50-60Hz; O/P: 12.0V dc, 7.0A
1385063-3	1385063	2012-05-24	Keyboard
1385063-4	1385063	2012-05-24	Mouse
Sampling Procedure (if used) :		N/A	





**PRODUCT REFERENCE PAGE**

Model:	TF-GCS-2500-IF-A10		
Product Coding:	--		
Model Differences:	--		
Base Product:	--		
Electrical Ratings:	Voltage <input type="checkbox"/> Vac <input checked="" type="checkbox"/> Vdc:	10 – 30 Vdc	
	Current <input checked="" type="checkbox"/> A <input type="checkbox"/> mA:	7.0 A	
	Frequency, Hz:	--	
	Power, Watts:	84 W	

Unit Configuration	Comments
Product Classification:	<input checked="" type="checkbox"/> Desktop Computer <input type="checkbox"/> Thin Client <input type="checkbox"/> Integrated Desktop Computer <input type="checkbox"/> Workstation <input type="checkbox"/> Notebook Computer <input type="checkbox"/> Small-Scale Server
Product Category (see Tables 3 and 4 provided in this data sheet package):	<input type="checkbox"/> Category A <input type="checkbox"/> Category D <input checked="" type="checkbox"/> Category B <input type="checkbox"/> N/A <input type="checkbox"/> Category C
Processor Type/Model:	Intel, Core i7-620M
Processor Speed/Core (GHz):	2.66 GHz
# of CPU Cores/Processor Package:	2
# of Discrete Processor Packages Installed:	1
Operating System:	Windows 7
# of HDDs:	TOSHIBA , MK1060GSC , 100GB
RPMs for HDDs:	4200
# of Solid State Drives:	N/A
System Memory (GB):	8 GB
# of DIMMs Installed:	2
Video Card (GPU) Brand/Model:	N/A
Discrete GPU:	N/A
Discrete GPU Frame Buffer Width:	N/A
Video Card Dedicated Non-Shared Memory (MB)	N/A
Ethernet Capable System:	Yes
WOL Enabled from Sleep:	Enabled
WOL Enable from Off:	Enabled
Other:	Test with adopter, FSP084-DMAA1

**POWER SUPPLY REFERENCE PAGE**

Product Type:	<input type="checkbox"/> Internal	<input checked="" type="checkbox"/> External	
Manufacturer:	FSP Group Inc.		
Brand Name:	FSP		
Model Number/Designation:	FSP084-DMAA1		
Nameplate Rating:	Input:	100-240 V~, 1.3A, 50-60Hz	
	Output:	12.0V dc, 7.0A	
UL EEC Certified?	<input type="checkbox"/> Yes	<input type="checkbox"/> No	EEC Certificate #:
EPA Approved Lab certified?	<input type="checkbox"/> Yes	<input type="checkbox"/> No	Lab Info:

- The internal power supply shall meet the applicable requirements from Table 1 provided in this data sheet package. See separate data sheet package for the internal power supply testing.
- The external power supply with integral cooling fans shall meet the applicable requirements from Table 1 provided in this data sheet package. See separate data sheet package for the external power supply testing.
- The external power supply without integral cooling fans shall meet the level V performance requirements under the International Efficiency Marking Protocol and include the level V marking. ~~See separate data sheet package for the external power supply testing.~~

**FSP GROUP INC.**  
全漢企業股份有限公司  
全漢企業股份有限公司  
AC/DC Adapter(직류전원장치)  
電源供應器/電源适配器  
MODEL NO.(모델명) 型號/型号: FSP084-DMAA1  
AC INPUT(交流輸入/交流輸入): 100-240V~, 1.3A, 50-60Hz  
DC OUTPUT(直流輸出/直流輸出):  
12.0V --- 7.0A MAX (84W MAX)  
**CAUTION/주의사항: 警告!**  
FOR INDOOR USE ONLY.  
(室內使用/戶內使用)  
For use with information Technology Equipment.  
(適用於資訊類產品/適用於資訊類產品)  
본 제품은 실내용이며, IT제품에 사용하십시오.  
**ATTENTION:**  
Nur innerhalb von Gebäuden benutzen.  
Nur zur Verwendung mit informationstechnischen Einrichtungen.  
UL LISTED  
I.T.E. POWER SUPPLY  
E190414  
A/12614EA  
GS TÜV Rheinland Product Safety  
CE  
RoHS  
TÜV RT  
PS E  
CCC S&E  
RoHS  
TÜV RT  
PS E  
CCC S&E  
EFFICIENCY LEVEL: V  
HU10142-10054  
A/S: +82-2-571-6680  
Made in China - Zhonghan Electronics(Shenzhen) Co., Ltd.  
중지스미포블기존 민화제음  
生尊企業名稱: 仲汉电子(深圳)有限公司  
MADE IN CHINA (中國製造/中國製造) 6LL0906501GP FJ-1

## TECHNICIAN'S REFERENCE GUIDE

### Definitions:

**Desktop Computer:** A computer whose main unit is designed to be located in a permanent location, often on a desk or on the floor. Desktop computers are not designed for portability and are designed for use with an external display, keyboard, and mouse. Desktop computers are intended for a broad range of home and office applications.

**Integrated Desktop Computer:** A desktop computer in which the computing hardware and display are integrated into a single housing, and which is connected to ac mains power through a single cable. Integrated desktop computers come in one of two possible forms: (1) a system where the display and computer are physically combined into a single unit; or (2) a system packaged as a single system where the display is separate but is connected to the main chassis by a dc power cord and both the computer and display are powered from a single power supply. As a subset of desktop computers, integrated desktop computers are typically designed to provide similar functionality as desktop systems.

**Notebook Computer:** A computer designed specifically for portability and to be operated for extended periods of time both with and without a direct connection to an ac mains power source. Notebook computers include an integrated display and are capable of being powered by an integrated battery or other portable power source. In addition, most notebooks use an external power supply and have an integrated keyboard and pointing device. Notebook computers are typically designed to provide similar functionality to desktops, including operation of software similar in functionality as that used in desktops.

**Small-Scale Server:** A computer that typically uses desktop components in a desktop form factor, but is designed primarily to be a storage host for other computers. Small-scale Servers are designed to perform functions such as providing network infrastructure services (e.g., archiving) and hosting data/media. These products are not designed to process information for other systems or run web servers as a primary function.

**Thin Client:** An independently-powered computer that relies on a connection to remote computing resources to obtain primary functionality. Main computing functions (e.g., program execution, data storage, interaction with other Internet resources) are provided by the remote computing resources. Thin Clients covered by this specification are (1) limited to devices with no rotational storage media integral to the computer and (2) designed for use in a permanent location (e.g. on a desk) and not for portability.

**Workstation:** A high-performance, single-user computer typically used for graphics, CAD, software development, financial and scientific applications among other compute intensive tasks. Workstations covered by this specification (a) are marketed as a workstation; (b) provide mean time between failures (MTBF) of at least 15,000 hours (based on either Bellcore TR-NWT-000332, issue 6, 12/97 or field collected data); and (c) support error-correcting code (ECC) and/or buffered memory.

**Typical Energy Consumption (TEC):** A method of testing and comparing the energy performance of computers, which focuses on the typical electricity consumed by a product while in normal operation during a representative period of time.

## TECHNICIAN'S REFERENCE GUIDE (Cont'd)

### Definitions:

**Off Mode:** The lowest power mode which cannot be switched off (influenced) by the user and that may persist for an indefinite time when the appliance is connected to the main electricity supply and used in accordance with the manufacturer's instructions. For systems where ACPI standards are applicable, Off Mode correlates to ACPI System Level S5 state.

**Sleep Mode:** A low power mode that the computer enters automatically after a period of inactivity or by manual selection. A computer with Sleep capability can quickly "wake" in response to network connections or user interface devices with a latency of less than or equal to 5 seconds from initiation of wake event to system becoming fully usable including rendering of display. For systems where ACPI standards are applicable, Sleep Mode most commonly correlates to ACPI System Level S3 (suspend to RAM) state.

**Idle State:** The power state in which the operating system and other software have completed loading, a user profile has been created, activity is limited to those basic applications that the system starts by default, and the computer is not in Sleep Mode.

**Active State:** The power state in which the computer is carrying out useful work in response to a) prior or concurrent user input or b) prior or concurrent instruction over the network. Active State includes active processing, seeking data from storage, memory, or cache, including Idle State time while awaiting further user input and before entering low power modes.

### Significant Digits and Rounding:

All calculations shall be carried out with actual measured or observed values. Only the final result of a calculation shall be rounded. Calculated results shall be rounded to the nearest significant digit as expressed in the corresponding specification limit.

Unless otherwise specified, compliance with specification limits shall be evaluated using exact values without any benefit from further rounding.

## TECHNICIAN'S REFERENCE GUIDE (Cont'd)

### AC Input Power:

Products intended to be powered from AC mains shall be connected to a voltage source appropriate for the intended market, as specified in Table 1 or Table 2.

1. Products shipped with external power supplies (EPSs) shall first be connected to the EPS and then to the voltage source specified in Table 1 or Table 2.

**Table 1: Input Power Requirements for Products with  
Nameplate Rated Power Less Than or Equal to 1500 W**

Market	Voltage	Voltage Tolerance	Maximum Total Harmonic Distortion	Frequency	Frequency Tolerance
North America, Taiwan	115 Vac	+/- 1.0 %	2.0 %	60 Hz	+/- 1.0 %
Europe, Australia, New Zealand	230 Vac	+/- 1.0 %	2.0 %	50 Hz	+/- 1.0 %
Japan	100 Vac	+/- 1.0 %	2.0 %	50 Hz/60 Hz	+/- 1.0 %

**Table 2: Input Power Requirements for Products with  
Nameplate Rated Power Greater than 1500 W**

Market	Voltage	Voltage Tolerance	Maximum Total Harmonic Distortion	Frequency	Frequency Tolerance
North America, Taiwan	115 Vac	+/- 4.0 %	5.0 %	60 Hz	+/- 1.0 %
Europe, Australia, New Zealand	230 Vac	+/- 4.0 %	5.0 %	50 Hz	+/- 1.0 %
Japan	100 Vac	+/- 4.0 %	5.0 %	50 Hz/60 Hz	+/- 1.0 %

**Ambient Temperature:** Ambient temperature shall be from 18°C to 28°C.

**Relative Humidity:** Relative humidity shall be from 10% to 80%.

## TECHNICIAN'S REFERENCE GUIDE (Cont'd)

### Input Meter Considerations:

The power meter shall include the following attributes:

1. Crest Factor: Possesses an available current crest factor of 3 or more at its rated range value.
2. Minimum Frequency Response: 3.0 kHz
3. Minimum Resolution:
  - a. W for measurement values less than 10 W;
  - b. 0.1 W for measurement values from 10 W to 100 W; and
  - c. 1.0 W for measurement values greater than 100 W.

### Measurement Accuracy:

1. Power measurements with a value greater than or equal to 0.5 W shall be made with an uncertainty of less than or equal to 2% at the 95% confidence level.
2. Power measurements with a value less than 0.5 W shall be made with an uncertainty of less than or equal to 0.01 W at the 95% confidence level.

### User Information Requirements:

Based on the informational materials shipped with the product, please confirm the following:

Requirement	Yes/No	
(1) A description of power management settings that have been enabled by default,	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
(2) A description of the timing settings for various power management features, and	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
(3) Instructions for properly waking the product from Sleep Mode.	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
The information materials shipped with the product that contains the above information (1-3) have been reviewed and stored in eCommunications.	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No

Please confirm that the products are shipped with one or more of the following:

Requirement	Yes/No	
(1) A listed of default power management settings.	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
(2) A note stating that default power management settings have been selected for compliance with ENERGY STAR (within 15 min of user inactivity for the display, within 30 min for the computer, if applicable per Table 2), and are recommended by the ENERGY STAR program for optimal energy savings.	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
(3) Information about ENERGY STAR and the benefits of power management, to be located at or near the beginning of the hard copy or electronic user manual, or in a package or box insert.	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
The information materials shipped with the product that contains the above information (1-3) have been reviewed and stored in eCommunications.	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No

Tested by: \_\_\_\_\_ Tested by: \_\_\_\_\_ Test date: 2012-05-25  
signature print  
Sample #: 1385063-1~4 Instrument Code / Range: \_\_\_\_\_

---

## UUT PREPARATION FOR ALL PRODUCTS

Test Method (Rev. Aug-2010)

### METHOD

The unit was connected to a variable ac source of supply as indicated below.

- Desktops, Integrated Desktops, Notebooks, Thin Clients, Small-Scale Servers with Ethernet (IEEE 802.3) capability shall be connected to a live Ethernet network switch and any wireless radios shall be turned off. Computers without Ethernet capability must maintain a live wireless connection to a wireless router or network access point.
- Thin Clients shall be connected to a live server via a live Ethernet (IEEE 802.3) network switch and shall run intended terminal/remote connection software.
- Desktop computers, Small-Scale Servers and Thin Clients shipped without accessories shall be configured with a standard mouse, keyboard and external computer display (if server has display output functionality).
- Integrated Desktop computers shipped without accessories shall be configured with a standard mouse and keyboard.
- Notebook computers without an integrated pointing device or digitizer shall be configured with a mouse.
- Notebook computers shall not be configured with a docking station.
- Notebooks should have the battery pack(s) removed during testing. For systems where operation without a battery pack is not a supported configuration, the test may be performed with fully charged battery pack(s) installed, making sure to report this configuration in the test results.
- Desktops, Integrated Desktop, and Notebook Computers shall be tested with proxying features enabled or disabled as shipped.
- Primary hard drives shall not be power managed ("spun-down") during Idle testing unless containing non-volatile cache integral to the drive (e.g. "hybrid" hard drives or similar non-removable disk caching architectures). Any secondary internal hard drive(s) may be tested with hard drive power management enabled as shipped. If these additional drives are not power managed when shipped to customers, they shall be tested without such features implemented.

Tested by: \_\_\_\_\_ Tested by: \_\_\_\_\_ Test date: 2012-05-25  
signature print  
Sample # : 1385063-1~4 Instrument Code / Range: \_\_\_\_\_

---

**UUT PREPARATION FOR ALL PRODUCTS (Cont'd)**

Test Method (Rev. Aug-2010)

## METHOD

Record the ac voltage and frequency. Boot the computer and wait until the operating system has fully loaded. If necessary, run the initial operating system setup and allow all preliminary file indexing and other one-time/periodic processes to complete.

Record basic information about the computer's configuration – computer type, operating system name and version, processor type and speed, and total and available physical memory, etc.

Record basic information about the video card or graphics chipset (if applicable) - video card/chipset name, frame buffer width, resolution, amount of onboard memory, and bits per pixel.

Record in the following table if the product includes the following power management features in their "as-shipped" condition, subject to the following conditions:

- a. For Thin Clients, the WOL requirement shall apply products designed to receive software updates from a centrally managed network while in Sleep Mode or in Off Mode. Thin Clients whose standard software upgrade framework does not require off-hours scheduling are exempt from the WOL requirement.
- b. For Notebooks, WOL may be automatically disabled when the product is disconnected from ac mains power.
- c. For all products with WOL, directed packet filters shall be enabled and set to an industry standard default configuration.

Shut down the UUT.



Tested by: \_\_\_\_\_ Tested by: \_\_\_\_\_ Test date: 2012-05-25

signature

print

Sample # : 1385063-1~4 Instrument Code / Range: \_\_\_\_\_

**UUT PREPARATION FOR ALL PRODUCTS (Cont'd)**

Test Method (Rev. Aug-2010)

## RESULTS

Mode or Model Transition	Requirement	Yes/No	
		Yes	No
Sleep Mode	(1) Sleep Model shall be set to activate after no more than 30 minutes of user inactivity.  (2) The speed of any active 1 Gb/s Ethernet network links shall be reduced when transitioning to Sleep Mode or Off Mode.	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
Display Sleep Mode	(1) Display Sleep Mode shall be set to activate after no more than 15 minutes of user inactivity.	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
Wake on LAN (WOL)	(1) Computers with Ethernet capability shall provide users with an option to enable and disable WOL for Sleep Mode.  (2) Computers with Ethernet capability that are shipped through enterprise channels shall either: (a) be shipped with WOL enabled by default for Sleep Mode, when the computer is operating on ac mains power; or (b) provide users with the ability to enable WOL that is accessible from both the client operating system user interface and over the network.	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
Wake Management	1) Computers with Ethernet capability that are shipped through enterprise channels shall either: (a) be capable of both remote (via network) and scheduled (via real-time clock) wake events from Sleep Mode, and (b) provide clients with the ability to centrally manage (via vendor tools) any wake management settings that are configured through hardware settings if the manufacturer has control over such features.	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No

The power management features  meet  does not meet the requirements outlined in Table 2 provided in this data sheet package.

Tested by: \_\_\_\_\_ Tested by: \_\_\_\_\_ Test date: 2012-05-25  
signature print  
Sample # : 1385063-1~4 Instrument Code / Range: \_\_\_\_\_

**OFF MODE POWER CONSUMPTION TEST**

Test Method (Rev. Aug-2010)

## METHOD

The unit was connected to a variable ac source of supply as indicated below while in the off mode condition.

Computers shall be tested in their "as-shipped" condition for Off Mode. Models that will be shipped with WOL enabled for Off Mode shall be tested with WOL enabled.

With the UUT shut down and in Off, set the meter to begin accumulating true power values at an interval of less than or equal to 1 reading per second. Accumulative power values for 5 additional minutes and record the watt-hour value observed during that 5 minute period using both the "Wh" and time functions on the input meter. The average power consumed over that time period was then calculated.

Off Mode Unit Configuration Details:	
Operating System/Version:	Windows 7
Processor Type and Speed:	Intel core i7-620M, 2.66GHz
Total/Available Physical Memory:	8 GB
Wake On LAN (WOL) Enabled:	Enabled
Other:	Test with adopter, FSP084-DMAA1

Tested by: \_\_\_\_\_ Tested by: \_\_\_\_\_ Test date: 2012-05-25  
signature print  
Sample #: 1385063-1~4 Instrument Code / Range: \_\_\_\_\_

**OFF MODE POWER CONSUMPTION TEST (Cont'd)**

Test Method (Rev. Aug-2010)

## RESULTS

Ambient Temperature, °C 22 Relative Humidity, % 70

Input								Elapsed Time	
Required		Measured							
V	Hz	V	Hz	A	Wh	Wh Integration time, min	P <sub>OFF</sub> , WATTS***	TIME START	TIME END
100	50	100.04	50	0.08634	0.28552	5	3.42624	00'00"	05'00"
100	60	99.96	60	0.08573	0.28491	5	3.41892	00'00"	05'00"
115	60	114.94	60	0.07889	0.28613	5	3.43356	00'00"	05'00"
230	50	230.71	50	0.06568	0.30239	5	3.62868	00'00"	05'00"

- For Small-Scale Servers**, the measured input power P<sub>off</sub> during the measurement period:  
 exceeded  did not exceed \_\_\_\_\_ Watt(s)\*.

Note (\*) this value is derived from the Equation 5 Worksheet provided in this data sheet package.

The results  comply  do not comply with the ENERGY STAR Program Requirements Product Specification for Computers, Version 5.2.

- For Thin Clients**, the measured input power P<sub>off</sub> during the measurement period:  
 exceeded  did not exceed \_\_\_\_\_ Watt(s)\*\*.

Note (\*\*) this value is derived from the Equation 6 Worksheet provided in this data sheet package.

The results  comply  do not comply with the ENERGY STAR Program Requirements Product Specification for Computers, Version 5.2.

\*\*\* The average power is calculated by the following equation:

$$\text{Avg. Power (Watts)} = (\text{Wh} \times 60 \text{ minutes/hr}) / (\text{Wh Interval, minutes})$$

## Supplemental Information:

- For UUT running Windows, "Off" is defined as selecting "Shut Down" from the start menu.
- For UUT running Linux, "Off" is defined as typing the "shutdown -h now" command from the Command Line Interface (CLI).
- Other:

Tested by: \_\_\_\_\_ Tested by: \_\_\_\_\_ Test date: 2012-05-25  
signature print  
Sample #: 1385063-1~4 Instrument Code / Range: \_\_\_\_\_

**IDLE MODE POWER CONSUMPTION TEST**

Test Method (Rev. Aug-2010)

## METHOD

Immediately after the off mode power consumption test, switch on the computer and begin recording elapsed time after completing any login activity necessary to fully boot the system. Once logged in with the operating system fully loaded and ready, close any open windows so that the standard operational desktop screen or equivalent ready screen is displayed. Between 5 and 15 minutes after the initial boot or log in, set the meter to begin accumulating true power values at an interval or greater than or equal to 1 reading per second. Accumulate power values for 5 additional minutes and record the watt-hour value value observed during that 5 minute period using both the "Wh" and time functions on the input meter. The average power consumed over that time period was then calculated.

- For Computers with external computer displays (most desktops), use the computer display power management setting to prevent the display from powering down to ensure it stays on for the full length of the Idle Mode Power Consumption Test as described below.
- For Computers with integrated computer displays (notebooks and integrated systems), use the power management settings to set the display to power down after 1 minute.
- For Small-Scale Servers and Thin Clients, if the initial unit tested is less than or equal to the applicable requirements for idle but falls within 10% of that level, one additional unit of the same model with an identical configuration must also be tested.

Idle Mode Unit Configuration Details:	
Operating System/Version:	Windows 7
Processor Type and Speed:	Intel core i7-620M, 2.66GHz
Total/Available Physical Memory:	8 GB
Wake On LAN (WOL) Enabled:	Enabled
Other:	Test with adopter, FSP084-DMAA1

Tested by: \_\_\_\_\_ Tested by: \_\_\_\_\_ Test date: 2012-05-25  
signature print  
Sample #: 1385063-1~4 Instrument Code / Range: \_\_\_\_\_

**IDLE MODE POWER CONSUMPTION TEST (Cont'd)**

Test Method (Rev. Aug-2010)

Ambient Temperature, °C 22 Relative Humidity, % 70

Input								Elapsed Time		
Required		Measured						Elapsed Time		
V	Hz	V	Hz	A	Wh	Wh Integration time, min	P <sub>idle</sub> , Watts***	Verified Screen Power Management Set for 1 minute (Y) Integrated Display Only	Time Start	Time End
100	50	100.1	50	0.7876	3.3826	5	40.5912	N/A	00'00"	05'00"
100	60	99.94	60	0.8665	3.3841	5	40.6092	N/A	00'00"	05'00"
115	60	115.17	60	0.7358	3.3696	5	40.4352	N/A	00'00"	05'00"
230	50	229.83	50	0.3957	3.3404	5	40.0848	N/A	00'00"	05'00"

 **For Small-Scale Servers:**

The measured input power P<sub>idle</sub> during the measurement period  exceeded  did not exceed \_\_\_\_\_ Watt(s)\*.

Note (\*) this value is derived from table 10 provided in this data sheet package.

The results  comply  do not comply with the ENERGY STAR Program Requirements Product Specification for Computers, Version 5.2.

 **For Thin Clients:**

The measured input power P<sub>idle</sub> during the measurement period  exceeded  did not exceed \_\_\_\_\_ Watt(s)\*\*.

Note (\*\*) this value is derived from table 11 provided in this data sheet package.

The results  comply  do not comply with the ENERGY STAR Program Requirements Product Specification for Computers, Version 5.2.

\*\*\* The average power is calculated by the following equation:

$$\text{Avg. Power (Watts)} = (\text{Wh} \times 60 \text{ minutes/hr}) / (\text{Wh Interval, minutes})$$

Tested by: \_\_\_\_\_ Tested by: \_\_\_\_\_ Test date: 2012-05-25  
signature print  
Sample # : 1385063-1~4 Instrument Code / Range: \_\_\_\_\_

## SLEEP MODE POWER CONSUMPTION TEST

Test Method (Rev. Aug-2010)

### METHOD

After completing the idle measurements, measure the time of user inactivity to place both the computer and display in sleep mode.

Then, reset the meter (if necessary) and begin accumulating true power values at an interval of greater than or equal to 1 reading per second. Accumulate power values for 5 additional minutes and record the watt-hour value value observed during that 5 minute period using both the "Wh" and time functions on the input meter. The average power consumed over that time period was then calculated.

- If testing both WOL enabled and WOL disabled for Sleep, wake the computer and change the WOL from Sleep setting through the operating system settings or by other means. Repeat the sleep mode test with the alternate configuration.

Sleep Mode Unit Configuration Details:	
Operating System/Version:	Windows 7
Processor Type and Speed:	Intel core i7-620M, 2.66GHz
Total/Available Physical Memory:	8 GB
Wake On LAN (WOL) Enabled:	Enabled
Other:	Test with adopter, FSP084-DMAA1

Tested by: \_\_\_\_\_ Tested by: \_\_\_\_\_ Test date: 2012-05-25  
signature print

Sample #: 1385063-1~4 Instrument Code / Range: \_\_\_\_\_

**SLEEP MODE POWER CONSUMPTION TEST (Cont'd)**

Test Method (Rev. Aug-2010)

## RESULTS

Ambient Temperature, °C 22 Relative Humidity, % 70

Input									
Required		Measured						Elapsed Time	
V	Hz	V	Hz	A	Wh	Wh Integration time, min	P <sub>sleep</sub> , Watts**	Time Start	Time End
100	50	100	50	0.12156	0.40882	5	4.90584	00'00"	05'00"
100	60	99.96	60	0.11887	0.41285	5	4.9542	00'00"	05'00"
115	60	115.16	60	0.11224	0.41049	5	4.92588	00'00"	05'00"
230	50	230.63	50	0.07898	0.43063	5	5.16756	00'00"	05'00"

 **For Thin Clients:**

The measured input power P<sub>sleep</sub> during the measurement period  exceeded  did not exceed \_\_\_\_\_ Watt(s)\*.

Note (\*) this value is derived from the Equation 7 Worksheet provided in this data sheet package.

The results  comply  do not comply with the ENERGY STAR Program Requirements Product Specification for Computers, Version 5.2.

## Notes:

\*\* The average power is calculated by the following equation:

$$\text{Avg. Power (Watts)} = (\text{Wh} \times 60 \text{ minutes/hr}) / (\text{Wh Interval, minutes})$$

Tested by: \_\_\_\_\_ Tested by: \_\_\_\_\_ Test date: \_\_\_\_\_  
signature print

Sample #: \_\_\_\_\_ Instrument Code / Range: \_\_\_\_\_

## MAXIMUM POWER TEST FOR WORKSTATIONS

Test Method (Rev. Aug-2010)

### Method

Record the ac voltage and frequency. The meter should be able to store and output the maximum power measurement reached during the test.

Run linpack (linx) with the memory allocation set to: \_\_\_\_\_ mb and the number of tests set to: \_\_\_\_\_.

Run specviewperf10/specviewperf10 with multithreading for all tests at the highest resolution supported by the display and graphic card used.

Set the meter to begin accumulating true power values at an interval of less than or equal to 1 reading per second, and begin taking measurements. Accumulate power values until specviewperf and all its instances have completed running. Record the maximum power value attained during the test.

This test must be repeated three times on the same UUT, and all three measurements must fall within a  $\pm 2\%$  tolerance relative to the average of the three measured maximum power values.

### Maximum Mode Unit Configuration Details:

Operating System/Version:	
Processor Type and Speed:	
Total/Available Physical Memory:	
Wake On LAN (WOL) Enabled:	
# of HDDs:	
Other:	

Johnny Hung  
2012-05-24





## WORKSHEETS

Equation 1: Calculation Of Typical Annual Electricity Use ( $E_{TEC}$ ) for Desktop, Integrated Desktop, and Notebook Computers:

$$E_{TEC} = (8760/1000) * (P_{off} * T_{off} + P_{sleep} * T_{sleep} + P_{idle} * T_{idle}),$$

Where all  $P_x$  are power values in watts, all  $T_x$  are mode weightings as specified in Table 5 (for Desktops and Integrated Desktops) or Table 6 (for Notebooks) , and the  $E_{TEC}$  is in units of kWh and represents annual consumption based on mode weightings.

Input		Calculated			
V	Hz	$P_{off}$	$P_{idle}$	$P_{sleep}$	$E_{TEC}$
100	50	3.42624	40.5912	4.90584	160.89
100	60	3.41892	40.6092	4.9542	160.94
115	60	3.43356	40.4352	4.92588	160.39
230	50	3.62868	40.0848	5.16756	160.20

Equation 2: Calculation of Maximum Typical Annual Electricity Use ( $E_{TEC\_MAX}$ ) For Desktop, Integrated Desktop, and Notebook Computers:

$$E_{TEC\_MAX} \text{ (kWh)} = TEC_{BASE} + TEC_{MEMORY} + TEC_{GRAPHICS} + TEC_{STORAGE}$$

Where  $TEC_{BASE}$ ,  $TEC_{MEMORY}$ ,  $TEC_{GRAPHICS}$  and  $TEC_{STORAGE}$  are adders as specified in Table 7 (for Desktops and Integrated Desktops) or Table 8 (for Notebooks).

Calculated				
$TEC_{BASE}$ (kWh)	$TEC_{MEMORY}$ (kWh)	$TEC_{GRAPHICS}$ (kWh)	$TEC_{STORAGE}$ (kWh)	$E_{TEC\_MAX}$ (kWh)
175	6	0	0	181

For Desktops, Integrated Desktop, and Notebook Computers, the calculated  $E_{TEC}$   exceeded  did not exceed  $E_{TEC\_MAX}$  .

The results  comply  do not comply with the ENERGY STAR Program Requirements Product Specification for Computers, Version 5.2.

For Desktops, Integrated Desktop, and Notebook Computers, if the initial unit tested is less than or equal to the applicable requirements for TEC but falls within 10% of that level, one additional unit of the same model with an identical configuration must also be tested.

### WORKSHEETS (Cont'd)

Equation 3: Calculation of Weighted Power Consumption ( $P_{TEC}$ ) for Workstations:

$$P_{TEC} = (P_{off} * T_{off}) + (P_{sleep} * T_{sleep}) + (P_{idle} * T_{idle}),$$

Where all  $P_x$  are power values in watts, all  $T_x$  are mode weightings as specified in Table 9.

Input		Calculated			
V	Hz	$P_{off}$	$P_{idle}$	$P_{sleep}$	$P_{TEC}$

Equation 4: Calculation of Maximum Weighted Power Consumption ( $P_{TEC\_MAX}$ ) for Workstations:

$$P_{TEC\_MAX} (W) \leq 0.28 * \{P_{MAX} + (N_{HDD} * 5)\},$$

Where  $P_{MAX}$  = measured maximum power consumption (W) and  $N_{HDD}$  = number of installed hard disk drives (HDD) or solid state drives (SSD).

$P_{MAX} (W)$	$N_{HDD}$	$P_{TEC\_MAX} (W)$

For Workstations, the calculated  $P_{TEC}$   exceeded  did not exceed  $P_{TEC\_MAX}$ .

The results  comply  do not comply with the ENERGY STAR Program Requirements Product Specification for Computers, Version 5.2.

For Workstations, if the initial unit tested is less than or equal to the applicable requirements for TEC but falls within 10% of that level, one additional unit of the same model with an identical configuration must also be tested.

Johnny Hung 2012-05-24
---------------------------

**WORKSHEETS (Cont'd)**

Equation 5: Calculation of Maximum Off Mode Power Consumption ( $P_{off\_Max}$ ) for Small-Scale Servers:

$$P_{OFF\_MAX} (W) = P_{OFF\_BASE} + P_{OFF\_WOL},$$

Where  $P_{OFF\_WOL}$  shall only be applied to products that offer WOL that is enabled by default upon shipment.

$P_{OFF\_BASE} (W)$	$P_{OFF\_WOL}$	$P_{OFF\_MAX} (W)$

Equation 6: Calculation of Maximum Off Mode Power Consumption ( $P_{off\_Max}$ ) for Thin Clients:

$$P_{OFF\_MAX} (W) = P_{OFF\_BASE} + P_{OFF\_WOL},$$

Where  $P_{OFF\_WOL}$  shall only be applied to products that offer WOL that is enabled by default upon shipment.

$P_{OFF\_BASE} (W)$	$P_{OFF\_WOL}$	$P_{OFF\_MAX} (W)$

Equation 7: Calculation of Maximum Sleep Mode Power Consumption ( $P_{sleep\_Max}$ ) for Thin Clients:

$$P_{SLEEP\_MAX} (W) = P_{SLEEP\_BASE} + P_{SLEEP\_WOL},$$

Where  $P_{SLEEP\_WOL}$  shall only be applied to products that offer WOL that is enabled by default upon shipment.

$P_{SLEEP\_BASE} (W)$	$P_{SLEEP\_WOL}$	$P_{SLEEP\_MAX} (W)$

Johnny Hung  
2012-05-24

**Table 1:**  
**Requirements for Internal Power Supplies and External Power Supplies with Integral Cooling**

<b>Loading Condition (Percentage of Nameplate Output Current)</b>	<b>Minimum Efficiency</b>	<b>Minimum Power Factor</b>
20%	0.82	-
50%	0.85	-
100%	0.82	0.90

**Table 2:  
Power management requirements**

Mode or Mode Transition	Requirement	Desktops	Integrated Desktops	Notebooks	Workstations	Small-scale Servers	Thin Clients
Sleep Mode	(1) Sleep Mode shall be set to activate after no more than 30 minutes of user inactivity. (2) The speed of any active 1 Gb/s Ethernet network links shall be reduced when transitioning to Sleep Mode or Off Mode.	Yes	Yes	Yes	Yes	No	No
Display Sleep Mode	(1) Display Sleep Mode shall be set to activate after no more than 15 minutes of user inactivity.	Yes	Yes	Yes	Yes	Yes	Yes
Wake on LAN (WOL)	(1) Computers with Ethernet capability shall provide users with an option to enable and disable WOL for Sleep Mode. (2) Computers with Ethernet capability that are shipped through enterprise channels shall either: (a) be shipped with WOL enabled by default for Sleep Mode, when the computer is operating on ac mains power; or (b) provide users with the ability to enable WOL that is accessible from both the client operating system user interface and over the network.	Yes	Yes	Yes	Yes	Yes	Yes
Wake Management	(1) Computers with Ethernet capability that are shipped through enterprise channels shall: (a) be capable of both remote (via network) and scheduled (via real-time clock) wake events from Sleep Mode, and (b) provide clients with the ability to centrally manage (via vendor tools) any wake management settings that are configured through hardware settings if the manufacturer has control over such features.	Yes	Yes	Yes	Yes	Yes	Yes

**Table 3:  
Categorization of Desktop and Integrated Desktop Computers**

<b>Category A</b>	All desktop computers that do not meet the definition of Category B, Category C, or Category D below will be considered under Category A for ENERGY STAR qualification.
<b>Category B</b>	To qualify under Category B, desktops <u>must</u> have: <ul style="list-style-type: none"> <li>▪ Equal to 2 Physical Cores; and</li> <li>▪ Greater than or equal to 2 gigabytes (GB) of System Memory.</li> </ul>
<b>Category C</b>	To qualify under Category C, desktops <u>must</u> have: <ul style="list-style-type: none"> <li>▪ Greater than 2 Physical Cores.</li> </ul> In addition to the requirement above, models qualifying under Category C must be configured with a minimum of 1 of the following 2 characteristics: <ul style="list-style-type: none"> <li>▪ Greater than or equal to 2 gigabytes (GB) of System Memory; and/or</li> <li>▪ A Discrete GPU.</li> </ul>
<b>Category D</b>	To qualify under Category D, desktops <u>must</u> have: <ul style="list-style-type: none"> <li>▪ Greater than or equal to 4 Physical Cores.</li> </ul> In addition to the requirement above, models qualifying under Category D must be configured with a minimum of 1 of the following 2 characteristics: <ul style="list-style-type: none"> <li>▪ Greater than or equal to 4 gigabytes (GB) of System Memory; and/or</li> <li>▪ A Discrete GPU with a Frame Buffer Width greater than 128-bit.</li> </ul>

**Table 4:  
Categorization of Notebook Computers**

<b>Category A</b>	All notebook computers that do not meet the definition of Category B or Category C below will be considered under Category A for ENERGY STAR qualification.
<b>Category B</b>	To qualify under Category B, notebooks <u>must</u> have: <ul style="list-style-type: none"> <li>▪ A Discrete GPU.</li> </ul>
<b>Category C</b>	To qualify under Category C, notebooks <u>must</u> have: <ul style="list-style-type: none"> <li>▪ Greater than or equal to 2 Physical Cores;</li> <li>▪ Greater than or equal to 2 gigabytes (GB) of System Memory; and</li> <li>▪ A Discrete GPU with a Frame Buffer Width greater than 128-bit.</li> </ul>

**Table 5:  
Mode Weightings for Desktop and Integrated Desktop Computers**

Mode Weighting	Conventional	Full Network Connectivity			
		Base Capability	Remote Wake	Service Discovery/Name Services	Full Proxying
T <sub>off</sub>	55%	50%	47%	43%	40%
T <sub>sleep</sub>	5%	14%	20%	25%	30%
T <sub>idle</sub>	40%	36%	33%	32%	30%

**Table 6:  
Mode Weightings for Notebook Computers**

Mode Weighting	Conventional	Full Network Connectivity			
		Base Capability	Remote Wake	Service Discovery / Name Services	Full Proxying
T <sub>off</sub>	60%	54%	49%	48%	45%
T <sub>sleep</sub>	10%	18%	24%	26%	30%
T <sub>idle</sub>	30%	28%	27%	26%	25%

**Table 7:  
Maximum TEC Allowances for Desktop and Integrated Desktop Computers**

Product Category	TEC <sub>BASE</sub> (kWh)	TEC <sub>MEMORY</sub> (kWh) <i>Where: m = System Memory (GB)</i>	TEC <sub>GRAPHICS</sub> (kWh)	TEC <sub>STORAGE</sub> (kWh) <i>(Applies once if system has more than one Additional Internal Storage element.)</i>
A	148.0	1.0 <i>(per GB &gt; 2.0)</i>	35.0 <i>(GPU Frame Buffer Width ≤ 128-bit)</i>	25.0
			50.0 <i>(GPU Frame Buffer Width &gt; 128-bit)</i>	
B	175.0	1.0 <i>(per GB &gt; 2.0)</i>	35.0 <i>(GPU Frame Buffer Width ≤ 128-bit)</i>	25.0
			50.0 <i>(GPU Frame Buffer Width &gt; 128-bit)</i>	
C	209.0	1.0 <i>(per GB &gt; 2.0)</i>	50.0 <i>(GPU Frame Buffer Width &gt; 128-bit)</i>	25.0
D	234.0	1.0 <i>(per GB &gt; 4.0)</i>	50.0 <i>(GPU Frame Buffer Width &gt; 128-bit)</i>	25.0



**Table 8:  
Maximum TEC Allowances for Notebook Computers**

Product Category	TEC <sub>BASE</sub> (kWh)	TEC <sub>MEMORY</sub> (kWh) <i>Where: m = System Memory (GB)</i>	TEC <sub>GRAPHICS</sub> (kWh)	TEC <sub>STORAGE</sub> (kWh) <i>(Applies once if system has more than one Additional Internal Storage element.)</i>
<b>A</b>	40.0	0.4 <i>(per GB &gt; 4.0)</i>	-	3.0
<b>B</b>	53.0	0.4 <i>(per GB &gt; 4.0)</i>	3.0 <i>(GPU Frame Buffer Width &gt; 64-bit)</i>	3.0
<b>C</b>	88.5	0.4 <i>(per GB &gt; 4.0)</i>	-	3.0

**Table 9:  
Mode Weightings for Workstations**

T <sub>OFF</sub>	T <sub>SLEEP</sub>	T <sub>IDLE</sub>
0.35	0.10	0.55

**Table 10:  
Classification & Power Consumption Requirements for Small-scale Servers**

Small-scale Server Classification		Operational Mode Requirements		
Product Category	Category Description	$P_{OFF\ BASE}$ (watts)	$P_{OFF\ WOL}$ (watts)	$P_{IDLE\ MAX}$ (watts)
A	All Small-Scale Servers that do not meet the definition of Category B will be considered under Category A for ENERGY STAR qualification.	2.0	0.7	50.0
B	To qualify under Category B Small-Scale Servers must have: <ul style="list-style-type: none"> <li>• Processor(s) with greater than 1 physical core or greater than 1 discrete processor; and</li> <li>• Minimum of 1 gigabyte of system memory.</li> </ul>	2.0	0.7	65.0

**Table 11:  
Classification & Power Consumption Requirements for Thin Clients**

Thin Client Classification		Operational Mode Requirements				
Product Category	Category Description	$P_{OFF\ BASE}$ (watts)	$P_{OFF\ WOL}$ (watts)	$P_{SLEEP\ BASE}$ (watts)	$P_{SLEEP\ WOL}$ (watts)	$P_{IDLE\ MAX}$ (watts)
A	All Thin Clients that do not meet the definition of Category B, below, will be considered under Category A for ENERGY STAR qualification.	2.0	0.7	2.0	0.7	12.0
B	To qualify under Category B, Thin Clients must support local multimedia encode/decode.	2.0	0.7	2.0	0.7	15.0