

Verification of Compliance

Product Name : Fanless Multi-Touch PPC
Brand Name : AAEON
Model Number : ACP-1103xxx-Ax-xxxx (x is 0-9,A-Z ,” - “or blank)
Applicant : AAEON Technology Inc.
Address : 5F, No. 135, Lane 235, Pao Chiao Rd., Hsin-Tien Dist.,
New Taipei City 23145, Taiwan, R.O.C
Report Number : F-A600-1307-006
Issue Date : August 6, 2013

Applicable Standards : FCC Part 15, Subpart B Class A ITE
ANSI C63.4:2009
Industry Canada ICES-003 Issue 5
CSA-IEC CISPR22-10 Class A ITE

One sample of the designated product has been tested in our laboratory and found to be in compliance with the FCC rules cited above.



NVLAP LAB CODE 200575-0

TAF 0905

FCC CAB Code TW1053

IC Code 4699A

VCCI Accep. No. R-1527, C-1609, T-1441, G-10,
C-4400, T-1334, G-614



Central Research Technology Co.
EMC Test Laboratory
11, Lane41, Fushuen St., Jungshan Chiu,
Taipei, Taiwan, 104, R.O.C.
Tel : 886-2-25984568
Fax: 886-2-25984546

(Tsun-Yu Shih/ General Manager)

Date: August 6, 2013

FCC Test Report

for

Fanless Multi-Touch PPC

Trade Name : AAEON
Model Number : ACP-1103xxx-Ax-xxxx
(x is 0-9,A-Z ,” - “or blank)
Report Number : F-A600-1307-006
Date of Receipt : July 18, 2013
Date of Report : August 6, 2013

Prepared for

AAEON Technology Inc.

5F, No. 135, Lane 235, Pao Chiao Rd., Hsin-Tien Dist., New Taipei City 23145,
Taiwan, R.O.C

Prepared by



Central Research Technology Co. **EMC Test Laboratory**

11, Lane 41, Fushuen St., Jungshan Chiu, Taipei, Taiwan, 104, R.O.C.



NVLAP LAB CODE 200575-0

This report shall not be reproduced, except in full, without the written approval of Central Research Technology Co.. It may be duplicated completely in its entirety for legal use with the permission of the applicant. It should not be used to claim product endorsement by NVLAP, NIST or any U.S. government agency. The test result in the report applies only to the sample tested.

Verification of Compliance

Equipment Under Test : Fanless Multi-Touch PPC
Model No. : ACP-1103xxx-Ax-xxxx (x is 0-9,A-Z ,” - “or blank)
Applicant : AAEON Technology Inc.
Address : 5F, No. 135, Lane 235, Pao Chiao Rd., Hsin-Tien Dist.,
New Taipei City 23145, Taiwan, R.O.C
Applicable Standards : **FCC Part 15, Subpart B Class A ITE**
ANSI C63.4:2009
Industry Canada ICES-003 Issue 5
CSA-IEC CISPR22-10 Class A ITE

Date of Testing : July 19~30, 2013
Deviation : N/A
Condition of Test Sample : Engineering Sample



We, **Central Research Technology Co.**, hereby certify that one sample of the designated product was tested in our facility during the period mentioned above. The test records, data evaluation and Equipment Under Test (EUT) configurations shown in the present report are true and accurate representation of the measurements of the sample's EMC characteristics under the conditions herein specified.

The test results show that the EUT as described in the present report is in compliance with the requirements set forth in the standards mentioned above and apply to the tested sample identified in the present report only. The test report shall not be reproduced, except in its entirety, without the written approval of Central Research Technology Co.

PREPARED BY : Iris Chen , **DATE** : Aug. 6, 2013
(Iris Chen/System Executive)

APPROVED BY : Tsun-Yu Shih , **DATE** : Aug. 6, 2013
(Tsun-Yu Shih/General Manager)

Contents

1. General Description	4
1.1 General Description of EUT.....	4
1.2 Test Mode.....	5
1.3 Applied standards	6
1.4 Test Setup for the EUT.....	7
1.5 The Support Units	8
1.6 Layout of the Setup.....	9
1.7 Test Capability	10
2. Conducted Emission Measurement.....	12
2.1 Limits for Emission Measurement.....	12
2.2 Test Instruments.....	13
2.3 Test Procedures	15
2.4 Test Configurations.....	16
2.5 Photographs of the Test Configurations.....	17
2.6 Test Results	18
3. Radiated Emission Measurement	20
3.1 Limits for Emission Measurement.....	20
3.2 Test Instruments.....	21
3.3 Test Procedures	24
3.4 Test Configurations.....	25
3.5 Photographs of the Test Configurations.....	26
3.6 Test Results	27
Attachment 1 Photographs of EUT	31
Attachment 2 Modifications of EUT	37

1. General Description

1.1 General Description of EUT

Equipment Under Test : Fanless Multi-Touch PPC

Model No. : ACP-1103xxx-Ax-xxxx (x is 0-9,A-Z ,” - “or blank)

Power in : Supplied by the power adapter

Power Adapter Specification : Trade Name : FSP
 Model No. : FSP060-DBAE1
 Input : 100-240V~ 1.5A, 50-60Hz
 Output : 12Vdc, 5A Max

Highest Operating Frequency : 1.6GHz from the test specification

Manufacturer : AAEON Technology Inc.

Function Description :

The EUT is an engineering sample of the Fanless Multi-Touch PPC. Please refer to the user’s manual for the details.

The I/O ports of EUT are listed below:

No.	I/O Port Type	Quantity
1	RS232 / RS422 / RS485 port	3
2	USB port	4
3	LAN port	1
4	MINI HDMI port	1

1.2 Test Mode

The Resolution 1280*800@75Hz was selected by its manufacturer to perform all tests. It was taken as the representative condition for testing and its data are recorded in the present document.

1.3 Applied standards

According to the specifications of the manufacturer and the requirements set in 47CFR Part 15, the applied standards to evaluate the compliance of the EUT are as following, and the measurement procedures specified in ANSI C63.4: 2009 are performed.

According to 47CFR Part 15 Section 15.33(b), the test frequency range of radiated emission measurements are listed below and the EUT herein shall be tested as:

Type of EUT	Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
<input type="checkbox"/>	Below 1.705	30
<input type="checkbox"/>	1.705 - 108	1000
<input type="checkbox"/>	108 - 500	2000
<input type="checkbox"/>	500 - 1000	5000
<input checked="" type="checkbox"/>	Above 1000	5 th harmonic of the highest frequency or 40GHz, whichever is lower

All the test items are as following:

Applied Standards	Test Items	Results
FCC Part 15, Subpart B Class A ITE	<input checked="" type="checkbox"/> Conducted Emission Measurement	<u>PASS</u>
	<input checked="" type="checkbox"/> Radiated Emission Measurement	<u>PASS</u>

1.4 Test Setup for the EUT

The EUT is an unique unit connected with other necessary accessories and support units listed in the next section. It has been tested against each standard after the following steps:

- a. Connect the EUT and all the support units to the appropriate power source.
- b. Turn on the EUT and all the accessories and support units.
- c. The EUT load an EMC test software and execute it under the Windows environment.
- d. The EUT sends “H” patterns to the monitor, which fills the whole screen of it.
- e. The EUT reads/writes messages from/to USB Flash Disk continuously.
- f. The EUT sends message to modem.
- g. Another PC sends/receives messages to/from the EUT through a Hub by executing the command of “PING”.
- h. Repeat and keep the setup steps listed above before and during all tests.

EUT I/O ports / Peripherals	Exerciser Program (software)	Version of Program
EUT	BurnIn Test.exe	V 7.0
Monitor		
USB Flash Disk		
Modem		

1.5 The Support Units


Conducted Emission Test

No.	Unit	Model No.	FCC ID	Trade Name	Power Cord	Supported by lab.
1	USB Mouse	MO56UC	DoC	DELL	N/A	✓
2	USB Keyboard	SK-8115	DoC	DELL	N/A	✓
3	Monitor	U2410	DoC	DELL	1.8m	✓
4	USB Flash Disk	U172	DoC	PQI	N/A	✓
5	Modem	DM-1414	IFAXDM1414	ACEEX	1.8m	✓

Radiated Emission Test

No.	Unit	Model No.	FCC ID	Trade Name	Power Cord	Supported by lab.
1	USB Mouse	MS111-P	N/A	DELL	N/A	✓
2	USB Keyboard	SK-8115	DoC	DELL	N/A	✓
3	Monitor	U2410	DoC	DELL	1.8m	✓
4	USB Flash Disk	U172	DoC	PQI	N/A	✓
5	Modem	DM-1414	IFAXDM1414	ACEEX	1.8m	✓

1.6 Layout of the Setup



Connecting Cables :

No.	Cable	Length	Shielded	Core	Shielded Backshell	Supported by lab.	Note
A	USB Mouse Cable	1.8m	✓			✓	
B	USB Keyboard Cable	1.8m	✓			✓	
C	Mini HDMI to HDMI Cable	2.0m	✓			✓	
D1	RS232 Cable	0.16m	✓				
D2		1.8m	✓	✓		✓	2 cores
E	LAN Cable	1.8m				✓	

1.7 Test Capability

Test Facility

The test facility used for evaluating the conformance of the EUT with each standard in the present report meets what required in CISPR16-1-4, CISPR16-2-3 and ANSI C63.4: 2009.

Test Room	Type of Test Room	Descriptions
TR1	10m semi-anechoic chamber (23m × 14m × 9m)	Complying with the NSA and the site VSWR requirements in documents CISPR 22 and ANSI C63.4: 2009. for the radiated emission measurement.
TR1	3m fully-anechoic chamber (23m × 14m × 9m)	
TR11	3m semi-anechoic chamber (9m × 6m × 6m)	Complying with the NSA requirements in documents CISPR 22 for the radiated emission measurement.
TR5	Shielding Room (8m × 5m × 4m)	For the conducted emission measurement.
TR4	Shielding Room (5m×3m×3m)	

Test Laboratory Competence Information

Central Research Technology Co. has been accredited / filed / authorized by the agencies listed in the following table.

Certificate	Nation	Agency	Code	Mark
Accreditation Certificate	USA	NVLAP	200575-0	ISO/IEC 17025
	R.O.C. (Taiwan)	TAF	0905	ISO/IEC 17025
	R.O.C. (Taiwan)	BSMI	SL2-IN-E-0033, SL2-IS-E-0033, SL2-R1/R2-E-0033, SL2-A1-E-0033 SL2-L1-E-0033	ISO/IEC 17025
Site Filing Document	USA	FCC	474046,TW1053	Test facility list & NSA Data
	Canada	IC	4699A-1,-3	Test facility list & NSA Data
	Japan	VCCI	R-1527,C-1609, C-4400, T-1441, T-1334, G-10, G-614	Test facility list & NSA Data
Authorization Certificate	Germany	TUV	10021687	ISO/IEC 17025
	Norway	Nemko	ELA 212	ISO/IEC 17025

The copy of each certificate can be downloaded from our web site: www.crc-lab.com

2. Conducted Emission Measurement

Test Result : PASS

2.1 Limits for Emission Measurement

Limits for conducted disturbances at the power mains

Frequency (MHz)	Class A Equipment		Class B Equipment	
	Quasi-peak (dBµV)	Average (dBµV)	Quasi-peak (dBµV)	Average (dBµV)
0.15 to 0.5	79	66	66 – 56	56 – 46
0.5 to 5	73	60	56	46
5 to 30	73	60	60	50

Note 1- The lower limit shall apply at the transition frequency.
 Note 2- The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5MHz for Class B equipment.

2.2 Test Instruments

Test Site and Equipment	Manufacturer	Model No./ Serial No.	Last Calibration Date	Calibration Due Date
Test Receiver	R&S	ESCS 30/ 836858/021	Jan. 14, 2013	Jan. 14, 2014
LISN	R&S	ESH2-Z5/ 880669/039	March 15, 2013	March 15, 2014
2 nd LISN	R&S	ENV4200/ 833209/010	March 29, 2013	March 29, 2014
50Ω terminator	N/A	N/A/ 001	Aug. 20, 2012	Aug. 20, 2013
RF Switch	R&S	RSU28/ 338965/002	Feb. 19, 2013	Aug. 19, 2013
RF Cable	N/A	N/A/ C0052 ~ 56	Feb. 19, 2013	Aug. 19, 2013
Test Software	Audix	e3/ Ver. 5.2004-2-19k	NCR	NCR
TR5 shielded room	ETS LINDGREN	TR5/ 15353-F	NCR	NCR

Note:

1. The calibrations are traceable to NML/ROC.
2. NCR : No Calibration Required.

Measurement Uncertainty


The assessed measurement uncertainty with a suitable coverage factor K to ensure 95% confidence level for the normal distribution are shown as below, the values are less than U_{CISPR} in table 1 of CISPR 16-4-2.

Equipment	Model Number	Uncertainty Value
LISN	ESH2-Z5	3.1dB
	ENV 4200	2.7dB

2.3 Test Procedures

- a. The EUT was set up per the test configuration figured in the next section of this chapter to simulate the typical usage per the user's manual.
- b. If the EUT is tabletop equipment, it was placed on a non-conducted table with a height of 0.8 meters above the reference ground plane and 0.4 meters from the conducting wall of the shielded room. Also if the EUT is floor-standing equipment, it was placed on a non-conducted support with a height of 12 millimeters above the reference ground plane.
- c. Connect the EUT's power source to the appropriate power mains through the LISN.
- d. All the other peripherals are connected to the 2nd LISN, if any.
- e. The LISN was placed 0.8 meters from the EUT and at least 0.8 meters from other units and other metal planes.
- f. Measure the conducted emissions on each power line (Neutral Line and Line 1 – Hot side) of the EUT's power source by using the test receiver connected to the coupling RF output port of LISN.
- g. Rapidly scan the signal from 150kHz to 30MHz by using the receiver through the Maximum-Peak detector to determine those frequencies associated with higher emission levels for each measured line.
- h. Then measure the maximum level of conducted disturbance for each frequency found from step g. by using the receiver through the Quasi-Peak and Average detectors per CISPR 16-1.
- i. Record the level for each frequency and compare with the required limit.

2.4 Test Configurations




2.5 Photographs of the Test Configurations



2.6 Test Results

Test Mode : As description of section 1.2
Test Voltage : 120V/60Hz to the power adapter
Tester : Kent **Temperature** : 26°C
Humidity : 68%RH **Frequency Range** : 150kHz~30MHz
IF Bandwidth : 9kHz **Phase** : Line




	Freq	Level	Factor	Read	Limit	Over	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.158	50.09	0.28	49.81	79.00	-28.91	LINE	QP
2	0.158	32.85	0.28	32.57	66.00	-33.15	LINE	AVERAGE
3	0.177	44.68	0.28	44.40	79.00	-34.32	LINE	QP
4	0.177	24.55	0.28	24.27	66.00	-41.45	LINE	AVERAGE
5	0.207	43.39	0.28	43.11	79.00	-35.61	LINE	QP
6	0.207	30.82	0.28	30.54	66.00	-35.18	LINE	AVERAGE
7	0.473	43.28	0.31	42.97	79.00	-35.72	LINE	QP
8	0.473	33.38	0.31	33.07	66.00	-32.62	LINE	AVERAGE
9	0.743	37.05	0.34	36.71	73.00	-35.95	LINE	QP
10	0.743	26.82	0.34	26.48	60.00	-33.18	LINE	AVERAGE
11	16.573	34.06	0.72	33.34	73.00	-38.94	LINE	QP
12	16.573	25.93	0.72	25.21	60.00	-34.07	LINE	AVERAGE

Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + insertion loss of LISN.
3. Q.P. is abbreviation of quasi-peak.

Test Mode : As description of section 1.2
Test Voltage : 120V/60Hz to the power adapter
Tester : Kent **Temperature** : 26°C
Humidity : 68%RH **Frequency Range** : 150kHz~30MHz
IF Bandwidth : 9kHz **Phase** : Neutral



	Freq	Level	Factor	Read Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.150	49.20	0.18	49.02	79.00	-29.80	NEUTRAL	QP
2	0.150	30.64	0.18	30.46	66.00	-35.36	NEUTRAL	AVERAGE
3	0.157	51.11	0.18	50.93	79.00	-27.89	NEUTRAL	QP
4	0.157	37.47	0.18	37.29	66.00	-28.53	NEUTRAL	AVERAGE
5	0.185	44.22	0.17	44.05	79.00	-34.78	NEUTRAL	QP
6	0.185	23.39	0.17	23.22	66.00	-42.61	NEUTRAL	AVERAGE
7	0.473	43.08	0.19	42.89	79.00	-35.92	NEUTRAL	QP
8	0.473	37.21	0.19	37.02	66.00	-28.79	NEUTRAL	AVERAGE
9	1.049	32.31	0.23	32.08	73.00	-40.69	NEUTRAL	QP
10	1.049	22.39	0.23	22.16	60.00	-37.61	NEUTRAL	AVERAGE
11	16.573	40.68	1.02	39.66	73.00	-32.32	NEUTRAL	QP
12	16.573	33.37	1.02	32.35	60.00	-26.63	NEUTRAL	AVERAGE

Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + insertion loss of LISN.
3. Q.P. is abbreviation of quasi-peak.

3. Radiated Emission Measurement

Test Result : **PASS**

3.1 Limits for Emission Measurement

Limits for radiated disturbances below 1000MHz

Frequency (MHz)	Class A Equipment (10m distance)	Class B Equipment (3m distance)
	Quasi-peak (dBµV/m)	Quasi-peak (dBµV/m)
30 to 88	39.1	40
88 to 216	43.5	43.5
216 to 960	46.4	46
960 to 1000	49.5	54

Note 1- The lower limit shall apply at the transition frequency.
 Note 2- Additional provisions may be required for cases where interference occurs.
 Note 3- According to 15.109(g), as an alternative to the radiated emission limits shown above, digital devices may be shown to comply with the standards (CISPR), Pub. 22 shown as below.

30 to 230	40	30
230 to 1000	47	37

Limits for radiated disturbances above 1000MHz at a measuring distance of 3m

Frequency (GHz)	Class A Equipment		Class B Equipment	
	Peak (dBµV/m)	Average (dBµV/m)	Peak (dBµV/m)	Average (dBµV/m)
1 to 40	80	60	74	54

3.2 Test Instruments

For Measurement below 1000MHz

Test Site and Equipment	Manufacturer	Model No./ Serial No.	Last Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESCS 30/ 836858/020	Sept. 10, 2012	Sept. 10, 2013
Broadband Antenna	R&S	HL-562/ 360543/007	March 27, 2013	March 27, 2014
Broadband Antenna	R&S	HL-562/ 830547/010	April 30, 2013	April 30, 2014
Pre-Amplifier	Mini Circuit	ZKL-2/ 001	July 15, 2013	Jan. 15, 2014
Pre-Amplifier	Mini Circuit	ZKL-2/ 002	July 15, 2013	Jan. 15, 2014
Spectrum Analyzer	R&S	FSP40/ 100031	July 15, 2013	July 15, 2014
Spectrum Analyzer	R&S	FSP7/ 100384	Jan. 3, 2013	Jan. 3, 2014
RF Cable	JYEBAO	0214/ C0049	July 15, 2013	Jan. 15, 2014
RF Cable	JYEBAO	0214/ C0050	July 15, 2013	Jan. 15, 2014
Test Software	Audix	e3/ Ver. 4.3.714.e	NCR	NCR
TR1 Semi - anechoic Chamber	ETS. LINDGREN	TR1/ 17627-B	May 4, 2013	May 4, 2014

Note:

1. The calibrations are traceable to NML/ROC.
2. NCR : No Calibration Required.
3. The calibration date of the semi-anechoic chamber listed above is the date of NSA measurement.

For Measurement above 1000MHz

Test Site and Equipment	Manufacturer	Model No./ Serial No.	Last Calibration Date	Calibration Due Date
Horn Antenna	EMCO	3117/ 00082847	March 5, 2013	March 5, 2014
Bore-sight Antenna Mast	Sunol	TLT2/ 051110-5	NCR	NCR
Pre-Amplifier	KMIC	<input type="checkbox"/> KMA010180A01/ 99056	Oct. 19, 2012	Oct. 19, 2013
	MITEQ	<input checked="" type="checkbox"/> JS4-00101800- 28-10P/1498979	Dec. 21, 2012	Dec.21, 2013
		JS4-00101800- 28-5A/742309	Dec. 19, 2012	Dec. 19, 2013
Spectrum Analyzer	R&S	FSP40/ 100031	July 15, 2013	July 15, 2014
RF Cable	Suhner	Sucoflex 106P / C0091 + C0092	April 17, 2013	Oct. 17, 2013
Test Software	Audix	e3/ Ver. 4.3.714.e	NCR	NCR
TR1 Fully - anechoic Chamber	ETS. LINDGREN	TR1/ 17627-B	Feb. 23, 2013	Feb. 23, 2014

Note:

1. The calibrations are traceable to NML/ROC.
2. NCR : No Calibration Required.
3. The calibration date of the chamber TR1 listed above is the date of site VSWR measurement.

Measurement Uncertainty

The assessed measurement uncertainty with a suitable coverage factor K to ensure 95% confidence level for the normal distribution are shown as below, the values are less than U_{cispr} in table 1 of CISPR 16-4-2.

Test Site (Measuring distance)	Polarization	Frequency Range	
		30MHz ~200MHz	200MHz ~1000MHz
TR1(10m)	Horizontal	3.2dB	3.5dB
	Vertical	3.3dB	3.6dB
TR11(3m)	Horizontal	3.8dB	4.1dB
	Vertical	3.3dB	3.7dB


Test Site (Measuring distance)	Polarization	Frequency Range
		1GHz ~18GHz
TR1(3m)	Horizontal	4.0dB
	Vertical	3.9dB

3.3 Test Procedures


- a. The EUT was set up per the test configuration figured in the next section of this chapter to simulate the typical usage per the user's manual.
- b. If the EUT is tabletop equipment, it was placed on a non-conducted table with a height of 0.8 meters above the reference ground plane in the semi-anechoic chamber. If the EUT is floor-standing equipment, it was placed on a non-conducted support with a height of 12 millimeters above the reference ground plane in the semi-anechoic chamber.
- c. For the measurement of frequency below 1000MHz, the EUT was set 10m away from the interference receiving antenna for the limit of Class A equipment or CISPR 22. For Class B equipment and the measurement of frequency above 1000MHz, the EUT was set 3m away from the interference receiving antenna.
- d. Rapidly sweep the signal in the test frequency range by using the spectrum through the Maximum-peak detector.
- e. Rotate the EUT from 0° to 360° and position the receiving antenna at heights from 1 to 4 meters above the reference ground plane continuously to determine at least six frequencies associated with higher emission levels and record them.
- f. For measurement of frequency above 1000MHz, the beamwidth of receiving horn antenna should keep covering EUT when the receiving horn antenna height varied.
- g. Then measure each frequency found from step e. by using the spectrum with rotating the EUT and positioning the receiving antenna height to determine the maximum level.
- h. Finely tune the antenna and turntable around the recorded position of each frequency found from step f.
- i. For measurement of frequency below 1000MHz, set the receiver detector to be Quasi-Peak per CISPR 16-1 to find out the maximum level occurred.
- j. For measurement of frequency above 1000MHz, set the spectrum detector to be Peak or Average to find out the maximum level occurred, if any.
- k. Record frequency, azimuth angle of the turntable, height, and polarization of the receiving antenna and compare the maximum level with the required limit.
- l. Change the receiving antenna to another polarization to measure radiated emission by following step d. to k. again.
- m. If the peak emission level measured from step e. is 4dB lower than the limit specified, then the emission values presented will be the peak value only. Otherwise, accurate Q.P. value will be measured and presented.

3.4 Test Configurations

Radiated Emission Measurement below 1000MHz



Radiated Emission Measurement above 1000MHz




3.5 Photographs of the Test Configurations



3.6 Test Results

Radiated Emission Measurement below 1000MHz

Test Mode : As description of section 1.2
Test Voltage : 120V/60Hz to the power adapter
Tester : Meng **Temperature** : 26°C
Humidity : 71%RH **Frequency Range** : 30MHz~1GHz
IF Bandwidth : 120kHz **Polarization** : Horizontal




	Freq	Level	Read Level	Factor	Limit Line	Over Limit	Ant Pos	Table Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	270.560	41.05	58.16	-17.11	47.00	-5.95	---	---	HORIZONTAL	Peak
2	357.860	38.02	52.48	-14.46	47.00	-8.98	---	---	HORIZONTAL	Peak
3 @	414.290	43.21	55.91	-12.70	47.00	-3.79	192	254	HORIZONTAL	QP
4	483.960	40.65	51.33	-10.68	47.00	-6.35	---	---	HORIZONTAL	Peak
5	675.050	40.28	47.63	-7.35	47.00	-6.72	---	---	HORIZONTAL	Peak
6	810.850	39.60	45.00	-5.40	47.00	-7.40	---	---	HORIZONTAL	Peak

Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.
3. Q.P is abbreviation of quasi-peak.

Test Mode : As description of section 1.2
Test Voltage : 120V/60Hz to the power adapter
Tester : Meng **Temperature** : 26°C
Humidity : 71%RH **Frequency Range** : 30MHz~1GHz
IF Bandwidth : 120kHz **Polarization** : Vertical




	Freq	Level	Read Level	Factor	Limit Line	Over Limit	Ant Pos	Table Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	137.670	33.88	53.79	-19.91	40.00	-6.12	---	---	VERTICAL	Peak
2	212.360	33.24	52.63	-19.39	40.00	-6.76	---	---	VERTICAL	Peak
3	270.000	38.28	55.18	-16.90	47.00	-8.72	345	198	VERTICAL	QP
4	399.978	38.54	51.19	-12.65	47.00	-8.46	398	358	VERTICAL	QP
5 @	675.010	41.53	47.82	-6.29	47.00	-5.47	200	188	VERTICAL	QP
6	839.950	40.12	44.06	-3.94	47.00	-6.88	---	---	VERTICAL	Peak

Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.
3. Q.P is abbreviation of quasi-peak.

Radiated Emission Measurement above 1000MHz

Test Mode : As description of section 1.2
Test Voltage : 120V/60Hz to the power adapter
Tester : Meng **Temperature** : 27°C
Humidity : 66%RH **Frequency Range** : 1GHz~8GHz
IF Bandwidth : 1MHz **Polarization** : Horizontal




	Freq	Level	Read Level	Factor	Limit Line	Over Limit	Ant Pos	Table Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	1213.410	30.43	73.86	-43.43	60.00	-29.57	205	189	HORIZONTAL	Average
2	1214.300	43.40	86.83	-43.43	80.00	-36.60	198	187	HORIZONTAL	Peak
3	1439.950	42.14	85.72	-43.58	80.00	-37.86	217	189	HORIZONTAL	Peak
4	1440.120	28.76	72.34	-43.58	60.00	-31.24	213	184	HORIZONTAL	Average
5	3000.048	44.80	81.84	-37.04	80.00	-35.20	186	178	HORIZONTAL	Peak
6	3001.940	29.61	66.65	-37.04	60.00	-30.39	182	171	HORIZONTAL	Average

Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.

Test Mode : As description of section 1.2
Test Voltage : 120V/60Hz to the power adapter
Tester : Meng **Temperature** : 27°C
Humidity : 66%RH **Frequency Range** : 1GHz~8GHz
IF Bandwidth : 1MHz **Polarization** : Vertical



	Freq	Level	Read Level	Factor	Limit Line	Over Limit	Ant Pos	Table Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV	dB/m	dBuV/m	dB	cm	deg		
1	1196.110	27.95	71.37	-43.42	60.00	-32.05	134	178	VERTICAL	Average
2	1197.470	41.27	84.69	-43.42	80.00	-38.73	130	174	VERTICAL	Peak
3	1575.926	37.35	80.08	-42.73	80.00	-42.65	205	4	VERTICAL	Peak
4	1576.220	26.30	69.03	-42.73	60.00	-33.70	208	8	VERTICAL	Average
5	2100.444	39.40	78.31	-38.91	80.00	-40.60	231	162	VERTICAL	Peak
6	2101.730	28.49	67.40	-38.91	60.00	-31.51	239	155	VERTICAL	Average

Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.

Attachment 1


Photographs of EUT











Attachment 2

Modifications of EUT

Statement of the EUT Modifications

According to the rules of ANSI C63.4-2009 clause 10.2.13, the following equipment (EUT):

Product : Fanless Multi-Touch PPC
Model No. : ACP-1103xxx-Ax-xxxx (x is 0-9,A-Z ,” - “or blank)
Manufacturer : AAEON Technology Inc.
Address : 5F, No. 135, Lane 235, Pao Chiao Rd., Hsin-Tien Dist.,
New Taipei City 23145, Taiwan, R.O.C

- should be **without** any modifications made
- should be **with** some modifications made

to bring the EUT into compliance with the appropriate specifications (47CFR Part 15, Subpart B). If any, the details of the modifications including the complete descriptions, reasons and so on are described in next page of this report.

We , AAEON Technology Inc. hereby ensure that the product specified above will have all of the modifications incorporated in the product when manufactured and placed on the market.

The following importer or manufacturer is responsible for this statement:

Company Name : _____

Company Address : _____

Telephone : _____ E-mail : _____

Legal Signature of the responsible personal:

Title / Name (full name)

Date

The details of the modifications:

Item	Solution Component	Specifications	Manufacturer	Quantity	Reasons
1					
2					
3					
4					
5					
6					
7					
8					
9					
10					
11					
12					
13					
14					
15					

If needed, some modification items are shown in the photographs in the following.