

# **AEC-6800**

## **Reliability Prediction Report**

### **(MTBF)**

Report NO : 07P070009

**10-02-2007**

Issue Date

**Wenyuan Yang**

Manager

**Jessica Chou**

Test Engineer

## Reliability Prediction (MTBF)

---

I . **Model Name:** TF-AEC-6800-A1

II . **Prediction Date:** Oct. 2nd, 2007

III . **Prediction Site:** AAEON Q.E. Dept.

IV . **Predicted by:** Jessica Chou

V . **Equipment:** Relex Ver.7.3 Visual Reliability Software

### VI. Simulation Environment:

- Temperature: 25 degrees C
- Standard: Telcordia (Bellcore) Standard

### VII. Term and Definition:

- Unit : An assembly of device.
- Duty Cycle : Used to specify the percentage of time that the element is in an on state, and it is equal to the percentage of total time the item is in the active environment.
- Quantity : The quantity of the selected item.
- Failure Rate : Used to specify that the failure rate is to be calculated based the selected Calculation models. The multiplier is 1,000,000.
- MTBF : MTBF is always specified in hours.

### VIII. Prediction Result:


TF-AEC-6800-A1 :

Failure Rate: 12.392319 ppm

MTBF: 80,695 Hours

### AAEON Reliability Prediction Report

**Part Number** TF-AEC-6800-A1  
**Reference Des**  
**Date** 10. 2, 2007  
**Environment** GF, GU - Ground Fixed, Uncontrolled  
**Temp. (°C)** 25.00



**Description** Top-level assembly  
**File Name** TF-AEC-6800-A1.RPJ  
**Time** 11:58 AM  
**Failure Rate** 12.392319  
**MTBF** 80,695

| Assembly Name                 | Part Number    | Model    | Method          | Environment            | Duty Cycle | Qty  | Failure Rate | MTBF        |
|-------------------------------|----------------|----------|-----------------|------------------------|------------|------|--------------|-------------|
| TF-AEC-6800-A1                | TF-AEC-6800-A1 | Bellcore | Method I Case 3 | GF, GU - Ground Fixed, | 100.00     | 1.00 | 12.392319    | 80,695      |
| Accessory Kit for AEC-6800-A1 | 9761680000     | Bellcore | Method I Case 3 | GF, GU - Ground Fixed, |            | 1.00 | 0.006828     | 146,463,378 |
| ASS'Y I/O Board T059          | 9697T05902     | Bellcore | Method I Case 3 | GF, GU - Ground Fixed, |            | 1.00 | 0.236518     | 4,228,004   |
| SMD ASS'Y I/O Board T059      | 9697T05903     | Bellcore | Method I Case 3 | GF, GU - Ground Fixed, |            | 1.00 | 0.117603     | 8,503,156   |
| GENE-5312-A10                 | 9697531212     | Bellcore | Method I Case 3 | GF, GU - Ground Fixed, |            | 1.00 | 11.335811    | 88,216      |
| ASS'Y Power Board E102        | 9697E10206     | Bellcore | Method I Case 3 | GF, GU - Ground Fixed, |            | 1.00 | 0.813163     | 1,229,766   |
| SMD ASS'Y Power Board E102    | 9697E10207     | Bellcore | Method I Case 3 | GF, GU - Ground Fixed, |            | 1.00 | 0.620625     | 1,611,278   |








### AAEON Reliability Prediction Report

**Part Number** 9697531212  
**Reference Des**  
**Date** 10. 2, 2007  
**Environment** GF, GU - Ground Fixed, Uncontrolled  
**Temp. (°C)** 25.00




**Description**  
**File Name** TF-AEC-6800-A1.RPJ  
**Time** 11:58 AM  
**Failure Rate** 11.335811  
**MTBF** 88,216

| Part Number | Category           | Location  | Calculation Model | Quality | Tem. Rise | Failure Rate, Unit | Quantity | Failure Rate, % | Failure Rate | MTBF, Unit    |
|-------------|--------------------|---|-------------------|---------|-----------|--------------------|----------|-----------------|--------------|---------------|
| 1653003101  | Connection         | JP2,JP3,JP6   | Bellcore Issue 6  | Level I |           | 0.001707           | 3.00     | .0452           | 0.005121     | 585853513.81  |
| 14S6200404  | Integrated Circuit | U8  | Bellcore Issue 6  | Level I |           | 0.043131           | 1.00     | .3805           | 0.043131     | 23185427.29   |
| 1656304022  | Connection         | CN9   | Bellcore Issue 6  | Level I |           | 0.002276           | 1.00     | .0201           | 0.002276     | 439390135.35  |
| 1654409103  | Connection         | CN19  | Bellcore Issue 6  | Level I |           | 0.005121           | 1.00     | .0452           | 0.005121     | 195284504.60  |
| 1653005201  | Connection         | CN4   | Bellcore Issue 6  | Level I |           | 0.005690           | 1.00     | .0502           | 0.005690     | 175756054.14  |
| 1654515308  | Connection         | CN20  | Bellcore Issue 6  | Level I |           | 0.008535           | 1.00     | .0753           | 0.008535     | 117170702.76  |
| 1111610194  | Capacitor          | EC1-EC5   | Bellcore Issue 6  | Level I |           | 0.042673           | 5.00     | 1.8822          | 0.213364     | 23434140.55   |
| 1189656190  | Capacitor          | EC6   | Bellcore Issue 6  | Level I |           | 0.071121           | 1.00     | .6274           | 0.071121     | 14060484.33   |
| 1653002100  | Connection         | JP1   | Bellcore Issue 6  | Level I |           | 0.001138           | 1.00     | .0100           | 0.001138     | 878780270.71  |
| 1759100008  | Miscellaneous      | SP1   | Bellcore Issue 6  | Level I |           | 0.150000           | 1.00     | 1.3232          | 0.150000     | 6666666.67    |
| 1653132220  | Connection         | CN11  | Bellcore Issue 6  | Level I |           | 0.036414           | 1.00     | .3212           | 0.036414     | 27461883.46   |
| 162512206   | Connection         | CN15,CN16   | Bellcore Issue 6  | Level I |           | 0.006828           | 1.00     | .0602           | 0.006828     | 146463378.45  |
| 1654606306  | Connection         | CN18  | Bellcore Issue 6  | Level I |           | 0.003414           | 1.00     | .0301           | 0.003414     | 292926756.90  |
| 1653003201  | Connection         | JP4   | Bellcore Issue 6  | Level I |           | 0.003414           | 1.00     | .0301           | 0.003414     | 292926756.90  |
| 1655902030  | Connection         | BAT1  | Bellcore Issue 6  | Level I |           | 0.001138           | 1.00     | .0100           | 0.001138     | 878780270.71  |
| 175011901C  | Miscellaneous      | BAT1  | Bellcore Issue 6  | Level I |           | 0.900000           | 1.00     | 7.9394          | 0.900000     | 1111111.11    |
| 105A710039  | Resistor           | R107, R113, R175, R182, R183, R184, R192, R194, R368, R369, R370, R371, R94 | Bellcore Issue 6  | Level I |           | 0.002268           | 13.00    | .2601           | 0.029480     | 440974090.03  |
| 1050502204  | Resistor           | R101, R102, R105, R109, R116, R118, R120, R121, R123-125, R131-135          | Bellcore Issue 6  | Level I |           | 0.002268           | 16.00    | .3201           | 0.036283     | 440974090.03  |
| 105A700003  | Resistor           | R157, R204, R320, R341  | Bellcore Issue 6  | Level I |           | 0.002268           | 4.00     | .0800           | 0.009071     | 440974090.03  |
| 105A501039  | Resistor           | R162, R166, R167, R179, R180, R188, R189                                    | Bellcore Issue 6  | Level I |           | 0.000756           | 7.00     | .0467           | 0.005291     | 1322922270.09 |
| 106B501031  | Resistor           | RT1,RT2   | Bellcore Issue 6  | Level I |           | 0.002268           | 2.00     | .0400           | 0.004535     | 440974090.03  |
| 105A503033  | Resistor           | R190  | Bellcore Issue 6  | Level I |           | 0.002268           | 1.00     | .0200           | 0.002268     | 440974090.03  |
| 105A703323  | Resistor           | R240,R319   | Bellcore Issue 6  | Level I |           | 0.002268           | 2.00     | .0400           | 0.004535     | 440974090.03  |
| 105A502223  | Resistor           | R262,R333   | Bellcore Issue 6  | Level I |           | 0.002268           | 2.00     | .0400           | 0.004535     | 440974090.03  |
| 105A507509  | Resistor           | R312, R313, R317  | Bellcore Issue 6  | Level I |           | 0.002268           | 3.00     | .0600           | 0.006803     | 440974090.03  |
| 105A514713  | Resistor           | R332  | Bellcore Issue 6  | Level I |           | 0.002268           | 1.00     | .0200           | 0.002268     | 440974090.03  |
| 105A568103  | Resistor           | R258  | Bellcore Issue 6  | Level I |           | 0.002268           | 1.00     | .0200           | 0.002268     | 440974090.03  |
| 105A702733  | Resistor           | R263,R318   | Bellcore Issue 6  | Level I |           | 0.002268           | 2.00     | .0400           | 0.004535     | 440974090.03  |

**AAEON Reliability Prediction Report**

**Part Number** 9697531212  
**Reference Des**  
**Date** 10. 2, 2007  
**Environment** GF, GU - Ground Fixed, Uncontrolled  
**Temp. (°C)** 25.00



**Description**  
**File Name** TF-AEC-6800-A1.RPJ  
**Time** 11:58 AM  
**Failure Rate** 11.335811  
**MTBF** 88,216

| Part Number | Category           | Location  | Calculation Model | Quality | Tem. Rise | Failure Rate, Unit | Quantity | Failure Rate, % | Failure Rate | MTBF, Unit   |
|-------------|--------------------|---|-------------------|---------|-----------|--------------------|----------|-----------------|--------------|--------------|
| 105A546403  | Resistor           | R323  | Bellcore Issue 6  | Level I |           | 0.002268           | 1.00     | .0200           | 0.002268     | 440974090.03 |
| 1189615190  | Capacitor          | TC1   | Bellcore Issue 6  | Level I | 15.50     | 0.006053           | 1.00     | .0534           | 0.006053     | 165195381.48 |
| 1189615190  | Capacitor          | TC3, TC5, TC6   | Bellcore Issue 6  | Level I |           | 0.004535           | 3.00     | .1200           | 0.013606     | 220487045.01 |
| 1653925216  | Connection         | CFD1  | Bellcore Issue 6  | Level I |           | 0.028449           | 1.00     | .2510           | 0.028449     | 35151210.83  |
| 14S5801402  | Integrated Circuit | U11   | Bellcore Issue 6  | Level I |           | 0.037889           | 1.00     | .3342           | 0.037889     | 26392869.26  |
| 14S3149103  | Integrated Circuit | U13   | Bellcore Issue 6  | Level I | 19.30     | 0.223575           | 1.00     | 1.9723          | 0.223575     | 4472772.10   |
| 14S5A00820  | Integrated Circuit | U17   | Bellcore Issue 6  | Level I | 2.50      | 0.072731           | 1.00     | .6416           | 0.072731     | 13749244.25  |
| 14S2303700  | Integrated Circuit | U22   | Bellcore Issue 6  | Level I | 12.60     | 0.143752           | 1.00     | 1.2681          | 0.143752     | 6956415.52   |
| 14S9820800  | Integrated Circuit | U40   | Bellcore Issue 6  | Level I |           | 0.070411           | 1.00     | .6211           | 0.070411     | 14202225.56  |
| 1654262300  | Miscellaneous      | Y1  | Bellcore Issue 6  | Level I |           | 0.150000           | 1.00     | 1.3232          | 0.150000     | 6666666.67   |
| 1654262300  | Connection         | MPC11   | Bellcore Issue 6  | Level I |           | 0.070552           | 1.00     | .6224           | 0.070552     | 14173875.33  |
| 1311119710  | Semiconductor      | Q3,Q6   | Bellcore Issue 6  | Level I |           | 0.023881           | 2.00     | .4213           | 0.047762     | 41874327.58  |
| 1540733085  | Resistor           | RP1, RP2, RP69~73, RP86~90  | Bellcore Issue 6  | Level I |           | 0.006246           | 12.00    | .6612           | 0.074952     | 160102772.00 |
| 1540756081  | Resistor           | RP10~25, RP7~9  | Bellcore Issue 6  | Level I |           | 0.006246           | 19.00    | 1.0469          | 0.118674     | 160102772.00 |
| 105A710053  | Resistor           | R1  | Bellcore Issue 6  | Level I |           | 0.013606           | 1.00     | .1200           | 0.013606     | 73495681.67  |
| 105A516513  | Resistor           | R3  | Bellcore Issue 6  | Level I |           | 0.002268           | 1.00     | .0200           | 0.002268     | 440974090.03 |
| 105A702269  | Resistor           | R148,R149,R242,R255,R5,R6   | Bellcore Issue 6  | Level I |           | 0.002268           | 6.00     | .1200           | 0.013606     | 440974090.03 |
| 105A704729  | Resistor           | RP27~42, RP50~52,RP54, RP56, RP57, RP77~79  | Bellcore Issue 6  | Level I |           | 0.002268           | 25.00    | .5001           | 0.056693     | 440974090.03 |
| 105A702229  | Resistor           | R14, R174, R245, R246, R27, R347, R348  | Bellcore Issue 6  | Level I |           | 0.002268           | 7.00     | .1400           | 0.015874     | 440974090.03 |
| 105A705609  | Resistor           | R177, R181, R195, R215, R216, R217, R220, R223, R227, R228, R235, R241, R244, R271, R286, R302, R306, R310, R328, R340, R344, R346, R82, R96, R97 | Bellcore Issue 6  | Level I |           | 0.002268           | 25.00    | .5001           | 0.056693     | 440974090.03 |
| 105A720053  | Resistor           | R58   | Bellcore Issue 6  | Level I |           | 0.013606           | 1.00     | .1200           | 0.013606     | 73495681.67  |
| 105A568123  | Resistor           | R80   | Bellcore Issue 6  | Level I |           | 0.002268           | 1.00     | .0200           | 0.002268     | 440974090.03 |
| 105A700139  | Resistor           | R177, R181, R195, R215~217, R220, R223, R227, R228, R235, R241, R244, R271, R286, R302, R306, R310, R328, R340, R344, R346, R82, R96, R97         | Bellcore Issue 6  | Level I |           | 0.002268           | 25.00    | .5001           | 0.056693     | 440974090.03 |
| 105A549969  | Resistor           | R139~146  | Bellcore Issue 6  | Level I |           | 0.002268           | 8.00     | .1600           | 0.018142     | 440974090.03 |



### AAEON Reliability Prediction Report

**Part Number** 9697531212  
**Reference Des**  
**Date** 10. 2, 2007  
**Environment** GF, GU - Ground Fixed, Uncontrolled  
**Temp. (°C)** 25.00



**Description**  
**File Name** TF-AEC-6800-A1.RPJ  
**Time** 11:58 AM  
**Failure Rate** 11.335811  
**MTBF** 88,216

| Part Number | Category           | Location                     | Calculation Model | Quality | Tem. Rise | Failure Rate, Unit | Quantity | Failure Rate, % | Failure Rate | MTBF, Unit   |
|-------------|--------------------|------------------------------|-------------------|---------|-----------|--------------------|----------|-----------------|--------------|--------------|
| 105A506823  | Resistor           | R160,R191                    | Bellcore Issue 6  | Level I |           | 0.002268           | 1.00     | .0200           | 0.002268     | 440974090.03 |
| 105A547003  | Resistor           | R186,R208                    | Bellcore Issue 6  | Level I |           | 0.002268           | 2.00     | .0400           | 0.004535     | 440974090.03 |
| 105A705629  | Resistor           | R218, R253, R259, R270, R276 | Bellcore Issue 6  | Level I |           | 0.002268           | 5.00     | .1000           | 0.011339     | 440974090.03 |
| 105A507533  | Resistor           | R257,R276                    | Bellcore Issue 6  | Level I |           | 0.002268           | 2.00     | .0400           | 0.004535     | 440974090.03 |
| 14S5A01400  | Integrated Circuit | U26,U46                      | Bellcore Issue 6  | Level I | 4.80      | 0.080932           | 2.00     | 1.4279          | 0.161865     | 12355989.78  |
| 1315993311  | Semiconductor      | U31                          | Bellcore Issue 6  | Level I |           | 0.079603           | 1.00     | .7022           | 0.079603     | 12562298.27  |
| 14S4553501  | Integrated Circuit | U3                           | Bellcore Issue 6  | Level I | 7.30      | 0.097529           | 1.00     | .8604           | 0.097529     | 10253371.72  |
| 1315446310  | Semiconductor      | U5,U9                        | Bellcore Issue 6  | Level I |           | 0.079603           | 2.00     | 1.4045          | 0.159207     | 12562298.27  |
| 14S4911216  | Integrated Circuit | U7                           | Bellcore Issue 6  | Level I | 16.50     | 0.186320           | 1.00     | 1.6436          | 0.186320     | 5367123.60   |
| 14S2202600  | Integrated Circuit | U25                          | Bellcore Issue 6  | Level I |           | 0.059366           | 1.00     | .5237           | 0.059366     | 16844654.92  |
| 1315992601  | Semiconductor      | U27                          | Bellcore Issue 6  | Level I | 14.20     | 0.117519           | 1.00     | 1.0367          | 0.117519     | 8509284.25   |
| 14S5A12505  | Integrated Circuit | U28                          | Bellcore Issue 6  | Level I | 5.20      | 0.082031           | 1.00     | .7236           | 0.082031     | 12190539.63  |
| 14S2272700  | Integrated Circuit | U30                          | Bellcore Issue 6  | Level I |           | 0.059366           | 1.00     | .5237           | 0.059366     | 16844654.92  |
| 14S2272700  | Integrated Circuit | U39                          | Bellcore Issue 6  | Level I | 15.50     | 0.174439           | 1.00     | 1.5388          | 0.174439     | 5732676.86   |
| 14S6334610  | Integrated Circuit | U32,U35                      | Bellcore Issue 6  | Level I |           | 0.022683           | 2.00     | .4002           | 0.045365     | 44086680.49  |
| 14S4758300  | Integrated Circuit | U37                          | Bellcore Issue 6  | Level I | 15.60     | 0.175595           | 1.00     | 1.5490          | 0.175595     | 5694921.04   |
| 14S4871203  | Integrated Circuit | U1                           | Bellcore Issue 6  | Level I | 13.00     | 0.124450           | 1.00     | 1.0978          | 0.124450     | 8035381.07   |
| 14S2533100  | Integrated Circuit | U2                           | Bellcore Issue 6  | Level I | 22.50     | 0.274286           | 1.00     | 2.4196          | 0.274286     | 3645829.71   |
| 14S3156500  | Semiconductor      | U6                           | Bellcore Issue 6  | Level I | 13.20     | 0.068683           | 1.00     | .6059           | 0.068683     | 14559626.92  |
| 1651203291  | Connection         | U8                           | Bellcore Issue 6  | Level I |           | 0.035845           | 1.00     | .3162           | 0.035845     | 27897786.37  |
| 14S4810000  | Integrated Circuit | U10                          | Bellcore Issue 6  | Level I | 10.50     | 0.111955           | 1.00     | .9876           | 0.111955     | 8932124.90   |
| 14S4810000  | Integrated Circuit | U33                          | Bellcore Issue 6  | Level I | 14.80     | 0.134160           | 1.00     | 1.1835          | 0.134160     | 7453812.96   |
| 14S4021301  | Integrated Circuit | U15                          | Bellcore Issue 6  | Level I | 12.20     | 0.139927           | 1.00     | 1.2344          | 0.139927     | 7146589.18   |
| 14S4021301  | Integrated Circuit | U14                          | Bellcore Issue 6  | Level I |           | 0.059366           | 1.00     | .5237           | 0.059366     | 16844654.92  |
| 14S3128420  | Integrated Circuit | U16                          | Bellcore Issue 6  | Level I |           | 0.070411           | 1.00     | .6211           | 0.070411     | 14202225.56  |
| 14S4081110  | Integrated Circuit | U18                          | Bellcore Issue 6  | Level I |           | 0.059366           | 1.00     | .5237           | 0.059366     | 16844654.92  |
| 14S5A12503  | Integrated Circuit | U23,U47                      | Bellcore Issue 6  | Level I |           | 0.059366           | 2.00     | 1.0474          | 0.118732     | 16844654.92  |
| 14S5A03200  | Integrated Circuit | U36                          | Bellcore Issue 6  | Level I | 3.00      | 0.074382           | 1.00     | .6562           | 0.074382     | 13444079.84  |
| 14S4048502  | Integrated Circuit | U41,U45                      | Bellcore Issue 6  | Level I |           | 0.059366           | 2.00     | 1.0474          | 0.118732     | 16844654.92  |
| 14S4033300  | Integrated Circuit | U12                          | Bellcore Issue 6  | Level I |           | 0.039296           | 1.00     | .3467           | 0.039296     | 25448028.36  |
| 1315970110  | Integrated Circuit | U42,U43                      | Bellcore Issue 6  | Level I |           | 0.059366           | 2.00     | 1.0474          | 0.118732     | 16844654.92  |

### AAEON Reliability Prediction Report

**Part Number** 9697531212  
**Reference Des**  
**Date** 10. 2, 2007  
**Environment** GF, GU - Ground Fixed, Uncontrolled  
**Temp. (°C)** 25.00




**Description**  
**File Name** TF-AEC-6800-A1.RPJ  
**Time** 11:58 AM  
**Failure Rate** 11.335811  
**MTBF** 88,216

| Part Number | Category      | Location  | Calculation Model | Quality | Tem. Rise | Failure Rate, Unit | Quantity | Failure Rate, % | Failure Rate | MTBF, Unit   |
|-------------|---------------|---|-------------------|---------|-----------|--------------------|----------|-----------------|--------------|--------------|
| 1231324555  | Miscellaneous | Y1  | Bellcore Issue 6  | Level I |           | 0.150000           | 1.00     | 1.3232          | 0.150000     | 6666666.67   |
| 1231332721  | Miscellaneous | Y2  | Bellcore Issue 6  | Level I |           | 0.150000           | 1.00     | 1.3232          | 0.150000     | 6666666.67   |
| 123131435B  | Miscellaneous | Y3  | Bellcore Issue 6  | Level I |           | 0.150000           | 1.00     | 1.3232          | 0.150000     | 6666666.67   |
| 1231325058  | Miscellaneous | Y4, Y5  | Bellcore Issue 6  | Level I |           | 0.150000           | 2.00     | 2.6465          | 0.300000     | 6666666.67   |
| 1211104769  | Inductor      | L3  | Bellcore Issue 6  | Level I | 5.00      | 0.002497           | 1.00     | .0220           | 0.002497     | 400465049.33 |
| 1211104769  | Inductor      | L2  | Bellcore Issue 6  | Level I |           | 0.086173           | 1.00     | .7602           | 0.086173     | 11604581.32  |
| 121110010T  | Inductor      | L4  | Bellcore Issue 6  | Level I |           | 0.086173           | 1.00     | .7602           | 0.086173     | 11604581.32  |
| 1315700212  | Semiconductor | Q1, Q10, Q2, Q5, Q9   | Bellcore Issue 6  | Level I |           | 0.047952           | 5.00     | 2.1151          | 0.239760     | 20854149.54  |
| 1310390411  | Semiconductor | Q7, Q8  | Bellcore Issue 6  | Level I | 50.60     | 0.054925           | 2.00     | .9690           | 0.109849     | 18206736.57  |
| 1311390610  | Semiconductor | Q11   | Bellcore Issue 6  | Level I |           | 0.023881           | 1.00     | .2107           | 0.023881     | 41874327.58  |
| 1540710382  | Resistor      | RP3~6, RP26, RP43~49, RP53, RP55, RP58, RP59, RP68, RP74, RP76, RP81~85   | Bellcore Issue 6  | Level I |           | 0.006246           | 24.00    | 1.3224          | 0.149904     | 160102772.00 |
| 1540722085  | Resistor      | RP27~42, RP50~52, RP54, RP56, RP57, RP77~ RP79  | Bellcore Issue 6  | Level I |           | 0.006246           | 25.00    | 1.3775          | 0.156150     | 160102772.00 |
| 1540715380  | Resistor      | RP75  | Bellcore Issue 6  | Level I |           | 0.006246           | 1.00     | .0551           | 0.006246     | 160102772.00 |
| 105A500139  | Resistor      | R2, R25, R26, R55, R56  | Bellcore Issue 6  | Level I |           | 0.002268           | 5.00     | .1000           | 0.011339     | 440974090.03 |
| 105A701003  | Resistor      | R289, R290, R298, R324, R4, R83   | Bellcore Issue 6  | Level I |           | 0.002268           | 6.00     | .1200           | 0.013606     | 440974090.03 |
| 105A733009  | Resistor      | R152, R154, R155, R156, R161, R168, R178, R367, R7  | Bellcore Issue 6  | Level I |           | 0.002268           | 9.00     | .1800           | 0.020409     | 440974090.03 |
| 105A701039  | Resistor      | R15, R17, R103, R111, R115, R129, R130, R136, R153, R163, R165, R176, R193, R197, R200, R206, R207, R209, R210, R212, R214, R219, R221, R222, R224~226, R229, R231~233, R238, R243, R252, R264, R265, R268, R278, R279, R283, R284, R292, R293, R297, R299, R30 | Bellcore Issue 6  | Level I |           | 0.002268           | 58.00    | 1.1603          | 0.131527     | 440974090.03 |
| 105A702209  | Resistor      | R10~13, R147, R247~251, R326, R335~336, R59~74, R86, R88~90   | Bellcore Issue 6  | Level I |           | 0.002268           | 33.00    | .6602           | 0.074834     | 440974090.03 |
| 105A700009  | Resistor      | R122, R19, R202, R260, R261, R274, R277, R280, R281, R287, R304, R309, R329, R353, R364~366, R374   | Bellcore Issue 6  | Level I |           | 0.002268           | 18.00    | .3601           | 0.040819     | 440974090.03 |
| 105A701539  | Resistor      | R20, R21, R22, R23, R285, R305  | Bellcore Issue 6  | Level I |           | 0.002268           | 6.00     | .1200           | 0.013606     | 440974090.03 |

**AAEON Reliability Prediction Report**

**Part Number** 9697531212  
**Reference Des**  
**Date** 10. 2, 2007  
**Environment** GF, GU - Ground Fixed, Uncontrolled  
**Temp. (°C)** 25.00



**Description**  
**File Name** TF-AEC-6800-A1.RPJ  
**Time** 11:58 AM  
**Failure Rate** 11.335811  
**MTBF** 88,216

| Part Number | Category   | Location  | Calculation Model | Quality | Tem. Rise | Failure Rate, Unit | Quantity | Failure Rate, % | Failure Rate | MTBF, Unit   |
|-------------|------------|---|-------------------|---------|-----------|--------------------|----------|-----------------|--------------|--------------|
| 105A703309  | Resistor   | R100, R106, R114, R126, R169, R196, R199, R236, R239, R275, R282, R315, R334, R337, R349, R362, R57   | Bellcore Issue 6  | Level I |           | 0.002268           | 17.00    | .3401           | 0.038551     | 440974090.03 |
| 105A716533  | Resistor   | R77   | Bellcore Issue 6  | Level I |           | 0.002268           | 1.00     | .0200           | 0.002268     | 440974090.03 |
| 105A512033  | Resistor   | R79   | Bellcore Issue 6  | Level I |           | 0.002268           | 1.00     | .0200           | 0.002268     | 440974090.03 |
| 105A710009  | Resistor   | R151, R164, R254, R81   | Bellcore Issue 6  | Level I |           | 0.002268           | 4.00     | .0800           | 0.009071     | 440974090.03 |
| 105A705133  | Resistor   | R343, R360, R361  | Bellcore Issue 6  | Level I |           | 0.002268           | 3.00     | .0600           | 0.006803     | 440974090.03 |
| 1189633181  | Capacitor  | TC2, TC4  | Bellcore Issue 6  | Level I |           | 0.042673           | 2.00     | .7529           | 0.085346     | 23434140.55  |
| 1653222208  | Connection | CN1   | Bellcore Issue 6  | Level I |           | 0.025035           | 1.00     | .2208           | 0.025035     | 39944557.76  |
| 1653205201  | Connection | CN13  | Bellcore Issue 6  | Level I |           | 0.005690           | 1.00     | .0502           | 0.005690     | 175756054.14 |
| 1653005203  | Connection | CN5, CN6  | Bellcore Issue 6  | Level I |           | 0.005690           | 2.00     | .1004           | 0.011379     | 175756054.14 |
| 1653007206  | Connection | CN7   | Bellcore Issue 6  | Level I |           | 0.007966           | 1.00     | .0703           | 0.007966     | 125540038.67 |
| 1174522180  | Capacitor  | CP1~5   | Bellcore Issue 6  | Level I |           | 0.004535           | 5.00     | .2000           | 0.022677     | 220487045.01 |
| 1129701690  | Capacitor  | C1, C2, C4, C5, C7, C16, C17, C21, C23, C24, C26, C28, C30~70, C73, C77, C78, C81~C83, C87, C90, C94~96, C100, C106, C108, C110, C112, C113, C117~120, C122, C127, C129, C135~137, C140~144, C146~150, C152, C156, C158, C162~165, C173, C181, C182, C184, C186, C190~193, C196~198, C202, C203, C206, C207, C2 | Bellcore Issue 6  | Level I |           | 0.004535           | 228.00   | 9.1222          | 1.034074     | 220487045.01 |
| 1129610051  | Capacitor  | C3, C6, C8, C18, C19, C27, C71, C72, C84, C85, C92, C128, C185, C195, C204, C205, C208, C214~216, C249, C254, C266, C283, C289, C306, C311, C312, C314, C315, C328, C345, C353, C373, C384, C385, C401  | Bellcore Issue 6  | Level I |           | 0.004535           | 37.00    | 1.4804          | 0.167810     | 220487045.01 |
| 11E9501090  | Capacitor  | C9, C12, C15, C20, C76, C99, C157, C166, C174~179, C183, C188~199, C201, C230, C293, C295, C302, C303, C309, C322~324, C327, C338, C341, C361, C364, C417   | Bellcore Issue 6  | Level I |           | 0.004535           | 34.00    | 1.3603          | 0.154204     | 220487045.01 |
| 1129710390  | Capacitor  | C10, C13  | Bellcore Issue 6  | Level I |           | 0.004535           | 2.00     | .0800           | 0.009071     | 220487045.01 |
| 1129722091  | Capacitor  | C11, C14, C187, C74, C75  | Bellcore Issue 6  | Level I |           | 0.004535           | 5.00     | .2000           | 0.022677     | 220487045.01 |

**AAEON Reliability Prediction Report**

**Part Number** 9697531212  
**Reference Des**  
**Date** 10. 2, 2007  
**Environment** GF, GU - Ground Fixed, Uncontrolled  
**Temp. (°C)** 25.00



**Description**  
**File Name** TF-AEC-6800-A1.RPJ  
**Time** 11:58 AM  
**Failure Rate** 11.335811  
**MTBF** 88,216

| Part Number | Category           | Location   | Calculation Model | Quality | Tem. Rise | Failure Rate, Unit | Quantity | Failure Rate, % | Failure Rate | MTBF, Unit   |
|-------------|--------------------|--|-------------------|---------|-----------|--------------------|----------|-----------------|--------------|--------------|
| 11E9610190  | Capacitor          | C226, C241, C273, C276, C284, C29, C409  | Bellcore Issue 6  | Level I |           | 0.004535           | 7.00     | .2801           | 0.031748     | 220487045.01 |
| 1129710090  | Capacitor          | C271, C287, C291, C349, C398, C400, C411, C412, C413, C415   | Bellcore Issue 6  | Level I |           | 0.004535           | 10.00    | .4001           | 0.045354     | 220487045.01 |
| 1129722060  | Capacitor          | C109, C153, C264, C358   | Bellcore Issue 6  | Level I |           | 0.004535           | 4.00     | .1600           | 0.018142     | 220487045.01 |
| 1124427090  | Capacitor          | C114, C115, C286, C290   | Bellcore Issue 6  | Level I |           | 0.004535           | 20.00    | .8002           | 0.090708     | 220487045.01 |
| 1129701790  | Capacitor          | C130~133, C139, C240, C258, C292, C294, C296, C307, C316, C317, C320, C326, C337, C339, C340, C366, C414                         | Bellcore Issue 6  | Level I |           | 0.004535           | 7.00     | .2801           | 0.031748     | 220487045.01 |
| 1124568280  | Capacitor          | C145   | Bellcore Issue 6  | Level I |           | 0.004535           | 1.00     | .0400           | 0.004535     | 220487045.01 |
| 1124522880  | Capacitor          | C151   | Bellcore Issue 6  | Level I |           | 0.004535           | 1.00     | .0400           | 0.004535     | 220487045.01 |
| 1124410190  | Capacitor          | C159, C160, C161, C167, C168   | Bellcore Issue 6  | Level I |           | 0.004535           | 5.00     | .2000           | 0.022677     | 220487045.01 |
| 1129747650  | Capacitor          | C242   | Bellcore Issue 6  | Level I |           | 0.004535           | 1.00     | .0400           | 0.004535     | 220487045.01 |
| 1124433090  | Capacitor          | C257, C368   | Bellcore Issue 6  | Level I |           | 0.004535           | 2.00     | .0800           | 0.009071     | 220487045.01 |
| 1124522280  | Capacitor          | C274, C374   | Bellcore Issue 6  | Level I |           | 0.004535           | 2.00     | .0800           | 0.009071     | 220487045.01 |
| 16515A0995  | Connection         | DIMM1  | Bellcore Issue 6  | Level I |           | 0.113794           | 1.00     | 1.0038          | 0.113794     | 8787802.71   |
| 1304101340  | Semiconductor      | D1   | Bellcore Issue 6  | Level I |           | 0.004877           | 1.00     | .0430           | 0.004877     | 205063180.81 |
| 1301005440  | Semiconductor      | D11, D12, D14, D16, D17, D2  | Bellcore Issue 6  | Level I |           | 0.023881           | 6.00     | 1.2640          | 0.143286     | 41874327.58  |
| 1301005442  | Semiconductor      | D21, D22, D25, D3, D9  | Bellcore Issue 6  | Level I |           | 0.023881           | 5.00     | 1.0533          | 0.119405     | 41874327.58  |
| 1301053040  | Semiconductor      | D4, D5   | Bellcore Issue 6  | Level I |           | 0.023881           | 2.00     | .4213           | 0.047762     | 41874327.58  |
| 1302001240  | Integrated Circuit | D6   | Bellcore Issue 6  | Level I |           | 0.059366           | 1.00     | .5237           | 0.059366     | 16844654.92  |
| 1301005441  | Semiconductor      | D19, D20, D23, D7, D8  | Bellcore Issue 6  | Level I |           | 0.023881           | 5.00     | 1.0533          | 0.119405     | 41874327.58  |
| 1302001040  | Integrated Circuit | D13  | Bellcore Issue 6  | Level I |           | 0.059366           | 1.00     | .5237           | 0.059366     | 16844654.92  |
| 1301000340  | Semiconductor      | D15, D18   | Bellcore Issue 6  | Level I |           | 0.023881           | 2.00     | .4213           | 0.047762     | 41874327.58  |
| 1212306030  | Inductor           | FB1, FB12, FB14, FB16, FB26, FB27, FB28, FB29, FB30, FB34, FB36, FB37, FB39, FB40, FB41, FB42, FB44, FB45, FB46, FB47, FB48, FB8 | Bellcore Issue 6  | Level I |           | 0.002268           | 22.00    | .4401           | 0.049890     | 440974090.03 |
| 1212306035  | Inductor           | FB10, FB11, FB13, FB18, FB19, FB2, FB20, FB21, FB22, FB23, FB24, FB25, FB3, FB31, FB32, FB33, FB35, FB4, FB5, FB9                | Bellcore Issue 6  | Level I |           | 0.002268           | 20.00    | .4001           | 0.045354     | 440974090.03 |
| 1212308054  | Inductor           | FB17, FB6, FB7   | Bellcore Issue 6  | Level I |           | 0.002268           | 3.00     | .0600           | 0.006803     | 440974090.03 |





