

EA1050A-120 of AEC-6410

Power Electronics Test Report

Report NO.: 08P0A0020_I

Wenyuan Yang

Approved By

Dec.23.2008

Date

Sean Hsu

Issued By

Dec.23.2008

Date

Table of Contents

1. Project	3
2. Power Manufacturer	3
3. Team Member	3
4. Test Equipment	3
5. Photos of Product	3
6. Test Item	4
6.1. AC Input Current	4
6.2. MAX Inrush Current	4
6.3. Input Frequency & Voltage	4
6.4. Switching Test	4
6.5. Efficiency	4
6.6. Line Regulation	4
6.7. Load Regulation	4
6.8. Over-Voltage Protection	4
6.9. Over-Circuit Protection	4
6.10. Over-Load Protection	4
6.11. Short Circuit Protect	4
6.12. Line Voltage Surge	4
6.13. Line Voltage Sag	4
6.14. Ripple & Noise	4
6.15. Setup Time	4
6.16. Hold up Time	4
6.17. Rise Time	4
6.18. Turn on Overshoot	4
6.19. Turn off Undershoot	5
6.20. Remote ON/OFF	5
6.21. Power Good Signal	5
6.22. Power On In Low Temperature	5
6.23. Power On In High Temperature	5
6.24. Room Burn-in test	5
6.25. On/Off Cycling	5
6.26. Power Consumption Test	5
7. Test Result and Observation	5

1. Project

EA1050A-120 AC-DC Adapter for AEC-6410

2. Power Manufacturer

EDACPOWER ELEC.

3. Team Member

PM : Linux Wang ; RD : River Yang

4. Test Equipment

- 4.1. CPU Board : EPIC-5536 , Rev.A1.0
- 4.2. CPU : AMD LX 800 Processor (500MHz)
- 4.3. Memory : Transcend , DDR333 512MB , M/N : K4H510838D-UCCC
- 4.4. CF Card : Transcend , 4GB
- 4.5. AC/DC Power Supply : EDACPOWER , M/N : EA1050A-120 60Watt O/P : 12V/5A

5. Photos of Product

Fig.5.1.—System Photo



6. Test Item

Test Item	Test Condition / Specification		Sanction	
			Measured	Result
6.1. AC Input Current	I/P:90VAC O/P: Full LOAD	A	1.38A	PASS
6.2. MAX Inrush Current	I/P:115VAC O/P :Full LOAD	A	9.06A	PASS
	I/P:230VAC O/P :Full LOAD	A	9.69A	PASS
6.3. Input Frequency & Voltage	I/P:90VAC/47HZ	■ON □ OFF	-	PASS
	I/P:90VAC/63HZ	■ON □ OFF	-	PASS
	I/P:264VAC/47HZ	■ON □ OFF	-	PASS
	I/P:264VAC/63HZ	■ON □ OFF	-	PASS
6.4. Switching Test	Switching Time: 0.5 Sec MIN Load / Full Load	@90VAC ■ON □ OFF	-	PASS
	Switching Time: 0.5 Sec MIN Load / Full Load	@115VAC ■ON □ OFF	-	PASS
	Switching Time: 0.5 Sec MIN Load / Full Load	@230VAC ■ON □ OFF	-	PASS
	Switching Time: 0.5 Sec MIN Load / Full Load	@264VAC ■ON □ OFF	-	PASS
6.5. Efficiency	I/P:90VAC FULL LOAD	78@%Min	86.369%	PASS
	I/P:115VAC FULL LOAD	78@%Min	87.905%	PASS
	I/P:230VAC FULL LOAD	78@%Min	88.857%	PASS
	I/P:264VAC FULL LOAD	78@%Min	87.224%	PASS
6.6. Line Regulation	I/P:90VAC~264VAC	<±1%	0.167%	PASS
6.7. Load Regulation	I/P:115VAC O/P:MINLOAD~FULL LOAD	<±5%	4.89	PASS
	I/P:230VAC O/P:MINLOAD~FULL LOAD	<±5%	4.67	PASS
6.8. Over-Voltage Protection	I/P:230VAC O/P:MIN LOAD	V1 : (MAX)	-	-
6.9. Over-Circuit Protection	O/P: 12V	A(MAX)	6.4A	-
6.10. Over-Load Protection	I/P:90VAC O/P:MIN LOAD	%	128	-
	I/P:115VAC O/P:MIN LOAD	%	127	-
	I/P:230VAC O/P:MIN LOAD	%	126	-
	I/P:264VAC O/P:MIN LOAD	%	128	-
6.11. Short Circuit Protect	I/P:115VAC O/P:MIN LOAD	12V&GND Short	-	PASS
	I/P:230VAC O/P:MIN LOAD	12V&GND Short	-	PASS
6.12. Line Voltage Surge	O/P: FULL LOAD	Surge voltage from 132VAC to 147VAC (0.5sec), back to 132VDC	-	PASS
	O/P: FULL LOAD	Surge voltage from 264VAC to 293VAC (0.5sec), back to 264VAC	-	PASS
6.13. Line Voltage Sag	O/P: FULL LOAD	Sag voltage from 108VAC to 80VAC (0.5sec), back to 108VAC	-	PASS
	O/P: FULL LOAD	Sag voltage from 198VAC to 161VAC (0.5sec), back to 198VDC	-	PASS
6.14. Ripple & Noise	I/P:115VAC O/P:FULL LOAD	≤144mv	7.8	PASS
	I/P:230VAC O/P:FULL LOAD	≤144mv	13.4	PASS
6.15. Setup Time	I/P:115VAC O/P:FULL LOAD	mS(MAX)	3.05S	-
	I/P:230VAC O/P:FULL LOAD	mS(MAX)	1.22S	-
6.16. Hold up Time	I/P:115VAC O/P:FULL LOAD	mS(MIN)	12.75	-
	I/P:230VAC O/P:FULL LOAD	mS(MIN)	65.2	-
6.17. Rise Time	I/P:115VAC O/P:FULL LOAD	mS (MAX)	5.35	-
	I/P:230VAC O/P:FULL LOAD	mS(MAX)	5.32	-
6.18. Turn on Overshoot	Turn on overshoot shall not exceed 10% over nominal voltages@ 20 % LOAD		-	PASS
	Turn on overshoot shall not exceed 10% over nominal voltages@ 20 % LOAD		-	PASS

6.19. Turn off Undershoot	Turn off undershoot shall not exceed 10% over nominal voltages	-	PASS
	Turn off undershoot shall not exceed 10% over nominal voltages	-	PASS
6.20. Remote ON/OFF	Simulate TTL signal to test this function		-
6.21. Power Good Signal	Shall go high level with a delay of100~500ms	-	-
6.22. Power On In Low Temperature	I/P:115VAC (0°C)After 2HR Power On		-
6.23. Power On In High Temperature	I/P:115VAC (40 °C)After 2HR Power On		-
6.24. Room Burn-in test	I/P:115VAC O/P: FULL LOAD TA:25 °C BURN-IN DURATION : 2 hour		PASS
6.25. On/Off Cycling	Times / on: 20 sec / off: 10 sec		-
6.26. Power Consumption Test	No Run Prime95 I/P:90VAC 0.27A 12.4W Run Prime95 I/P:90VAC 0.3A 13.7W	O/P: 12V/0.78A O/P: 12V/0.86A	PASS PASS

7. Test Result and Observation

No fault was found during the test