

FSP084-DMAA1 of AIS-E1-H61A Power Electronics Test Report

Summary	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail <input type="checkbox"/> Pass with Deviation Comment: _____			
Test Result Summary				
	Critical	Major	Minor	Enhancement
Defect Found	0	0	0	0
Defect Unsolved	0	0	0	0

Issue date	Approval	Test Engineer
07/11/2013	Tom Lin	Sean Hsu

Table of Contents

1. Project.....	3
2. Power Manufacturer	3
3. Team Member	3
4. Test Equipment	3
5. AC Adapter Spec.....	3
6. Test Item.....	4
6.1. AC Input Current	4
6.2. MAX Inrush Current	4
6.3. Input Frequency & Voltage.....	4
6.4. Switching Test.....	4
6.5. Efficiency.....	4
6.6. Line Regulation.....	4
6.7. Load Regulation.....	4
6.8. Over-Voltage Protection.....	4
6.9. Over-Circuit Protection	4
6.10. Over-Load Protection	4
6.11. Short Circuit Protect	4
6.12. Line Voltage Surge.....	5
6.13. Line Voltage Sag.....	5
6.14. Ripple & Noise	5
6.15. Setup Time	5
6.16. Hold up Time	5
6.17. Rise Time	5
6.18. Turn on Overshoot	5
6.19. Turn off Undershoot.....	5
6.20. Power On In Low Temperature	5
6.21. Power On In High Temperature	5
6.22. System Power Consumption Test (With AC Adapter)	5

1. Project

FSP084-DMAA1 AC-DC Adapter for AIS-E1-H61A

2. Power Manufacturer

FSP

3. Team Member

PM : Jill Chu ; ISD H/W : Gary Lin

4. Test Equipment

4.1. PCB : EMB-H61A REV.A1.0 BIOS: R0.1 (06/19/2013)

4.2. CPU : Intel Core I3-2120M 3.3GHz

4.3. Memory : DSL DDR3-1333 4GB*2

4.4. SATA HDD : Toshiba MK1060GSC 100GB

4.5. SATA HDD : Toshiba MK1676GSC 160GB

4.6. AC Adapter : FSP , Model : FSP084-DMAA1 , O/P : 12V/7A , 84Watt

4.7. USB Mouse : Logitech , Model : M-BT85

4.8. USB Keyboard : Logitech , Model : Y-BL49

4.9. LCD Monitor : CHIMEI , Model : 22SH-L1920*1080

5. AC Adapter Spec

AC Input : 90VAC~264VAC / 47Hz~63Hz

DC Output : 12Vdc Min Load : 0A Full Load : 7A / 84W

FSP084-DMAA1 of AIS-E1-H61A Power Electronics Test Report

6. Test Item

Test Item	Test Condition / Specification		Sanction	
			Measured	Result
6.1. AC Input Current	I/P:115VAC	1.3A	0.995A	PASS
6.2. MAX Inrush Current	I/P:115VAC	A	5.2A	-
	I/P:230VAC	A	8.6A	-
6.3. Input Frequency & Voltage	I/P:90VAC/47HZ	■ON □ OFF	-	PASS
	I/P:90VAC/63HZ	■ON □ OFF	-	PASS
	I/P:264VAC/47HZ	■ON □ OFF	-	PASS
	I/P:264VAC/63HZ	■ON □ OFF	-	PASS
6.4. Switching Test	Switching Time: 0.5 Sec MIN Load / Full Load	@90VAC ■ON □ OFF	-	PASS
	Switching Time: 0.5 Sec MIN Load / Full Load	@115VAC ■ON □ OFF	-	PASS
	Switching Time: 0.5 Sec MIN Load / Full Load	@230VAC ■ON □ OFF	-	PASS
	Switching Time: 0.5 Sec MIN Load / Full Load	@264VAC ■ON □ OFF	-	PASS
6.5. Efficiency	I/P:90VAC O/P:5A	@83%Min	86.52%	PASS
	I/P:115VAC O/P:5A	@83%Min	87.34%	PASS
	I/P:230VAC O/P:5A	@83%Min	87.62%	PASS
	I/P:264VAC O/P:5A	@83%Min	86.82%	PASS
6.6. Line Regulation	I/P:90VAC~264VAC	<%	0.046%	-
6.7. Load Regulation	I/P:115VAC O/P:MIN~FULL LOAD	<%	2.02%	-
	I/P:230VAC O/P:MIN~FULL LOAD	<%	2.15%	-
6.8. Over-Voltage Protection	I/P:230VAC O/P:MIN LOAD	V1 : 17 (MAX)	-	-
6.9. Over-Circuit Protection	O/P: 12V	9.4A(MAX)	8.6A	PASS
6.10. Over-Load Protection	I/P:90VAC O/P:MIN LOAD	135%	125%	PASS
	I/P:115VAC O/P:MIN LOAD	135%	124%	PASS
	I/P:230VAC O/P:MIN LOAD	135%	125%	PASS
	I/P:264VAC O/P:MIN LOAD	135%	126%	PASS
6.11. Short Circuit Protect	I/P:115VAC O/P:MIN LOAD	12V&GND Short	-	PASS
	I/P:230VAC O/P:MIN LOAD	12V&GND Short	-	PASS

FSP084-DMAA1 of AIS-E1-H61A Power Electronics Test Report

6.12. Line Voltage Surge	O/P: FULL LOAD	Surge voltage from 132VAC to 147VAC (0.5sec), back to 132VAC	-	PASS
	O/P: FULL LOAD	Surge voltage from 264VAC to 293VAC (0.5sec), back to 264VAC	-	PASS
6.13. Line Voltage Sag	O/P: FULL LOAD	Sag voltage from 108VAC to 80VAC (0.5sec), back to 108VAC	-	PASS
	O/P: FULL LOAD	Sag voltage from 198VAC to 161VAC (0.5sec), back to 198VAC	-	PASS
6.14. Ripple & Noise	I/P:115VAC O/P:FULL LOAD	$\leq 150\text{mv}$	115mv	PASS
	I/P:230VAC O/P:FULL LOAD	$\leq 150\text{mv}$	98mv	PASS
6.15. Setup Time	I/P:115VAC O/P:FULL LOAD	3S(MAX)	732ms	PASS
	I/P:230VAC O/P:FULL LOAD	mS(MAX)	515ms	PASS
6.16. Hold up Time	I/P:115VAC O/P:FULL LOAD	20mS(MIN)	32.5ms	PASS
	I/P:230VAC O/P:FULL LOAD	mS(MIN)	86.8ms	PASS
6.17. Rise Time	I/P:115VAC O/P:FULL LOAD	mS(MAX)	4.95ms	PASS
	I/P:230VAC O/P:FULL LOAD	mS(MAX)	5.85ms	PASS
6.18. Turn on Overshoot	Turn on overshoot shall not exceed 10% over nominal voltages@ 20 % LOAD		-	PASS
	Turn on overshoot shall not exceed 10% over nominal voltages@ 20 % LOAD		-	PASS
6.19. Turn off Undershoot	Turn off undershoot shall not exceed 10% over nominal voltages		-	PASS
	Turn off undershoot shall not exceed 10% over nominal voltages		-	PASS
6.20. Power On In Low Temperature	I/P:115VAC (0°C) After 2HR Power On		-	-
6.21. Power On In High Temperature	I/P:115VAC (40°C)After 2HR Power On		-	-
6.22. System Power Consumption Test (With AC Adapter)	No Run Prime95	I/P:100VAC 0.57A 28.0W	O/P: 12V/1.3A 15.6W	PASS
	Run Prime95	I/P:100VAC 0.69A 70.4W	O/P: 12V/4.84A 58.08W	PASS