

Power Consumption / Connector Test

Platform Information:

PCB Model & Version	Gene-6310 Rev.A0.3 BIOS 0.8 (03/19/2002)
CPU Type & FSB	VIA C3 667MHz (133 ×5.0)
Memory Type	NEC D45128163G5-A80-9JF PC100 128MB
Backplane	N/A
CF Card Type	PQI Compact Flash <input type="checkbox"/> 4MB <input type="checkbox"/> 8MB <input type="checkbox"/> 16MB <input type="checkbox"/> 32MB <input checked="" type="checkbox"/> 64MB
Power Supply	DEC DP-ATX725B 250W
VGA Card (Chipset)	S3 Graphics Twister 4.13.01.3025-13.00.25

Operating System Environment :

DOS 6.22	Config.sys	Device=c:\dos\himem.sys dos=high,umb files=35 Buffers=40
	Autoexec.bat	Prompt \$p\$g C:\dos\smartdrv.exe /x

A. Power Consumption Test :

Test Software (DOS Mode):

Test Software	Landmark Speed V.2.0(Speed200.exe)
---------------	------------------------------------

Test Result:

Mode Type	CPU TYPE				Note
	VIA C3 667MHz				
Normal Mode(+5V)	2.38 A				
Suspend Mode(+5V)	1.45 A				
Normal Mode(+12V)	0				
Suspend Mode(+12V)	0				
Normal Mode(+3.3V)	N/A				
Suspend Mode(+3.3V)	N/A				