

## Power Consumption

### Platform Information:

DRAM Type	MT 48LC2M8A1TG-10S 32MB
VGA CARD	Onboard C&T 6900
HDD Type	Fujitsu MPC3032AT
VGA Testing Mode	640x480x16 colors
O.S	DOS 6.22

### Operating System Environment :

Config.sys	Autoexec.bat
Device=c:\dos\himem.sys dos=high,umb files=35 Buffers=40	Prompt \$p\$g C:\dos\smartdrv.exe/x

### Test Software (Dos Mode):

Test Software	Landmark Speed V2.0(Speed2000.exe)
---------------	------------------------------------

## Power Consumption Test: Under DOS Mode.

### Test Result :

Mode Type	CPU TYPE					Note
	Pentium MMX-200	Pentium MMX-233	Pentium MMX Tillamook-200	CyrixM2 PR-233	Cyrix M2 PR-300	
Normal Mode (+5V)	4A	4.4A	2.5A	6.8A	8A	
Suspend Mode (+5)	1.6A	1.8A	1.4A	1.4A	8.1A	

Mode Type	CPU TYPE								Note
	AMD K6-233	AMD K6-266	AMD K6-2 300	AMD K6 2-400	AMD K6 2-450	AMD K6 2-500	AMD K6 2-550	AMD K6 3-450	
Normal Mode (+5V)	8.1A	3.2A	4.2A	N/A	5.2A	5.8A	6.8A	5.6A	
Suspend Mode (+5)	1.5A	1.4A	1.4A	N/A	1.5A	1.5A	1.6A	1.4A	