

Power Consumption

Platform Information:

PCB Model & Version	PCM-6894 Rev.A0.2 BIOS Rev 0.6(07/19/2002)
CPU Type & FSB	Pentium III 1G / 133
Memory Type	INFINEDN HYB39S64800CT-75 / PC133 /128MB
DOC Type	M-System DOC2000 <input type="checkbox"/> 4MB <input type="checkbox"/> 8MB <input type="checkbox"/> 16MB <input type="checkbox"/> 32MB <input type="checkbox"/> ___MB
Power Supply	Seasonic SSG-250G / 250W
VGA Card (Chipset)	OnBoard Silicon Motion Lynx3DM / Driver Ver.4.12.01.0034

Operating System Environment :

DOS 6.22	Config.sys	Device=c:\dos \setup.exe Device=c:\dos \power.exe
	Autoexec.bat	dos=high files=30 c:\dos\smartdrv.exe/x @ echo off path c:\dos set temp=c:\dos

A. Power Consumption Test :

Test Software (DOS Mode):

Test Software	QAPlus/Fe 5.5 (Run QAPlusfe.exe/ Memory module test programming)
---------------	--

Test Result:

Mode Type	CPU TYPE					Note
	P 1.4GHz 133 FSB	P 1GHz 133 FSB	P 850MHz 100 FSB	Celeron 1GHz 100 FSB	VIA C3 800MHz 133 FSB	
Normal Mode(+5V)	5.92 A	6.63 A	5.16 A	6.02 A	2.63 A	
Suspend Mode(+5V)	5.29 A	2.62 A	1.82 A	1.88 A	1.61 A	
Normal Mode(+12V)	0.19 A	0.18 A	0.20 A	0.18 A	0.21 A	
Suspend Mode(+12V)	0.17 A	0.15 A	0.18 A	0.15 A	0.19 A	
Normal Mode(+3.3V)	N/A	N/A	N/A	N/A	N/A	
Suspend Mode(+3.3V)	N/A	N/A	N/A	N/A	N/A	