

5. Power Consumption Data

System Information:

DRAM Type & Capacity	NEC D4564841G5-A10-9JF 64M
VGA Card	Onboard C&T 69000
Disk-on-chip	MD2200-D08
VGA Testing Mode	640x480x16 Colors
O.S.	DOS 6.22

Operating System Environment (DOS Only)

Config.sys	autoexec.bat
Device=C:\Dos\Himem.sys	Prompt \$P\$G
Dos=High,Umb	C:\Dos\Smartdrv.Exe /X
Files=35	
Buffers=40	

The Application of Software

Brand	Landmark System Speed Test Version 2.0
-------	--

Test Result

Processor Type \ Mode Type	Normal Mode (+5V)	Suspend Mode (+5V)	Note
Intel Pentium II MMX-300	8.2 A	2.4 A	
Intel Pentium II MMX-400	5.7 A	2.4 A	
Intel Pentium II MMX-450	6.2 A	2.4 A	
Intel Pentium III MMX-450	6.0 A	2.4 A	
Intel Celeron 300A	4.4 A	2 A	
Intel Celeron 366	5.0 A	2 A	
Intel Celeron 400	5.2 A	2 A	
Intel Celeron 433	5.2 A	2 A	
Intel Celeron 466	5.5 A	2 A	

Note:

- 1.Power supply voltage : +5V.
- 2.Normal Model is measured while run Landmark Speed Rev.2.0 in dos mode.
- 3.Suspend Model is all function off.