

Reliability & Communication Testing Instruments

KING DESIGN INDUSTRIAL CO., LTD. 5F, NO. 3, LANE 94, TSAO TI WEI, SHEN KENG HSIANG, TAIPEI HSIEN, TAIWAN, R.O.C.

http://www.instrument.com.tw E-mail: kingdsgn@ms8.hinet.net TEL: 886-2-2662-5100 FAX: 886-2-2662-3094

TESTING / INSPECTION REPORT

DATE: July 17, 2000

REPORT NO: ST-000717-8

COMPANY: AAEON Technology Inc.

5F, No.135, Lane 235, Pao Chiao Rd. Hsin-Tien City, Taipei, Taiwan, R. O. C.

TEL:886-2-8919-1234 FAX:886-2-8919-1049

SPECIMEN: Control Boxes & Chassis

TEST / INSPECTION ITEMS : Shock Test (See Page 2)

REMARKS:

- The results only apply to the device under test.
- This report is 9 pages, and no part of it may be abstracted or reproduced.
- Attached pages are controlling pulse of shock test.

Test Engineer :	hiping			
Approved by :	Dave	Lee	Laboratory Head	Lang Cation LAGO
				金额科技 股份有限公司 报動實驗室

TELECOMS / VIBRATION / SHOCK INSTRUMENTS

1



Reliability & Communication Testing Instruments

KING DESIGN INDUSTRIAL CO., LTD. 5F, NO. 3, LANE 94, TSAO TI WEI, SHEN KENG HSIANG, TAIPEI HSIEN, TAIWAN, R.O.C.

http://www.instrument.com.tw E-mail: kingdsgn@ms8.hinet.net TEL: 886-2-2662-5100 FAX: 886-2-2662-3094



TESTING / INSPECTION REPORT

TESTING EQUIPMENT:

1.Shock Testing System : (KD-DP-1200-60, S/N:KDS11054983)

2.Controller

: (KD-1200-03C, S/N:KD674)

3.Accelerometer

: (WR-732AT, S/N:871)

TEST ENVIRONMENT:

Temperature : 20± 2°C

Humidity

: 70± 20% RH

SPECIMEN:

Model : AMB-2023

Quantity

: 1 piece

SHOCK TEST SPECIFICATION:

Wave Form :

: Half Sine wave

Acceleration

: 10 g

Duration Time

: 11 ms

No. of Shock

: Each axis 3 times

Shock Direction

: +X, -X, +Y, -Y, +Z, -Z axis

TEST RESULT:

Appearance check: No damage



Reliability & Communication Testing Instruments

KING DESIGN INDUSTRIAL CO., LTD. 5F, NO. 3, LANE 94, TSAO TI WEI, SHEN KENG HSIANG, TAIPEI HSIEN, TAIWAN, R.O.C.

http://www.instrument.com.tw E-mail: kingdsgn@ms8.hinet.net TEL: 886-2-2662-5100 FAX: 886-2-2662-3094



TESTING / INSPECTION REPORT

Testing photos

AXIS+X



AXIS -X



AXIS+Y



AXIS -Y



AXIS+Z




AXIS -Z



AMB2023+X

容據 10G11ms.pg Project File Name:




Control Peal: 10.295336 G Control RMS: 1.078344 G Full Level Elapsed Pulses: 3 0.000167 Seconds Demand Peak: 10.000000 G Demand RMS: 0.997329 G Remaining Pulses: Pulse Type: Half Sine Amplitude: 10 000000 G Pulse Width: 11.000001 ms Block Size: 4096 Elapsed Pulses; 10 Frame Time: 0.682667 Seconds Level

Report created at 10:09:32 AM, Thursday, July 6, 2000 Data saved at 10:09:08 AM, Thursday, July 06, 2000

AMB2023 -X

研捌 10G11ms.prj Project File Name:




0.000167 Seconds Demand Peak: 10,000000 G Demand RMS: 0.997329 G Remaining Pulses: Pulse Type: Half Sine Amplitude: 10 000000 G Pulse Width: 11.000001 ms Block Size: 4096 Elapsed Pulses: 10 Level:

Report created at 10:11:90 AM, Thursday, July 6, 2000

Data saved at 10:10:50 AM, Thursday, July 06, 2000

AMB2023+Y

Project File Name. 研錄 10G11ms.ptj



 Level:
 100 %
 Block Size: 40%
 Elapsed Pulses: 10

 Frame Time:
 0.682667 Seconds
 Control Peak:
 10.360634 G
 Control RMS:
 1.011539 G Full Level Elapsed Pulses: 3

 dT:
 0.000167 Seconds
 Demand Peak:
 10.000000 G
 Demand RMS:
 0.997329 G Remaining Pulses:
 0

Pulse Type: Half Sine Amplitude: 10.00000 G Pulse Width: 11.000001 ms


Data saved at 10.12:47 AM, Thursday, July 06, 2000 Report created at 10.12:57 AM, Thursday, July 6, 2000

AMB2023 -Y

Project File Name: 新棚 10G11ms.pg

Profile Name 10G HmSec Test Type: Classical Shock Run Folder:

.\Run Jul 06,2000 10-13-33



 Level:
 100 %
 Block Size: 4096
 Elapsed Pulses: 10

 Frame Time:
 0.682667 Seconds
 Control Peak:
 10.616247 G
 Control RMS:
 1.006928 G Full Level Elapsed Pulses: 3


 dT:
 0.000167 Seconds
 Dernand Peak:
 10.00000 G
 Demand RMS:
 0.997329 G Remaining Pulses:
 0

 Pulse Type: Half Sine
 Amplitude: 10.00000 G
 Pulse Width:
 11.000001 ms
 11.000001 ms

AMB2023+Z

Project File Name: 研練 10G11ms.pg

Profile Name: 10G 11mSec Test Type: Classical Shock Run Folder: \text{\tinte\text{\tin}\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\texi}\text{\text{\texi}\text{\text{\texi}\text{\text{\text{\tex{\texit{\texi}\text{\texi}\text{\text{\text{\text{\text{\text{\te



Level: 100 % Block Size: 4096 Elapsed Pulses: 10

Frame Time: 0.682667 Seconds Control Peak 10,373483 G Control RMS: 1,007183 G Full Level Elapsed Pulses: 3 dT: 0.000167 Seconds Demand Peak: 10,000000 G Demand RMS: 0,997329 G Remaining Pulses: 0

Pulse Type: Half Sine Amplitude: 10.000000 G Pulse Width: 11.000001 ms

Data saved at 10:36:50 AM, Thursday, July 06, 2000 Report created at 10:37:17 AM, Thursday, July 6, 2000


AMB2023-Z

研纂 10G11ms.prj

Profile Name: 10G 11mSec

Run Folder. Test Type: Classical Shock

NRun Jul 06,2000 10-15-59



Frame Time: 0.682667 Seconds Control Peak: 10.955111 G Control RMS: 1.014569 G Full Level Elapsed Pulses: 3 0.000167 Seconds Demand Peak: 10.000000 G Demand RMS, 0.997329 G Remaining Pulses; Pulse Type: Balf Sine Amplitude: 10 000000 G Pulse Width: 11.000001 ms Block Size: 4096 Elapsed Pulses: 10 100 %

Report created at 10:16:35 AM, Thursday, July 6, 2000 Data saved at 10:16:22 AM, Thursday, July 06, 2000