

5. Power Consumption Data

System Information:

DRAM Type & Capacity	KOREA HY57V168010D 32MB
VGA Card	OnBoard C&T 69000
FLOPPY	TEAC FD-235HF
VGA Testing Mode	640x480x16 colors
O.S.	DOS 6.22

Operating System Environment (DOS Only)

Config.sys	Autoexec.bat
Device=c:\dos\himem.sys dos=high,umb files=35 Buffers=40	Prompt \$p\$g c:\dos\smartdrv.exe /x

The Application of Software

Brand	Landmark System Speed Test Version 2.0
-------	--

Test Result

Mode Type Process Type	Normal Mode	Doze Mode	Standby Mode	Suspend Mode	Unit
PENTIUM MMX-200	4	3.2	2	1.6	Amp/Max
PENTIUM MMX-233	4.4	3.4	2.2	1.6	Amp/Max
PENTIUM Tillamook 266	2.8	2.4	1.7	1.4	Amp/Max
AMD K6-233	8.4	5.6	2.8	1.4	Amp/Max
AMD K6-266	3.4	2.6	1.8	1.4	Amp/Max
AMD K6-300	3.2	2.6	1.7	1.4	Amp/Max
AMD K6/2 300	4.3	3.2	2	1.4	Amp/Max
AMD K6/2 400	5.2	3.8	2.2	1.4	Amp/Max
AMD K6/2 450	5.6	4.1	2.5	1.6	Amp/Max
AMD K6/2 500	6.4	4.5	2.8	1.7	Amp/Max
AMD K6/3 450	6.4	4.2	2.8	1.8	Amp/Max
Cyrix M2 PR-200	6.4	4.4	2.4	1.4	Amp/Max
Cyrix M2 PR-233	6.8	4.8	2.6	1.4	Amp/Max
Cyrix M2 PR-300	8	5.8	2.8	1.2	Amp/Max
IDT Winchip 225	3.2	2.8	2	1.8	Amp/Max
IDT Winchip 240	3.5	3	2.2	1.8	Amp/Max

Note :

- 1.Power supply voltage : +5V
- 2.Suspend Model all function off