

P/N	DESCRIPTION	MAKER	PART NO.	UL NO./ Flame Class
1211000180	(TF)COIL.1uH.+/- 20%.SMD.7.3*6.8*3.0mm.DCR=9mohm.Irms=1 1Amp.GOTREND.GSTC063P-1R0MN	GOTREND	GSTC063P- 1R0MN	E84081,
1211100109	(TF)INDUCTOR.1uH.10%.SMD 1210 DCR=0.08 ohm IDC=1.5A.高創.GNLC-3225P-	GOTREND	GNLC-3225P- 1R0K	E75077(S),
1211101161	(TF)COIL.1.1uH.DIP Wire Size 2.3mm.35材 3wire 30Amp.三集瑞.LG-11AM12J19	TRIO	LG-11AM12J19	E201575,E8564 0,E180908,E35 586,
1211105674	(TF)COIL.0.56uH.20%.DIP.35A.GOTREND.G MAT-131210-P-R56-M	GOTREND	GMAT-131210- P-R56-M	E218438 / E84081,
1214309002	(TF)Common Choke.4P.90 Ohm(100Mhz) 2.0*1.2mm SMD.永馳.YFD2012T#900S	YOUTH	YFD2012T#900S	E84081(S),
1315970110	(TF)PWR.SMD.SOT-25 High-Side Switch.RICHTEK.RT9701PBL	RICHTEK	RT9701PBL	E219878,
1651203291	(TF)IC SKT PLCC.SMD.32P(9P*7P).PRECI- DIP(LEASONIC).PLCC-L-32F-9-D	PRECI-DIP(LEASONIC)	PLCC-L-32F-9-D	E53829,
1651612992	(TF)ZIF LGA 775 SKT.SMD.775P.FOXCONN.PE077526-1041-0D	FOXCONN	PE077526-1041- 0D	E93750,
1652508212	(TF)PHONE JACK.8P.90D.(F).RJ45 W/Transformer & LED.BOTHHAND.LU1T516-	BOTHHAND	LU1T516-43 LF	E130155,E1748 37,
1653002100	(TF)PIN HEADER.2*1P.180D.(M).2.54mm.DIP	JVE	21B12564- XXS10B-01G- 6/3	E107536 UL94V-0,
1653003100	(TF)PIN HEADER.3*1P.180D.(M).2.54mm.DIP	Astron	27-0103-1XX-1G	E107536 UL94V-0,
1653004200	(TF)PIN HEADER.4*2P.180D.(M).2.54mm.DIP	JVE	21B22564- XXS10B-01G- 6/3-VXX	E107536 UL94V-0,
1653005201	(TF)PIN HEADER.5*2P.180D.(M).2.0mm.DIP	JVE	21B22050- XXS10B-01G- 4/2.8	E107536 UL94V-0,
1653005205	(TF)PIN HEADER.5*2P.180D.(M).W/O PIN9 2.0mm.DIP	1=>JVE 2=>HO-BASE	1=>21N22050- 10S10B-01G- 4/2.8-V1-G 2=>@165300520 5	E54695,E52579 ,
1653006101	(TF)PIN HEADER.6*1P.180D.(M).2.0mm.DIP	JVE	21B12050- XXS10B-01G- 4/2.8	E107536 UL94V-0,
1653205203	(TF)BOX HEADER.5*2P.180D.(M).2.0mm.DIP. 凱迅.1147-000-10S	CATCH	1147-000-10S	E132701 UL94V-0 ,
1653213203	(TF)BOX HEADER.13*2P.180D.(M).2.0mm.DIP.凱	CATCH	1147-000-26S	E132701 UL94V-0 ,
1653217205	(TF)BOX HEADER.17*2P.180D.(M).2.54mm.DIP W/O	CATCH	1137-000-34SA	E107536A UL94V-0,
1653220208	(TF)BOX HEADER.20*2P.180D.(M).2.54mm.DIP W/O	CATCH	1137-020-40SA	E107536(A) UL94V-0,

P/N	DESCRIPTION	MAKER	PART NO.	UL NO./ Flame Class
1653300100	(TF)MINI JUMPER.(YELLOW)	JVE	27S1002-OPS60B-01G-Y	E107536(M) UL94V-0,E59481,
1653300101	(TF)MINI JUMPER.(RED)	JVE	27S1002-OPS60B-01G-R	E107536(M) UL94V-0,E59481,
1653302150	(TF)JUMPER WIRE.1*2P.180D.2.54mm DIP for 845e Heat sink	JVE	21N12564-03A10B-01G-5.4/3.1	E107536(M) UL94V-0,E59481,
1654030003	(TF)Board-Wire Connector.30P.180D(M).SMD.Pitch=1.25mm.W/Reinforcem.E-call.0110-01-553-300	E-call	0110-01-553-300	E113875,
1654515308	(TF)D-SUB H/D CONNECTOR.15P.90D.(F).Blue.DIP.凱迅.3125-000-15SB	CATCH	3125-000-15SB	E107536(M) UL94V-0,
1654606200	(TF)MINI DIN RECEPT TABLE.6P.90D.(F).W/SPRING DIP.CONTEK.MAN3061F1G401	CONTEK	MAN3061F1G401	E130155(M) 94V-0,
1654804100	(TF)USB CONNECTOR SINGLE PORT.Upright.4P.90D(M).何迪.KS-001V-ANW	HO-BASE	KS-001V-ANW	E52579(M),
1654907002	(TF)SATA CONNECTOR.7P.180D(M).DIP.TECHBEST.161S01-025A	TECHBEST	161S01-025A	E204143 UL94V-0,
1654907003	(TF)SATA CONNECTOR.7P.180D(M).DIP.BLUE.TECHBEST.161S01-029A-L	TECHBEST	161S01-029A-L	E130155(M) UL94V-0,
1655003022	(TF)WAFER BOX.3P.180D.(M).2.5mm.W/LOCK DIP.凱迅.1190-700-042	CATCH	1191-700-03S	E119177(M) UL94V-0 ,
1655004014	(TF)WAFER.4P.180D.(M).2.54mm.DIP.CATCH.1190-700-042	CATCH	1190-700-042	E132701 UL94V-0 ,
1655005021	(TF)WAFER BOX.5P.180D.(M).2.5mm.W/LOCK.DIP.HO-BASE.2503-WS-5	HO-BASE	2503-WS-5	E135898 UL94V-0,E44716 UL94V-0
1655404020	(TF)ATX POWER CONNECTOR.2P*2.180D.DIP.凱迅.1121-700-	CATCH	1121-700-04S	E132701 UL94V-0,
1655420023	(TF)ATX POWER CONNECTOR.12P*2.180D(M).DIP.W/O 1&2&12&13 pin.凱迅.1121-700-24SA	CATCH	1121-700-24SA	E132701 UL94V-0,
1700060192	(TF)Cable.6P-6P-6P.19cm.IVORY PS2/KB&Mouse	1=>CATCH 2=>HO-BASE	1=>A003-114 2=>1700060192	E119932(S), E107536(M) UL94V-0, UL2725,UL2464, E107536(M) UL94V-0,

P/N	DESCRIPTION	MAKER	PART NO.	UL NO./ Flame Class
1701100305	(TF)Flat Cable.9P/DB9P MALE.10P/2.0mm Pitch/IDC NO FOLD.30cm.W/BRACKET	CATCH	A002-014	UL2651,E72332,E107536(M) UL94V-0,E209329 ULVW-1,E107536(M) UL94V-0,E212834,E56070(S) UL94HB,E186230,
1701260307	(TF)Flat Cable.9P/DB9P MALE&25P DB25P FEMALE.10P 2mm&26P 2mm/IDC NO FOLD.30cm.W/BKT.凱迅.A002-015	CATCH	A002-015	UL2651 VW-1,E72332,E107536(M) UL94V-0,
1701340704	(TF)Flat Cable.34P.70cm.GRAY for FDD	CATCH	A003-246	E107536(M) UL94V-0,UL2651 VW-1,
1701400453	(TF)Cable.40P 2.54mm IDC W/Nose W/Fold.40P 2.54mm IDC W/Nose	CATCH	B016-009-2	E107536(M) 94V-0,E101344,
1703030501	(TF)Wire.3P 2.5mm Housing.3P 2.5mm Housing.50cm	CATCH	A003-232	E170689 VW-1,E41797(M),E144392 UL94V-0,E108485(S) VW-1,E132701 VW-1,E108485(S) ULVW-1,E191023,
1709070800	(TF)SATA CABLE.7P Pitch 1.27mm.80cm.W/Lock	1=>CATCH 2=>Alphaplus	1=>A003-569 2=>CB-AA-0006	E177865,E107536 UL94V-0 ,E107536(M),E96118,
1709100201	(TF)Usb Cable.20cm2.0mm.W/Bracket	CATCH	1709100201	E101344 VW-1,E107536(M) UL94V-0,E209436,E107536(M) UL94V-0 ,
1750119011	(TF)BATTERY.3V.200mA.SONY.CR2032	SONY	CR2032	MH12566,
1750220323	(TF)Battery Holder.CR2032 DIP.Straight.LOTES.KB7566BP5L	LOTES	KB7566BP5L	E135714 V-0,
1752310000	(TF)PolySwitch.8V.1.1A(Max 40A).TYCO.miniSMDC110F-2	TYCO	miniSMDC110F-2	E74889,
1759200161	(TF)CPU Cooler Fan.for LGA775 Pentium4 3.6G.4P.12V.Dual ball bearing.捷豐.LGA-775-959546008	CMT	LGA-775-959546008	E236658,

P/N	DESCRIPTION	MAKER	PART NO.	UL NO./ Flame Class
9657666600	(TF)Accessory.for All Series Jumper	CATCH	9657666600	E107536(M) 94V-0,
9681666600	(TF)Cable ASSY.for SBC Series	CATCH	A003-252	E144392 UL94V- 0,E108485(S) VW-1,E132701 VW-1,
121110010X	(TF)COIL.1uH.Wire Size 1.3mm.1.3mm.1wire 20Amp.高創.C5052BP-12A04YDPS	GOTREND	C5052BP- 12A04YDPS	E218438,E8408 1,
121110100H	(TF)COIL.10uH.20%.DCR=182mOhm.Idc=1.15 A.4.5*4.0mm.SMD.GOTREND.GSDR43P-	GOTREND	GSDR43P-100M	E75077,E84081 ,E218438,
16515C0495	(TF)DDR2 SKT.DIP.240P.(Blue).FOXCONN.AT24017-	FOXCONN	AT24017-H3L- 4F	E93750,
1653925216	(TF)Compact Flash Header.25*2P.90D.SMD.1.27mm pitch.for TypeII.SPEED TECH.N016@0140- 004+N01P4011-0099	SPEED TECH	N016@0140- 004+N01P4011- 0099	E192672,
175910000A	(TF)Buzzer.SMD.5V.80mA.90dB.KINGSTATE. KSSGJ5D26	KINGSTATE	KSSGJ5D26	E59481,
1907868G11	(TF)PCB.FSB-868G-B.Rev.B1.0.8Layers Green	K-BRIDGE	K267F8227B	E120558,
M06866G000	(TF)Metal.AL.Heat sink.36.8*36*10.1mm.研揚 字型.For BGA Package.捷豐.JF-363601	CMT	JF-363601	E41938(M) UL94V-2,